



**MICROWAVE ABSORBER BASED ON BIOCOMPOSITES
DERIVED FROM AGRICULTURAL WASTES WITH
REINFORCEMENT OF POLY LACTIC ACID**

By

ELFARIZANIS BINTI BAHARUDIN

**Thesis Submitted to the School of Graduate Studies, Universiti Putra
Malaysia, in Fulfilment of the Requirements for the Degree of
Doctor of Philosophy**

January 2021

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs, and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



DEDICATION

This thesis is dedicated to

Those who kept faith in me:

*With love, respect and a bunch of memories
There is neither might nor strength except with Allah
Indeed, we belong to Allah and indeed to Him we will return.*



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Doctor of Philosophy

**MICROWAVE ABSORBER BASED ON BIOCOMPOSITES
DERIVED FROM AGRICULTURAL WASTES WITH
REINFORCEMENT OF POLY LACTIC ACID**

By

ELFARIZANIS BINTI BAHARUDIN

January 2021

Chairman : Professor Alyani binti Ismail, PhD
Faculty : Engineering

The development of new microwave absorber (MA) materials has been motivated by an increasing ecological and environmental consciousness. Biocomposites is natural fibre-reinforced polymers has low density and biodegradable nature obtain from natural fibers which are cheap, continuous supply, easy and safe handling. The idea of this research is to develop a MA from biocomposite derived from oil palm fronds (OPF), empty fruit bunch (EFB), pineapple leaf fiber (PALF) and strengthened with poly-lactic acid (PLA). The fibers samples are prepared in 0.3 mm particle size, meanwhile the polymer and biocomposites are in ring shaped forms using mix and blend process and injection moulding. Their dielectric constant, (ϵ') and loss tangent, ($\tan \delta$) are extracted using open ended coaxial probe and S-parameter Reflection measurements. OPF, EFB and PALF show ϵ' with 1.92, 1.88 and 2.04 respectively and $\tan \delta$ with 0.105, 0.096 and 0.102 respectively. PLA ϵ' and $\tan \delta$ is about 1.99 ± 0.25 and 0.044 ± 0.02 respectively in the X band. Each type of biocomposite mixture of fiber and PLA composition (wt%) namely OPFPLA, EFBPLA, and PALFPLA prepared in 10 wt%, 20 wt%, 30 wt%, 40 wt% and 50 wt% fiber loadings. The optimum ϵ' and $\tan \delta$ for each biocomposite is 2.718 and 0.165 at $f_0 = 8.6$ GHz for OPFPLA5050 with 50 wt% OPF and 50 wt% PLA, meanwhile 2.079 and 0.168 at $f_0 = 8.8$ GHz for EFBPLA5050 with 10 wt% EFB and 90 wt% PLA and 2.23 and 0.09 at $f_0 = 8.4$ GHz for PALFPLA with 50 wt% PALF and 50 wt% PLA. The MA performance is observe from CST simulation, where S_{11} and S_{21} parameters are the key factors of MA absorption rates (AR), fractional bandwidth (FBW) and its thickness, d is used to determine the new formulation of figure of merit (FOM) for the percentage of wave absorption per unit millimeter (mm). OPFPLA5050 MA with $d = 9$ mm resonates at 8.6 GHz show the optimum performance with AR of 40.9%, FBW of 31.2% and the FOM is 4.5% per unit mm using normal incident in TE and TM polarization. When incident wave transmitted in variation angles of θ , the AR and FBW increase as θ increases until 45° in TE and

TM polarization. Then, OPFPLA5050 MA is fabricated using $30 \times 30 \times 1 \text{ cm}^3$ mould and hot press machine. It is measured using free space and bistatic reflection methods. The results shows OPFPLA5050 MA with $d = 10 \text{ mm}$ resonates at 8.17 GHz with AR is 35.9%, FBW is 7.42 % and FOM is 3.6% per unit mm. Due to fabrication error, the MA thickness is different form the simulation although their plots show same trends except for the shifted resonant frequency. A fine-tune simulation shows that the fabricated MA consider to have $\epsilon' = 2.46$ and $\tan \delta = 0.12$ and frequency at 8.17 GHz where the corresponding AR is 32%, FBW is 26.8% and FOM is 3.2% per unit mm which is close to the fabricated results. Then, a similar trend observed with the simulations when θ varies from 0° in 45° in TE and TM polarization. Therefore, these findings on natural fiber reinforced PLA biocomposites have significant implications in the application of microwave absorber. The unique composition between oil palm frond fibers and PLA demonstrates promising wave absorption for further exploration as alternative material in future research.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

**PENYERAP GELOMBANG MIKRO BERASASKAN BIOKOMPOSIT
DARIPADA SISA PERTANIAN YANG DIPERKUKUH DENGAN
POLI LAKTIK ASID**

Oleh

ELFARIZANIS BINTI BAHARUDIN

Januari 2021

Pengerusi : Profesor Alyani binti Ismail, PhD

Fakulti : Kejuruteraan

Peningkatan kesedaran terhadap ekologi dan persekitaran menjadi motivasi kepada penyelidikan pembangunan bahan-bahan bagi menyerap gelombang mikro (MA). Biokomposit adalah serat yang diperteguhkan dengan polimer yang berkepadatan rendah dan bersifat biodegradasi dari sumber semula jadi yang murah, mudah didapati serta senang diuruskan. Idea penyelidikan ini adalah membangunkan penyerap MA dari biokomposit yang berasal dari sisa pertanian seperti pelepah kelapa sawit (OPF), tandan buah kosong (EFB) dan serat daun nanas (PALF) yang diperkuat oleh poli-laktik asid (PLA). Serat sisa pertanian tersebut dihancurkan menjadi sampel bersaiz 0.3 mm, manakala sampel PLA dan biokomposit dihasilkan seperti bentuk cincin menggunakan proses gaul dan kisar serta kaedah acuan suntikan. Sifat pemalar elektrik (ϵ') dan tangen kehilangan, ($\tan \delta$) bagi bahan-bahan tersebut diekstrak menggunakan kaedah prob koaksial terbuka dan refleksi S-parameter. OPF, EFB dan PALF menunjukkan nilai ϵ' masing-masing dengan 1.92, 1.88 dan 2.04 manakala $\tan \delta$ dengan nilai 0.105, 0.096 dan 0.102. Bagi PLA, ϵ' dan $\tan \delta$ adalah 1.99 ± 0.25 dan 0.044 ± 0.02 masing-masing pada jalur X. Setiap biokomposit OPFPLA, EFBPLA dan PALFPLA, iaitu campuran serat dan PLA, disediakan dalam komposisi (wt%) sebanyak 10 wt%, 20 wt%, 30 wt%, 40 wt% dan 50 wt% muatan serat. Nilai-nilai optimum ϵ' dan $\tan \delta$ setiap biokomposit adalah 2.718 dan 0.165 pada $f_0 = 8.6$ GHz (OPFPLA5050) yang mempunyai 50 wt% OPF dan 50 wt% PLA, manakala 2.079 dan 0.168 pada $f_0 = 8.8$ GHz (EFBPLA5050) dengan 10 wt% EFB dan 90 wt% PLA dan akhirnya 2.23 and 0.09 pada $f_0 = 8.4$ GHz (PALFPLA) dengan 50 wt% PALF dan 50 wt% PLA. Prestasi MA dari simulasi CST dilihat pada parameter pantulan (S_{11}) dan hantaran (S_{21}) serta ia adalah kunci utama kadar serapan (AR) MA, jalur lebar pecahan (FBW) manakala ketebalan (d) MA adalah untuk menentukan angka merit (FOM) iaitu nisbah kadar serapan gelombang per unit milimeter (mm). OPFPLA5050 MA dengan $d = 9$ mm menghasilkan resonan pada 8.6 GHz dan ia menunjukkan prestasi optimum dengan

AR sebanyak 40.9%, FBW selebar 31.2% dan FOM adalah 4.5% per unit mm dengan hala tuju normal dalam pengutuban TE dan TM. Ketika hala tuju dipancarkan dalam sudut θ , didapati nilai AR dan FBW meningkat sehingga θ mencapai sudut 45° pada pengutuban TE dan TM. Kemudian, OPFPLA5050 MA difabrikasi menggunakan acuan $30 \times 30 \times 1 \text{ cm}^3$ dan juga mesin tekanan panas. Ia diukur menggunakan kaedah ruang bebas serta kaedah refleksi bistatik. Keputusan menunjukkan OPFPLA5050 MA dengan $d = 10 \text{ mm}$ mempunyai resonan pada 8.17 GHz dengan AR sebanyak 35.9%, FBW selebar 7.42 % dan FOM adalah 3.6% per unit mm. Disebabkan kelemahan pada proses fabrikasi, maka hasil ketebalan MA adalah berbeza dari nilai optimum simulasi walaupun bentuk graf yang terhasil mempunyai corak yang sama kecuali pada anjakan frekuensi resonan. Simulasi pembaikan bagi menentukan perbezaan keputusan ukuran dilakukan dan didapati bahawa MA yang telah fabrikasi mempunyai $\epsilon' = 2.46$ dan $\tan \delta = 0.12$ pada frekuensi 8.17 GHz. Hasil dapatannya adalah AR, 32%, FBW, 26.8% dan FOM 3.2% per unit mm di mana ia hampir sama dengan keputusan ukuran MA yang telah difabrikasi. Hasil simulasi tersebut juga menunjukkan corak yang hampir sama dengan hasil simulasi asal apabila sudut hala tuju θ dipelbagaikan dari 0° ke 45° dalam pengutuban TE and TM. Oleh yang demikian, penyelidikan terhadap pembangunan penyerap MA dari biokomposit yang diperbuat daripada serat semula jadi diperkukuhkan dengan PLA ini menunjukkan hasil yang signifikan dan mempunyai implikasi penting terhadap aplikasi penyerap gelombang. Komposisi yang unik antara OPF dan PLA membuktikan penyerapan gelombang dalam medium adalah meyakinkan dan ia sebagai bahan alternatif yang berpotensi untuk kajian yang lebih jauh pada masa hadapan.

ACKNOWLEDGEMENTS

With the name of Allah the Most Compassionate and Most Merciful

All praise and thanks to Almighty Allah, with His blessing giving me the strength and passion, could manage to finish the research until this manuscript completed be compiled.

I would like to express my deep and sincere gratitude to my research supervisor, Prof. Dr. Alyani binti Ismail for giving me the opportunity to do research and providing invaluable guidance throughout this research. My gratitude also goes to my co supervisors, Assoc. Dr. Dayang Laila binti Abang Haji Abdul Majid, Assoc. Prof. Dr. Edi Syams bin Zainudin and Assoc. Prof. Dr. Fauziahanim binti Che Seman for their constructive comments and feedbacks.

I wish to express my greatest appreciation to my beloved husband, daughter, father, sister and also to all my family members for their love and patience, and their faith for never giving up on me during this period of struggle. Not forgetting to all my supportive friends, for their doa and encouragement. Thank you also to those who have direct or indirectly assisted me in completing this thesis successfully.



PTAA
PERPUSTAKAAN TUNJAU AMINAH

I certify that a Thesis Examination Committee has met on 5th January 2021 to conduct the final examination of Elfarizanis binti Baharudin on her thesis entitled “Microwave Absorber based on Biocomposites Derived from Agricultural Wastes with Reinforcement of Poly Lactic Acid” in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student is awarded the Doctor of Philosophy.

Members of the Thesis Examination Committee were as follows:

Fazirulhisyam bin Hashim, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Ir. Aduwati binti Sali, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Raja Syamsul Azmir bin Raja Abdullah, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Mohamad Kamal bin A Rahim, PhD

Professor
Faculty of Engineering
Universiti Teknologi Malaysia
(External Examiner)

ZURIATI AHMAD ZUKARNAIN, PhD

Professor Ts. and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

This thesis was submitted to the Senate of the Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee were as follows:

Alyani binti Ismail, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Dayang Laila binti Abang Haji Abdul Majid, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Edi Syams bin Zainudin, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Adam Reda Hasan Alhawari

Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Fauziahanim binti Che Seman, PhD

Associate Professor
Faculty of Electrical and Electronic Engineering
Universiti Tun Hussein Onn Malaysia
(Member)

ZALILAH MOHD SHARIFF, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 12 August 2021

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature: _____




Date: 31 August 2021

Name and Matric No: Elfarizanis binti Baharudin, GS34410


Declaration by Members of Supervisory Committee

This is to confirm that:


- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) were adhered to.


Signature:  _____
Name of Chairman of Supervisory Committee: **PROF. DR ALYANI ISMAIL**
Professor
Jabatan Kejuruteraan Sistem Komputer Dan Komunikasi
Fakulti Kejuruteraan
Universiti Putra Malaysia

Professor
Dr. Alyani binti Ismail

Signature:  _____
Name of Member of Supervisory Committee: **Assoc. Prof. Dr. Dayang Laila Abg Haji Abdul Majid**
Associate Professor
Department of Aerospace Engineering
Faculty of Engineering
Universiti Putra Malaysia

Associate Professor
Dr. Dayang Laila binti Abang Haji Abdul Majid

Signature:  _____
Name of Member of Supervisory Committee: Associate Professor
Dr. Edi Syams bin Zainudin

Signature:  _____
Name of Member of Supervisory Committee: Lecturer
Dr. Adam Reda Hasan Alhawari


Signature:  _____
Name of Member of Supervisory Committee: Associate Professor
Dr. Fauziahanim binti Che Seman

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xx

CHAPTER

1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement and Motivation	2
	1.3 Research Aim and Objectives	4
	1.4 Research Scopes	4
	1.5 Thesis Outline	5
2	LITERATURE REVIEW	8
	2.1 Introduction	8
	2.2 Brief History of Microwave Absorber	8
	2.3 Fundamentals of Microwave Absorber	10
	2.3.1 Frequency and Application of Microwave Absorber	13
	2.3.2 Microwave Absorbing Material	16
	2.3.2.1 Biomaterial	17
	2.3.2.2 The Permittivity and Permeability	19
	2.3.2.3 The Loss Tangent	20
	2.3.3 Type of Microwave Absorber Structure	21
	2.3.4 Microwave Absorption	23
	2.3.5 Bandwidth	25
	2.3.6 Polarization and Incident Angles	25
	2.3.6.1 TE and TM Polarization	26
	2.3.6.2 Normal and Oblique Incidents	26
	2.4 Overview on Biocomposite	28
	2.4.1 Natural Fiber	29
	2.4.1.1 Oil Palm Fiber	29
	2.4.1.2 Pineapple Leaf Fiber	30
	2.4.2 Natural Polymer	32
	2.5 Overview Dielectric Measurement Techniques	33
	2.6 Summary	37

3	METHODOLOGY	38
3.1	Introduction	38
3.2	Material Characterization	38
3.2.1	Natural Fiber Samples Preparation	41
3.2.2	Determination of Material Densities	42
3.2.3	Identification of Natural Fiber Electrical Properties	43
3.2.4	Natural Polymer Samples Preparation	44
3.2.5	Identification of Natural Polymer Electrical Properties	46
3.2.6	Biocomposite Sample Preparation	48
3.2.7	Identification of Biocomposites Electrical Properties	52
3.3	Electromagnetic Simulation of Microwave Absorber	52
3.3.1	Calculation on Microwave Absorber Design	53
3.3.2	Microwave Absorber Parametric Study	54
3.4	Realization of Microwave Absorber	55
3.4.1	Fabrication Process Flow	55
3.4.2	Microwave Absorber Testing Setup	57
3.5	Summary	60
4	MATERIAL CHARACTERIZATION OF BIOCOMPOSITES	61
4.1	Introduction	61
4.2	Natural Fiber Properties	61
4.2.1	Preparation of Pulverized Fibers	61
4.2.2	Material Densities	62
4.2.3	Dielectric Properties using Open-ended Coaxial Probe	62
4.2.4	Natural Fiber Dielectric Properties Analysis	64
4.3	Natural Polymer Properties	68
4.3.1	Samples Preparation	69
4.3.2	Dielectric Properties using S'Parameter Reflection Method	70
4.4	Biocomposites Properties	74
4.4.1	Biocomposite Mixture	74
4.4.2	Samples Preparation	75
4.4.3	Biocomposite Properties using S'Parameter Reflection Method	77
4.4.4	Biocomposite Properties Analysis	83
4.5	Summary	85
5	MICROWAVE ABSORBER SIMULATION BASED ON BIOCOMPOSITE MATERIALS	86
5.1	Introduction	86
5.2	Calculations on the Dimension of Microwave Absorber	87
5.3	Parametric Study of Microwave Absorber through Electromagnetic Simulation	88

5.3.1	Effect on the Signal Reflection and Transmission due to variation of MA width and length	88
5.3.2	Effect on the Signal Reflection and Transmission due to variation of MA Thickness	91
5.4	Thickness Optimization of Microwave Absorber based Natural Fiber Reinforced PLA Biocomposites	94
5.4.1	Thickness Optimization of OPFPLA Biocomposites	94
5.4.2	Thickness Optimization of EFBPLA Biocomposites	102
5.4.3	Thickness Optimization of PALFPLA Biocomposites	110
5.5	Absorption Rates of the Optimized MA based on Natural Fiber Reinforced PLA Biocomposites	118
5.5.1	OPFPLA Biocomposites Absorption Rates Comparison	119
5.5.2	EFBPLA Biocomposites Absorption Rates	120
5.5.3	PALFPLA Biocomposites Absorption Rates	121
5.6	Microwave Absorber Absorption Rates Analysis	121
5.6.1	Effect of Signal Reflection and Transmission on Microwave Absorber Parameter	122
5.6.1.1	Effect of Loss Tangent on Signal Reflection and Transmission of MA	124
5.6.1.2	Effect of Dielectric Constant on Signal Reflection and Transmission of MA	127
5.6.2	Effect of Optimized Thickness on Absorption Rates	129
5.6.2.1	Effect of Dielectric Constant on Optimized Thickness	131
5.6.2.2	Effect of Loss Tangent on Optimized Thickness	133
5.7	Performance Indicator of Microwave Absorber Realization	135
5.7.1	Microwave Absorber Figure of Merit (FOM)	135
5.8	OPFPLA5050 Microwave Absorber Performance	137
5.8.1	Signal Reflection and Transmission in TE and TM Polarization	137
5.8.2	Bandwidth	137
5.8.3	Incident Angles in TE and TM Polarization	139
5.9	Summary	144
6	REALIZATION OF BIOCOSMPOSITE MICROWAVE ABSORBER	145
6.1	Introduction	145
6.2	Fabrication of Microwave Absorber	145
6.3	Comparison of Measurement and Simulation of Microwave Absorber	146

6.4	Fine-tuning of OPFPLA5050 MA Parameters due to Differences in Measurement and Simulation Results	148
6.5	Fine Tuned of Measured OPFPLA5050 Performance	154
6.5.1	Bandwidth and Absorption rates in TE and TM Polarization	154
6.5.2	Absorption Rates in Variation of Phi Angles in TE and TM Polarization	155
6.5.3	Absorption Rates in Variation of Theta Angles in TE Polarization	157
6.5.4	Absorption Rates in Variation of Theta Angles in TM Polarization	159
6.5.5	Comparison of Key Features of OPFPLA 5050	161
6.6	Summary	162
7	CONCLUSION AND FUTURE RESEARCH	
	RECOMENDATIONS	163
7.1	Conclusion	163
7.2	Recommendation of Future Research	165
	REFERENCES	167
	APPENDICES	179
	BIODATA OF STUDENT	186
	LIST OF PUBLICATIONS	187



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF TABLES

Table	Page	
2.1	Microwave Bands (ITU-T, 2015)	14
2.2	Overview previous research on Microwave absorber at X band	15
2.3	Microwave absorbing materials classifications (reconstructed)	16
2.4	Advantage and disadvantage for previous work on MA biomaterials	18
2.5	Overview previous research on absorption rates over the thickness	24
2.6	Basic Properties of OPF, EFB and PALF	31
2.7	General comparison for dielectric measurement technique	34
2.8	Advantage and disadvantage for previous research on biomaterials and MA measurements	35
4.1	The focus of Chapter 4	61
4.2	Natural Fiber mass before and after drying process	61
4.3	Fiber densities based on Accupynometer	62
4.4	Maximum Loss tangent and dielectric constant for OPF, EFB and PALF in the X- band	68
4.5	Dielectric properties of PLA from 8 to 9.4 GHz	73
4.6	Biocomposite mixture percentage	74
4.7	Calculated final biocomposite densities	75
4.8	Calculated fiber and PLA masses for mixing process	76
4.9	Biocomposite properties with maximum loss tangent	85
5.1	Comparison for best figure of merit	136
5.2	Key Performance for 9 mm OPFPLA5050 microwave absorber with variation of theta	143
6.1	Characteristic of OPFPLA5050 MA	154
6.2	Comparison of Key Features of OPFPLA5050	161

LIST OF FIGURES

Figure	Page	
1.1	Research Scopes	5
1.2	Thesis Outline	7
2.1	Source of EMI	9
2.2	Propagation of electromagnetic wave in a material	11
2.3	Multiple reflection within the material interfaces	12
2.4	Microwave Absorber)	22
2.5	Full width half maximum (FWHM) principle	25
2.6	Oblique incidence	27
2.7	Fiber reinforced plastic used in 2002	28
2.8	Anatomy of a oil palm tree and oil palm frond	30
2.9	Example of TGA of EFB	31
2.10	PLA synthesis path	32
3.1	General Flow Chart of Research Methodology in accordance to the respective research objectives	38
3.2	Flow chart for material characterization	40
3.3	Agricultural wastes from oil palm and pineapple plantations	41
3.4	Process of sample preparation for natural fiber	42
3.5	Material density measurement	43
3.6	Open-ended coaxial probe method	44
3.7	(a) Ring sample dimensions (b) PLA granules (c) Injection moulding machine used in UTHM (d) Process flow in an injection mould (Rajeshkumar <i>et al.</i> , 2021) (e) Final ring samples	45
3.8	(a) S-Parameter reflection measurement components, 1. GPC7 Unit, 2. Sample holder, 3. Short conductor, 4. Open resin, 5. Open conductor, 6. Center pin, 7. Connector top, 8. Connector base, 9. Connector resin (b) Connection between completed component setup with network analyzer (c) Open calibration setup (d) Short calibration setup	47
3.9	Process flow of S-Parameter reflection measurement	47
3.10	Block diagram of composite mixing	48
3.11	Mixing process using internal mixer	50
3.12	Variation of fiber loading in the biocomposite mixing	51
3.13	(a) Biocomposites samples (b) Open calibration sample fitting (c) Short calibration sample fitting with sample holder	52
3.14	Process flow of electromagnetic simulation of microwave absorber	53
3.15	MA three dimensional parameters	54
3.16	CST Simulation Setup	54
3.17	Process of fabricating MA slab	57
3.18	Fabrication of MA	57
3.19	Reflection measurements of biocomposite microwave absorber	59
3.20	Transmission measurement of biocomposite microwave absorber	59
4.1	Electrical properties of OPF, EFB and PALF against frequency	64
4.2	Electrical properties of OPF, EFB and PALF in the X-band	66

4.3	The loss factor transformation for OPF, EFB and PALF after eliminating the values less than the zero line	67
4.4	The loss tangent of OPF, EFB and PALF with zero loss factors	68
4.5	Variation of ring thickness versus frequency	70
4.6	Final product of ring shaped samples of PLA	70
4.7	Dielectric constant of PLA against frequency	71
4.8	Loss factor of PLA against frequency	72
4.9	Loss tangent of PLA against frequency	73
4.10	Final product of ring shaped biocomposite	77
4.11	Variation of dielectric properties of OPFPLA against frequency	79
4.12	Variation of dielectric properties of EFBPLA against frequency	81
4.13	Variation of dielectric properties of PALFPLA against frequency	82
4.14	Comparison of loss tangent between biocomposites	84
5.1	Focus of Chapter 5	86
5.2	Geometry of microwave absorber	87
5.3	Signal reflection of OPFPLA1090 when width = length are varied	89
5.4	Signal transmission of OPFPLA1090 when width = length are varied	90
5.5	Signal reflection for OPFPLA1090 when thickness is varied	92
5.6	Variations of signal transmission for OPFPLA1090	93
5.7	OPFPLA1090 MA performance	96
5.8	OPFPLA2080 MA performance	98
5.9	OPFPLA3070 MA performance	99
5.10	OPFPLA4060 MA performance	101
5.11	OPFPLA5050 MA performance	102
5.12	EFBPLA1090 MA performance	104
5.13	EFBPLA2080 MA performance	106
5.14	EFBPLA3070 MA performance	107
5.15	EFBPLA4060 MA performance	108
5.16	EFBPLA5050 MA performance	110
5.17	PALFPLA1090 MA performance	112
5.18	PALFPLA2080 MA performance	114
5.19	PALFPLA3070 MA performance	115
5.20	PALFPLA4060 MA performance	117
5.21	PALFPLA5050 MA performance	118
5.22	Absorption rates for OPFPLA biocomposites	119
5.23	Absorption rates for EFBPLA biocomposites	120
5.24	Absorption rates for PALFPLA biocomposites	121
5.25	Biocomposites Absorption rates versus operating frequency	122
5.26	Relationship between S_{11} and S_{21} against AR of OPFPLA5050	123
5.27	Relationship between S_{11} and S_{21} against AR of EFBPLA1090	124
5.28	Relationship between S_{11} and S_{21} against AR of PALFPLA5050	124
5.29	Relationship between S_{11} and S_{21} against $\tan \delta$ of OPFPLA5050	125
5.30	Relationship between S_{11} and S_{21} against $\tan \delta$ of EFBPLA1090	126
5.31	Relationship between S_{11} and S_{21} against $\tan \delta$ of PALFPLA5050	126
5.32	Relationship between S_{11} and S_{21} against ϵ_r' of OPFPLA5050	128
5.33	Relationship between S_{11} and S_{21} against ϵ_r' of EFBPLA1090	128
5.34	Relationship between S_{11} and S_{21} against ϵ_r' of PALFPLA5050	129

5.35	Relationship between absorption rates and optimized MA thickness for OPFPLA5050	130
5.36	Relationship between absorption rates and optimized MA thickness for EFBPLA1090	130
5.37	Relationship between absorption rates and optimized MA thickness for PALFPLA5050	131
5.38	Relationship between thickness against ϵ_r' of OPFPLA5050	132
5.39	Relationship between thickness against ϵ_r' of EFBPLA1090	132
5.40	Relationship between thickness against ϵ_r' of PALFPLA5050	133
5.41	Relationship between thickness and loss tangent of OPFPLA5050	134
5.42	Relationship between thickness and loss tangent of EFBPLA5050	134
5.43	Relationship between thickness and loss tangent of PALFPLA5050	135
5.44	Optimum Absorption Rates within full span of X band	136
5.45	OPFPLA5050 S11 and S21 based on TE and TM polarization.	137
5.46	OPFPLA5050 MA Bandwidth	138
5.47	OPFPLA5050 MA Absorption Bandwidth	139
5.48	Effect of variation of phi angles to OPFPLA5050 biocomposite	141
5.49	Effect of variation of theta angles to OPFPLA5050 biocomposite	142
6.1	Focus of Chapter 6	145
6.2	(a) Dimensions of the center mould (b) Fabricated OPFPLA5050 MA	146
6.3	Results of measured OPFPLA5050 MA in relative to the simulation	147
6.4	Absorption Rates for measured and simulated OPFPLA5050 MA	148
6.5	Results of the readjustment of OPFPLA5050 MA thickness d	149
6.6	Results of the readjustment of OPFPLA5050 dielectric constant, ϵ'	151
6.7	Results of the readjustment of OPFPLA5050 loss tangent, $\tan \delta$	152
6.8	Final results of the readjustment of OPFPLA5050 properties	153
6.9	Comparison between fine tune of measured and simulated OPFPLA5050	155
6.10	Comparison between fine tune measured and simulated OPFPLA5050 in variation of ϕ	156
6.11	Comparison between fine tune measured and simulated OPFPLA5050 by varying θ for TE polarization	158
6.12	Comparison between fine tune measured and simulated OPFPLA5050 with varying θ for TM polarization	160

LIST OF ABBREVIATIONS

ε	Permittivity
ε_r	Dielectric constant,
μ	Permeability
σ	Conductivity
ρ	Density
m	Mass
v	Volume
$\tan \delta$	Loss tangent
S_{11}	Reflection
S_{21}	Transmission
MHz	Mega hertz
CST	Computer Simulation Technology
EFB	Empty fruit bunches
OPF	Oil palm frond
PALF	Pineapple Leaf Fibre
PLA	Polylactic acid
MUT	Material under test
VNA	Vector network analyser
SUT.	Sample under test
CST	Computer Simulation Technology
MA	Microwave Absorber
w	Width
l	Length
d	Thickness
FOM	Figure of merit
AR	Absorption Rates
dB	Decibel

CHAPTER 1

INTRODUCTION

1.1 Research Background

Urbanization and economic growth over the past few years have increased the consumption of resources such as electronic, and energy resources. With the increment in demand due to technological change in the society, have also created an impact towards producing more new products and processes. With so many research and development to meet this needs, improvements and also limitations are revealed through the products and systems.

As the industries and manufacturer taking advantage of evolution of engineering technology, there are three principle of development which need to be considered. One is no waste where it is a discipline applied at all stages of design, appraisal, manufacturer, use, re-use, recycling and disposal. Second is the environment is to considered at every stage and finally 'valuable' where it preserves or enhances the environment and life processes (Baillie, 2004).

Biocomposite are those natural fibers reinforced with natural polymers (Mngomezulu *et al.*, 2014). Natural fiber are greatly used for applications in composite manufacturing (Faruk *et al.*, 2012). Natural fibers such as plant fibers are used to replace synthetic fibers in composites because of its sustainability. Natural polymer are biodegradable eco-friendly material with low environmental loads, which can be decomposed by microbes (Ohki *et al.*, 2007). There are may be natural, synthetic or semi-synthetic in origin polymer types. They are synthesized by the process called polymerization and if the combining monomers which may be two or more are different then the resultant is called copolymer (Chauhan, 2012). Biodegradable biocomposite are low cost, low relative density, and high specific strength, the interfacial adhesion between fiber and matrix is still an issue (Faruk *et al.*, 2012) which benefits the future.

Microwave absorbers (MA) are absorber materials that have been used for electromagnetic interference isolation and radio frequency absorption. There are many applications of (MA) from as low as 300 MHz up to 300 GHz (Raveendran and Sebastian, 2019), from a simple circuitry up to military application for stealth technology (Edries *et al.*, 2019). In the MA material, two important parameter that determines the absorption performance are the dielectric and magnetic losses. The higher the loss the more electromagnetic signal will be absorbed (Vinoy and Jha, 1996a). In addition to that, the MA design for example its physical thickness or resonator layer also plays an important role in achieving good absorber performance such as unity absorption rates, wide bandwidth, covers all polarizations and all incident angles (Tirkey and Gupta, 2019) which then reflect to the potential application of the MA themselves at the operating frequencies. According to

Khanna, 2020, by having MA design with a the closed ring structure indicates the absorption rates of 10% whilst a ring with dual split, the absorption increases to 90% for K and Ku-band application. As reported by Pandit *et al.*, 2018, more than 80 % of both of TE and TM polarized incident waves is absorbed for a wide incident angle for a single-layer of thickness 3.2 mm microwave absorber for stealth applications

This thesis presents, the microwave absorber based on the newly developed agriculture wastes derived biocomposite with the reinforcement of poly-lactic acid (PLA). The MA material properties that are significant at X band frequency range made from cheap, low density and biodegradable biocomposite that has dielectric properties with high loss tangents. The combination of prospective fibres and PLA show potential wave absorption will give impact to the research of microwave absorber application and environmental issues.

1.2 Problem Statement and Motivation

Due to the materials utilised at microwave frequencies, microwave materials have been widely used in a number of applications ranging from communication devices to military satellite services. The wavelength and velocity of electromagnetic waves vary within a material medium according to their dielectric properties. In recent studies of microwave absorber, there have been many reports in the use of magnetic, carbon based, biomaterials and metamaterial (Raveendran and Sebastian, 2019). Many studies have been drawn to biomaterial or biocomposites because of their ease of disposal and ability to compost after the expiration date, which is not often attainable with typical synthetic materials (Yıldızhan *et al.*, 2018). The use of natural fiber as filler for the biocomposites has also gained a lot of attention for their absorption properties. This includes the use of rice straw, sugar cane bagasse, coconut shell, rubber wood saw dust, rice husk, dried banana leaves, and bamboo-based ash (Raveendran and Sebastian, 2019). Natural fibers such as oil palm fronds (OPF) and empty fruit bunch (EFB) are agricultural wastes in Malaysia as the second largest oil palm plantation area in the world (Nordin, Sulaiman and Hashim, 2017) meanwhile pineapple leaf fiber (PALF) are a waste product of pineapple cultivation (Saravanakumar *et al.*, 2020) where Malaysia being part of 448,193 metric tonnes of the pineapple production (Adam, Yusof and Yahya, 2016). This means higher production in oil palm and pineapple will increase the amount of agricultural wastes and if not properly managed, they may intensify environmental issues. These fibers, on the other hand, have been widely examined in many fields such as biomass for biofuel (Abdul Khalil *et al.*, 2016), in the application of automotive and construction industries (Sudamrao and Patel, 2020), as fabrics for textile materials and in the manufacture of yarns and handicrafts in many countries (Leão *et al.*, 2015) due to their chemical and mechanical advantages which makes them less noticeable in microwave absorber applications.

Several reports show that there are many types of eco-friendly or renewable material binder used as matrix in the biocomposite for absorber application including polyester resin, and methyl ethyl ketone peroxide (Zahid *et al.*, 2013), polyol and isocyanate to produce activated carbon loaded polyurethane foam (Se *et al.*, 2011) and multi wall carbon nano tube (MWCNT) (Lee *et al.*, 2016). PLA also one of the renewable material which is commercial bio-based, biodegradable, biocompatible, compostable and non-toxic polymer that has competitive material and processing costs, as well as having desirable mechanical properties (Nofar *et al.*, 2019). PLA have been utilized in many application including commodity and biomedical applications (Tsuji, 2016) and 3D printing application (Pal *et al.*, 2020). PLA has the drawback for low melt strength, slow crystallization rate, poor processability, high brittleness, low toughness, and low service temperature, which limit its applications (Nofar *et al.*, 2019). To overcome this PLA is blended with various natural fibers to improve the chemical and mechanical properties (Rajeshkumar *et al.*, 2021) as well as its dielectric properties. However, very less report found on the dielectric properties for fiber reinforced PLA biocomposites particularly between OPF, EFB and PALF with PLA respectively.

Generally, microwave absorber performance are based on its strong absorption, wide bandwidth, light weight (Li *et al.*, 2018) easy fabrication and low cost (Yah *et al.*, 2019). A good absorption is due to the material used where its depends on their complex permittivity and permeability for the concern frequency range (Yah *et al.*, 2019). For biocomposite material, the dielectric constant, ϵ' and lost tangent, $\tan \delta$ are the key features for good absorption where the material with higher $\tan \delta$ demonstrates higher absorption (Y. S. Lee *et al.*, 2013). In addition to that, high absorption also depends on the minimum reflection and transmission factors (Tian *et al.*, 2020) within the material. Many reports show free space reflectivity measurement (Kharber *et al.*, 2018), and monostatic and bistatic measurements (Masaki *et al.*, 2017) are used for determining the absorption of the MA. It is a non-destructive method where applicable to large samples and they are simple to prepare. This measurement yields reflection results, but it is also necessary to obtain transmission results. As a result, a free space tunnel method (Vinoy and Jha, 1996a) is used to obtain both parameters, reflection and transmission, from the same sample in order to determine absorption. Furthermore, large absorption bandwidth is one of the key features of MA (Tirkey and Gupta, 2019). Obtaining wideband properties is one of the primary difficulties while constructing a microwave absorber (Kumar and Singh, 2016) and to able to achieve that, the MA design tends to be thick and bulkier or multi-layer absorber. The concern with this is that, thick and bulky absorber limits its application and usually impractical (Yah *et al.*, 2019) and furthermore, the it gains in cost in the material and difficult in fabrication.

To reduce the effect on environment, to obtain good microwave absorption and to able practically fabricate a microwave absorber, the agricultural wates such as OPF, EFB and PALF are mixed with PLA to become a biocomposite where the material properties such as permittivity and loss tangent are characterized for microwave absorber application in the X-band region. The material with high loss tangent is determined from the characterized biocomposite using both reflection and

REFERENCES

- Abdul Khalil, H. P. S. *et al.* (2016) 'Oil Palm Biomass Fibres and Recent Advancement in Oil Palm Biomass Fibres Based Hybrid Biocomposites', *Intech*, (tourism), p. 13. doi: <http://dx.doi.org/10.5772/57353>.
- Abdullah, H. *et al.* (2013) 'Performance study of preliminary mini anechoic chamber fitted with coconut shell coated absorbers', *2013 IEEE International Conference on Control System, Computing and Engineering*. Ieee, pp. 602–607. doi: 10.1109/ICCSC.2013.6720036.
- Adam, A. *et al.* (2017) 'Microwave dielectric properties of Malaysian palm oil and agricultural industrial biomass and biochar during pyrolysis process', *Fuel Processing Technology*. Elsevier B.V., 166, pp. 164–173. doi: 10.1016/j.fuproc.2017.06.006.
- Adam, A., Yusof, Y. and Yahya, A. (2016) 'Extraction of pineapple leaf fibre: Josapine and moris', *ARPN Journal of Engineering and Applied Sciences*, 11(1), pp. 161–165.
- Agilent Technologies (2013) *Agilent Basics of Measuring the Dielectric Properties of Materials*.
- Ahmad Zawawi, N. (2013) *Dielectric Constant and Loss Tangent Charcterization of Natural Fibers Reinforced with Polypropylene for RF/Microwave Application*.
- Alam, A. K. M. M. *et al.* (2012) 'Composites : Part A Structures and performances of simultaneous ultrasound and alkali treated oil palm empty fruit bunch fiber reinforced poly (lactic acid) composites', *Composites Part A*. Elsevier Ltd, 43(11), pp. 1921–1929. doi: 10.1016/j.compositesa.2012.06.012.
- Amar K. Mohanty, Manjusri Misra, L. T. D. (2005) *Natural Fibers, Biopolymers and Biocomposite*. CRC Press Taylor & Francis Group.
- Ameenah, A. *et al.* (2019) 'Microwave-assisted pyrolysis of EFB-derived biochar as potential renewable solid fuel for power generation : Biochar versus sub-bituminous coal', 142. doi: 10.1016/j.renene.2019.04.035.
- Annapurna, D. and Sisir, K. Das (2001) *Microwave Engineering*. McGraw-Hill.
- Asim, M. *et al.* (2015) 'A Review on Pineapple Leaves Fibre and Its Composites', *Hindawi Publishing Corporation*, 2015.
- Asim, M. *et al.* (2018) 'Thermal, physical properties and flammability of silane treated kenaf/pineapple leaf fibres phenolic hybrid composites', *Composite Structures*. Elsevier, 202(February), pp. 1330–1338. doi: 10.1016/j.compstruct.2018.06.068.

- Bahar, A. A. M. *et al.* (2017) 'Microstrip planar resonator sensors for accurate dielectric measurement of microfluidic solutions', *2016 3rd International Conference on Electronic Design, ICED 2016*, pp. 416–421. doi: 10.1109/ICED.2016.7804680.
- Baillie, C. (ed.) (2004) *Green Composites - Polymer composites and the environment*. Woodhead Publishing Limited.
- Bell, E. C. *et al.* (1971) 'Anechoic chamber of novel design', pp. 841–848.
- Błędzki, A. K. *et al.* (2012) 'Biocomposites in the Past and in the Future', (96), pp. 15–22.
- Boreddy, S. R. and Subbiah, J. (2016) 'Temperature and moisture dependent dielectric properties of egg white powder', *Journal of Food Engineering*. Elsevier Ltd, 168, pp. 60–67. doi: 10.1016/j.jfoodeng.2015.07.023.
- Carruthers, J. and Quarshie, R. (2014) 'Technology Overview Biocomposites', *NetComposites*, p. 70. Available at: <https://netcomposites.com/media/1211/biocomposites-guide.pdf>.
- Chala, G. T. *et al.* (2018) 'Thermogravimetric analysis of empty fruit bunch', *MATEC Web Conference*, 02002, pp. 1–6.
- Chauhan, A. (2012) 'Environment-Friendly Biodegradable Polymers and Their Applications', *Journal, Malaysian Polymer*, 7(2), pp. 62–67.
- Chawla K., K. (1993) *Ceramic Matrix Composite*. London: Chapman and Hall.
- Cheldavi, A. and Kamarei, M. (1997) 'Practical optimum design for a single-layer electromagnetic wave absorber at C and X-band using genetic algorithm', *IEEE Antennas and Propagation Society, AP-S International Symposium (Digest)*, 3, pp. 1708–1711. doi: 10.1109/aps.1997.631506.
- Chen, L. F. *et al.* (2004) *Microwave Electronics: Measurement and Materials Characterisation*. John Wiley & Sons, Ltd.
- Choi, J. H. *et al.* (2020) 'Investigation on microwave absorption characteristics of conductive-coated honeycomb absorber', *Composite Structures*. Elsevier, 242(January), p. 112129. doi: 10.1016/j.compstruct.2020.112129.
- Choo, H. *et al.* (2003) 'Shape Optimization of Corrugated Coatings Under Grazing Incidence Using a Genetic Algorithm', 51(11), pp. 3080–3087.
- Collier, R. and Skinner, D. (2007) *Microwave Measurement*. 3rd Editio. Edited by R. Collier and D. Siknner. The Institution of Engineering and Technology.
- Crerar, X. L. L. G. T. S. P. w. J. (2014) 'The Influence of Fiber Content on Properties of Injection Molded Flax Fiber- The Influence of Fiber Content on Properties of Injection Molded Flax Fiber-HDPE Biocomposites', *The Canadian Society for Bioengineering*, (October 2006). doi: 10.13031/2013.22101.

- Cruickshank, D. B. (2011) *Microwave Materials for Wireless Application*. Artech House.
- Djordjevi, Z., Gavrilovi, O. and Savi, S. (2016) 'Biocomposites – Ecologically Acceptable Materials', *1st International Conference on Quality of Life, June 2016*, (June), pp. 267–270.
- Duggal, S., Aul, G. D. and Chawla, V. (2017) 'Investigation of absorption properties of Sugarcane Bagasse-Coal pyramidal microwave absorber', *Asia-Pacific Microwave Conference Proceedings, APMC*, 0. doi: 10.1109/APMC.2016.7931361.
- Edries, M. *et al.* (2019) 'Literature review on radar absorbers using metamaterials', *2019 URSI International Symposium on Electromagnetic Theory, EMTS 2019*. URSI, (May), pp. 15–18. doi: 10.23919/URSI-EMTS.2019.8931453.
- Fan, S. (2020) 'Ultra-Wideband Flexible Absorber in Microwave Frequency Band'. doi: 10.3390/ma13214883.
- Farhany, Z. S. *et al.* (2012) 'Potential of dried banana leaves for pyramidal microwave absorber design', *IEEE Symposium on Wireless Technology and Applications, ISWTA*. IEEE, pp. 60–65. doi: 10.1109/ISWTA.2012.6373878.
- Faruk, O. *et al.* (2012) 'Biocomposites reinforced with natural fibers: 2000–2010', *Progress in Polymer Science*. Elsevier Ltd, pp. 2000–2010. doi: 10.1016/j.progpolymsci.2012.04.003.
- Fayazbakhsh, K. and Abedian, A. (2012) 'Materials selection for electronic enclosures in space environment considering electromagnetic interference effect', *Advances in Space Research*. COSPAR, 49(3), pp. 586–593. doi: 10.1016/j.asr.2011.10.025.
- Gagnon, N. *et al.* (2004) 'Low-cost free-space measurement of dielectric constant at Ka band', pp. 271–276. doi: 10.1049/ip-map.
- Ghosh, S., Nguyen, T. T. and Lim, S. (2019) 'Recent progress in angle-insensitive narrowband and broadband metamaterial absorbers', 12.
- Goda, K. *et al.* (2014) 'Advances in Polymer Composites : Biocomposites – State of the Art , New Challenges , and Opportunities', 3.
- Graupner, N., Herrmann, A. S. and Müssig, J. (2009) 'Natural and man-made cellulose fibre-reinforced poly(lactic acid) (PLA) composites: An overview about mechanical characteristics and application areas', *Composites Part A: Applied Science and Manufacturing*. Elsevier Ltd, 40(6–7), pp. 810–821. doi: 10.1016/j.compositesa.2009.04.003.
- Guo, W. *et al.* (2008) 'Frequency, moisture and temperature-dependent dielectric properties of chickpea flour', *Biosystems Engineering*. IAgRE, 101(2), pp. 217–224. doi: 10.1016/j.biosystemseng.2008.07.002.

- Haraguchi, K. (2014) 'Biocomposites Recent Studies on Biocomposites Fundamental Properties of NC Gels and M-NCs', *Encyclopedia of Polymeric Nanomaterial*, pp. 1–8. doi: 10.1007/978-3-642-36199-9.
- Hardiati, S. *et al.* (2017) 'Performance of microwave absorbers with fabric form in S-band operational frequency', *Proceeding - 2016 International Conference on Radar, Antenna, Microwave, Electronics, and Telecommunications, ICRAMET 2016*, pp. 67–70. doi: 10.1109/ICRAMET.2016.7849584.
- Hee, K., Putra, A. and Zulkefli, M. (2017) 'Oil palm empty fruit bunch fibres as sustainable acoustic absorber', 119, pp. 9–16.
- Hegde, V. (2018) *Dielectric Study of Biodegradable and/or Bio-based Polymeric Material*.
- hollandshielding.com (2019) *Rubber flat narrowband absorber*.
- Hong, L. S., Ibrahim, D. and Omar, I. C. (2012) 'Oil Palm Frond for the Production of Bioethanol', 1(1), pp. 7–11.
- Hoque, A. *et al.* (2019) 'A New Split Pitch Square Shape Metamaterial Absorber for X band Application', (July), pp. 28–30.
- Hu, R. *et al.* (2019) 'The Design of A Single-layer Broadband Metamaterial Absorber', *2019 International Symposium on Antennas and Propagation, ISAP 2019 - Proceedings*, (3), pp. 6–8.
- Ibrahim, I. M. *et al.* (2011) 'on the Pyramidal Microwave Absorbers', (3), pp. 141–145.
- ITU-T (2015) *Nomenclature of the frequency and wavelengh bands used in telecommunications V Series*.
- Jaji, K., Man, N. and Nawi, N. . (2018) 'Factors affecting pineapple market supply in Johor, Malaysia', *International Food Research Journal*, 25(February), pp. 366–375.
- Jamal, R. (2019) 'A basic concept to anechoic chamber and determination of highly selective absorber material with respect to insertion loss and refection coefficient', *International Journal of Applied Engineering Research ISSN 0973-4562*, 14(2), pp. 196–199.
- Jawaid, M. and Khalil, H. P. S. A. (2011) 'Cellulosic / synthetic fibre reinforced polymer hybrid composites : A review', *Carbohydrate Polymers*. Elsevier Ltd., 86(1), pp. 1–18. doi: 10.1016/j.carbpol.2011.04.043.
- John, M. J. and Thomas, S. (2008) 'Biofibres and biocomposites', 71, pp. 343–364. doi: 10.1016/j.carbpol.2007.05.040.
- Kaur, R., Aul, G. D. and Chawla, V. (2015) 'Improved Reflection Loss Performance of Dried Banana Leaves Pyramidal Microwave Absorbers by Coal for Application in Anechoic Chambers', *Progress In Electromagnetics Research M*, 43(July), pp. 157–164.

- Khanna, Y. (2020) 'Wideband Ultra-thin Metamaterial Absorber for Ku & K- Band Applications', (1).
- Kharber, N. N. *et al.* (2017) 'Preliminary study of palm oil biomass cement based microwave absorber', *Proceedings - 6th IEEE International Conference on Control System, Computing and Engineering, ICCSCE 2016*. IEEE, (November), pp. 557–562. doi: 10.1109/ICCSCE.2016.7893638.
- Kharber, N. N. *et al.* (2018) 'Characteristic of biomass percentage in cement brick composites microwave absorber', *2017 International Conference on Electrical, Electronics and System Engineering, ICEESE 2017*, 2018-Janua, pp. 21–26. doi: 10.1109/ICEESE.2017.8298390.
- Kolop, R., Hazima, W. I. . and Eng, J. W. (2006) 'Properties of Cement Blocks Containing High Content of Oil Palm Empty Fruit Bunches (EFB) Fibres', in.
- Krishna, V. *et al.* (2019) 'Additive manufacturing of natural fiber reinforced polymer composites : Processing and prospects', *Composites Part B*. Elsevier Ltd, 174(May), p. 106956. doi: 10.1016/j.compositesb.2019.106956.
- Kumar, A. and Singh, S. (2016) 'Design of two-layer microwave absorber at X-band using genetic algorithm', in *11th International Conference on Industrial and Information Systems, ICIIS 2016 - Conference Proceedings*, pp. 503–506. doi: 10.1109/ICIINFS.2016.8262992.
- Kumar, P., Ingle, A. and Jhavar, S. (2019) 'Parametric review of microwave-based materials processing and its applications', *Integrative Medicine Research*. Elsevier B.V., 8(3), pp. 3306–3326. doi: 10.1016/j.jmrt.2019.04.004.
- Kundu, D., Mohan, A. and Chakrabarty, A. (2015) 'Thickness Reduction of Single Layer Circuit Analog Absorber'. IEEE, pp. 11–12.
- Laemsak, Nikhom *et al.* (2000) 'Development of boards made from oil palm frond Ih properties of binderless boards from steam-exploded fibers of oil palm frond', *J Wood Sci*, 46(November 1998), pp. 322–326. doi: 10.1007/BF00766224.
- lairdtech.com (2017) *ECCOSORB* ® AN *Eccosorb* ® AN.
- Leão, A. L. *et al.* (2015) 'The use of pineapple leaf fibers (PALFs) as reinforcements in composites', *Biofiber Reinforcements in Composite Materials*, pp. 211–235. doi: 10.1533/9781782421276.2.211.
- Lee, C. *et al.* (2019) 'Evaluation of Microwave Characterization Methods for Additively Manufactured Materials'.
- Lee, Y. S. *et al.* (2013) 'Difference loss tangent layer microwave absorber effect absorption in X-band frequency', *2013 IEEE International RF and Microwave Conference (RFM)*. Ieee, pp. 425–428. doi: 10.1109/RFM.2013.6757298.

- Lee, Y S *et al.* (2013) 'Difference Loss Tangent Layer Microwave Absorber Effect Absorption in X-band Frequency', pp. 425–428.
- Lee, Y. S. *et al.* (2016) 'Single Layer Microwave Absorber based on Rice Husks-MWCNTs Composites', 11(14), pp. 8932–8937.
- Lembaga Perindustrian Nanas Malaysia (2004) *Pengurusan Tanaman Nanas Malaysia*. Available at: <http://www.mpib.gov.my/pengurusan-tanaman-nanas/>.
- Li, F. *et al.* (2018) 'A thin broadband microwave absorber with hexagonal resistive frequency selective surface', *IEEE Antennas and Wireless Propagation Letters*. IEEE, 60(8). doi: 10.1109/LAWP.2018.2830413.
- Li, M. *et al.* (2020) 'Recent advancements of plant-based natural fiber – reinforced composites and their applications ☆', 200(February). doi: 10.1016/j.compositesb.2020.108254.
- Lim, D., Lee, D. and Lim, S. (2016) 'Angle- and Polarization-Insensitive Metamaterial Absorber using Via Array', *Nature Publishing Group*. Nature Publishing Group, pp. 1–9. doi: 10.1038/srep39686.
- Lim, L.-T., Auras, R. and Rubino, M. (2008) 'Processing technologies for poly(lactic acid)', *Progress in Polymer Science*, 33(8), pp. 820–852. doi: 10.1016/j.progpolymsci.2008.05.004.
- Liyana, Z., Malek, F., Nornikman, H., Mohd Affendi, N. A., *et al.* (2012) 'Investigation of sugar cane bagasse as alternative material for pyramidal microwave absorber design', *IEEE Symposium on Wireless Technology and Applications, ISWTA*. IEEE, pp. 66–70. doi: 10.1109/ISWTA.2012.6373879.
- Liyana, Z., Malek, F., Nornikman, H., Mohd Affendi, N. a., *et al.* (2012) 'Investigation of sugar cane bagasse as alternative material for pyramidal microwave absorber design', *2012 IEEE Symposium on Wireless Technology and Applications (ISWTA)*. Ieee, pp. 66–70. doi: 10.1109/ISWTA.2012.6373879.
- Lohr, C. *et al.* (2019) 'Mechanical properties of foamed long glass fiber reinforced polyphenylene sulfide integral sandwich structures manufactured by direct thermoplastic foam injection molding', *Composite Structures*. Elsevier, 220(February), pp. 371–385. doi: 10.1016/j.compstruct.2019.03.056.
- Masaki, T. *et al.* (2017) 'Monostatic and Bistatic RCS Measurements for Thin Metasurfaces', pp. 351–352.
- Mathew, B. *et al.* (2011) 'Cellulose nanocomposites with nanofibres isolated from pineapple leaf fibers for medical applications', *Carbohydrate Polymers*. Elsevier Ltd., 86(4), pp. 1790–1798. doi: 10.1016/j.carbpol.2011.07.009.

- Micheli, D., Apollo, C., *et al.* (2011) 'Acta Astronautica Nanostructured composite materials for electromagnetic interference shielding applications \$', *Acta Astronautica*. Elsevier, 69(9–10), pp. 747–757. doi: 10.1016/j.actaastro.2011.06.004.
- Micheli, D., Pastore, R., *et al.* (2011) 'Broadband Electromagnetic Absorbers Using Carbon Nanostructure-Based Composites', 59(10), pp. 2633–2646.
- Micheli, D., Apollo, C. and Pastore, R. (2011) 'Electromagnetic Characterization of Composite Materials and Microwave Absorbing Modeling', in Reddy, D. B. (ed.) *Advances in Nanocomposites - Synthesis, Characterization and Industrial Applications*. InTech, p. 966.
- Mngomezulu, M. E. *et al.* (2014) 'Review on flammability of biofibres and biocomposites', *Carbohydrate Polymers*. Elsevier Ltd., 111, pp. 149–182. doi: 10.1016/j.carbpol.2014.03.071.
- Mohamed Yusoff, M. Z. *et al.* (2010) 'Mechanical Properties of Short Random Oil Palm Fibre Reinforced Epoxy Composites', *Sains Malaysiana*, 39(1), pp. 87–92.
- Mohideen, M. F. *et al.* (2011) 'Drying of oil palm frond via swirling fluidization technique', *Proceedings of the World Congress on Engineering 2011, WCE 2011*, 3, pp. 2375–2380.
- Nanjing, T. (2014) 'Bandwidth Enhancement of Folded Dipole-based Microwave Absorber Surface', pp. 262–263.
- Nawal, K. A. and Gupta, S. C. (1992) 'Design Of a Single Layer Broadband Microwave Absorber Using Cobalt-Substituted Barium Hexagonal Ferrite', pp. 317–320.
- Nelson, S. and Kraszewski, A. W. (1998) 'Resonant Cavity Measurements', pp. 589–591.
- Nelson, S. O. (2005) 'Density-Permittivity Relationships for Powdered and Granular Materials', 54(5), pp. 2033–2040.
- Nelson, S. and Philip, F. (2001) 'Measuring Frequency- and Temperature-Dependent Permittivities of Food Materials', *IEEE Instrumentaion and Measurement Technology Conference*, pp. 975–978.
- Nofar, M. *et al.* (2019) 'International Journal of Biological Macromolecules Poly (lactic acid) blends : Processing , properties and applications', *International Journal of Biological Macromolecules*. Elsevier B.V., 125, pp. 307–360. doi: 10.1016/j.ijbiomac.2018.12.002.
- Nordin, N. A., Sulaiman, O. and Hashim, R. (2017) 'Oil Palm Frond Waste for the Production of Cellulose Nanocrystals', *Journal of Physical Science*, 28(2), pp. 115–126.

- Nornikman, H. *et al.* (2009) ‘Investigation of an Agricultural Waste as an Alternative Material for Microwave Absorbers’, *Progress In Electromagnetics Research Online*, pp. 3–7.
- Nornikman, H. *et al.* (2010) ‘Reflection loss performance of hexagonal base pyramid microwave absorber using different agricultural waste material’, in *2010 Loughborough Antennas & Propagation Conference*. IEEE, pp. 313–316. doi: 10.1109/LAPC.2010.5666029.
- Nornikman, H. and Malek, F. (2010) ‘Parametric Studies of the Pyramidal Microwave Absorber using Rice Husk’, pp. 145–166.
- Ohki, Y. *et al.* (2007) ‘Search for Adequate Biodegradable Polymer as an Eco-friendly Electrical Insulating Material’, 07, pp. 488–493.
- Orloff, N. D. *et al.* (2014) ‘Dielectric characterization by microwave cavity perturbation corrected for nonuniform fields’, *IEEE Transactions on Microwave Theory and Techniques*, 62(9). doi: 10.1109/TMTT.2014.2336775.
- Ozden, K., Mert, O. and Kocer, H. (2016) ‘Metamaterial based broadband RF absorber at X-band’, 70, pp. 1062–1070.
- Pal, A. K. *et al.* (2020) ‘Materials Today Sustainability Recycled poly (lactic acid) e based 3D printed sustainable biocomposites : a comparative study with injection molding’, 8, pp. 1–12. doi: 10.1016/j.mtsust.2019.100027.
- Pandit, S., Mohan, A. and Ray, P. (2018a) ‘Single-layer wideband wide-angle microwave absorber for stealth applications’, *IEEE MTT-S International Microwave and RF Conference, IMArc 2018*. IEEE, pp. 2018–2020. doi: 10.1109/IMaRC.2018.8877201.
- Pandit, S., Mohan, A. and Ray, P. (2018b) ‘Single-Layer Wideband Wide-Angle Microwave Absorber for Stealth Applications’, *2018 IEEE MTT-S International Microwave and RF Conference (IMaRC)*. IEEE, pp. 1–3.
- Pattanayak, S. S., Laskar, S. H. and Sahoo, S. (2019) ‘Modelling Coconut Fiber Coir and Charcoal Powder Made Microwave Absorber over X-band Frequency’, *2019 IEEE 5th International Conference for Convergence in Technology, I2CT 2019*. IEEE, (4), pp. 6–9. doi: 10.1109/I2CT45611.2019.9033898.
- Pozar, D. M. (2005) *Microwave Engineering*. 3rd edn. John Wiley & Sons, Ltd.
- Rahayu, I. *et al.* (2012) ‘Investigation of Oil Palm Ash Microwave Absorber for Broadband Application .’, pp. 232–235.
- Rajeshkumar, G. *et al.* (2021) ‘Environment friendly , renewable and sustainable poly lactic acid (PLA) based natural fiber reinforced composites – A comprehensive review’, *Journal of Cleaner Production*. Elsevier Ltd, 310(April), p. 127483. doi: 10.1016/j.jclepro.2021.127483.
- Raveendran, A. and Sebastian, M. T. (2019) ‘Applications of Microwave Materials : A Review’, 48(5). doi: 10.1007/s11664-019-07049-1.

- Reddy, N. and Yang, Y. (2005) 'Biofibers from agricultural byproducts for industrial applications', 23(1). doi: 10.1016/j.tibtech.2004.11.002.
- Rianto, D. and Putra, A. (2017) 'Study of Single Layer Radar Absorber Material (RAM) Based on Coconut Shell Activated Carbon', pp. 19–22.
- Sadashiv, S. and Abasaheb, S. (2019) 'Review on mechanical properties evaluation of pineapple leaf fibre (PALF) reinforced polymer composites', *Composites Part B*. Elsevier Ltd, 174(May), p. 106927. doi: 10.1016/j.compositesb.2019.106927.
- Salleh, M. K. *et al.* (2013) 'Chebyshev multi-layer microwave absorber design', *2013 IEEE International RF and Microwave Conference (RFM)*. Ieee, 1(1), pp. 306–309. doi: 10.1109/RFM.2013.6757272.
- Salleh, M K M *et al.* (2011a) 'Binomial Multi-Layer Coconut Shell-Based Rubber Microwave Absorber Design', (December), pp. 187–190.
- Salleh, M K M *et al.* (2011b) 'Experimental Verification of Multi-Layer Coconut Shell-Derived Microwave Absorbers', (December), pp. 115–118.
- Salleh, M. K. M. *et al.* (2011) 'Single layer coconut shell-based microwave absorbers', *TENCON 2011 - 2011 IEEE Region 10 Conference*. Ieee, pp. 1110–1113. doi: 10.1109/TENCON.2011.6129283.
- Salleh, M K M *et al.* (2011c) 'Single Layer Coconut Shell-Based Microwave Absorbers', pp. 10–13.
- Sarasini, F. and Fiore, V. (2018) 'A systematic literature review on less common natural fibres and their biocomposites', *Journal of Cleaner Production*. Elsevier Ltd, 195, pp. 240–267. doi: 10.1016/j.jclepro.2018.05.197.
- Saravanakumar, M. *et al.* (2020) 'Materials Today : Proceedings Influence of fiber loading on mechanical characterization of pineapple leaf and kenaf fibers reinforced polyester composites', *Materials Today: Proceedings*. Elsevier Ltd., (xxxx). doi: 10.1016/j.matpr.2020.09.804.
- Saville, P. (2005) *Review of Radar Absorbing Materials Defence R & D Canada – Atlantic*.
- Se, S. M. *et al.* (2011) 'Microwave Absorbing Material Using Rubberwood Sawdust', pp. 192–197.
- Seman, F. C. *et al.* (2011) 'PERFORMANCE ENHANCEMENT OF SALISBURY SCREEN ABSORBER USING', 53(7), pp. 1538–1541. doi: 10.1002/mop.
- Seman, F. C. and Goussetis, R. C. V. F. F. G. (2011) 'Design of a Salisbury screen absorber using frequency selective surfaces to improve bandwidth and angular stability performance', 0072(May 2010). doi: 10.1049/iet-map.2010.0072.

- Sheen, J. (2009) 'Measurements of microwave dielectric properties by an amended cavity perturbation technique', *Measurement*. Elsevier Ltd, 42(1), pp. 57–61. doi: 10.1016/j.measurement.2008.03.017.
- Shinoj, S. *et al.* (2011) 'Oil palm fiber (OPF) and its composites : A review', *Industrial Crops & Products*. Elsevier B.V., 33(1), pp. 7–22. doi: 10.1016/j.indcrop.2010.09.009.
- Shinozaki, Y. and Arai, H. (2019) 'A Single Layer Microwave Absorber using FSS of Notched Circular Patch', *ISAP 2018 - 2018 International Symposium on Antennas and Propagation*. KIEES, pp. 9–10.
- Singh, M., Kaur, M. and John, S. (2013) 'E-waste: Challenges and opportunities in India', *2013 IEEE Global Humanitarian Technology Conference: South Asia Satellite (GHTC-SAS)*. Ieee, pp. 128–133. doi: 10.1109/GHTC-SAS.2013.6629902.
- Soheilifar, M. R. and Sadeghzadeh, R. A. (2015) 'Design, fabrication and characterization of stacked layers planar broadband metamaterial absorber at microwave frequency', *AEU - International Journal of Electronics and Communications*, 69(1), pp. 126–132. doi: 10.1016/j.aeue.2014.08.005.
- Sohrab, A. P., Member, S. and Atlasbaf, Z. (2013) 'A Circuit Analog Absorber With Optimum Thickness and Response in X-Band', 12(2), pp. 276–279.
- Soroudi, A. and Jakubowicz, I. (2013) 'Recycling of bioplastics , their blends and biocomposites : A review', *European Polymer Journal*. Elsevier Ltd, 49(10), pp. 2839–2858. doi: 10.1016/j.eurpolymj.2013.07.025.
- Sudamrao, A. and Patel, B. (2020) 'Materials Today : Proceedings A Review : Bio-fiber ' s as reinforcement in composites of polylactic acid (PLA)', *Materials Today: Proceedings*. Elsevier Ltd., 26, pp. 2116–2122. doi: 10.1016/j.matpr.2020.02.457.
- Tennant, A. and Chambers, B. (2004) 'A Single-Layer Tuneable Microwave Absorber Using an Active FSS', *IEEE Microwave and Wireless Components Letters*, 14(1), pp. 46–47. doi: 10.1109/LMWC.2003.820639.
- Tian, Y. *et al.* (2020) 'Customized Inverse Design of Metamaterial Absorber Based on Target-Driven Deep Learning Method', 8, pp. 211849–211859. doi: 10.1109/ACCESS.2020.3038933.
- Tirkey, M. M. and Gupta, N. (2019) 'Electromagnetic absorber design challenges', *IEEE Electromagnetic Compatibility Magazine*. IEEE, 8(1), pp. 59–65. doi: 10.1109/MEMC.2019.8681370.
- Trabelsi, S. and Nelson, S. O. (2003) 'Free-space measurement of dielectric properties of cereal grain and oilseed at microwave frequencies', *Measurement Science and Technology*, 14(5), pp. 589–600. doi: 10.1088/0957-0233/14/5/308.

- Tsuji, H. (2016) 'Poly (lactic acid) stereocomplexes : A decade of progress ☆', *Advanced Drug Delivery Reviews*. Elsevier B.V., 107, pp. 97–135. doi: 10.1016/j.addr.2016.04.017.
- Vinoy, K. J. and Jha, R. M. (1996a) *Radar Absorbing Materials: From Theory to Design and Characterization*. KluwerAcademic Publisher.
- Vinoy, K. J. and Jha, R. M. (1996b) *Radar Absorbing Materials*. Kluwer Academic Publisher.
- Wang, J. F. *et al.* (2009) 'Three-Dimensional Metamaerial Microwave Absorbers Composed Coplanar Magnetic and Electric Resonators', 7, pp. 15–24.
- Wee, F. H. *et al.* (2009) 'Free Space Measurement Technique on Dielectric Properties of Agricultural Residues at Microwave Frequencies', (I), pp. 183–187.
- Wong, P. *et al.* (2019) 'A Study on Barriers to Implement E-Waste Management', 6, pp. 1–9.
- Yah, N. F. N. *et al.* (2019) 'Ultrathin metamaterial microwave absorber using coconut coir fibre over x-band frequency range', *2019 3rd International Conference on Communications, Signal Processing, and their Applications, ICCSPA 2019*. IEEE, pp. 2–6. doi: 10.1109/ICCSPA.2019.8713715.
- Yah, N. F. N. *et al.* (2020) 'Green Nanocomposite-Based Metamaterial Electromagnetic Absorbers: Potential, Current Developments and Future Perspectives', *IEEE Access*. IEEE, 8, pp. 33289–33304. doi: 10.1109/ACCESS.2020.2968867.
- Yang, J. *et al.* (2020) 'Research and development of high-performance new microwave absorbers based on rare earth transition metal compounds: A review', *Journal of Magnetism and Magnetic Materials*. Elsevier B.V., 497(September 2019), p. 165961. doi: 10.1016/j.jmmm.2019.165961.
- Yee, S. K. (2015) *Electromagnetic Shielding Effectiveness Cement Powder Mixed with Graphite for Mitigation Againts Electromagnetic Interference*. Universiti Tun Hussein Onn Malaysia.
- Yıldızhan, Ş. *et al.* (2018) 'Bio-composite materials : a short review of recent trends , mechanical and chemical properties , and applications', (March). doi: 10.26701/ems.369005.
- Yohandri, Rianto, D. and Putra, A. (2017) 'Study of single layer radar absorber material (RAM) based on coconut shell activated carbon', *Progress in Electromagnetics Research Symposium, 2017-Novem*, pp. 1536–1539. doi: 10.1109/PIERS-FALL.2017.8293376.
- Zahari, M. W. *et al.* (2002) 'Utilization of Oil Palm Frond - Based Diets for Beef and Dairy Production in', *International Symposium on 'Recent Advances in Animal Nutrition'*.

- Zahid, L. *et al.* (2013) 'Development of Pyramidal Microwave Absorber Using Sugar Cane Bagasse (SCB)', 137(January), pp. 687–702.
- Zawawi, A. *et al.* (2012) 'From Waste To Electronics : Printed Circuit Boards Using Renewable Resources of Oil Palm Empty Fruit Bunch', 567, pp. 263–266. doi: 10.4028/www.scientific.net/AMR.567.263.
- Zeng, X. *et al.* (2020) 'Electromagnetic microwave absorption theory and recent achievements in microwave absorbers', *Carbon*. Elsevier Ltd, 168, pp. 606–623. doi: 10.1016/j.carbon.2020.07.028.
- Zhao, J. and Feng, Y. (2012) 'One-way electromagnetic energy absorber base on composite metamaterial slabs', *2012 International Conference on Microwave and Millimeter Wave Technology (ICMMT)*. IEEE, pp. 1–4. doi: 10.1109/ICMMT.2012.6230433.



BIODATA OF STUDENT



Elfarizanis binti Baharudin was born on 11th January 1977, in Selangor, Malaysia. She obtained her Bachelor Degree in Engineering (Electrical) (Hons.) from Universiti Teknologi Mara in 2001. She was given a two-year position as a research and development engineer before accepting a position as a tutor at Kolej Institut Tun Hussein Onn Malaysia. Later in 2004, she furthered her study in Universiti Kebangsaan Malaysia. She has been awarded with Master of Engineering in Communication and Computer in 2006. In June 2006, she joined Universiti Tun Hussein Onn Malaysia (UTHM) as a lecturer at the Faculty of Electrical and Electronic Engineering. She worked with UTHM for more than 6 years. In 2012, she enrolled as a PhD candidate at Universiti Putra Malaysia's Faculty of Engineering to pursue research in the field of microwave material characterization and measurement under Professor Dr. Alyani Ismail's supervision.



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF PUBLICATIONS

Journal Articles

- Baharudin, E. *et al.* (2014) 'Investigation on the dielectric properties of pulverized oil palm frond and pineapple leaf fiber for X-band microwave absorber application', in *Advanced Materials Research*, pp. 488–491. doi: 10.4028/www.scientific.net/AMR.893.488.
- Baharudin, E. *et al.* (2017) 'Investigate of Wave Absorption Performance for Oil Palm Frond and Empty Fruit Bunch at 5.8 GHz', *International Journal of Advanced and Applied Sciences*, (Special Issue), pp. 335–348.
- Manab, N. H. *et al.* (2020) 'Enhancement of Microwave Ring Resonator (MRR) Based on PLA Thermoplastic Substrate', 8(1), pp. 8–15. doi: 10.11591/eei.v8i1.xxxx.

Conference Proceedings

- Baharudin, E. *et al.* (2013) 'Determination of pulverized material permittivity for microwave absorber application', in *Proceedings - RSM 2013: 2013 IEEE Regional Symposium on Micro and Nano Electronics*. doi: 10.1109/RSM.2013.6706479.
- Manab, N. H. *et al.* (2018) '2.45 GHz Patch Antenna Based on Thermoplastic Polymer Substrates', *RFM 2018 - 2018 IEEE International RF and Microwave Conference, Proceedings*. IEEE, pp. 93–96. doi: 10.1109/RFM.2018.8846493.