

INTEGRATED PROTOCOL FOR GROUND AND STRUCTURES
CONDITION ASSESSMENTS USING AMBIENT VIBRATION

AHMAD FAHMY BIN KAMARUDIN

A thesis submitted in
fulfilment of the requirements for the award of the
Doctor of Philosophy in Civil Engineering



Faculty of Civil Engineering and Built Environment
Universiti Tun Hussein Onn Malaysia

SEPTEMBER 2020

ACKNOWLEDGEMENT

Praise to Allah S.W.T the mighty god for the blessing to the accomplishment of this PhD research. Being as a PhD candidate was an extreme challenge experience. It is very hard to thrive for a doctoral award without a great supports and commitments. It is a tremendous journey with lots of obstacles, commitments and extra effort to complete this PhD journey. Thus, there has no such word could be revealed by only Alhamdulillah and HasbunAllahuwani'malwa-kil. Herewith, is a small tribute to all people who have put their attentions, support and involvement along the process of this research journey.

Many government and privates agencies have been involved in the process of approval application, data collections, fee reduction as well as their consultations. Thankful for their great cooperation especially to District Educational Office of Batu Pahat, SK Seri Molek, SK Sungai Tongkang, SMK Bukit Tinggi, Malaysia Meteorological Department (MMD), Public Works of Malaysia (JKR) Department of Survey and Mapping Malaysia (JUPEM), Mineral and Geoscience Department (JMG), IKRAM Selatan Sdn. Bhd. and all respondents involved toward the completion of this PhD research activities.

To all my supervisors, I wish to express my countless gratitude to Associate Prof. Sr Dr Effendi Daud, Professor Dr Azmi Ibrahim and Associate Prof. Dr Zainah Ibrahim for their great guidance, supports and previous times. Your valuable suggestions, precious time and contributions are really appreciated and will never be forgotten.

My acknowledgement is also extended to Faculty of Civil and Built Environment, UTHM, for the convenience of instruments and other testing facilities. Besides, the research grants of ERGS E011 and TIER U837 have definitely lightened all expenses involved along the research processes. To all colleagues, students and my close friends, it could be hard to keep on going to the end of this journey without your motivation and assistance. Thank you all.

Last but not least, I would like to express my deepest and privilege gratitude to my beloved families for their support, happiness and encouragement. To my late father, nephew and my best friend, hope you are in Allah S.W.T blessing all the times. Thank you everyone.

ABSTRACT

Safety and serviceability issues on ground or structure normally arise after deterioration or damage appearances. It is worst when there is no regular maintenance program or complete engineering record to carry out the re-evaluation work. Application of ambient vibration (AV) technique is widely used on ground and structures diagnosis works, but none of an effort to integrate them into a specific protocol. The main goal of this thesis is to develop a robust integrated condition assessment protocol on ground and structure using ambient vibration and the main assessment parameter of origin natural frequency. AV testing was performed using a tri-axial seismometer on ground and reinforced concrete (RC) school buildings, with different geotechnical profiles, building configurations and structural health conditions. Determination of peak natural frequency was computed based on the popular methods of Horizontal to Vertical Spectral Ratio (HVSr) and Fourier Amplitude Spectra (FAS) via GEOPSY software. Started by ground condition assessment protocol, the soil classification, soil thickness, and microzonation maps were determined for local soil condition. Meanwhile, in structural condition assessment protocols, the evaluations were made on rocking effect, soil-structure resonance, structural health monitoring (SHM), and building vulnerability. The analysis was initiated by validation of HVSr method on ground, and verification of FAS method on 4-storey of RC buildings. HVSr has proven to be the reliable method. From repetitive AV measurements had indicated consistent prediction with less than 7.0 % disparity of fundamental ground frequency (F_0). FAS method showed 0 % of difference at the first mode of predominant building frequency (f_0) prediction and 9.5 % at the fifth f_0 , with the comparison made to prior research. Microzonation map successfully described the sub-surface profile and the resonance zone. Good health of buildings was obtained in repetitive AV measurement within 1.5 years of maximum gap. In rocking effect protocol, the existence of friction piles was clearly identified. Illustrations of mode shapes at respective f_0 explained the influence of adjacent building, mass and geometric irregularities. A nomograph was introduced for quick evaluation of several components in the integrated protocols at the end analysis. In conclusion, the developed integrated protocol has demonstrated a novel, reliable and robust condition assessment. It will benefit to any ground and comparable RC building even without complete engineering database.

ABSTRAK

Isu keselamatan dan kebolehhidmatan tanah dan struktur kebiasaan timbul selepas berlakunya kemerosotan atau kerosakan. Lebih diburukkan apabila tiada program penyelenggaraan berkala dan rekod kejuruteraan lengkap untuk proses penilaian semula. Aplikasi teknik getaran (AV) ambien digunakan secara meluas dalam kerja-kerja diagnosis tanah dan stuktur. Namun tiada usaha menyatupadukannya ke bentuk protokol yang lebih spesifik. Matlamat tesis ini ialah untuk membangunkan sebuah protokol mapan penilaian keadaan bersepadu ke atas tanah dan struktur menggunakan teknik getaran ambien dan parameter utama frekuensi tabii. Ujian AV dijalankan menggunakan pengesan seismometer 3-paksi ke atas beberapa kawasan tanah dan bangunan sekolah konkrit bertetulang (RC) yang berbeza profil geoteknik, konfigurasi bangunan dan keadaan kesihatan struktur. Penentuan puncak frekuensi tabii dikira berdasarkan kaedah popular Nisbah Spektrum Mengufuk-Menegak (HVSR) dan Spektrum Fourier Amplitud (FAS) melalui perisian GEOPSY. Bermula dengan protokol penilaian keadaan tanah, pengelasan tanah, ketebalan tanah dan peta mikrozonasi ditentukan dalam penyiasatan keadaan tanah tempatan. Sementara itu, pada protokol penilaian keadaan struktur, penilaian dilakukan terhadap kesan goyangan, resonan tanah-struktur, pemantauan kesihatan struktur (SHM), dan kelonggaran bangunan. Analisis dimulakan dengan pengesahan kaedah HVSR di tapak yang dikenalpasti, dan pengesahaan kaedah FAS bangunan-bangunan RC 4-tingkat. Terbukti kaedah HVSR boleh dipercayai. Berdasarkan pengukuran AV ulangan menunjukkan ramalan kosisten dengan peratusan perbezaan frekuensi asas tanah (f_0) sebanyak 7.0 %. Kaedah FAS menunjukkan 0 % perbezaan pada frekuensi dominan bangunan (f_0) pertama dan 9.5 % pada f_0 kelima melalui perbandingan yang dilakukan pada penyelidikan lepas. Peta mikrozonasi berjaya menjelaskan profil sub-permukaan dan zon resonan. Kesihatan bangunan yang baik juga diperolehi dalam pengukuran ulangan AV. Dalam protokol kesan goyangan, kewujudan cerucuk geseran jelas dikenalpasti. Ilustrasi ragam bentuk pada keadaan mod f_0 masing-masing menjelaskan faktor pengaruh bangunan bersebelahan, ketidakseragaman jisim dan geometri. Sebuah nomograf diperkenalkan untuk penilaian cepat beberapa komponen dalam protokol bersepadu ini di akhir analisis. Sebagai kesimpulan, protokol integrasi yang dibangunkan merupakan sebuah kaedah penilaian yang baharu, mantap dan boleh dipercayai. Ia boleh dimanfaatkan terhadap kawasan tapak dan bangunan RC seumpamanya, walaupun dengan rekod pengkalan data kejuruteraan yang tidak lengkap.

TABLE OF CONTENTS

TITLE	iii
DECLARATION	iv
ACKNOWLEDGEMENT	v
ABSTRACT	vi
ABSTRAK	vii
TABLE OF CONTENTS	viii
LIST OF TABLES	xiii
LIST OF FIGURES	xix
LIST OF SYMBOLS AND ABBREVIATIONS	xxxiv
CHAPTER 1 INTRODUCTION	1
1.1 Research background	1
1.2 Problem statement	3
1.3 Goal and objectives	4
1.4 Research scopes	5
1.5 Research limitations	15
1.6 Significances of research	15
1.7 Thesis outlines	16
CHAPTER 2 LITERATURE REVIEW	19
2.1 Introduction	19
2.2 Ambient vibration method	20
2.2.1 Background of microtremor or ambient vibration or ambient noise	20

2.2.2	Horizontal-to-Vertical Spectral Ratio (HVSr) method	23
2.2.3	Arguments in HVSr method	27
2.3	Ambient vibration testing	33
2.3.1	Ambient vibration instrument	33
2.3.2	Fieldwork guidelines and testing parameters	38
2.3.2.1	Ground measurement	40
2.3.2.2	Building measurement	43
2.3.3	Processing tool	47
2.3.3.1	Fundamental ground frequency, F_0	49
2.3.3.2	Predominant building frequency, f_0	50
2.3.3.3	Modal shape	56
2.4	Ground condition assessment	59
2.4.1	Local soil condition	59
2.4.2	Ground classification	62
2.4.3	Soil thickness estimation	63
2.5	Structural condition assessment	66
2.5.1	Rocking effect	66
2.5.2	Soil-structure resonance	68
2.5.3	Building configuration deficiencies	70
2.5.3.1	Geometrical irregularities	72
2.5.3.2	Mass irregularities	75
2.5.3.3	Adjacent buildings	78
2.5.4	Structural health monitoring	79
2.6	Summary	82
CHAPTER 3 RESEARCH METHODOLOGY		83
3.1	Introduction	83
3.2	Preparation of ambient vibration testing and processing	85
3.2.1	Ambient vibration instruments and data acquisition	86

3.2.2	Processing tool of GEOPSY and SESAME (2004) guidelines	89
3.2.3	Filtering protocols for ground and building natural frequency	93
3.2.4	General procedure of ambient vibration testing on building	96
3.2.5	General guideline of ambient vibration testing on ground surface (soil)	98
3.3	Secondary data collections	99
3.3.1	Geological map of Peninsular Malaysia	100
3.3.2	Topography maps of Batu Pahat and Senggarang	100
3.3.3	Site investigation (SI) report and soil classification based on V_{s30}	101
3.3.4	Civil and structural drawing	103
3.3.5	WM and SM of acceleration records	104
3.4	Ambient vibration fieldworks on ground and building in the research area	108
3.4.1	Minyak Beku outcrop in Batu Pahat, Johor	109
3.4.2	Seismological stations: Kuala Lumpur (FRM station) and Kluang (KGM station)	110
3.4.3	SK Seri Molek, Senggarang, Batu Pahat, Johor	114
3.4.4	SK Sg Tongkang, Rengit, Batu Pahat, Johor	122
3.4.5	SMK Bukit Tinggi, Bentong, Pahang	130
3.5	Summary	138

CHAPTER 4 RESULT AND DISCUSSIONS 140

4.1	Introduction	140
4.2	Validation of HVSR method at Minyak Beku outcrop bedrock	142
4.2.1	Concluding remark	150

4.3	Investigations of fundamental ground frequencies against strong motion (SM) and weak motion (WM) time series, using HVSR method at KGM and FRM seismological stations	151
4.3.1	KGM station in Kluang, Johor	154
4.3.2	FRM station in Kepong, Kuala Lumpur	164
4.3.3	Concluding remark	171
4.4	Consistency test on ground and buildings at SK Seri Molek and SK Sg Tongkang	174
4.4.1	SK Seri Molek, Senggarang, Batu Pahat, Johor	175
4.4.2	SK Sg Tongkang, Rengit, Batu Pahat, Johor	178
4.4.3	Concluding remark	180
4.5	Verification of f_0 prediction based on FAS method	181
4.6	Integrated protocol of ground and structures condition assessments	186
4.6.1	Ground condition assessment	187
4.6.1.1	Local soil conditions	188
4.6.2	Structural condition assessments	190
4.6.2.1	Soil-structure resonance	192
4.6.2.2	Rocking effect	193
4.6.2.3	Building condition assessments	195
4.7	Identification of ground and building natural frequencies	198
4.7.1	SK Seri Molek	198
4.7.2	SK Sg Tongkang	206
4.7.3	SMK Bukit Tinggi	217
4.7.3.1	Building A (free damage)	218
4.7.3.2	Building B (free damage)	222
4.7.3.3	Building C (partially damaged)	226
4.7.3.4	Building D (free damage)	231
4.7.4	Concluding remark	234
4.8	Ground condition assessment	237

		xii
4.8.1	Local soil conditions	237
4.8.1.1	SK Seri Molek	238
4.8.1.2	SK Sg. Tongkang	246
4.8.2	Concluding remark	250
4.9	Structural condition assessments	251
4.9.1	Soil-structure resonance	251
4.9.1.1	SK Seri Molek	252
4.9.1.2	SK Sg. Tongkang	253
4.9.1.3	SMK Bukit Tinggi	256
4.9.1.4	Concluding remark	260
4.9.2	Rocking effect	262
4.9.3	Building condition assessments	265
4.9.3.1	SK Seri Molek	265
4.9.3.2	SK Sg Tongkang	274
4.9.3.3	SMK Bukit Tinggi	281
4.9.3.4	Concluding remark	301
4.10	Nomograph of ground and structures condition assessments	306
4.11	Summary	308
CHAPTER 5 CONCLUSIONS AND RECOMMENDATIONS		312
5.1	Conclusions	312
5.2	Recommendations	315
REFERENCES		316
APPENDICES		336
VITA		374

LIST OF TABLES

1.1	Details of data collection, method of testing and analyses involved in ground measurement	13
1.2	Details of data collection, method of testing and analyses involved on building measurement	14
2.1	Microseism versus microtremor (SESAME, 2004)	21
2.2	Summary of estimated site frequencies (Pando <i>et al.</i> , 2008)	30
2.3	Comparison of the average spectral amplification between microtremor, weak and strong motion data set (Atakan <i>et al.</i> , 2004)	32
2.4	Recommended recording duration for ambient vibration testing on ground (SESAME, 2004)	38
2.5	Details description from each model (Shakal and Huang, 2001)	46
2.6	Summary of empirical relationships of natural period prediction from previous studies (Oliveira and Navarro, 2010)	53
2.7	Influence of infill bricks wall of 9-storey RC buildings based on the first mode of building frequencies (Oliveira and Navarro, 2010)	54
2.8	Soil classification (Eurocode 8, 2004)	63
2.9	Estimation of sediment thickness from previous empirical relationships	64
2.10	HVSR resonance frequency seismic survey results – Outer Cape Cod, Massachusetts (Lane <i>et al.</i> , 2008).	65
2.11	Microtremor measurements on the building and ground (Gosar, 2009)	69
2.12	Comparison frequencies measured and computed with an computational model Navarro and Oliveira (2006)	73

2.13	Decreasing frequency of Building D during demolition of neighboring Building E and F	79
2.14	Experimental frequencies before and after May 2003 based on ambient vibration testing (Meziane <i>et al.</i> , 2012)	81
3.1	Technical specifications for seismometer sensors	86
3.2	Technical specifications for data acquisition system	86
3.3	Recording parameters of ambient vibration testing	87
3.4	Recommended processing tool parameters from previous studies and guidelines	91
3.5	Quick guidelines before ambient vibration recording SESAME (2004)	99
3.6	Bore log records of SK Seri Molek, Batu Pahat, Johor (IKRAM, 2008)	102
3.7	Bore log records of SK Sg Tongkang, Rengit, Johor (IKRAM, 2009)	102
3.8	Soil classification based on average V_{S30} and SPT 'N' values	103
3.9	Details of six random earthquake events obtained from MMD and MMI (2013)	106
3.10	Peak ground acceleration of selected earthquakes recorded by KGM and FRM stations (MMD, 2013)	107
3.11	Details of ambient vibration measurements	109
3.12	Details of FRM and KGM seismological stations (Devadas, personal communication, January 23, 2013) and Chai <i>et al.</i> (2011)	111
3.13	Horizontal sensors' arrangement in SK Seri Molek	119
3.14	Vertical sensors' arrangement in SK Seri Molek	120
3.15	Horizontal sensors' arrangement in SK Sg Tongkang	128
3.16	Vertical sensors' arrangement in SK Sg Tongkang	128
3.17	Arrangement of S1, S2 and S3 in vertical sensors arrangement at all Buildings A, Building B, Building C and Building D	135
3.18	Arrangement of S1, S2 and S3 in horizontal sensors arrangement on the 3 rd floor for Building A, Building B and Building C	135

3.19	Arrangement of S1, S2 and S3 in horizontal sensors arrangement on the 2 nd floor for Building A, Building B and Building C	136
3.20	Arrangement of S1, S2 and S3 in horizontal sensors arrangement on the 1 st floor for Building A, Building B and Building C	137
4.1	R&C review from Minyak Beku HVSR curves	148
4.2	Soil classification for seismic design (Shinoda <i>et al.</i> , 2009)	149
4.3	Simplified geotechnical site categories (Marek <i>et al.</i> , 2009)	149
4.4	RPA 99 site categories (Beneldjouzi <i>et al.</i> , 2012)	149
4.5	R&C of HVSR peak frequencies from AV signals at KGM and FRM stations	153
4.6	R&C of HVSR peak frequencies from WM vibration signals at KGM and FRM stations	153
4.7	R&C of HVSR peak frequencies from SM vibration signals at KGM and FRM stations	154
4.8	Summary of F_0 among AV, WM and SM with their mean, SD and RNFD	160
4.9	Summary of F_0 among AV, WM and SM with their mean, mean, SD and RNFD	170
4.10	Consistency test between two periods (December 2012 and June 2014) of AV measurement based on predominant modes of building frequencies on the upper floor at SK Seri Molek.	176
4.11	Consistency test between two periods (August 2013 and June 2014) of AV measurement based on predominant modes of building frequencies on the upper floor at SK Sg Tongkang	179
4.12	Predominant building frequencies of Building A, Building B, Building C and Building D	184
4.13	Deviation percentage of f_0 between FAS method and ARTeMIS predictions	185
4.14	Fundamental ground frequencies of SK Seri Molek from HVSR curves (in December 2012)	201

- 4.15 Peak frequencies of SK Seri Molek building from FAS curves on the upper floor in the NS, EW and UD components (in December 2012) 201
- 4.16 Relative deviation of predominant building frequencies of SK Seri Molek; (a) first mode, (b) second mode, (c) third mode and (d) no subsequence clear peak from FAS curves, with spectral Ratio 1, Ratio 2 and fundamental ground frequencies in December 2012 202
- 4.17 Peak frequencies of SK Seri Molek building from FAS curves on the upper floor in the NS, EW and UD components (in June-2014) 205
- 4.18 Fundamental ground frequencies of SK Seri Molek from HVSR curves (in June-2014) 205
- 4.19 Relative deviation of predominant building frequencies of SK Seri Molek; (a) first mode, (b) second mode, (c) third mode and (d) no subsequence clear peak from FAS curves, with spectral Ratio 1, Ratio 2 and fundamental ground frequencies in June-2014 205
- 4.20 Peak frequencies of SK Sg. Tongkang building from FAS curves on the upper floor in the NS, EW and UD components (in August 2013) 209
- 4.21 Fundamental ground frequencies of SK Sg. Tongkang from HVSR curves (in August 2013) 209
- 4.22 Relative deviation of predominant building frequencies of SK Sg. Tongkang; (a) second mode, (b) first mode and (c) third mode, with spectral Ratio 1, Ratio 2 and ground fundamental frequencies in August 2013 209
- 4.23 Soil descriptions of two boreholes in SK Sg Tongkang (IKRAM, 2009) 210
- 4.24 Peak frequencies of SK Sg. Tongkang building from FAS curves on the upper floor in the NS, EW and UD components (in June-2014) 215

4.25	Fundamental ground frequencies of SK Sg. Tongkang from HVSR curves (in June-2014)	215
4.26	Relative deviation of predominant building frequencies of SK Sg. Tongkang; (a) second mode, (b) first mode and (c) third mode, with spectral Ratio 1, Ratio 2 and fundamental ground frequencies in June-2014	215
4.27	Peak frequencies of SMK Bukit (Building A) from FAS curves on the upper floor in the NS, EW and UD components (in January 2013)	221
4.28	Ground resonance frequencies of SMK Bukit Tinggi from HVSR curves bounded to Building A at 3 rd floor, from the 1 st to 6 th column (in January 2013)	221
4.29	Ground resonance frequencies of SMK Bukit Tinggi from HVSR curves bounded to Building A at 2 nd floor, from the 6 th to 20 th column (in January 2013)	221
4.30	Relative deviation of Building A predominant building frequencies of SMK Bukit Tinggi; (a) second mode and (b) first mode with spectral Ratio 1, Ratio 2 and fundamental ground frequencies in January 2013	222
4.31	Peak frequencies of SMK Bukit (Building B) from FAS curves on the upper floor in the NS, EW and UD components (in January 2013)	224
4.32	Ground resonance frequencies of SMK Bukit Tinggi from HVSR curves bounded to Building B (in January 2013)	224
4.33	Relative deviation of Building B predominant building frequencies of SMK Bukit Tinggi; (a) second mode, (b) first mode and (c) third mode, with spectral Ratio 1, Ratio 2 and fundamental ground frequencies in January 2013	226
4.34	Peak frequencies of SMK Bukit Tinggi (Building C) from FAS curves on the upper floor in the NS, EW and UD components (in January 2013)	229
4.35	Ground resonance frequencies of SMK Bukit Tinggi from HVSR curves bounded to Building C (in January 2013)	229

4.36	Relative deviation of Building C predominant building frequencies of SMK Bukit Tinggi; (a) first mode, (b) second mode, (c) fourth mode, (d) third mode and (e) fourth mode, with spectral Ratio 1, Ratio 2 and fundamental ground frequencies in January 2013	229
4.37	Peak frequencies of SMK Bukit (Building D) from FAS curves on the upper floor in NS, EW and UD components (in January 2013)	233
4.38	Ground resonance frequencies of SMK Bukit Tinggi from HVSR curves bounded to Building D (in January 2013)	233
4.39	Relative deviation of Building D predominant building frequencies of SMK Bukit Tinggi; (a) first mode, (b) second mode, (c) third mode and (d) fourth mode, with Ratio 1, Ratio 2 and fundamental ground frequencies in January 2013	233
4.40	Soil descriptions of borehole 1 in SK Seri Molek (IKRAM, 2008)	239
4.41	Soil description of borehole 2 in SK Seri Molek (IKRAM, 2008)	240
4.42	Chronology of damages and type of structural failures on Building C (Ariffin personal communication retrieved on 17 th October 2012)	256
4.43	Bukit Tinggi earthquakes catalogue (Chai <i>et al.</i> , 2011)	257
4.44	Predominant building frequencies observed in December 2012 and June 2014 on the upper floor of SK Seri Molek building	266
4.45	Vulnerability percentages of structural health monitoring (comparison between initial and subsequent measurements) (Oliveira and Navarro, 2010)	266
4.46	Predominant building frequencies observed in August 2013 and June 2014 on the upper floor of SK Sg Tongkang building	275
4.47	Summary of building condition assessments for all buildings	302

LIST OF FIGURES

1.1	Pictograph of research flowchart	12
2.1	Typical subsurface ground profile (Nakamura, 1996)	25
2.2	Image of HVSR at different sub-surface profile (Nakamura, 2008)	27
2.3	HVSR amplitude from several sites and earthquake motion record (Nakamura, 1989)	27
2.4	Comparison between microtremor and strong motion in Mexico City (Nakamura, 2001)	28
2.5	Comparison of three different site response techniques, the average microtremor HVSR (solid lines), the average HVSR for up to five weak-motion earthquakes (dotted lines) and estimates from the standard spectral ratio (dashed lines) based on 2001 Nisqually earthquake input motions (Cassidy and Molnar, 2009)	29
2.6	Free field strong motion stations in the city of Mayagüez, Puerto Rico (Pando <i>et al.</i> , 2008)	30
2.7	Urban city map of Pereira, Columbia (Ojeda and Escallon, 2000)	31
2.8	(a) Nakamura spectra for strong motion, weak motions and microtremors at UTP station and, (b) Nakamura spectra for strong motion, weak motions and microtremors at CAST station (Ojeda and Escallon, 2000)	31
2.9	Analogue and digital recorder for accelerometer and seismometer (Gibson, 1992)	35
2.10	Frequency dependent dynamic range due to mechanical or electronic limitations, a: electronic limitation of Mark L15 B (4.5 Hz) with velocity feedback for extending its response to an equivalent frequency of 1 Hz, b: electronic limitation of a Mark	

	L4-C (1Hz), c: Mark L15B considering mechanical clipping and, d: Mark L4-C considering mechanical clipping (Havskov and Alguacil, 2004)	36
2.11	Four types of HVSR curves patterns found in El Ejido: (a) curves with a single clear peak, (b) broad peaks whose widths vary from 0.2 to 0.4 Hz, (c) plateau-type shape with low amplitude and (d) peaks showing narrower peaks on top (García-Jerez <i>et al.</i> , 2019)	41
2.12	HVSR curves pattern observed in Wang <i>et al.</i> (2008) sites	42
2.13	HVSR amplified frequencies correlate with the effects of alluvial deposits, thickness variation and lateral irregularities of the subsurface (Moisidi <i>et al.</i> , 2012)	43
2.14	Instrumentation of a building, (a) base or reference free-field only, (b) base and roof, (c) reference free-field, base and roof, (d) base, mid-height and roof, (e) multi-level lateral motion and roof only torsion and, (f) multi-level lateral and torsional motions (Shakal and Huang, 2001)	45
2.15	Three different set-up of the sensor in the laboratory experiment, (a) with four tromometers, (b) with two instruments and, (c) the stand-alone configuration (Detommaso <i>et al.</i> , 2010)	45
2.16	Flowchart of processing the average H/V-Ratio $\overline{H/V}$ and standard deviation $\sigma_{\overline{H/V}}$ (Wenzel and Achs, 2006)	48
2.17	S-wave velocity profile in Tuladhar <i>et al.</i> (2004) sites	50
2.18	Fundamental period of buildings due to seismic response (Ambrose and Vergun, 1995)	51
2.19	Simplified period vs height relationships for concrete moment resistant frame (Masi and Vona, 2009).	52
2.20	Selection of the predominant peak using spectral ratio (Uehan and Meguro, 2000)	56
2.21	(a) Position of sensors on roof storey, (b) sample of velocity sensor wired to the computer, (c) the Fourier spectrum of measured velocities time histories by central sensor and (d) the	

Fourier spectrum of measured velocities time histories by corner South West-SW sensor (Snoj <i>et al.</i> , 2013)	58
2.22 Elevation of Pisa Tower, sub-soil profile and first mode shape in both NS and EW directions (Nakamura <i>et al.</i> , 2009)	59
2.23 Experimental mode shapes before and after rehabilitation works (Ramos <i>et al.</i> , 2010)	59
2.24 Conditions of foundation on variable sub-surface profiles (Ambrose and Vergun, 1995)	60
2.25 Inclination of dominant soil periods proportionally to the depth changes of soft and hard soil/ rock material (Shelley <i>et al.</i> , 2012)	61
2.26 Shapes of the analysed hill by Towhata (2008)	62
2.27 Houses completely destroyed on terrace hill in Balakot of Pakistan 2005 earthquakes	62
2.28 Profile of bedrock surface along outer Cape Cod, Massachusetts, interpreted from HVSR results and depth to bedrock interpreted from seismic refraction surveys and boring logs (Lane <i>et al.</i> , 2008)	65
2.29 Model of building for SSI and rocking effect evaluation on 10-storey RC building (Tobita <i>et al.</i> , 2000)	66
2.30 Out-of-plane deformation at the ground level from the NS translational mode at 1.82 Hz (Tobita <i>et al.</i> , 2000)	67
2.31 Typical instrumentation scheme (Celebi, 2000)	67
2.32 Flowchart of field vibration monitoring and significant spectral picking for rocking frequency assessment (Safak and Cakti, 2014)	67
2.33 Modification of building frequency after the wall demolished (Bouth and Hans, 2009)	73
2.34 RC Buildings studied in Potenza town (Masi and Vona, 2009)	74
2.35 (a) Torsional effects created by irregular shape of building plan (L configuration) and by irregular distribution of plan stiffness and (b) Torsional failure of the second story of the Hotel Terminal, Guatemala City, during the 1976 earthquake (Ditommaso <i>et al.</i> , 2010)	75

2.36	Multimassed building form (Ambrose and Vergun, 1995)	76
2.37	Deformations shapes and storey drift of various conditions of softstorey and mass irregularities of 10-storey frame using CSI-ETABS computational modelling (Poonam <i>et al.</i> , 2012)	77
2.38	Seismic movements in multimassed buildings (Ambrose and Vergun, 1995)	78
2.39	5-storey RC Building of D, E, F separated by 5 cm gap with polystyrene over a small part of longitudinal facade (Boutin and Hans, 2009)	79
2.40	Deviation of natural frequencies and mode shape between undamaged and damaged slab (Hasim <i>et al.</i> , 2013)	81
3.1	Flowchart of research methodology	84
3.2	Ambient vibration equipment	88
3.3	Connection of data logger and seismometer sensors	88
3.4	FAS and HVSR computation flowchart (GEOPSY, 2014)	90
3.5	Processing parameters used in FAS and HVSR analyses	92
3.6	Reliability and clarity (R&C) criteria of HVSR curves (SESAME, 2004)	93
3.7	Filtering protocol for determination of predominant frequencies of building and fundamental ground frequencies	95
3.8	Example of Ratio 1 and Ratio 2 in the application of filtering protocol on SK Seri Molek building	95
3.9	(a) Illustration of sensor alignments and the NS orientation for ambient vibration measurement on the building, (b) photograph of horizontal sensors alignment and (c) photograph of vertical sensors alignment	97
3.10	Ambient vibrating testing on ground	98
3.11	Geological Map of Peninsular Malaysia (JMG, 1985)	100
3.12	Topography Map of Batu Pahat and Senggarang (JUPEM, 1996)	101
3.13	Contract document of SK Seri Molek, civil and structural drawing collected from JKR Batu Pahat	104

3.14	Distribution of epicenters (green and yellow pin verified by searching engine of IRIS catalogue) on a similar date/time of event 1 to 6 (red pin) obtained from MMD	105
3.15	Sample of decoded time series in the NS component (MMD, 2013)	108
3.16	(a) Location of Minyak Beku outcrop and, (b) position of S1 and S2 sensors	110
3.17	FRM seismological station; (a) digitiser and electrical devices room, (b) location of sensors container, (c) distance between digitiser station and sensors container, (d) 3 units of seismometer and an accelerometer sensors, (e) 1 Hz uniaxial Kinematic Ranger seismometer and, (f) triaxial force balance Episensor accelerometer	111
3.18	KGM seismological station; (a) & (b) Elevation of sensors vault, (c) 3 units of seismometer and an accelerometer sensors, (d) 1 Hz uniaxial Kinematic Ranger seismometer and (e) tri-axial force balance Episensor accelerometer	112
3.19	Positions of S1 and S2 (near to permanent accelerometer and seismometer sensors) at FRM station	113
3.20	Positions of S1 and S2 (near to permanent accelerometer and seismometer sensors) at KGM station	114
3.21	(a) Photograph of SK Seri Molek, (b) geological map of the school (JMG, 1985) and, (c) topography map of SK Seri Molek published by Department of Survey and Mapping Malaysia (JUPEM, 1996)	115
3.22	Buildings layout of SK Seri Molek, Senggarang	116
3.23	Landscapes and buildings in SK Seri Molek	116
3.24	The investigated 4-storey building of SK Seri Moleks	117
3.25	(a) Front elevation and side elevation of SK Seri Molek and, (b) floor plan of every storey	118
3.26	Positions of seismometer sensors in ambient vibration testing at 4-storey building of SK Seri Molek	119

3.27	(a) Ambient vibration testing grids on SK Seri Molek ground area and, (b) fieldwork photographs	121
3.28	(a) Photograph of SK Sg Tongkang, (b) geological map of the school (JMG, 1985) and, (c) topography map of SK Seri Molek published by Department of Survey and Mapping Malaysia (JUPEM, 1996)	122
3.29	Building layout of SK Sg Tongkang, Rengit	123
3.30	The main buildings in SK Sg Tongkang	124
3.31	The investigated 4-storey building of SK Sg Tongkang	124
3.32	(a) Front and side elevations of SK Sg Tongkang and, (b) floor plan of every storey	126
3.33	Position of seismometer sensor in ambient vibration testing at 4-storey building of SK Sg Tongkang	127
3.34	(a) Ambient vibration testing grids on SK Sg Tongkang ground area and, (b) fieldwork photographs	129
3.35	(a) The geological map of SMK Bukit Tinggi and, (b) reinforced concrete buildings in SMK Bukit Tinggi	130
3.36	(a) Bukit Tinggi faults zone (Lat and Ibrahim, 2009) and, (b) earthquake epicenters in Bukit Tinggi region based on the local earthquake events from 30 th November 2007 until 4 th December 2009	131
3.37	Buildings layout of SMK Bukit Tinggi	132
3.38	Grid points of AVT on ground in SMK Bukit Tinggi	133
3.39	(a) Rooms; of Building A, Building B, Building C and Building D, and (b) sketch of respective building elevations	134
3.40	Ambient vibration testing and location of the measured beam-column joints on the 3 rd floor of Building A, Building B and Building C	135
3.41	Location of the measured beam-column joints on the 2 nd floor of Building A, Building B, Building C and Building D	136
3.42	Locations of measured joints on the 1 st floor of Building A, Building B, Building C and Building D	137

4.1	Validation, verification and consistency work processes of HVSR and FAS methods, and sesimomter instrument	141
4.2	Location of Minyak Beku outcrop bedrock (study area) on geological map of Peninsular Malaysia (JMG, 1985)	142
4.3	Mackintosh probe testing closer to S2 area	143
4.4	(a) Ambient vibration time series for S1 and S2 in three main components of NS, EW and UD from measurement no. 1 (FI 175), (b) CSA for S1 by NS, EW and UD components and, (c) CSA for S2 for NS, EW and UD components	144
4.5	(a) Ambient vibration time series for S1 and S2 in three main components of NS, EW and UD from measurement no. 2 (FI 176), (b) CSA for S1 by NS, EW and UD components and, (c) CSA for S2 for NS, EW and UD components	145
4.6	(a) FAS curves for FI 175 S1, (b) FAS curves for FI 175 S2, (c) FAS curves for FI 176 S1 and, (d) FAS curves for FI 176 S2	146
4.7	HVSR on outcrop bedrock in Minyak Beku: (a) Measurement 1: FI 175 and, (b) Measurement 2: FI 176.	148
4.8	Verification of F_0 prediction based on AV, WM and SM input motions	151
4.9	Geological map and photographs at KGM station	155
4.10	EpiSensor accelerometer and Quanterra seismic digitiser installed at KGM and FRM stations	156
4.11	(a) AV time series for S1 in first measurement (FI 20), (b) AV time series for S1 in second measurement (FI 21), (c) CSA for S1-FI 20, (d) CSA for S1-FI 21, (e) AV time series for S2 in first measurement (FI 20), (f) AV time series for S2 in second measurement (FI 21), (g) CSA for S2-FI 20 and (h) CSA for S2-FI 21	158
4.12	(a) Comparison of HVSR curves between AV, WM and SM at KGM seismological station, (b) distribution of F_0 among AV, WM and SM, (c) distribution of A_0 from peak frequencies among AV, WM and SM	161

4.13	Seismic refraction survey at Kluang seismological station in the West-East (WE) alignment (Zainal Abidin and Kamarudin, 2016)	162
4.14	Variation of amplification factor with different local soil condition (Towhata, 2008)	163
4.15	FAS curves of the NS, EW and UD components from both S1 and S2 sensors of FI 20 and FI 21 measurement files	163
4.16	Geological formation and photographs at FRM station	165
4.17	(a) AV time series for S1 in the 1 st measurement (FI 12), (b) AV time series for S1 in the 2 nd measurement (FI 310), (c) CSA for S1-FI 12, (d) CSA for S1-FI 310, (e) AV time series for S2 in the 1 st measurement (FI 12), (f) AV time series for S2 in the 2 nd measurement (FI 310), (g) CSA for S2-FI 12 and (h) CSA for S2-FI 310.	166
4.18	FAS Curves of the NS, EW and UD components from both S1 and S2 sensors of FI 20 and FI 21 measurement files at KGM station	167
4.19	Magnified FAS curves of the NS, EW and UD components at the first peak frequency of S1 at Minyak Beku outcrop	167
4.20	(a) Comparison of HVSR curves between AV, WM and SM at FRM seismological station, (b) distribution of F_o among AV, WM and SM, (c) distribution of A_o from peak frequencies among AV, WM and SM	169
4.21	Summary of AV processing for F_o prediction from the ground measurement at Minyak Beku, KGM station and FRM station	172
4.22	CSA pattern for preliminary assessment of ground condition based on the input motion of ambient vibration wavefields	173
4.23	Samples of site obstacles at SK Seri Molek and Sg Tongkang	174
4.24	Ambient vibration testing conducted on ground and buildings within two periods of measurement	175
4.25	The difference of resonance frequencies at each grid point based on AVT made in year 2012 and 2014 at SK Seri Molek	177

4.26	The difference of resonance frequencies at each grid point based on AVT made in year 2013 and 2014 at SK Sg Tongkang	180
4.27	Structural and non-structural cracks and repairs at Building C of SMK Bukit Tinggi	182
4.28	Workstation of 24 channels OMC CRONOXflex data logger and recording process of ambient vibration wave field from bi-axial SYSCOM accelerometers at one of the joint of building C, conducted by local researcher of University of Malaya	183
4.29	Peak picking of building frequencies from (a) EFDD spectrum and (b) SSI spectrum (Ibrahim et al., 2014)	185
4.30	The summarized flowchart of sites condition assessments	188
4.31	Local soil condition assessments flowchart	189
4.32	The summarised flowchart of structural condition assessments	191
4.33	Soil-structure resonance assessment flowchart	193
4.34	Rocking effect assessment flowchart	194
4.35	Building condition assessments flowchart	196
4.36	Conversion of normalized amplitudes for mode shape illustration	197
4.37	SK Seri Molek, December 2012, (a) NS direction: spectral Ratio 1 (b) NS direction: spectral Ratio 2, (c) NS direction: FAS curves at 3 rd floor, (d) UD direction: FAS curves at 3 rd floor, (e) HVSR curves at lines B/S3'-S2' and (f) HVSR curves at lines C/S3'-S2'	199
4.38	SK Seri Molek, December 2012, (a) EW direction: spectral Ratio 1 (b) EW direction: spectral Ratio 2, (c) EW direction: FAS curves at 3 rd floor, (d) UD direction: FAS curves at 3 rd floor, (e) HVSR curves at lines B/S3'-S2' and (f) HVSR curves at lines C/S3'-S2'	199
4.39	FAS curves from vertical sensor orientation at Column 11 in the NS direction	200
4.40	SK Seri Molek, June 2014, (a) NS direction: spectral Ratio 1 (b) NS direction: spectral Ratio 2, (c) NS direction: FAS curves at 3 rd floor, (d) UD direction: FAS curves at 3 rd floor, (e) HVSR	

REFERENCES

- Abdul Rahman, A. (2009). *Theoretical Model for Damage and Vibration Response in Concrete Bridges*. Universiti Teknologi Malaysia: FRGS 78007.
- Ali, M.Y., Berteussen, K.A., Small, J. and Barkat, B. (2009). Low-frequency passive seismic experiments in Abu Dhabi, United Arab Emirates: implications for hydrocarbon detection. *European Association of Geoscientists & Engineers, Geophysical Prospecting, Vol 58, Issue 5*, pp. 1-25.
- Anbazzhagan, P., Srilakshmi, K.N., Bajaj, K., Moustafa, S.R. and Al-Arifi, N.S.N. (2019). Determination of seismic site classification of seismic recording stations in the Himalayan region using HVSR method. *Soil Dynamics and Earthquakes Engineering, 116*, pp. 304-316.
- Anbazzhagan P., Kumar, A. and Sitharam, T.G. (2012). Seismic Site Classification and Correlation between Standard Penetration Test N Value and Shear Wave Velocity for Lucknow City in Indo-Gangetic Basin. *Pure and Applied Geophysics, 170 (3)*, pp. 299-318.
- Ambrose, J. and Vergun, D. (1995). *Simplified building design for wind and earthquake forces*. United States of America: John Willey & Sons. Inc.
- Architectural Institute of Japan (2005). *Recommendations for Loads on Buildings*. Retrieved November 2, 2016, from AIJ publications website via <http://www.aij.or.jp/jpn/symposium/2006/loads/loads.htm>.
- Atakan, K. (2009). The Need for Standardized Approach for Estimating the Local Site Effect Based on Ambient Noise Recordings. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 3-15.
- Atakan, K., Duval, A.M., Theodulidis, N., Bard, P.Y. and the SESAME team. (2004). The H/V spectral ratio: Experimental conditions, data processing and empirical reliability assessment. *Proceeding of the 13th World Conference on Earthquake Engineering, Paper No. 2268*. Vancouver, Canada. pp. 1-6.

- Atakan, K., Real, M.C. and Torress, R. (2004). Local site effects on microtremors, weak and strong ground motion in San Salvador. *Geological Society of America* (375). pp. 1-17.
- Balendra, T. and Li, Z. (2008). Seismic Hazard of Singapore and Malaysia. *EJSE Special Issue: Earthquake Engineering in the low and moderate seismic regions of Southeast Asia and Australia*. pp. 57-63.
- Bard, P.Y. (2004). The SESAME project: an overview and main results. *Proceeding of the 13th World Conference on Earthquake Engineering*. Vancouver, Canada.
- Bard, P.Y. (1999). Microtremor measurement: a tool for site effect estimation. In Irikura, K., Kudo, K., Okada, H., Sasatami, T. (Eds). *The effects of surface geology on seismic motion*. Rotterdam: Balkema. pp. 1251-1279.
- Bard, P.-Y. (1998). Microtremor measurements: a tool for site effect estimation. *The Second International Symposium on the Effects of Surface Geology on Seismic Motion, Vol. 3*. Yokohama, Japan. pp. 1251–1279.
- Bendat, J.S. and Piersol, A.G. (1993). *Engineering Application of Correlation and Spectral Analysis*. (2nd Edition). New York: Wiley.
- Beneldjouzi, M., Laouami, N. and Slimani, A. (2012). Design site characterization via stochastic transfer functions. *The 15th World Conference on Earthquake Engineering*. 24-28 September 2012. Portugal, Lisbon.
- Beskhyroun, S., Navabian, N., Wotherspoon, L. and Ma, Q. (2020). Dynamic behaviour of a 13-story reinforced concrete building under ambient vibration, forced vibration, and earthquake excitation. *Journal of Building Engineering*, 28, pp. 1-16.
- Boutin, C. and Hans, S. (2009). How far ambient noise measurement may help to assess building vulnerability. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 151-180.
- British Standards Institution. (2004). *Eurocode 8: Design of structures for earthquake resistance - Part 1: General rules, seismic actions and rules for buildings*. London, BS EN 1998-1:2004.
- Building Seismic Safety Council. (2001). *NEHRP recommended provisions for seismic regulations for new buildings and other structures. Part 1: Provisions*. Washington D.C., FEMA 368.

- Cassidy, J.F. and Molnar, S. (2009). Recent earthquake site response studies in Canada. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 257-279.
- Castellaro, S., Perricone, L., Bartolomei, M. and Isani, S. (2016). Dynamic characterization of the Eiffel tower. *Engineering Structure*, 126, pp. 628-640.
- Celebi, M. (2013). Seismic Monitoring of Structures and New Developments. In: Garevski, M. *Earthquakes and Health Monitoring of Civil Structures*. Netherlands: Springer. pp. 37-84.
- Celebi, M. (2000). *Seismic instrumentation of buildings*. United States Geological Survey (USGS): Open-File Report 00-157, pp. 1-37.
- Chang, P.C., Flatau, A. and Liu, S.C. (2003). Review paper: health monitoring of civil infrastructure. *Structural Health Monitoring*, 2(3), pp. 257–267.
- Chavez-Garcia, F.J. (2009). Ambient noise and site response: From estimation of site effects to determination of the subsoil structure. In Mucciarelli, M, Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 53-71.
- Chai, M.F., Z.B.Z., Devadas, R., Zaty Aktar, M., Asmadi, A.W. and Mohd Roshaidi, C.A. (2001). *Study on Hypocenter Relocation of Local Earthquakes in Malay Peninsula Using the Modified Joint Hypocenter Determination and HYPOCENTER Programs*. Malaysia: Malaysia Meteorological Department and Ministry of Science, Technology and Innovation. Research Publication No. 2/2011, Research Report. pp. 241-279.
- Chatelain, J.L. and Guillier, B. (2013). Reliable fundamental frequencies of soils and building down to 0.1 Hz obtained from ambient vibration recordings with a 4.5 Hz sensor. *Seismological Research Letter*, Vol. 84, No. 2, pp. 199-209.
- Chatelain J.L., Guillier, B, Guéguen, P., Fréchet, J. and Sarrault, J. (2013). *Ambient vibration recording for single-station, array and building studies made simple: CityShark II*. France: Scientific Research Documents archive, HAL Id: hal-00790355.
- Chatelain, J.L., Guillier, B., Cara, F., Duval, A-M., Atakan, K. and Bard, P-Y. (2008). Evaluation of the influence of experimental conditions on H/V results from ambient noise recordings. *Bulletin of Earthquake Engineering*, 6, pp. 33-74.

- Chapman, M. (2009). A comparison of short period and broadband seismograph system in the context of the seismology of the Eastern. *Seismological Research Letters, Vol 80(6)*, pp. 1019-1034.
- Choobbasti, A. J., Rezaei, S. and Farrokhzad, F. (2013). Evaluation of site response characteristics using microtremors. *Gradevinar, 65, 8*. pp. 731-741.
- Claudet, S.B., Baize, S., Bonilla, L.F., Thierry, C.B., Pasten, C. and Campos, J. (2009). Site effect evaluation in the basin of Santiago de Chile using ambient noise measurements. *Geophysical Journal International, Vol. 176*. pp. 925-937.
- Corciulo, M., Cusano, P. and Petrosino, S. (2010). New constraints for site effect characterization from seismic noise analysis in southern Italy, San Fele case study. *Annals of Geophysics, 53, 4*, pp. 59-67.
- Costa, A.G. (2006). Strengthening and repairing earthquake damaged structures. In Oliveira, C.S., Roca, A. and Goula, X. *Assessing and Managing Earthquake Risk*. Netherlands: Springer.
- Darshan D. and Shruthi, H.K. (2016). Study on mass irregularity of high rise buildings. *International Research Journal of Engineering and Technology, 03*, pp. 1123-1131.
- Delgado J., Lopez Casado C., Giner J., Estevez A., Cuenca A, and Molina S. (2000). Microtremors as a Geophysical Exploration Tool: Applications and Limitations. *Pure and Applied Geophysics, 157*, pp. 1445-1462.
- Dinesh, B.V., Nair, G.J., Prasad, A.G.V., Nakkeeran, P.V. and Radhakrishna, M.C. (2010). Estimation of sedimentary layer shear wave velocity using microtremor H/V ration measurements for Bangalore city. *Soil Dynamics and Earthquake Engineering, 30*, pp. 1377-1382.
- Dinesh, B.V., Nair, G.J., Prasad, A.G.V., Nakkeeran, P.V. and Radhakrishna, M.C. (2009). Relation between sedimentary layer thickness and fundamental frequency of the H/V spectra for Bangalore city. *Current Science, 97, 7*, pp. 1073-1077.
- Ditommaso, R., Vona, M., Mucciarelli, M. and Masi, A. (2010). Identification of building rotational modes using an ambient vibration technique. *14th European Conference on Earthquake Engineering, Ohrid, Republic of Macedonia. 30th August – 3rd September 2010. Ohrid: Republic of Macedonia.*

- Dowrick, D.J. (2003). *Earthquake risk reduction*. England: John Wiley & Sons. Ltd. 1 – 506.
- Duval, A.M., Chatelain, J.L., Guillier, B. and the SESAME WP02 team. (2004). Influence of experimental conditions for << H/V >> on ambient vibration noise vibration method. *13th World Conference on Earthquake Engineering*. 1st – 6th August 2004. Canada: Vancouver, B.C. Paper No. 306.
- Entezami, A. and Shariatmadar, H. (2019). Structural health monitoring by a new hybrid feature extraction and dynamic time warping methods under ambient vibration and nonstationary signals. *Measurement*, 134, pp. 548-568.
- Eze, E.O. and Orié, O.U. (2010). Earthquake-induced phenomena and structural damage: A review. *Journal of Emerging Trends in Engineering and Applied Sciences*, 1 (2), pp. 209-215.
- Farsi, M.N., Guillier, B., Chatelain, J.L and Zermout, S.A. (2009). Retrofitting and strengthening evaluation from stiffness variations of a damaged building from ambient vibration recordings. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 227-238.
- Federal Emergency Management Agency (2006). *Risk Management Series Designing for Earthquakes A Manual for Architects*. Washington D.C.: FEMA 454.
- Federal Emergency Management Agency (2000). *Prestandard and commentary for seismic rehabilitation of buildings*. Washington D.C.: FEMA 356.
- Filiatrault, A., Tremblay, R., Christopoulos, Folz, B. and Pettinga, D. (2013). *Elements of Earthquake Engineering and Structural Dynamics*. 3rd ed. Canada: Presses Internationales Polytechnique.
- Fujino, Y., Siringoringo, S.M., Ikeda, Y. Nagayama, T. and Mizutani, T. (2019). Research and implementations of structural monitoring for bridges and buildings in Japan. *Engineering*, 5, pp. 1093-1119.
- Gallipoli, M.R., Mucciarelli, M. and Vona, M. (2009). Empirical estimate of fundamental frequencies and damping for Italian buildings. *Earthquake Engineering Structural Dynamic*, 38, pp. 973–988.
- Gallipoli, M.R., Mucciarelli, M., Castro, R.R., Monachesi, G. and Contri, P. (2004). Structure, soil-structure response and effects of damage based on

- observations of horizontal-to-vertical spectral ratio of microtremors. *Soil Dynamics and Earthquake Engineering*, 24, pp. 487-495.
- Gara, F., Regni, M., Roia, D., Carbonari, S. and Dezi, F. (2019). Evidence of coupled soil-structure interaction and site response in continuous viaducts from ambient vibration tests. *Soil Dynamics and Earthquake Engineering*, Vol. 120, pp. 408-422.
- García-Jereza, A., Seivanea, H., Navarroa, M., Martínez-Segurab, M. and Piña-Floresc, J. (2019). Joint analysis of Rayleigh-wave dispersion curves and diffuse-field HVSR for site characterization: The case of El Ejido town (SE Spain). *Soil Dynamics and Earthquake Engineering*, 121, pp. 102-120.
- Garcia, F.J. (2009). Ambient noise and site response from estimation of site effects to determination of the subsoil structure. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 53-71.
- GEOPSY (2013, April). *Geopsy*. Retrieved April 14, 2013, from Geopsy website via <http://www.geopsy.org/documentation/geopsy/hv.html>.
- GEOPSY (2012, November). *H/V measurements*. Retrieved November 12, 2012 from <http://www.GEOPSY.org/>
- Gentile, C., Ruccolo, A. and Canali, F. (2019). Inspection Techniques for Damage Detection in Civil Engineering Structures Long-term monitoring for the condition-based structural maintenance of the Milan Cathedral. *Construction and Building Materials*, 228, pp. 1-15.
- Gibson, G. (1992). Seismic instrumentation. *Proc. Conf. of Aust. Earthquake Eng. Soc., Sydney*. pp. 7-20.
- Giocoli, A., Hailemikael, S., Bellanova, J. Calamita, G., Perrone, A. and Piscitelli, S. (2019). Site and building characterization of the Orvieto Cathedral (Umbria, Central Italy) by electrical resistivity tomography and single-station ambient vibration measurements. *Engineering Geology*, Vol. 260, pp. 1-14.
- Gioncu, V. and Mazzolani, F. (2011). *Earthquake engineering for structural design*. New York: Spon Press.
- Goretti, A. and Di Pasquale, G. (2006). Technical emergency management. In Oliveira, C.S., Roca, A. and Goula, X. *Assessing and Managing Earthquake Risk*. Netherlands: Springer. pp. 339-368.

- Gosar, A. (2010). Site effects and soil-structure resonance study in the Kobarid basin (NW Slovenia) using microtremors. *Natural Hazards Earth System Sciences*, 10, pp. 761-772.
- Gosar, A., Roser, J., Motnikar, B.S. and Zupancic, P. (2010). Microtremor study of site effects and soil-structure resonance in the city of Ljubljana (central Slovenia). *Bulletin of Earthquake Engineering*, 8, pp. 571-592.
- Gosar, A. (2009). Microtremor Soil-Structure Resonance in the Bovec Basin (NW Slovenia) Related to 1998 and 2004 Damaging Earthquake. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 241-279.
- Gosar, A. (2007). Microtremor HVSR study for assessing site effects in the Bovec basin (NW Slovenia) related to 1998 M_w 5.6 and 2004 M_w 5.2 earthquakes. *Engineering Geology*, 91, pp. 178-193.
- Gueguen, P., Gallipoli, M.R., Navarro, M, Masi, A., Michel, C., Guillier, B., Karakostas, C., Lekidis, V., Mucciarelli M., Ponzio, F. and Spina, D. (2014). Testing building using ambient vibration for earthquake engineering: A European review. *Second European Conference on Earthquake Engineering and Seimology*. Turkey: Istanbul. pp. 1-12.
- Guillier, B., Atakan, K., Chatelein, J.L, Havskov, J. Ohrnberger, M. Cara, F., Duval, A.M., Zacharopoulos S., Teves-Costa, P. and the SESAME team (2008). Influence of instrument on HVSR spectral ratio of ambient vibration. *Bulletin of Earthquake Engineering*, Vol 6, Issue 1, pp. 3-31.
- Greco, B., Radulian, M., Mandrescu, N. and Panza, G. (2008). Relevance of H/V spectral ratio technique for Bucharest City. In Zacenco, A., Craifaleanu, I. and Paskaleva, I. *Harmonization of Seismic Hazard in Vrancea Zone*. Netherlands: Springer. pp. 133-149.
- Hashim, H., Ibrahim, Z and Abdul Razak, H. (2013). Dynamic characteristics and model updating of damaged slab from ambient vibration measurements. *Measurement*, 46, pp. 1371-1378.
- Havskov, J. and Alguacil, G. (2002). *Instrumentation in Earthquake Seismology*. Netherland: Springer.
- Herak, M. (2009). Recent applications of ambient vibration measurement in Croatia. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by*

Combining Engineering Technologies and Seismological Data. Netherlands: Springer. pp. 281-292.

Hinzen, K.G. and Weber, B. (2004). On the resolution of H/V measurements to determine sediment thickness, a case study across a normal fault in the lower rhine embayment, Germany. *Journal of Earthquake Engineering*, Vol. 8, No. 6, pp. 909-906.

Indian Standard. (2002). *Criteria for Earthquake Resistant Design Of Structures*. New Delhi, India: IS 1893:2002.

Ibrahim, Z., Jamadin, A. Kamarudin, A.F., Ibrahim, A. Daud, M.E. and Madun, A. (2014). Ambient vibration testing of partially damaged reinforced concrete building structure. *International Conference on Innovation Trends in Multidisciplinary Academic Research, ITMAR 20th-21st October 2014*. Turkey: Istanbul. pp. 1-9.

Ibs-von Seht, M. and Wohlenberg, J. (1999). Microtremor measurements used to map thickness of soft sediments. *Bulletin of the Seismological Society of America*, 89, pp. 250–259.

Jun, Y. (2006). Frequency-dependent amplification of unsaturated surface soil layer. *Journal Geotech and Geoenvironmental Engineering*, V 132, pp. 526-531.

IKRAM Group Sdn. Bhd. (2009). Laporan Akhir Penyiasatan Tapak untuk Cadangan Membina Bangunan Gantian di Sekolah Kebangsaan Sungai Tongkang, Batu Pahat, Johor Darul Takzim, Malaysia. Malaysia: SI Report.

IKRAM Group Sdn. Bhd. (2008). *Laporan Akhir Penyiasatan Tapak untuk Cadangan Membina Bangunan Gantian di Sekolah Kebangsaan Sri Molek, Batu Pahat Johor. Malaysia*. Malaysia: SI Report.

Imai, T. and Yoshimura, Y. (1970). Elastic wave velocity and soil properties in soft soil. *Tsuhito-Kiso* 18(1), pp. 17–22.

Jabatan Kerja Raya-JKR. (2010). *Kerja kerja pembinaan blok gantian dan lain-lain kerja berkaitan di Sek. Keb. Seri Molek, Senggarang, Johor*. Malaysia: Document Kontrak (Lukisan).

Jabatan Kerja Raya-JKR. (2008). *Kerja kerja pembinaan blok gantian dan lain-lain kerja berkaitan di Sek. Keb. Sg Tongkang, Rengit, Johor*. Malaysia: Document Kontrak (Lukisan).

Jabatan Ukur dan Pemetaan Malaysia. (1996) *Topography Maps of Senggarang (4252d) Batu Pahat*. JUPEM. Siri L8028 Edisi 1 PPNM . Peta Topografi.

- Jabatan Ukur dan Pemetaan Malaysia. (1996). *Topography Maps of Batu Pahat (168)*. JUPEM. Siri DNMM 5101 Edisi 1 PPNM . Peta Topografi.
- Jafari, M.K., Asghari, A. and Rahmani, I. (1997) Empirical correlation between shear wave velocity (V_s) and SPT-N value for south Tehran soils. *The 4th International Conference on Civil Engineering*. Iran: Tehran.
- Kamarudin, A.F., Ibrahim, A., Mokhtar, S.N., Zainal Abidin, M.H., Faisal, A. Abu Bakar, A., Tian, L.Z., Zhu, G.J., Khairul, M.F. and Ahmad Johari, H.H. (2020). Dynamic Characteristics Evaluation on Portable Steel Frame against Vertical Mass Irregularities. *International Journal of Integrated Engineering (IJIE)*, UTHM, 9, 224. (accepted for publication).
- Kamarudin, A.F., Daud, M.E., Ibrahim, A. and Ibrahim Z. (2016). Empirical filtering method for natural frequencies evaluation of low rise reinforced concrete school building using ambient vibration approach. In Kim, D. K., Jung, J. and Seo, J. *Advances in Civil, Architectural, Structural and Constructional Engineering*. Netherland: CRC Press/Balkema. pp. 247-252.
- Kanai, K. (1957). The requisite conditions for predominant vibration ground. *Bull. Earthq. Res. Inst. Tokyo Univ*, 31, pp. 457.
- Karapetrou, S., Manakaou, M. Bindi, D., Petrovic, B. and Pitilakis, K. (2016). “Time-building specific” seismic vulnerability assessment of a hospital RC building using field monitoring data. *Engineering Structures*, 112, pp.114-132.
- Kastner, R., Kjekstad, O. and Standing, J. (2003). *Avoiding damage caused by: soil-structure interaction: lesson learnt from case histories*. London: Thomas Telford.
- Kebeasy, T.R.M, Husebye, E.S. and Hestholm, S. (2005). Are the rock avalanches and landslides due to large earthquake or local topographic effect? A case study of Luroy Earthquake of August 31, 1819, A 3D finite difference approach. In Husebye, E.S. *Earthquake monitoring and seismic hazard mitigation in Balkan countries*. Norway: Springer, Dordrecht. pp. 271-289.
- Keceli, A. (2012). Soil parameter which can be determined with seismic velocities. *Jeofizik*, 16, pp. 17-29.
- Ko, J.M. and Ni, Y.Q. (2005). Technology developments in structural health monitoring of large-scale bridges. *Engineering Structures*, 27(12), pp. 1715-1725.

- Kobayashi, H., Vidal, F., Feriche, D., Samano, T. and Alguacil, G. (1996). Evaluation of dynamic behavior of building structures with microtremors for seismic microzonation mapping. *11th World Conference on Earthquake Engineering*. Mexico: Acapulco. pp. 23-28.
- Koller, M.G., Chatelain, J.L., Guillier, B., Duval, A.M., Atakan, K., Lacave, C., Bard, P.Y. and SESAME participants (2004). Practical user guidelines and software for the implementations of the H/V ratio technique: Measuring conditions, processing method and results interpretation. *13th World Conference on Earthquake Engineering*, Canada: Vancouver, B.C. Paper No. 3132.
- Koong, N.K. and Won, L.K. (2005). Earthquake hazard and basic concepts of seismic resistant design of structure. *Master Builders: 4th Quarter*, pp. 90-95.
- Konno, K. and Omachi, T. (1998). Ground-Motion Characteristics Estimated from Spectral Ratio between Horizontal and Vertical Components of Microtremor. *Bulletin of the Seismological Society of America*, 88, (1), pp. 228-241.
- Kostinakis, K. and Athanatopoulou, A. (2019). Effects of in-plan irregularities caused by masonry infills on the seismic behavior of R/C buildings. *Soil Dynamics and Earthquake Engineering, Articles in press*, pp.1-14. <https://doi.org/10.1016/j.soildyn.2019.03.012>
- Lachet, C. and Bard, P.Y. (1994). Numerical and theoretical investigation on the possibilities and limitation of Nakamura's technique. *Journal of Physics of the Earth* 42, pp. 337-397.
- Lane, J.W., Jr., White, E.A., Steele, G.V. and Cannia, J.C. (2008). Estimation of bedrock depth using the horizontal-to-vertical (H/V) ambient-noise seismic method. In *Symposium on the Application of Geophysics to Engineering and Environmental Problems, Proceedings: Denver, Colorado, Environmental and Engineering Geophysical Society, April 6th-10th, 2008*. Philadelphia: Pennsylvania.
- Lat, C.N. and Ibrahim, A.T. (2009) Bukit Tinggi earthquakes: November 2007 – January 2008. *Bulletin of Geological Society of Malaysia* 55, pp. 81-86.
- Lee, C.T. and Tsai, B.R. (2008) Mapping V_{s30} in Taiwan. *Terrestrial, Atmospheric and Oceanic Sciences* 19(6), pp. 671-682.

- Lermo, J. and Chavez-Garcia, J. (1994). Are Microtremors useful in site response evaluation? *Bulletin of Seismological Society of America*, 84 (5), pp. 1350-1364.
- Leyton, F., Ruiz, S., Sepúlveda, S.A., Contreras, J. P., Rebolledo, S. and Astroza, M. (2013). Microtremors' HVSR and its correlation with surface geology and damage observed after the 2010 Maule earthquake (Mw 8.8) at Talca and Curicó, Central Chile. *Engineering Geology*, Vol. 161, pp. 26-33.
- Li, Q. and Li, D. (2017). Structure damage identification under ambient excitation based on wavelet packet analysis. *Journal of Physics: Conf. Series* 842, pp. 1-12.
- Li, H.N., Li, D. S. and Song, G. B. (2004). Recent applications of fiber optic sensors to health monitoring in civil engineering. *Engineering Structures*, 26(11), pp. 1647-1657.
- Lin, J-L., Tsaur, C-C. and Tsai, K-C. (2019). Two-degree-of-freedom modal response history analysis of buildings with specific vertical irregularities. *Engineering Structures*, 184, pp. 505-523.
- Lindeburg, M.R. and Baradar, M. (2006). *Seismic design of building structures*. 8th ed. USA: Professional Publication, Inc.
- Lungu, D., Arion, C. and Aldea, A. (2008). Seismic protection and protection against demolition of Bucharest historical buildings. In Zacenco, A., Craifaleanu, I. and Paskaleva, I. *Harmonization of Seismic Hazard in Vrancea Zone*. Netherlands: Springer. pp 101-116.
- Malaysia Meteorological Department (2013). *MMD Seismic Station Code and Location*. Fi and services from MMD archive, Petaling Jaya, Malaysia: Malaysia seismological station.
- Malaysia Meteorological Department (2013). *Record of Felt Earthquake and Intensity in Peninsular Malaysia*. Fi and services from MMD archive, Petaling Jaya, Malaysia: Earthquake event catalogue.
- Malaysia Meteorological Department (2013). *Record of Felt Earthquake and Intensity in Peninsular Malaysia*. Fi and services from MMD archive, Petaling Jaya, Malaysia: Earthquake felt event.
- Malaysia Meteorological Department (2013). *Intensity Record*. Fi and services from MMD archive, Petaling Jaya, Malaysia: Earthquake intensity.

- Malaysia Meteorological Department (2013). *Weak Motion and Strong Motions Time Histories recorded by KGM and FRM stations*. Fi and services from MMD archive, Petaling Jaya, Malaysia: Acceleration time series.
- Marek, A.R., Bray, J.D. and Abrahamson, N.A. (2009). An empirical geotechnical seismic site response procedure. in Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*, Netherlands: Springer. pp. 353-380.
- Mana, F., Bozzo, L. and Irizaary, J. (2006). Building against earthquakes. In Oliveira, C.S., Roca, A. and Goula, X. *Assessing and Managing Earthquake Risk*. Netherlands: Springer. pp. 287-308.
- Manafizad, A.N., Pradhan, B. and Abdullahi, S. (2016). Estimation of peak ground acceleration (PGA) for peninsular Malaysia using geospatial approach. *IOP Conf. Series: Earth and Environmental Science*, 37, pp. 1-12.
- Maresca, R., Nardone, L. Gizzi, F.T. and Potenza, M.R. (2018). Ambient noise HVSR measurements in the Avellino historical centre and surrounding area (southern Italy). Correlation with surface geology and damage caused by the 1980 Irpinia-Basilicata earthquake. *Measurement*, 130, pp. 211-222.
- Masi, A. and Vona, M. (2009). Estimation of the period vibration of existing RC building types based on experimental data and numerical result. In Mucciarelli, M., Herak, M. and Cassidy, J., *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 207-225.
- Mavko, G. (n.d.). *Conceptual Overview of Rock and Fluid Factors that Impact Seismic Velocity and Impedance from Stanford Rock Physics Laboratory*, Retrieved April, 6 2016, from p. 73-112 at <https://pangea.stanford.edu/courses/gp262/Notes/8.SeismicVelocity.pdf>
- Mendecki, M. Bieta, B. and Mycka, M. (2014). Determination of the resonance frequency – thickness relation based on the ambient seismic noise records from Upper Silesia Coal Basin. *Contemporary Trends in Geoscience*, 3, 1, pp. 41-51.
- Meziane, Y.A., Djakab, E., Benouar, D. and Esat, I.I. (2012). Vulnerability of existing buildings: empirical evaluation and experimental measurements Yamina. *Natural Hazards*, 62. pp. 189-206.

- Minerals & Geoscience Department Malaysia. (1985). Geological Map of Peninsular Malaysia. Malaysia: JMG 8th edition.
- Mirzaoglu, M. and Dýkmen, U. (2003). Application of microtremors to seismic microzoning procedure. *Journal of the Balkan Geophysical Society*, 6, 3, pp. 143-156.
- Mitchel, C., Karbassi, A. and Lestuzzi, P. (2018). Evaluation of the seismic retrofitting of an unreinforced masonry building using numerical modeling and ambient vibration measurements. *Engineering Structures*, Vol. 158, pp. 124-135.
- Moisidi, M., Vallianatos, F., Soupios, P. and Kershaw, S. (2012). Spatial spectral variations of microtremors and electrical resistivity tomography surveys for fault determination in southwestern Crete, Greece. *Journal of Geophysics and Engineering*, 9, 3, pp. 261-270.
- Montesinos, F.G., Camacho, A.G., Nunes, J.C., Oliveira, C.S and Vieira, R. (2003). A 3-D gravity model for a volcanic crater in Terceira Island (Azores). *Geophysical Journal International*, 154, pp. 393-406.
- Motamed, R., Ghalandarzadeh, A., Tawhata, I. and Tabatabaei, S.H. (2007). Seismic microzonation and damage assessment of Bam City. Southern Iran, *J. Earthquake Eng.*, 11, pp. 110-132.
- Mucciarelli, M. and Gallipoli, M.R. (2007). Non-parametric analysis of a single seismometric record to obtain building dynamic parameters. *Annals of Geophysics*, Vol. 50, pp. 259-266.
- Mucciarelli, M. and Gallipoli, M.R. (2004). In-situ measurements of site effects and building dynamic behaviour related to damage observed during the 9/9/1998 earthquake in southern Italy. *Proceeding, ERE99 Conference*. Italy: Catania. Pp. 253-265.
- Mucciarelli, M. and Gallipoli, M.R. (2001). A critical review of 10 years of microtremor HVSR technique. *Bollettino Di Geofisica Teorica Applicata*, 42, pp. 255-266.
- Mucciarelli, M. (2001). An empirical method to assess the seismic vulnerability of existing buildings using HVSR technique. *Pure and Applied Geophysics*, 158, pp. 2635-2647.
- Mukherjee, A. and Joshi, M. (2005). FRPC reinforced concrete beam-column joints under cyclic excitation. *Composite Structures*, 70, pp. 185-199.

- Murty, C.V.R., Goswami, R., Vijayanarayanan, A. R. and Mehta, V.V. (2012). *Some Concepts in Earthquake Behaviour of Buildings*. Gujarat State Disaster Management Authority: Government of Gujarat, India. pp. 1-252.
- Nakamura, Y. (2019). What is the Nakamura Method? *Seismological Research Letters*, 90 (4), pp. 1437-1443.
- Nakamura, Y. (2009). Basic Structure of QTS (HVSr) and Examples of Applications. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 33-51.
- Nakamura, Y., Saita, J. and Sato, T. (2009). Application to World Heritage Sites. In Mucciarelli, M., Herak, M. and Cassidy, J. *Increasing Seismic Safety by Combining Engineering Technologies and Seismological Data*. Netherlands: Springer. pp. 293-324.
- Nakamura, Y. (2008). On the H/V Spectrum. *The 14th World Conference on Earthquake Engineering*. China: Beijing. pp. 1-10.
- Nakamura, Y. (2001). Inventory Development for Natural and Built Environments: Use of Seismic Motion and Microtremor for Vulnerability Assessment. *4th EQTAP Workshop in Kamakura, Japan*. pp. 1-6.
- Nakamura, Y. (2000). Clear identification of fundamental idea of Nakamura's technique and its applications. *12th World Conference on Earthquake Engineering*. New Zealand: Auckland. pp. 1-8.
- Nakamura, Y. (1996). Real-Time Information System for Seismic Hazard Mitigation UrEDAS, HERAS and PIC. *QR of RTRI, Vol. 37, No.3*, pp. 112-127.
- Nakamura, Y. (1989). A method for dynamic a dynamic characteristics estimations of subsurface using microtremor on the ground surface. *Q. Rept. Railway Technical Institute Japan*, 30, (1), pp. 25-33.
- NATO (2005). *Procedure Manual (Measurements Protocol & Crew Manual): Assessment of Seismic Site Amplification and Seismic Building Vulnerability in the Former Yugoslav Republic of Macedonia, Croatia and Slovenia*. Siena, Italy: SfP project 980857.
- Navarro, M. and Oliveira, C.S. (2006). Experimental techniques for assessment of dynamic behavior of buildings. In Oliveira, C.S., Roca, A. and Goula, X. *Assessing and Managing Earthquake Risk*. Netherlands: Springer. pp. 159-183.

- Navarro, M., Vidal, F., Feriche, M., Enomoto, T., Sánchez, F. J. and Matsuda, I. (2004). Expected ground–RC building structures resonance phenomena in Granada city (Southern Spain). *Proc. 13th World Conference on Earthquake Engin. Vancouver, B.C., Canada*. Paper No. 3308
- Nogoshi, N. and Igarashi, T. (1971). On the amplitude characteristics of microtremors. *J. Seism. Soc. Japan*, 24, pp. 24-40 (in Japanese with English abstract).
- Nogoshi, N. and Igarashi, T. (1970). On propagation characteristics of microtremors. *J. Seism. Soc. Japan*, 23, pp 264-280 (in Japanese with English abstract).
- Nozari, A., Behmanesh, I., Yousefianmoghadam, S., Moaveni, B. and Stavridis, A. (2017). Effects of variability in ambient vibration data on model updating and damage identification of a 10-story building. *Engineering Structures*, Vol. 151, pp. 540-553.
- NZSEE (2006). *Assessment and improvement of the Structural Performance of Buildings in Earthquakes*. New Zealand: Recommendations of a NZSEE Study Group on Earthquake Risk Buildings.
- Ojeda, A. and Escallon, J. (2000). Comparison between different techniques for evaluation of predominant periods using strong ground motion records and microtremors in Pereira Colombia. *Soil Dynamics and Earthquake Engineering*, 20, pp 137-143.
- Oliveira, C.S. and Navarro, M. (2010). Fundamental periods of vibration of RC buildings in Portugal from in-situ experimental and numerical techniques. *Bulletin of Earthquake Engineering*, 8, pp. 609-642.
- Pando, M., Cano, L., Suarez, L.E., Ritta, R. and Montejo, L.A. (2008). Comparison of site fundamental period estimates using weak motion earthquakes and microtremors. *The 14th World Conference on Earthquake Engineering*. China: Beijing.
- Panou, A.A., Theodulidis, N. Cornou. C., Hatzidimitriou, P.A., Papazachos, C.B., Bard, P.Y. and George, L. (2007). Use of ambient for microzonation studies in urban environment: The city of Thessaloniki (N. Greece). *4th International Conference on Earthquake, Geotechnical Engineering*. Paper no. 1580.
- Papadopoulos, M., Van Beeumen, R., François, S.G., Degrandea, G. and Lombaert, G. (2017). Computing the modal characteristics of structures considering soil-

- structure interaction effects. *Procedia Engineering Volume, 199*, pp. 2414-2419.
- Parolai, S., Bormann, P. and Milkereit, C. (2002). New Relationships between V_s , Thickness of Sediments, and Resonance Frequency Calculated by the H/V Ratio of Seismic Noise for the Cologne Area (Germany). *Bulletin of the Seismological Society of America, Vol. 92, No. 6*, pp. 2521–2527.
- Personal communication Zainuddin Sakiman, 26th September 2016.
- Personal communication Devadas, R., 23rd January 2013
- Personal communication Chatelain, J.L. 8th December, 2013.
- Personal communication Ariffin, 17th October 2012.
- Pinzón, L.A., Pujades, L.G., Macau, A. and Figueras, A. (2019). Increased seismic hazard in Barcelona (Spain) due to soil-building resonance effects. *Soil Dynamics and Earthquake Engineering, Vol. 117*, pp. 245-250.
- Poonam, A.K. and Gupta, A.K. (2012). Study of Response of Structurally Irregular Building Frames to Seismic Excitations. *International Journal of Civil, Structural, Environmental and Infrastructure Engineering Research and Development (IJCSEIERD)*, 2(2), pp. 25–31.
- Rahimi, E., Nikoudel, M.R., Moghaddas, N.H. and Ghayamghamian, M.R. (2012). Evaluating local geological condition and V_s profiles in Khash Area, SE Iran, *Science Series Data Report, 4*.
- Ramos, L.F., Marques, L., Lourenco, P.B., De Roeck, G., Campos-costa, A. and Roqe, J. (2010). Monitoring historical masonry structures with operational .modal analysis: Two case studies. *Mechanical Systems and Signal Processing, 24*, pp. 1291-1305.
- Roca, A., Oliveira, C.S., Ansal, A. and Figueras, S. (2006). Local Site Effect and Microzonation. In Oliveira, C.S., Roca, A. and Goula, X. *Assessing and Managing Earthquake Risk*. Netherlands: Springer. pp. 67-89.
- Roy, N., Shiuly, A, Sahu, R.B. and Jakka, R.S. (2018). Effect of uncertainty in VS–N correlations on seismic site response analysis. *J. Earth Syst. Sci. 127, 103*, pp. 1-21.
- RPA (2004). *Algerian seismic regulation 1999-version2003. DTR-BC 248 - National Center for Applied Research in Seismic Engineering*. Algeria: Alger. RPA-99/v2003.

- Sadashiva, V.K., MacRae, G.A. and Deam, B.L. (2009). Determination of structural irregularity limits –mass irregularity example. *Bulletin of the New Zealand Society for Earthquake Engineering*, Vol. 42, pp. 288-300.
- Safak, E. and Cakti, E. (2014). Simple Techniques to Analyze Vibration Records from Buildings. *7th European Workshop on Structural Health Monitoring, July 8-11*. France: Nantes. pp. 2153-2158.
- Sato, T., Nakamura, Y. and Saita, J. (2004). Evaluation of the amplification characteristics of subsurface using microtremor and string motion-the studies at Mexico city-. *13th World Conference on Earthquake Engineering*. Canada: Vancouver, B.C. Paper no. 862.
- SESAME. (2004). *Guidelines for the implementation of the H/V spectral ratio technique on ambient vibrations: measurements, processing and interpretation*. European Commission: Research General Directorate Project No. EVG1-CT-2000-00026.
- Shah, K. and Vyas, P. (2017). Effects of vertical geometric and mass irregularities in structure. *Kalpa Publications in Civil Engineering, 1*, pp. 87-92.
- Shakal, A.F. and Huang, M.-J. (2001). *CSIMP building instrumentation measurement objectives and models*. USA: COSMOS, Emeryville.
- Shelley, E.O., Smaniego, J.L., Aunivet, G. and Sanchez, E.M. (2012). Microtremor measurements to identify zones of potential fissuring in the basin of Mexico. *Geofisica Internacional*, 51-2, pp.143-156.
- Shih, H.W. (2009). *Damage assessment in structures using vibration characteristics*. Queensland University of Technology: PhD thesis.
- Shinoda, M., Watanabe, K., Kojima, K. and Tateyama, M. (2009). Outline of performance-based design for railway earth structure in Japan. In Kokusho, T., Tsukamoto, Y. and Yoshimine, M. *Performance-Based Design in Earthquake Geotechnical Engineering-from Case History to Practice*. Netherlands: CRC Press. pp. 137-148.
- Shuib, M.K. (2009). The recent Bukit Tinggi earthquake and their relationship to major geological structures. *Bulletin of the Geological Society of Malaysia*. pp. 67–72.
- Shye, K.Y. and Robinson, A.R. (1980). *Dynamic soil-structure interaction*. United States: University of Illinois: Technical Report of Research supported by

- National Science Foundation under Grant ENV 77-07190 and PFR 80-02582 (Structural Engineering Studies No. 484). pp 1-128.
- Snoj, J. Osterreicher, M. and Dolsek, M. (2013). The importance of ambient and force vibration measurements for the result of seismic performance assessment of buildings obtained by using simplified non-linear procedure: case study of an old masonry building. *Bull Earthquake Eng.* DOI 10.1007/s10518-013-9494-8.
- Soemitro, R.A.A., Warnana, D.D., Utama, W. and Asmaranto, R. (2011). Assessment to the Local site effects during earthquake induced landslide using microtremor measurement. *J. Basic. Appl. Sci.* 1(5), pp. 412-417.
- Stanko, D., Markušić, S., Strelec, S. and GAzdek, M. (2017). HVSR analysis of seismic site effects and soil-structure resonance in Varaždin city (North Croatia). *Soil Dynamics and Earthquake Engineering*, Vol. 92, pp. 666-677.
- Talib, R., Ahmad, A.G., Zakaria, N. and Sulieman, M.Z. (2014). Assessment of Factors Affecting Building Maintenance and Defects of Public Buildings in Penang, Malaysia. *Architecture Research*, pp. 48-53.
- Türker, T. (2014). Ambient vibration test of building base slab for different ground Conditions, *Measurement*, 52, pp. 77-84.
- Tobita, J., Fukuwa, N. and Yagi, S. (2000). Experimental evaluation of dynamic characteristics of low and medium-rise buiding with soil-structure interaction. *12th World Conference on Earthquake Engineering*. New Zealand: Auckland.
- Towhata, I (2008). *Geotechnical Earthquake Engineering*. Germany: Springer.
- Tuan Chik, T. N., Asie, R. A., Wan Ibrahim, M. H. and Yusoff, N. A. (2013). Dynamic performance of multistorey structure due to ground borne vibration input from passing vehicles. *International Journal of Integrated Engineering*, Vol. 5, No. 2, pp. 51-58.
- Tuladhar, R., Yamazaki, F., Warnitchai and Saita, J. (2004). Seismic microzonation of the greater Bangkok area using microtremor observations. *Earthquake Engineering and Structural Dynamics*, 33, pp. 211-225.
- Trifunac, M. D. (1972). Comparisons between ambient and forced vibration experiments. *Earthquake Enineering Structural Dynamics*, 1, pp. 133-150.
- Uehan, F. and Meguro, K. (2000). Vulnerability evaluation of jacketed viaduct using microtremor measurement & numerical simulation. *12th World Conference on Earthquake Engineering*. New Zealand: Auckland. pp. 1-8.

- Uniform Building Code (1997). *International Conference of Building Officials*. USA: Whittier, CA. UBC 1997 Volume 1.
- Uniform Building Code (1988). *International Conference of Building Officials*. USA: Whittier, CA. UBC 1988.
- Ventura, C.E., Ford, J.F., Turek, M., Brincker, R., Andersen, P. and Dascotte, E. (2005). *FEM updating of tall buildings using ambient vibration data*. 6th Structural Dynamics, Eurodyn.
- Warnana, D.D., Triwulan, Sungkono and Utama, W. (2011). Assessment to the soil-structure resonance using microtremor analysis on Pare - East Java, Indonesia. *Asian Transactions on Engineering (ATE ISSN: 2221-4267) Volume 01, Issue 04*, pp. 6-12.
- Wang, C., Xiao, J., Zhang, C. and Xiao, X. (2020). Structural health monitoring and performance analysis of a 12-story recycled aggregate concrete structure. *Engineering Structures*, 205, pp. 1-18.
- Wang, J., Dai, K. Yin, Y. and Tesfamariam, S. (2018). Seismic performance-based design and risk analysis of thermal power plant building with consideration of vertical and mass irregularities. *Engineering Structures*, Vol. 164, pp. 141-145.
- Wang, W., Liu, L., Chen, Q. and Rohrbach, E. (2008). Site responses and sediment structures along the NW and NE profiles in Beijing area revealed by microtremor H/V spectral ratio studies. *The 14th World Conference on Earthquake Engineering October 12-17*. China: Beijing.
- Wenzel, H. and Achs, G. (2006). Determination of site effects by ambient vibration monitoring. *First European Conference on Earthquake Engineering and Seismology (a joint event of the 13th ECEEE & 20th General Assembly of the ESC), 3-8 September*. Switzerland: Geneva. Paper number 1320. pp. 1-10
- Wolf, J.P. (1985). *Dynamic Soil-Structure Interaction*. United States: Prentice-Hall International. pp. 1-466.
- Woon, C.E. and Mitchell, L.D. (1996). Variation in structural dynamic characteristics caused by changes in ambient vibration temperature: I. Experimental. *Proceedings of the 14th International Modal Analysis Conference (IMAC XIV), February 12-15*. USA: Dearborn, Michigan. pp. 963-971.

- Wu, J.R. and Li, Q.S. (2006). Structural parameter identification and damage detection for a steel structure using a two-stage finite element model updating method. *Journal of Constructional Steel Research*, 62, pp. 231-239.
- Yuen, K.-V and Kuok, S-C. (2010). Ambient interference in long-term monitoring of buildings. *Engineering Structures*, 32, 8, pp. 2379-2386.
- Yuen, K.-V., Beck, J. L., and Katafygiotis, L. S. (2002). Probabilistic approach for modal identification using non-stationary noisy response measurements only. *Earthquake Engineering & Structural Dynamics*. Vol. 31, pp. 1007–1023. (DOI: 10.1002/eqe.135).
- Zainal Abidin, M.H. and Kamarudin, A.F. (2016). *Seismic Refraction Survey at Meteorological Station, Kluang Johor*. Faculty of Civil and Environmental Engineering. Universiti Tun Hussein Onn Malaysia: Fieldwork Report. pp.1-12. Unpublished.



VITA



Ts. Ahmad Fahmy bin Kamarudin presently is a lecturer in Faculty of Civil Engineering and Built Environment (FKAAB), UTHM. He obtained his B.Eng. (Civil Engineering) in 2003 and MSc. Civil Engineering (Structures) in 2006. He started his academic carrier as a tutor in KUiTTHO since 2004 and appointed as a permanent lecturer in UTHM since 2006. He has eight UTHM short term grants, three grants honored by The Ministry of Educational Malaysia, one e-science grant awarded by The Ministry of Science, Technology and Innovation Malaysia. He was appointed as assistance laboratory manager of FKAAB in 2019 to manage the heavy structure and light structure laboratories. He is now also a research member in Jamilus Research Centre, UTHM. His professional qualification includes a graduates engineer and Professional Technologist (Building and Construction Technologies). He is an active researcher especially in ambient vibration method for ground and structures condition assessments. Along his PhD journey, he had published a few indexed and non-indexed journal, conference proceeding and book chapter. He was awarded for the best paper award in international conference of ICCASCE 2015 in Busan, South Korea and the best paper presentation in IPN-IWNEST 2015 in Ho Chi Minh, Vietnam. Recently he won a gold award in research and innovation symposium of RISE 2019 in UTHM. The details of his publications and awards along his PhD path are listed as below:

Book Chapter:

- Kamarudin, A.F., Daud, M.E., Ibrahim, A. and Ibrahim, Z.** (2016). Empirical Filtering Method for Natural Frequencies Evaluation Of Low Rise Reinforced Concrete School Building Using Ambient Vibration Approach. In: Kim, D.K., Jung, J. and Seo, J. *In Advances Civil, Architectural, Structural And Constructional Engineering*. London, UK: CRC Press/Balkema, Taylor & Francis Group. pp. 247-252. ISBN:978-1-138-02849-4
- Kamarudin, A.F., Daud, M.E., Boon, K.H., Ibrahim, Z. and Ibrahim, A.** (2013). Dynamic Characteristics and Seismic Performance Evaluation of Low Rise Existing RC Moment Resisting Frame using Microtremor Technique and Standard Code of Practice. In: Camarinhas, C.L., Zaharia, R., Dan, D., Lucaci, G., Batisha, A and Arad, V *In Recent Advances in Civil and Mining Engineering*. Antalya, Turkey: WSEAS Press. pp. 182-191. ISBN: 978-960-474-337-7.

Journal Publication (SCOPUS):

- Kamarudin, A.F., Mokhtar, S.N., Md Noh, M.S., Mohd Sulaiman, M.A., Abdul Haris, A.N., Zainal Abidin, M.H., Daud, M.E., Ibrahim, A. and Ibrahim, Z.** (2019). Evaluation of Steel Stairwell Dynamic Characteristics, Under Few Mass Configurations using Ambient Vibration Method. *International Journal of Integrated Engineering (IJIE), UTHM, 11, No.6*, pp. 224-235.
- Kamarudin, A.F., Md Noh, M.S., Mokhtar, S.N., Mohd Anuar, M.A., Ibrahim, A., Ibrahim, Z. and Daud, M.E.** (2018). Influence of Traffic Vehicles against Ground Fundamental Frequency Prediction using Ambient Vibration Technique. *Journal of Physics: Conf. Series, 995*, pp. 1-10.
- Kamarudin, A.F., Zainal Abidin, M.H., Mokhtar, S.N., Daud, M.E., Ibrahim, A., Ibrahim, Z. and Md Noh, M.S.** (2018). Identification of Natural Frequency of Low Rise Building on Soft Ground Profile using Ambient Vibration Method. *Journal of Physics: Conf. Series, 995*, pp. 1-10.
- Kamarudin, A.F., Daud, M.E., Ibrahim, Z., Ibrahim, A., Yub, M.K. and Mohd Noor, M.A.** (2014). Estimation of Site Dynamic Characteristics from Ambient Noise Measurements using HVSR Method in Microzonation Study: Senggarang, Batu Pahat, Malaysia. *Advanced Materials Research. 2014, Vols., 931-932*, pp. 803-807.

Journal Publication (NON-SCOPUS):

- Kamarudin, A. F., Daud, M.E., Ibrahim, A., Ibrahim, Z. and Koh, H. B.** (2014). Dynamic Characteristics of Site And Existing Low Rise RC Building for Seismic Vulnerability. *International Journal of Geology, Vol. 8*, pp. 28-38.
- Kamarudin, A.F., Daud, M.E., Ibrahim, A., Ibrahim, A.** (2015). Part 1: Verification of HVSR Method at Minyak Beku Outcrop Bedrock in Johor, Peninsular Malaysia. *International Journal of Applied Engineering Research, Vol. 10, No. 81*, pp. 1-5.
- Kamarudin, A.F., Daud, M.E., Ibrahim, A., Ibrahim, A.** (2015). Part 2: Case Studies - Evaluation of Site Fundamental Frequency and Ground Characterization on Rock and Sedimentary Sites Using HVSR Method. *International Journal of Applied Engineering Research, Vol. 10, No. 81*, pp. 72-76.

Conference Series (SCOPUS):

- Kamarudin, A.F., Mokhtar, S.N., Zainal Abidin, M.H., Daud, M.E., Rosli, M.S., Ibrahim, A., Ibrahim, Z. and Md Noh, M.S.** (2018). Structural Health Monitoring on Medium Rise Reinforced Concrete Building using Ambient Vibration Method. *4th International Conference on Civil and Environmental Engineering for Sustainability. 4 - 5 December 2017. Malaysia: Langkawi: IOP Conf. Series: Earth and Environmental Science*, pp.1-8.

Conference Series (NON SCOPUS):

- Kamarudin, A.F. Daud, M.E., Ibrahim, Z. and Ibrahim, A.** (2016). Sustainable Non-Destructive Technique Ambient Vibrations for

Ground Assessments. *Procedia - Social and Behavioral Sciences* 216, Elsevier, pp. 701-711. ISBN: 1877-0428.

Kamarudin, A.F. and Mohd. Noor, M.A. (2013). Application of HVSR Method from Ambient Noise Measurement for Microzonation Study in Batu Pahat Region. *The International Conference on Engineering and Built Environment (ICEBE) 2013, 19th to 20th November 2013*. Malaysia: Universiti Kebangsaan Malaysia, Bangi.

Awards:

Best Presenter Award in the 2nd International Conference on Agriculture, Biotechnology, Science and Engineering 2015 (IPN-IWNEST 2015), 28th to 29th August 2015. Vietnam: Ho-Chi Minh.

Best Paper Award in International Conference on Civil, Architectural, Structural and Constructional Engineering (ICCASCE 2015). 21st to 23rd August 2015. South Korea: Busan.

Innovative Portable Steel Frame Structure (PostFrame) – **Gold Award** in International Research and Innovation Symposium and Exposition 2019. 24th September 2019. Malaysia: Johor.

Accepted SCOPUS Journal (Waiting for Publication):

Kamarudin, A.F., Ibrahim, A., Mokhatar, S.N., Zainal Abidin, M.H., Ade Faisal, Abu Bakar, A., Lim, Z.T., Goh, J.Z., Khairul, M.F. and Ahmad Johari, H.H. (2020). Dynamic Characteristics Evaluation on Portable Steel Frame against Vertical Mass Irregularities. *International Journal of Integrated Engineering (IJIE), UTHM*, 9. ISSN:2229838X



PERPUSTAKAAN UNIVERSITI TEKNIKAL MELAKA