

PERFORMANCE OF SHORT PILED RAFT FOUNDATION SYSTEM  
ON PEAT SOIL UNDER STATIC LOAD

SAJIHARJO BIN MARTO SURO

A thesis submitted in  
fulfilment of the requirement for the award of the  
Doctor of Philosophy in Civil Engineering



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH  
Faculty of Civil Engineering and Built Environment  
Universiti Tun Hussein Onn Malaysia

DECEMBER 2020

For my beloved family, especially my dearest wife Tuty Handayani, as well as the three my beloved sons, Herolistra Baskoroputro, Elgodwistra Kartikoputro and Paripurna Bawonoputro, also the three my dearest grandchildren and my two daughters in law



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## ACKNOWLEDGEMENT

First of all, the author praises Allah for His grace, gifts, and blessings bestowed upon the author, so that this research can be completed. Alhamdulillah.

The author wishes to express his much gratitude to Assoc. Prof. Ts. Dr. Adnan bin Zainorabidin, as Supervisor, for his very kind encouragement, guidance patiently, friendship, 24 hours per day his time availability to assist and inspiration given throughout the Post Graduate period.

The author is also grateful to his Co-Supervisors, Prof. Dato' Dr. Ismail bin Bakar, and Dr. Ir. Agus Sulaeman, for their kind encouragement from the beginning of this research, competent guidance, excellent ideas and very nice friendship.

Besides, the author thanks to ORICC for financial support as GRA and Research Contract Grant, also to Prof. Dato' Dr. Mohd Idrus bin Mohd Masirin, former Head of RECESS, Ts. Dr. Nor Azizi bin Yusoff, Head of RECESS, and UTHM staff, Mr. Amirzaki bin Salikin, Mr. Mudzaffar Syah bin Kamarudin, Mrs. Salina binti Sani, Mr. Mohamad Johari bin Zainal and Mr. As'shar bin Kasalan who have given many valuable assistants during Post Graduate period.

The gratitude is extended to Dr. Ir. Supriadi Legino, MM, MBA, MA, former Director of Sekolah Tinggi Teknik-PLN who has given the opportunity and support for the author to carry out Ph.D Program at UTHM, and also Prof. Dr. Ir. Iwa Garniwa Mulyana K, MT., current Rector of Institut Teknologi-PLN who has supported the author to complete this Ph.D Program.

Last but not least, the author thanks to all of UTHM Post Graduate students and all other people that impossible to be mentioned one by one, for their valuable contribution during the Post Graduate research period that enable this PhD Program can be completed.



## ABSTRACT

Peat is known as problematic soil, because has low shear strength and high compressibility characteristics. Particular attention should be paid, when building a construction on it. In recent years, there is no special established foundation structure for peat yet, without any treatment of soil. Thus, notably for a depth of 3 to 10 m of the peat layer, there is a challenge to develop a foundation system on peat without any stabilization nor remove and replace, especially for foundation under static point load. This research was conducted to explore a proposed Short Piled Raft (SPR) foundation system, which is a combination of a pile foundation and raft foundation, with a pile length short enough. The objectives of this research were to optimize pile spacing of SPR foundation system related to its stability, especially immediate settlement. The optimization was carried out by comparing some results of simulation using Plaxis 3D Foundation software for numerical modelling. The software was also used for another simulation series with some different soil parameters and site conditions. The selected results of numerical modelling were verified by using the full scale model. Optimum pile spacing of the SPR foundation system with the pile length of 3.0 m and pile outer diameter of 0.32 m is 1.0 m. It was found that SPR foundation system has superiority than other previous methods (Chicken Claw and Nailed Slab). The main reason is that SPR has weight relatively lighter than others, caused by utilizing the uplift force to closed end pipe as pile and the thin concrete slab. While for loading test of full scale model of 3.0 m x 3.0 m concrete slab with the thickness of 0.15 m and 9 closed end short piles, the result shown a good performance. The SPR was able to support 100% design load of 100 kN, with maximum immediate settlement was 19 mm and for 160% design load, maximum immediate settlement was 34 mm. The knowledge contribution of this research is a proposed chart for basic step to design SPR. With these findings, it is hoped that the next research is recommended to research stability of the SPR on peat under static load in the long term and also for dynamic load.

## ABSTRAK

Gambut dikenali sebagai tanah bermasalah, kerana mempunyai kekuatan ricih rendah dan ciri-ciri mampatan yang tinggi. Perhatian khusus harus diberikan, ketika membina bangunan di atasnya. Hingga masa ini, belum ada struktur asas khas untuk gambut, tanpa rawatan tanah. Oleh itu, terutama untuk kedalaman 3 hingga 10 m lapisan gambut, ada cabaran untuk mengembangkan sistem asas pada gambut tanpa penstabilan atau pembuangan dan penggantian, terutama untuk asas di bawah beban titik statik.. Penyelidikan ini dijalankan untuk meneroka sistem asas Rakit Cerucuk Pendek (RCP), yang merupakan gabungan asas cerucuk dan asas rakit, dengan panjang cerucuk cukup pendek. Objektif penyelidikan ini adalah untuk mengoptimumkan jarak cerucuk sistem asas RCP yang berkaitan dengan kestabilannya, terutama penurunan segera. Pengoptimuman itu dilakukan dengan membandingkan beberapa hasil simulasi menggunakan perisian Plaxis 3D Foundation untuk pemodelan berangka. Perisian ini juga digunakan untuk siri simulasi lain dengan beberapa parameter yang berbeda. Hasil pemodelan berangka yang dipilih disahkan dengan menggunakan model skala penuh. Jarak cerucuk optimum sistem asas RCP dengan panjang cerucuk 3.0 m dan diameter luar cerucuk 0.32 m ialah 1.0 m. Didapati bahawa sistem asas RCP mempunyai kelebihan berbanding kaedah sebelumnya yang lain (Chicken Claw dan Nailed Slab). Sebab utama adalah bahawa RCP mempunyai berat yang relatif lebih ringan daripada yang lain, disebabkan oleh penggunaan daya angkat ke paip hujung tertutup sebagai cerucuk dan papak konkrit tipis. Sedangkan untuk ujian beban model skala penuh papak konkrit 3.0 m x 3.0 m dengan ketebalan 0.15 m dan 9 cerucuk pendek hujung tertutup, hasilnya menunjukkan prestasi yang baik. RCP mampu menyokong beban jangkaan 100% 100 kN, dengan penurunan segera maksimum adalah 19 mm dan untuk beban jangkaan 160%, penurunan segera maksimum adalah 34 mm. Sumbangan pengetahuan penyelidikan ini adalah anjuran carta untuk langkah awal untuk merancang RCP. Dengan penemuan ini, diharapkan penyelidikan seterusnya disarankan untuk meneliti kestabilan RCP pada gambut di bawah beban statik dalam jangka panjang dan juga beban dinamik.

## TABLE OF CONTENT

<b>ACKNOWLEDGEMENT</b>	<b>iii</b>
<b>ABSTRACT</b>	<b>iv</b>
<b>ABSTRAK</b>	<b>v</b>
<b>TABLE OF CONTENT</b>	<b>vi</b>
<b>LIST OF TABLES</b>	<b>x</b>
<b>LIST OF FIGURES</b>	<b>xi</b>
<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xv</b>
<b>LIST OF APPENDIXES</b>	<b>xvii</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 Background	1
1.2 Problem Statements	2
1.3 Aims	3
1.4 Objectives	3
1.5 Scopes and Limitations	4
1.6 Significant Knowledge Contributions	4
1.7 Outline of Thesis	5
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>6</b>
2.1 Introduction	6
2.2 Peat	6
2.2.1 Distribution of peatland	7
2.2.2 Definition of peat and organic soil	9
2.2.3 Classification of fibre content and degree of humification	11
2.2.4 Index properties of peat	12
2.2.4.1 Water content	12
2.2.4.2 Atterberg limit	14



2.2.4.3	Unit weights	14
2.2.4.4	Specific gravity	15
2.2.4.5	Internal friction angle ( $\phi$ ) and cohesion (C)	16
2.2.5	Settlement of peat	17
2.3	Construction Methods on Peat	18
2.4	Raft Foundations	20
2.5	Piled Raft Foundations	20
2.5.1	Chicken claw foundation system	22
2.5.2	Nailed slab foundation system	24
2.6	Modelling in Geotechnics	26
2.7	Loading Test on Full Scale Model	27
2.8	Settlement of Full Scale Model on Peat	34
2.9	Plaxis 3-D Application Software	35
2.10	Chapter Summary	36
<b>CHAPTER 3</b>	<b>RESEARCH METHODOLOGY</b>	<b>39</b>
3.1	Introduction	39
3.2	Description and Selection Project Site	40
3.3	Soil Investigations	43
3.3.1	Laboratory Works	46
3.3.1.1	Moisture Content	47
3.3.1.2	Density of soil	49
3.3.1.3	Triaxial	50
3.4	Setting-up Proposed SPR Foundation System	53
3.5	Establishment of SPR foundation system	53
3.5.1	Pile spacing optimization	55
3.5.2	Sensitivity analysis	57
3.5.3	Influence of pile length	60
3.5.4	Influence of peat layer thickness	60
3.5.5	Eccentric load	61
3.5.6	Comparison to previous researches	62
3.6	Full Scale Model	62
3.6.1	Implementation of full scale model construction	63
3.6.1.1	Preparation of field and workshop	63
3.6.1.2	Mobilization and piling	66
3.6.1.3	Constraints during piling	68



3.6.1.4 Concrete slab reinforcement and casting	71
3.6.2 Loading test	74
3.6.2.1 Preparation of loading test	78
3.6.2.2 Loading procedures	79
3.6.2.3 Procedures of measuring movements	81
3.6.2.4 Implementation of loading test	85
3.7 Chapter Summary	88
<b>CHAPTER 4 RESULTS AND DISCUSSIONS RELATED TO NUMERICAL MODELLING</b>	<b>90</b>
4.1 Introduction	90
4.2 Laboratory Work	90
4.3 Establishment of SPR Foundation System	90
4.3.1 Pile spacing optimization	91
4.3.2 Sensitivity analysis	93
4.3.2.1 Internal friction angle $\phi$	93
4.3.2.2 Cohesion C	93
4.3.2.3 Unit weight $\gamma_{\text{unsat}}$	94
4.3.2.4 Ground water level (GWL)	95
4.3.3 Influence of pile length	97
4.3.4 Influence of peat layer thickness	98
4.3.5 Eccentric load	100
4.3.6 Comparison to other previous researches	101
4.4 Chapter Summary	102
<b>CHAPTER 5 RESULTS AND DISCUSSIONS RELATED TO FULL SCALE MODEL TESTING</b>	<b>104</b>
5.1 Introduction	104
5.1.1 Overall settlements	104
5.1.2 Differential settlements	107
5.1.3 Deduction of loading test duration	110
5.2 Developing Design Chart for SPR Foundation System	113
5.3 Chapter Summary	115
<b>CHAPTER 6 CONCLUSIONS AND RECOMMENDATIONS</b>	<b>117</b>
6.1 Introduction	117
6.2 Conclusions	117
6.3 Recommendation	118





<b>REFERENCES</b>	<b>118</b>
<b>APPENDICES</b>	<b>125</b>
<b>Appendices A1 – A 5 Loding Test</b>	<b>126</b>
<b>Stages Loading from 20 to 100 kN</b>	<b>126</b>
<b>Appendices B1 – B 5 Loding Test</b>	<b>132</b>
<b>Stages Unloading from 80 to 0 kN</b>	<b>132</b>
<b>Appendices C1 – C 8 Loding Test</b>	<b>138</b>
<b>Stages Reloading from 20 to 160 kN</b>	<b>138</b>
<b>Appendices D Loading Test</b>	<b>147</b>
<b>Stages Remain 160 kN</b>	<b>147</b>
<b>Appendices E1 –E8 Loding Test</b>	<b>149</b>
<b>Stages Unloading from 140 to 0 kN</b>	<b>149</b>
<b>Appendix F</b>	<b>158</b>
<b>Example Using Chart Design Short Piled Raft Foundation System</b>	<b>158</b>
<b>APPENDIXES G-1 TO G-9</b>	<b>160</b>
<b>PUBLISHED PAPERS</b>	<b>160</b>
<b>VITA</b>	<b>171</b>



## LIST OF TABLES

2.1	Peat land area in some countries of the world (Huat et al., 2014)	8
2.2	Classification of peat in ASTM (ASTM D1997; ASTM D2974; ASTM D2976)	11
2.3	Qualifying terms of von Post scale	11
2.4	von Post degree of humification	13
2.5	Natural water content of various peat deposits	13
2.6	Typical unit weight of various peat deposits	15
2.7	Typical specific gravity of various peat deposits	15
2.8	Typical of internal friction angle ( $\phi$ ) and cohesion (C) of various peat deposits	17
2.9	Summary of previous researches of piled raft variant	26
2.10	Summary of explained foundation system	37
3.1	Soil, pile and raft parameters used for SPR foundation simulation	55
3.2	Variation of pile spacing for simulation series	55
3.3	Selected parameters for sensitivity analysis	60
3.4	Selected pile size for simulation	60
3.5	Selected thickness of peat layer	61
3.6	Sequence of reading during loading and unloading test	84
4.1	Peat soil properties of Parit Nipah	90
4.2	Parameters used for comparison simulation and results	103
5.1	Relationship between load and settlement	106
5.2	Relationship between load and settlement at point CR based on original and shortened reading time	113

## LIST OF FIGURES

1.1	Sedenak Factory Park Project, Sedenak, Johor, Malaysia.	1
1.2	Removal and replacement method of peat at Sedenak Factory Park Project, Sedenak, Johor, Malaysia.	3
2.1	Distribution of peat land in the worldwide	9
2.2	Distribution of peat land in Malaysia	9
2.3	Location of peat land in Indonesia and vicinity	10
2.4	Simplified load transfer mechanism of piled raft foundations	21
2.5	Nature of variation of lateral earth pressure at a certain depth	22
2.6	Chicken claw foundation system	24
2.7	Nailed slab foundation system, (a) plan; (b) cross section A-A	25
2.8	Schematic of foundation tests	28
2.9	Compression pile group load test	28
2.10	Load-displacement behaviour for S1 and corner and centre piles of G1	29
2.11	Soil condition at test point 1	30
2.12	Cross-sectional sketch showing arrangement of the reinforcement	30
2.13	Load-settlement curves of test point 1	31
2.14	Applying loads to pile using hydraulic jack acting against anchored reaction frame (ASTM D 1143 – 81)	32
2.15	Applying loads to pile using hydraulic jack acting against a weighted box or platform (ASTM D 1143 – 81)	32
2.16	Applying load to pile group using weighted platform	33
2.17	Applying tests loads directly on pile cap for group tests	33
2.18	Loading tests results	34
2.19	Typical of SPR foundation system (a) general plan; (b) section A-A	38
3.1	Flow chart of research outline	39
3.2	Map of Malaysia, inset: Johor Darul Takzim	40
3.3	Map of Johor Darul Takzim, inset: direction to the project site	41

3.4	Soil profile of Parit Nipah Darat using peat sampler	42
3.5	Direction from UTHM to project site, at Parit Nipah Darat	42
3.6	Surrounding project site area; (a) house of villager	43
3.7	Area identity; (a) sign board of Research on Peat Station (REPEATS) and (b) tag of research project at Parit Nipah Darat	43
3.8	Execution of von Post	44
3.9	Soil Sampling; (a) cleared top soil; (b) inserting sampler tubes	45
3.10	Soil Sampling; (a) peat samples; (b) cleaning before wrapping	45
3.11	Soil Sampling, (a) wax covering; (b) wrapping	46
3.12	Triaxial cell	51
3.13	Pattern of pile configuration (a) square pattern;	55
3.14	Pile spacing configuration of 0.50 m, 1.00 m and 2.00 m	57
3.15	Pile spacing configuration of 0.75 m, 1.50 m and 3.00 m	58
3.16	Model of SPR with 7.0 m x 7.0 m concrete slab, (a) plan with pile spacing of 0.50 m; (b) & (c) upper & bottom view with pile spacing of 0.75 m	58
3.17	Model size with pile spacing of 0.50 m, 1.00 m or 2.00 m	59
3.18	Model size with pile spacing of 0.75 m, 1.50 m or 3.00 m	59
3.19	Slope peat layer	61
3.20	Location of load for numerical modelling simulation	62
3.21	Full scale model of SPR foundation system (a) plan; (b) section A-A	64
3.22	Detail of join between concrete slab and pile (a) plan of steel bar configuration; (b) section B-B	65
3.23	Site Preparation, (a) setting-out important points; (b) result of setting- out	66
3.24	Galvanized steel pipe	66
3.25	Closed end pipe as pile	67
3.26	Closed end pipe equipped with anchors at upper part of pile	67
3.27	Mobilizing to the project site	68
3.28	Moving the pile for piling	68
3.29	Piling a pile	69
3.30	Removing residual wood of a big tree	69
3.31	Hole of woody residue as like “soil porridge”	70
3.32	Adjusting verticality of pile, due to pile tends to incline	70
3.33	Unsatisfied piling results	71



PTA UTHM

REPOSITORI TUNKU TUN AMINAH

3.34	Wooden pattern for piling pipe as pile	72
3.35	Re-piling and keeping verticality of pile	73
3.36	After re-piling, (a) satisfied piling results and	73
3.37	Top part of pile with steel anchors	74
3.38	Reinforcement of concrete slab	74
3.39	Concrete slab during curing	75
3.40	Mark of pile locations (a) and point of loading tests, red circle (b)	75
3.41	Configuration of loading test, plan	76
3.42	Configuration of loading test, section D-D	76
3.43	Configuration of loading test, section E-E	77
3.44	Hydraulic jack with capacity of 20 tons.	77
3.45	Plate bearing for avoiding punching action of hydraulic jack	78
3.46	Shallow brick foundation, (a) crock and (b) foundation under construction	79
3.47	Concrete beams as load during loading test	80
3.48	Arranging concrete beams, (a) the first concrete beam would be laid, and (b) arranging the next concrete beams	80
3.49	Completion of the concrete beam arrangement, (a) the last concrete beam would be laid, and (b) the completed arrangement of concrete beams	81
3.50	Levelling instrument, (a) Sprinter and (b) staff gauge.	81
3.51	Detail of measuring movements	82
3.52	Sequence of measuring movements.	83
3.53	Plan of loading test	85
3.54	Some concrete cubes used for levelling concrete beams	86
3.55	Concrete beams are completely arranged	86
3.56	Hydraulic jack in operation during loading test	87
3.57	Conducting loading test at night	87
3.58	Reading the settlement, (a) aiming staff gauge, and (b) instrument monitor was displaying the level changing.	88
4.1	Optimization result of pile spacing	92
4.2	Effect of internal friction angle $\phi$ ( $^{\circ}$ ) against settlement	94
4.3	Effect of cohesion $C$ against settlement	95
4.4	Effect of unit weight $\gamma_{\text{unsat}}$ against settlement	96
4.5	Effect of varying GWL against settlement	97



4.6	Influence of different pile length against settlement	99
4.7	Influence of peat layer thickness against settlement	100
4.8	Influence of slope peat layer against settlement	100
4.9	Effect of eccentric load against settlement	102
5.1	Plan of loading test	105
5.2	Load vs settlement for observed point at [CR]/P(2.2)	107
5.3	Load vs settlement at each point for loading up to 100 kN	108
5.4	Load vs settlement at each point for unloading from 100 kN	108
5.5	Load vs settlement at each point for reloading up to 160 kN	109
5.6	Load vs settlement at each point for unloading from 160 kN	109
5.7	Relationship between load and settlement at every phase of loading up to 100 kN	111
5.8	Relationship between load and settlement at every phase of reloading up to 160 kN	112
5.9	Relationship between load and settlement at every phase of unloading from 80 kN	112
5.10	Relationship between load and settlement at every phase of unloading from 140 kN	113
5.11	Relationship between load and settlement at point CR with different duration of reading.	114
5.12	Chart for basic step to design SPR	115



## LIST OF SYMBOLS AND ABBREVIATIONS

C	Cohesion
D	Pile outer diameter
d	Diameter of cylindrical specimen
E	Elastic modulus
$G_s$	Specific gravity of soil
g	Acceleration due to gravity
H	Height of retaining wall
I	Moment of inertia
L	Pile depth/pile length
LL	Liquid Limit
l	Length of cylindrical specimen
M	Mass of soil
$M_s$	Weight of solid particle
PL	Plastic Limit
S	Pile spacing
$S_c$	Primary consolidation settlement
$S_e$	Elastic or immediate settlement
SL	Shrinkage Limit
$S_s$	Secondary consolidation settlement
$S_T$	Total settlement
$S_{T(max)}$	Maximum of total settlement
T	Raft or concrete slab thickness
V	Total volume of soil
$V_s$	Volume of solid particle
W	Total weight of soil
w	Water content
$w_s$	Weight of dry soil
$w_w$	Weight of water

$\Delta H$	Retaining wall movement
$\Delta S_{T(\max)}$	Maximum of difference in total settlement between any two points
$\gamma$	Unit weight
$\gamma_d$	Dry unit weight of soil
$\gamma_s$	Unit weight of soil solids
$\gamma_{\text{sat}}$	Saturated unit weight of soil
$\gamma_{\text{unsat}}$	Unsaturated unit weight of soil
$\gamma_w$	Unit weight of water
$\rho$	Density
$\rho_d$	Dry density
$\rho_w$	Density of water
$\sigma$	Normal stress
$\tau$	Shear strength
$\phi$	Internal friction angle





## LIST OF APPENDIXES

APPENDIX	TITLE	PAGE
A-1	Loading test data for loading of 20 kN	128
A-2	Loading test data for loading of 40 kN	129
A-3	Loading test data for loading of 60 kN	130
A-4	Loading test data for loading of 80 kN	131
A-5	Loading test data for loading of 100 kN	132
B-1	Loading test data for un-loading of 80 kN	133
B-2	Loading test data for un-loading of 60 kN	134
B-3	Loading test data for un-loading of 40 kN	135
B-4	Loading test data for un-loading of 20 kN	136
B-5	Loading test data for un-loading of 0 kN	137
C-1	Loading test data for re-loading of 20 kN	138
C-2	Loading test data for re-loading of 40 kN	139
C-3	Loading test data for re-loading of 60 kN	140
C-4	Loading test data for re-loading of 80 kN	141
C-5	Loading test data for re-loading of 100 kN	142
C-6	Loading test data for re-loading of 120 kN	143
C-7	Loading test data for re-loading of 140 kN	144
C-8	Loading test data for re-loading of 160 kN	146
D	Loading test data for remain loading of 160 kN	146
E-1	Loading test data for un-loading of 140 kN	147
E-2	Loading test data for un-loading of 120 kN	148
E-3	Loading test data for un-loading of 100 kN	149
E-4	Loading test data for un-loading of 80 kN	150
E-5	Loading test data for un-loading of 60 kN	151
E-6	Loading test data for un-loading of 40 kN	152



PTTA UTHM  
PERPUSTAKAAN TUNJUNGU TUN AMINAH

E-7	Loading test data for un-loading of 20 kN	153
E-8	Loading test data for un-loading of 0 kN and final rebound	154
F	Example Using Chart Design Short Piled Raft	155



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## CHAPTER 1

### INTRODUCTION

#### 1.1 Background

Peat generally has much greater moisture content rather than inorganic soils which has exceeded 100% and it even can reach 3000% (Zainorabidin & Wijeyesekera, 2007). More over Bakar (2014) emphasised that peat was often regarded as problematic soils and was known as soft soils with organic matter content more than 75%. Recently, because the available land is very limited, as a result many construction projects have penetrated challenging soil areas, with some problems faced (Patil, Vasanvala & Solanki, 2013). As an example among several similar projects was Sedenak Factory Park Project in Johor Malaysia. Figure 1.1 shows a construction project at a peatland area as a challenging soil area, located at Sedenak, as mentioned above.



Figure 1.1: Sedenak Factory Park Project, Sedenak, Johor, Malaysia.

Completion of construction on peatland area by implementing a conventional foundation system such as pile foundation system is still considered unsatisfactory (Effendi, 2013). Therefore, some attempts in geotechnical and foundation engineering are still needed to be developed for overcoming those problems.

## 1.2 Problem Statements

In Geotechnical Engineering, peat has always attracted special attention because of the challenges and problems that should be faced when building a construction on it. These problems rise a trend to avoid the construction on these areas, or if impossible, to simply remove or replace them, which can cause to uneconomic alternative of design and construction (Huat, 2004).

The method of construction on peat is different, depending on the depth of peat (Bakar, 2014). The removal and replacement method are usually used for peat with depth less than 3 m, While for the depth 3 m to 10 m, engineers normally used sand drain, lightweight fills and stone column. The use of sand drain may encounter some difficulties, when making vertical holes in peat with shallow ground water level, because the hole will soon be closed again, As for the use of lightweight fill is highly dependent on the availability of materials suitable for that purpose, so it is not always easy to implement it technically. While the use of stone column is not recommended, because of the very small lateral strength of the peat. Finally, for the depth more than 10 m, the suitable method is deep stabilization techniques such as pile and dynamic compaction. Figure 1.2 shows removal and replacement method was used at Sedenak Factory Park Project, Sedenak, Johor, Malaysia.

By remembering the difficulties encountered even before, during and after construction on peat, especially with a layer thickness of 3 m to 10 meters, then an opportunity is open to develop a suitable foundation system which can be applied on peat. In addition, until now, there is no foundation structure system that is being specially developed, applied to peat soils. However, it is necessary to pay attention to the problems that arise related to the performance of the stability of the foundation that will be developed, namely the bearing capacity and settlement that will occur. Besides, the use of what materials are appropriate and how to build them should be paid more attention.



Figure 1.2: Removal and replacement method of peat at Sedenak Factory Park Project, Sedenak, Johor, Malaysia.

### 1.3 Aims

This research was conducted to explore a proposed Short Piled Raft (hereinafter abbreviated as SPR only) foundation system, which is expected suitable to be applied on peat. The SPR foundation system is a modified piled raft foundation system, which is a combination of pile foundation and raft foundation, with a pile length relatively short enough,  $\frac{L}{D} \leq 20$  (Das and Sivakugan, 2017) and considered as a reinforced concrete slab floating on a number of piles. By understanding the stability performance of SPR foundation system, it can be ensured that this foundation system is suitable or not to be implemented on peat.

### 1.4 Objectives

The objectives of this research were:

- i. To optimize pile spacing of SPR foundation system related to its stability, by using numerical model Plaxis 3-D Foundation software.
- ii. To conduct a sensitivity analysis of stability of the SPR foundation system with optimum pile spacing, based on different parameter ( $\phi$ ,  $C$ ,  $\gamma$ ), pile length, ground water level fluctuation, peat layer thickness and eccentric load.

- iii. To verify stability of the SPR foundation system by using full scale model related to immediate settlement.
- iv. To develop design chart for the SPR foundation system.

### 1.5 Scopes and Limitations

This research focused on experimental research and verify the results accordingly.

- i. Numerical Modelling of SPR foundation system on peat for static load by using Plaxis 3-D Foundation software. Typical model was concrete slab with the thickness of 0.15 m and outer diameter of steel galvanized pipe as pile of 0.32 m. For optimizing pile spacing, the concrete slab model size was 7.0 m x 7.0 m, and pile length was 3.0 m. While for simulations, the concrete slab model size was 3.0 m x 3.0 m. Different parameters were used for simulation and pile length were 1.0 m, 2.0 m and 3.0 m. The different parameters used for the simulation were pile length, internal friction angle  $\phi$ , cohesion C, unit weight  $\gamma$ , ground water level fluctuation, peat layer thickness and slope of peat layer.
- ii. Full Scale Model Testing of selected SPR foundation system on peat for static load at REPEATS (Research on Peat Station) area, Parit Nipah Darat, Johor, Malaysia. The concrete slab model size was 3.0 m x 3.0 m, pile length 3.0 m and outer diameter 0.32 m. Static load varied from 20 kN to 160 kN with the increment of 20 kN. The load acted on the centre of concrete slab, with the step of loading, unloading, reloading, remain, unloading and final rebound.

### 1.6 Significant Knowledge Contributions

After conducting this research, some knowledge contributions were found as follows.

- i. There is an optimum pile spacing of SPR in order to achieve minimum settlement. With the pile length of 3.0 m, outer diameter 0.32 m and concrete slab thickness of 0.15 m, the optimum pile spacing is 1.0 m.
- ii. Conducting erection of the pile on peat during the rainy season turns out to be technically unprofitable. It is caused the ground water level is very high, the bearing capacity at the ground level is to be very low and therefore the verticality of the pile being erected is difficult to be maintained, The use of

- wooden pattern for erecting the pile is very effective to assist adjusting verticality of the pile and to ensure the precision of piling at the specified point.
- iii. Deduction of reading duration for vertical movements by up to 50% on the loading test of full scale model of SPR on peat, shows that the reading results do not significantly differ from the reading results with full duration based on ASTM D 1143 - 81, so it can reduce the duration of the loading test. However, this step is not fulfil the standard of test procedure.
  - iv. A chart for basic step to design SPR has been developed. This chart is limited to typical of SPR foundation system, with 0.15 m thickness of concrete slab, pile spacing of 1,0 m, with the dimensionless L/D of 4, 8 and 12, and thickness of peat layer is 3.0 m to 10.0 m.

### 1.7 Outline of Thesis

Short explanation of this thesis which contains six chapters is conceived as follows:

- Chapter 1 : Background in general, that peat is known a problematic soil, difficulties to build a construction on it, therefore the needs to conduct this research related to develop a foundation system, problem statements, aims of the research, objectives of the research, and scope and limitation.
- Chapter 2 : Literatures review of peat, distribution of peatland, settlement of peat, construction method on peat, suitability to apply foundation system on peat, especially for raft foundation, piled raft foundation, chicken claw foundation system, nailed slab foundation system, previous researches to solve soft soil problem, modelling in geotechnics, full scale model and Plaxis 3-D Application Software for numerical modelling.
- Chapter 3 : Methodology to conduct the entire works of this research project, mainly regarding to set-up and explore numerical modelling and full scale model testing.
- Chapter 4 : Data analysis and results, related to numerical modelling, presents of the documented whole works, from the desk works, project site and material selection, numerical modelling for pile spacing optimization,

simulation with different parameters and conditions, compared to other previous methods numerically and discussed the results.

Chapter 5 : Data analysis and results, related to full scale model testing, presents of the documented whole works implementation of full scale model construction, loading test and discussed the results.

Chapter 6 : Conclusions and recommendations, highlight the results of this research and suggests recommendation for future research projects.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH



- Altaee, A. and Fellenius, B.H. (1994). *Physical Modelling In Sand*. Canadian Geotechnical Journal Vol. 31
- Atkinson, J.H. and Bransby, P.L. (1978). *The Mechanics of Soils, An Introduction to Critical State Soil Mechanics*. Maidenhead, Berkshire, England: McGRAW-HILL.
- Azhar, A. T. S., Norhaliza, W., Bakar, I., Abdullah, M. E. & Zakaria, M. N. (2016). *Comparison of Shear Strength Properties for Undisturbed and Reconstituted Parit Nipah Peat, Johor*. IOP Conf. Series: Materials Science and Engineering 160 (2016) 012058
- Badie, S. S. and Silva, P. (2008). *Optimum Beam-To-Column Stiffness Ratio for Portal Frames*. Structure Magazine, March.
- Bakar, I. (2014). *Challenges in Peat Soil Research - Malaysian Experiences*. South East Asia Conference on Soft Soils Engineering and Ground Improvement, Bandung.
- Boiko, I. L., Alhassan, M. & Adejumo, T. W. (2013). *Load-Settlement Test of Full-Scale Foundation on Concrete-Grid Reinforced Soil*. Academic Journal, Journal of Civil Engineering and Construction Technology, 4(6), pp:211-216.
- Butterfield, R. (1999). *Dimensional analysis for geotechnical engineers*. Geotechnique 49, No. 3, 357-366.
- Cola, S. and Cortellazzo, G. (2005). *The Shear Strength Behaviour of Two Peaty Soils*. Geotechnical and Geological Engineering, (2005) 23: 679-695, 10.1007/s10706-004-9223-9.
- Dao, T.P.T. (2011). *Validation of PLAXIS Embedded Piles for Lateral Loading*. Master of Science Thesis, Delft University of Technology, The Netherlands.
- Das, B.M. (2011). *Principles of Foundation Engineering*. Seventh Edition, Cengage Learning.
- Das, B.M., & Sobhan K. (2014). *Principles of Geotechnical Engineering*. Eighth Edition, Cengage Learning.
- Das, B.M., & Sivakugan N. (2017). *Principles of Foundation Engineering*. Ninth Edition, Cengage Learning, pp. 508-509.
- Daud, S., Junica, M. I., Sunaryo, M. E. & Pertiwi, D.(2008). *Kajian Dan Monitoring Hasil Uji Coba Skala Penuh Teknologi Cakar Ayam Modifikasi*. Pusat Penelitian dan Pengembangan Jalan dan Jembatan, Bandung.
- Direktorat Bina Teknik Direktorat Jenderal Bina Marga Departemen Pekerjaan Umum (2010). *Katalog Sistem Perkerasan Cakar Ayam Modifikasi*.



PT. PUSTAKAAN TUN AMINAH

- Direktorat Bina Teknik Direktorat Jenderal Bina Marga Departemen Pekerjaan Umum. (2010). *Tata Cara (Interim) Pelaksanaan Konstruksi Perkerasan Cakar Ayam Modifikasi*.
- Direktorat Bina Teknik Direktorat Jenderal Bina Marga Departemen Pekerjaan Umum. (2010). *Tata Cara (Interim) Perancangan Sistem Perkerasan Cakar Ayam Modifikasi*.
- Dunn, I.S., Anderson, L.R., & Kiefer, F.W. (1980). *Fundamentals of Geotechnical Analysis*. John Wiley & Sons.
- Effendi, S. (2011). *Pondasi Dan Perkerasan Di Tanah Lunak Dengan Sistem Cakar Ayam*. Energi & Kelistrikan.
- Effendi, S. (2013). *Cakar Ayam Soft Foundation System Revisited*. Soft Soil Engineering International Conference 2013, Kucing, Sarawak, Malaysia.
- Fatnanta, F., Satibi, S. & Muhandi (2018). *Bearing capacity of helical pile foundation in peat soil from different, diameter and spacing of helical plates*. IOP Conf. Series: Materials Science and Engineering 316 (2018) 012035
- Fellenius, B. H. & Altaee, A. (1994). *Stress and Settlement of Footings in Sand*, Geotechnical Special Publication, GSP, No. 40, College Station, Vol. 2.
- Forestry Civil Engineering, Scottish Natural Heritage (2010). *Floating Roads on Peat*. A Report into Good Practice in Design, Construction and Use of Floating Roads on Peat with particular reference to Wind Farm Developments in Scotland.
- Gofar, N. (2006). *Determination Of Coefficient Of Rate Of Horizontal Consolidation Of Peat Soil*. Faculty of Civil Engineering , Universiti Teknologi Malaysia, Malaysia.
- Hadmodjo, R. P. (1991). *Cakar Ayam Construction System - Pavement and Foundation System for Structures on Soft Soil*, PT Cakar Bumi Consulting Engineers, Jakarta.
- Hajon, S. K., Mos, H., Jantan, N. & Haniff, M. H. (2018). *Classification of Tropical Peat in Malaysia*. Oil Palm Bulletin 76, Malaysia. pp. 2-6.
- Hardiyatmo, H. C. (2011). *Analisis dan Perancangan Fondasi I*. Edisi Kedua, Gadjah Mada University Press.
- Hardiyatmo, H. C. (2011). *Analisis dan Perancangan Fondasi II*. Edisi Kedua, Gadjah Mada University Press.
- Hardiyatmo, H. C. (2014). *Perancangan Sistem Cakar Ayam Modifikasi Untuk Perkerasan Jalan Raya*. Edisi Kedua, Gadjah Mada University Press.



PT TAAU  
PERPUSTAKAAN TUNJUNG  
TUNJUNG

- Holtz, R.D. & Kovacs, W.D. (1981). *An Introduction to Geotechnical Engineering*. Prentice Hall, Inc., Englewood Cliffs, New Jersey.
- Huat, B. B. K. (2004). *Organic and Peat Soils Engineering*. Universiti Putra Malaysia Press.
- Huat, B. B. K., Prasad, A., Asadi, A. & Kazemian, S. (2014). *Geotechnics of Organic Soils and Peat*. CRC Press/Balkema.
- Johari, N. N., Bakar, I. & Razali, S.N.M. (2014). *Oedometer Testing on Undisturbed and Reconstituted Peat*. South East Asia Conference on Soft Soils Engineering and Ground Improvement, Bandung, Indonesia.
- Kamash, W. E. (2012). *The positioning and thickness effect for soft clay layer on 3D-building resting on piled raft*. Ain Shams Engineering Journal, 3(1), 17-26.
- Kazemian, S., Huat B. B. K., Prasad A. & Barghchi M. (2011). *A state of art review of peat: Geotechnical engineering perspective*. International Journal of the Physical Sciences Vol. 6(8), pp. 1974-1981, ISSN 1992 - 1950 ©2011 Academic Journals.
- Kelly, B. C. O. (2015). *Effective stress strength testing of peat*. Environmental Geotechnics, Volume 2, Issue EG1, pp 34–44, Paper 13.00112.
- Kogure, K. (1999). *Consolidation and Settlement of Peat under Loading*. Problematic Soils, Yanagisawa, Moroto & Mitachi (eds) © 1999 Balkema, Rotterdam, ISBN 90 5410 997 1, pp 817832.
- Mansor, S. H. & Zainorabidin, A. (2014). *The Shear Strength Behaviour of Johore's Hemic Peat*. South East Asia Conference on Soft Soils Engineering and Ground Improvement (Vol. 2, p. H3).
- McCabe, B.A. & Phillips, D.T. (2008). *Design Lessons from Full-scale Foundation Load Tests*. Conference Paper · January 2008, <https://www.researchgate.net/publication/270904304>
- Othman, M. A. (2014). *Construction on Peat Soil in Malaysia*. Seminar Construction on Peat Soil in Malaysia.
- Paghaleh, S. J. & Kalantari, B. (2016). *Parametric Study on Settlement of Piled Raft Foundation Using 3D Finite Element Method*. Electronic Journal of Geotechnical Engineering, 2016 (21.26), pp 10531-10542.
- Patil, J.D., Vasanvala, S. A. & Solanki, C. H. (2013). *A Research on Piled Raft Foundation: State of Art*. International Journal of Engineering Research & Technology (IJERT), Vol. 2 Issue 8, pp. 1464-1470.



- Prakoso, W.A. & Kulway, F.H. (2001). *Contribution To Piled Raft Foundation Design*. Journal of Geotechnical and Geoenvironmental Engineering.
- Priadi, E. (2008). *Behaviour of Tiang Tongkat Foundation over Pontianak Soft Organic Soil Using 3D - Finite Element Analysis*. Technischen Universität Bergakademie Freiberg: PhD Thesis.
- PT PLN (PERSERO). (2015). *Kriteria Desain Pondasi Tower Rangka Saluran Udara Tenaga Listrik Berdasarkan Uji Penetrasi Konus/Sondir*. Standar PT PLN (PERSERO), SPLN T5.008:2015, Lampiran Peraturan Direksi PT PLN (PERSERO) No. 0102.P/DIR/2015.
- Punmia, B.C. (1975). *Soil Mechanics and Foundations*. Rajinder Kumar Jain, Delhi.
- Qaissy, M. A., Karim, H. H. & Hameedi, M. K. (2013). *Behaviour of Experimental Model of Piled Raft Foundations on Clayey Soils*. International Journal of Engineering Research and Science & Technology. Vol. Part (A), No. 20 , 2013.
- Rahgozar, M. A. & Saberian, M. (2015). *Physical and chemical properties of two Iranian peat types*. Mires and Peat, Volume 16 (2015), Article 07, 1–17, <http://www.mires-and-peat.net/>, ISSN 1819-754X © 2015 International Mire Conservation Group and International Peat Society
- Rahgozar, M. A. & Saberian, M. (2016). *Geotechnical Properties of Peat Soil Stabilised with Shredded Waste Tyre Chips*. Mires and Peat, Volume 18 (2016), Article 03, 1–12, <http://www.mires-and-peat.net/>, ISSN 1819-754X © 2016 International Mire Conservation Group and International Peatland Society.
- Saedon, N., Zainorabidin, A. & Razali, S. N. M. (2014). *Temperatur Effect of the Shrinkage Characteristics of Peat Soil*. South East Asia Conference on Soft Soils Engineering and Ground Improvement (Vol. 2, p. H7).
- Said, M. J. M., Zainorabidin, A. & Madun, A. (2014). *Seismic Refraction on Peat Soils at Parit Nipah*. South East Asia Conference on Soft Soils Engineering and Ground Improvement, Bandung, Indonesia.
- Shien, P. T., Seneviratne, H.N. & Ismail, D. S. A. (2011). *A Research on Factors Influencing the Determination of Moisture Content of Fibrous Peat*. UNIMAS E-Journal of Civil Engineering, Vol. 2 (2), pp. 39-47.
- Sibarani, A. S., Fatnanta, F. & Satibi, S. (2017). *Pengaruh Jarak, Jumlah dan Diameter Helix Pada Pondasi Screw Pile Terhadap Beban Aksial Pada Tanah Gambut (Full Scale)*. Jurnal APTEK 9 (2), pp. 94-104



PTTA (Pusat Penelitian dan Pengembangan Tanah dan Tambak)  
 PERPUSTAKAAN TUNJUKU TAMBAH  
 BERKUALITAS

- Sing, W. L., Hashim, R. & Ali, F.H. (2008). *Engineering Behaviour of Stabilized Peat Soil*. European Journal of Scientific Research, ISSN 1450-216X Vol. 21 No. 4, pp. 581-591.
- Sönmez, N. (2013). *A Study on Design of Piled Raft Foundation Systems*. Middle East Technical University: MSc Thesis.
- Srilakshmi, G. & Moudgalya, D. (2013). *Analysis of Piled Raft Foundation Using Finite Element Method*. International Journal of Engineering Research and Science & Technology. Vol. 2 No. 3
- Sulaeman, A. (2010). *The Use of Lightweight Concrete Piles for Deep Foundation on Soft Soils*. Universiti Tun Hussein Onn Malaysia: PhD Thesis
- Suro, S. M., Sulaeman, A. & Omar, S. A. F. S. (2014). *Short Piled Raft Foundation System as An Alternative Solution to Reduce Settlement*. South East Asia Conference on Soft Soils Engineering and Ground Improvement, Bandung, Indonesia.
- Suro, S. M., Bakar, I. & Sulaeman, A. (2016) *Pile Spacing Optimization of Short Piled Raft Foundation System for Obtaining Minimum Settlement on Peat*. IOP Conference Series: Materials Science and Engineering.
- Susanti, R. D., Maulana & Waruwu, A. (2017). *Bearing Capacity Improvement of Peat Soil by Preloading*. ARPN Journal of Engineering and Applied Sciences, Vol. 12, No. 1, pp. 120 - 123
- Susila, E. & Apoji, D. (2012). *Settlement of a Full Scale Trial Embankment on Peat in Kalimantan: Field Measurements and Finite Element Simulations*. Jurnal Teknik Sipil, Jurnal Teoretis dan Terapan Bidang Rekayasa Sipil, Vol. 19 No. 3, pp. 249-264.
- Tandjiria, V. (1999). *Numerical Modelling of Chicken-Foot Foundation*. Dimensi Teknik Sipil Volume I, no. 1, Maret.
- Waruwu, A., Hardiyatmo, H. C. & Rifa'i, A. (2016). *Studi Eksperimental Pembebanan Pelat yang Diperkuat Tiang pada Tanah Gambut*. Seminar Nasional Geoteknik 2016 HATTI, Yogyakarta, Indonesia.
- Waruwu, A., Hardiyatmo, H. C. & Rifa'i, A. (2017). *Behaviour of Nailed-Slab System on Peat Soil Under Loading*. The 1st Warmadewa University International Conference on Architecture and Civil Engineering, Bali, Indonesia.
- Zainorabidin, A. & Wijeyesekera, D.C. (2007). *Geotechnical Challenges with Malaysian Peat*. Advances In Computing and Technology, The School of Computing and Technology 2nd Annual Conference, Malaysia.



PT. AUSTIN  
PEPUSATAKAN TUNKU TUN AMINAH

Zainorabidin, A. & Mansor, S. H. (2016). *Investigation on The Shear Strength Characteristic at Malaysian Peat*. ARPN Journal of Engineering and Applied Sciences, Vol. 11, No. 3, February 2016. [www.arpnjournals.com](http://www.arpnjournals.com), pp1600-1606.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH