

RISK LEVEL OF FACTORS CAUSING CONSTRUCTION WASTE
GENERATION THROUGHOUT CONSTRUCTION PROJECT LIFE CYCLE

NOR SOLEHAH BINTI MD AKHIR

A thesis submitted in
fulfillment of the requirement for the award of the
Degree of Master of Civil Engineering

Faculty of Civil and Environmental Engineering
Universiti Tun Hussein Onn Malaysia

APRIL 2015

*For my beloved mom and dad,
Khoriah Hj Ismail & Md. Akhir Chin
For their endless love, support and prayers.*



ACKNOWLEDGEMENT

Alhamdulillah, all praise is due to Allah for His blessings in providing me the strength to complete this thesis. I wish to express my special appreciations to my project supervisor and co-supervisor, Prof. Dr. Hj. Ismail Abdul Rahman and Dr. Aftab Hameed Memon for the continuous support in my master's study and research, and also for their patience, motivation, enthusiasm, and immense knowledge in the area of expertise. Their guidance had tremendously helped me throughout the research and writing of this thesis.

Sincere thanks to Mr. Sasitharan Nagapan who played a vital part in the successful completion of this work. I also would like to express special gratitude and appreciation to all the respondents who were involved in this study, especially for their cooperation in sharing their experience.

Last but not least, my deepest gratitude to my beloved parents, Md. Akhir Chin and Khoriah Ismail, and also my family for their endless love, prayers, and encouragement. Not forgetting my husband, Afiq Rusydi Jamlus, for his continuous love and support. A great big thank you to my colleague, Ismaaini Ismail, who was always with me during the completion of this thesis. To those who had indirectly contributed in this research, your kindness really means a lot to me. Thank you very much.

ABSTRACT

The construction industry has an adverse impact on the environment from the wastes generated during construction work. The amount of wastes generated increases yearly due to rapid economic growth worldwide which includes Malaysia. Due to waste generation, one of the major issues faced is the increase of illegal dumpsites. The illegal dumping may caused a risk to human health and environment. Thus, it calls for serious measures to regulate wastes generation. The waste is generated due to various factors throughout construction project life cycle (CPLC). For controlling purpose, it is very important to identify the generation factors and also to determine the level of risk from each factor. Hence, this study focuses on assessing the risk level of factors causing wastes generation throughout CPLC. Besides, it also proposes mitigation measures for the high risk factors. For assessing the risk level, a total of 33 factors that causes construction wastes generation that have been identified from literature review were considered. The assessment involved 15 experts who are experienced in handling construction projects. This investigation adopted two rounds of Delphi method in determining level of occurrence and severity of each factor in relation with different phases of CPLC. The experts were required to fill out the questionnaire set and the analysis on the gathered data from the questionnaire work was done using risk matrix. The result indicated that in the construction phase, majority of the identified factors occurred in this phase are critical due to having high risk level and most of them are categorised in Human Resource/Manpower (HRM) group. It is followed by finishing phase, design phase, and planning phase. However, in planning phase, the chances of wastes generation are minimal with no high risk factors. In order to control the construction wastes generation problem, mitigation measures for high risk factors were proposed. The findings of this study can be a useful guide for the practitioners in controlling construction wastes generation.

ABSTRAK

Industri pembinaan telah menyumbang kesan buruk terhadap persekitaran akibat daripada penjanaaan sisa semasa kerja pembinaan. Jumlah penjanaaan sisa kian meningkat setiap tahun disebabkan pertumbuhan ekonomi yang semakin pesat di seluruh dunia termasuk di Malaysia. Hal ini menyebabkan jumlah tapak pelupusan sampah secara haram semakin meningkat. Tapak pelupusan sampah yang berleluasa boleh mendatangkan risiko kepada kesihatan manusia dan alam sekitar. Oleh yang demikian, perhatian yang serius diperlukan bagi mengawal masalah ini. Penjanaaan sisa boleh berlaku disebabkan pelbagai faktor di sepanjang kitaran hayat projek pembinaan (CPLC). Bagi tujuan pengawalan, ia adalah penting untuk mengenalpasti faktor-faktor penyebab penjanaaan sisa dan juga menentukan tahap risiko bagi setiap faktor. Oleh itu, kajian ini fokus kepada menilai tahap risiko bagi faktor-faktor penyebab penjanaaan sisa di sepanjang CPLC. Di samping itu, kajian ini juga mencadangkan langkah-langkah mengatasi untuk faktor-faktor yang berisiko tinggi. Untuk menilai tahap risiko, sebanyak 33 faktor penyebab penjanaaan sisa pembinaan yang telah dikenalpasti daripada kajian literatur dipertimbangkan. Penilaian ini melibatkan 15 orang pakar yang berpengalaman dalam mengendalikan projek-projek pembinaan. Dua pusingan kaedah Delphi digunakan bagi menentukan tahap berlaku dan tahap impak setiap faktor bagi setiap fasa di sepanjang CPLC. Pakar-pakar diminta untuk mengisi borang soal selidik dan analisis yang dilakukan ke atas data yang diperolehi adalah dengan menggunakan matrik risiko. Keputusan mendapati bahawa dalam fasa pembinaan, sebahagian besar faktor-faktor yang dikenal pasti berlaku dalam fasa ini adalah kritikal kerana mempunyai tahap risiko yang tinggi dan kebanyakan faktor yang berisiko tinggi adalah dari kategori Sumber Manusia/Tenaga Kerja (HRM). Ia diikuti dengan fasa kemas, fasa reka bentuk, dan fasa perancangan. Walau bagaimanapun, dalam fasa perancangan kemungkinan penjanaaan sisa adalah minimum dan tiada faktor yang berisiko tinggi dalam fasa ini.

Dalam usaha untuk mengawal masalah penjanaaan sisa pembinaan, langkah-langkah mengatasi bagi faktor yang berisiko tinggi telah dicadangkan. Hasil kajian ini dapat menjadi panduan kepada pihak industri dalam mengawal penjanaaan sisa binaan.



CONTENTS

	TITLE	i
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xiii
	LIST OF SYMBOLS AND ABBREVIATIONS	xiv
	LIST OF APPENDICES	xv
CHAPTER 1:	INTRODUCTION	
	1.1 Research Background	1
	1.2 Problem Statement	2
	1.3 Aim and Objectives	4
	1.4 Scope of Study	4
	1.5 Research Methodology	4
	1.6 Thesis Organization	5
CHAPTER 2:	LITERATURE REVIEW	
	2.1 Introduction	6
	2.2 Risk Management in Construction Project	6
	2.3 Construction Wastes	9
	2.3.1 Definition	9
	2.3.2 Construction Wastes Generated	11
	2.3.3 Waste Management	13
	2.3.4 Impacts of the Waste	17



2.4	Causative Factors of Construction Waste Generation	19
2.5	Causative Factors in Construction Project Life Cycle	25
2.5.1	Construction Project Life Cycle (CPLC)	25
2.5.2	Incorporation of Causative Factors in CPLC	28
2.6	Mitigation Measures of Construction Wastes Generation	32
2.7	Summary	34
CHAPTER 3: METHODOLOGY		
3.1	Introduction	35
3.2	Flow of the Research	35
3.3	Questionnaire Development	36
3.4	Data Collection	38
3.4.1	Pilot Study	38
3.4.2	The Delphi Method	38
3.5	Analysis Method	41
3.5.1	Reliability Test	41
3.5.2	Descriptive Analysis	41
3.5.3	Risk Matrix	42
CHAPTER 4: ANALYSIS AND DISCUSSION		
4.1	Introduction	44
4.2	The Pilot Study Analysis	44
4.2.1	Experts' Demography	45
4.2.2	Reliability Test	45
4.2.3	Analysis of Factors	46



PTTA
PERPUSTAKAAN TUN AMINAH

4.3	Analysis of Delphi Survey	52
4.3.1	Respondents' Demography	52
4.3.2	Identification of Risk Level	55
4.3.3	Agreeability on Identified Risk Level	60
4.4	Proposed Mitigations for Risk Factor	65
4.5	Summary	68
CHAPTER 5:	CONCLUSION AND RECOMMENDATION	
5.1	Introduction	70
5.2	Significant Findings	70
5.3	Limitations of the Study	74
5.4	Recommendations for Future Work	75
REFERENCES		76
APPENDIX		91



LIST OF TABLES

2.1	Wastes definition	11
2.2	Construction wastes generated	13
2.3	Mapping of impact of construction waste	19
2.4	Mapping of factors contributing construction wastes generation	23
2.5	Comparison between proposed CPLC with others CPLC based on literature review	26
2.6	Factors of construction wastes according to CPLC	29
3.1	Scale represents the probability of occurrence and level of severity	37
3.2	Applied Delphi method by researchers in construction research	39
3.3	Suggested Delphi method for this study	41
4.1	Expert's demography in pilot study	45
4.2	Reliability test results	46
4.3	AI value of factors in each phase	47
4.4	Significant factors in each phase	48
4.5	Risk level of causative factor in the planning phase	56
4.6	Risk level of causative factors in the design phase	56
4.7	Risk level of causative factors in the construction phase	58
4.8	Risk level of causative factors in the finishing phase	59

4.9	Percentage of agreeability for the risk level of causative factors in the planning phase and the design phase	61
4.10	Percentage of agreeability for the risk level of causative factors in the construction phase	62
4.11	Percentage of agreeability from panels for the risk level of causative factors in the finishing phase	64
4.12	Proposed mitigation measures of high risk factors	65



LIST OF FIGURES

2.1	Six stage of waste management hierarchy	14
2.2	Construction project life cycle diagram	27
3.1	Research methodology flowchart	36
3.2	Process of the Delphi method	40
3.3	Risk matrix	43
4.1	Highest educational qualification of respondents	51
4.2	Respondents' working experiences	53
4.3	Respondents' position	53
4.4	Type of organization of respondents	54
4.5	Category of organization of respondents	54
4.6	Highest contract amount of projects that respondents have dealt with	55
4.7	Risk level of causative factor in the planning phase	56
4.8	Risk level of causative factors in the design phase	57
4.9	Risk level of causative factors in the construction phase	59
4.10	Risk level of causative factors in the finishing phase	60
5.1	Factors causing construction waste generation	71
5.2	Risk level of the factors throughout CPLC	73

LIST OF SYMBOLS AND ABBREVIATIONS

AI	-	Average Index
CPLC	-	Construction Project Life Cycle
CWDCS	-	Construction Wastes Disposal Charging Scheme
C&D	-	Construction and Demolition
DEL	-	Delivery/Procurement
EQP	-	Equipments
EXT	-	External/Unpredictable
GHG	-	Green House Gas
HRM	-	Human Resource/Manpower
IBS	-	Industrialized Building System
ICT	-	Information, Communication, and Technology
MAT	-	Material
PCM	-	Project and Contract Management
RIBA	-	Royal Institute of British Architects
SPSS	-	Statistical Package for the Social Sciences
WGR	-	Wastes Generation Rate
WMP	-	Wastes Management Plan
α	-	Cronbach's Alpha Coefficient

LIST OF APPENDICES

A	Questionnaire Form: Pilot Study	91
B	Questionnaire Form: Delphi Round 1	94
C	Questionnaire Form: Delphi Round 2	97
D	Description of the Factors	99



PTTHM
PERPUSTAKAAN TUNKU TUN AMINAH

CHAPTER 1

INTRODUCTION

1.1 Research Background

Construction is an imperative industry that plays a vital role in the socio-economic growth of a country. It provides necessary infrastructure and physical structure for activities such as commerce, services, and utilities (Khan, Liew, & Ghazali, 2014). Besides that, it also generates employment opportunities and enhances the nation's economy by creating foreign and local investment opportunities (Wibiwo, 2003). However, the industry is facing the problem of construction wastes generation. As reported by Kartam et al. (2004), based on statistics and assumptions, a total of Construction and Demolition (C&D) wastes production was estimated to be 1.6 million ton/year. According to Ferguson et al. (1995), over 50% of the wastes in a typical United Kingdom landfill is contributed by construction wastes. Bossink & Brouwers (1996) indicated that 9% of the totally purchased materials ended up as wastes. Furthermore, Masudi et al. (2011) stated that wastage level for major materials in some projects in Malaysia may reach up to 10%.

This generation of wastes has negative impact to the environment, cost, productivity, time, social, and economy of the industry (Kozlovská & Spišáková, 2013; Marzouk & Azab, 2014; Osmani, 2012; Wang, Kang, & Tam, 2008). In addition, production of wastes may weaken the efficiency, effectiveness, value, and profitability of construction activities (Augustine, 2011). Thus, the risk of generation of construction wastes needs to be proactively managed.

There are various factors that contribute to generation of construction wastes. These factors pose different levels of risk in wastes generation. Various researchers have identified factors that contribute to wastes generation. As an example: A study conducted in Sri Lanka revealed that the domestic construction industry workforce is ignorant of the flow of activities that generated wastes (Senaratne & Wijesiri, 2008). In Malaysia, it was found that there were five significant factors that caused generation of construction wastes in this country. The factors are poor site management or supervision, lack of experience, inadequate planning and scheduling, mistakes and errors in design, and mistakes during construction (Nagapan, Rahman, & Asmi, 2012a). In addition, contractors and consultants agreed that three most important factors that contribute to generation of material wastes at construction site are rework contrary to drawings and specification, design changes and revision, and wastes from uneconomical shapes (Adeweyu & Oтали, 2013).

A number of study highlighted that construction wastes are effectively generated during the whole Construction Project Life Cycle (CPLC) from start until completion of construction work (Kozlovská & Spišáková, 2013; Osmani, Glass, & Price, 2008). It may be generated during planning, design, procurement, and construction phase (Bossink & Brouwers, 1996; Ekanayake & Ofori, 2004; Wahab & Lawal, 2011). While, several studies highlighted that construction wastes is commonly generated during design and construction phase (Osmani, Glass, & Price, 2006; Panos & Danai, 2012).

Therefore, it can be concluded that construction wastes may be generated by various factors and it may occur in the whole of CPLC. It also contributes to a lot of negative impacts either to the project, environment or life. Thus, reducing wastes at the source is the most effective measure in wastes management (Masudi et al., 2011). By identifying the risk level of the factors and proposing the mitigations of the risky factors, it may help the practitioners to figure out the best way to control this problem.

1.2 Problem Statement

Production of construction wastes is directly related with the increasing demand of infrastructure projects, residential development projects, and other facilities which are required to improve the level of Malaysians' living conditions (Begum, Satari, &

Pereira, 2010; Nasaruddin & Ravana, 2008). Out of these projects, the construction of residential building contributes the largest amount of construction wastes (Begum & Pereira, 2011; Foo et al., 2013).

According to Oh (2014) in The Star daily publication in March 2014, Solid Wastes Management and Public Cleansing Corporation highlighted that in 2007, Kuala Lumpur generated 1.04 million metric tonnes of construction wastes per year and this amount is expected to increase to 1.34 million metric tonnes a year by 2020. However, these wastes were not properly handled by the construction parties involved. Research studies have indicated that dumping of construction wastes in landfill is a common practice in Malaysia (Foo et al., 2013; Nagapan et al., 2012a). In 2007, a study conducted by Rahmat & Ibrahim (2007) showed that 42% of the wastes were dumped illegally in the district of Johor Bahru Tengah, Johor. The study also found 46 illegal dumping sites in the district and most of them were located near the road side. A study in the Klang Valley found only 20% of C&D wastes were disposed at legal landfills while others were disposed at illegal landfills or private lands (Begum & Pereira, 2011). There are also a number of contractors that disposed material wastes through open burning especially timber and packaging wastes, and also by burying concrete wastes (Masudi et al., 2011).

The wastes then pose a threat to the environment and society if they are not handled properly. Thus, it is important to control the source of construction wastes generation. Before it can be controlled, it is vital to identify the factors that contribute to wastes generation. Previous studies had identified factors that caused construction wastes generation (Ikau, Tawie, & Joseph, 2013; Masudi et al., 2011; Nagapan, Rahman, & Asmi, 2012b). However, not much emphasis was given in assessing the relative risk level of these factors towards construction wastes generation, which is very important for proper planning and development of strategies in controlling the factors. This has motivated the author to conduct this research in identifying the risk level of various causative factors that occurs in CPLC phases and propose mitigations of risky factors, which can serve as a useful guide for the practitioners in controlling the construction wastes generation.

1.3 Aim and Objectives

The aim of this research is to assess the risk level of factors causing construction wastes generation throughout CPLC. In order to achieve this aim, three objectives have been established namely:

- 1) Identifying major factors causing construction wastes along the CPLC.
- 2) Determining the risk level of factor causing construction wastes along the CPLC.
- 3) Proposing mitigation of the risky factors.

1.4 Scope of Study

The scope of this research is limited to construction-related companies in Peninsular Malaysia. Data collection involves questionnaire survey using the Delphi method. The survey is start conducted in the early of 2014. The targeted respondents are the clients, consultants, and contractors whom are registered with CIDB between Grade 5 and 7. Respondents are selected among those who have more than ten years of working experience in the construction industry. Construction wastes are limited to material wastes only.

1.5 Research Methodology

This study is carried out based on the qualitative and quantitative mode of research. It involves a comprehensive literature review from past researches to identify the factors causing construction wastes generation. Based on that, a questionnaire is developed to determine the factors occurrence and severity with respect to the various phases of a construction project. The investigation for the developed questionnaire is carried out using the Delphi method to assess the level of occurrence and severity of the factors causing wastes generation for the construction industry in Malaysia. The data are then analyzed using the average index and risk matrix to identify the risk level of each factor. Mitigations of the risky factors are proposed based on literature review.

1.6 Thesis Organization

This thesis is divided into five chapters as follows:

Chapter 1: This chapter describes the need of this study. It contains study background, problem statements, objectives, scope of study, research methodology, and thesis organization.

Chapter 2: This chapter elaborates on related literature through the published research work. It includes the definition, wastes generation scenarios, handling the wastes, and factors causing construction wastes generation. Besides that, the phases in CPLC are discussed.

Chapter 3: This chapter describes how this research is carried out. It explains the technique of data collection and the way to analyze them.

Chapter 4: The survey results will be illustrated in this chapter. It includes the factors of wastes generation throughout CPLC, level of occurrence, severity, and risk of the factors causing generation construction wastes throughout the CPLC. At the end of this chapter, the mitigation measures of high risk factors are presented.

Chapter 5: This chapter presents the conclusion of the study. It also presents some recommendations for future study and limitations that arise while this study was conducted.



CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

This chapter provides literature reviews that are related to this study. It is to gain an overview of the current study and to provide a theoretical basis in refining the research methodology and also the analysis approach for the current work. In this chapter, risk management in construction projects, the definitions of construction wastes, issues related to wastes generation, wastes management, impacts, and factors causing construction wastes generations are reviewed. In addition, the concept of four phases of CPLC is also discussed.

2.2 Risk Management in Construction Project

Project success can be defined by fulfilling the project objectives on the cost, time and quality. However, to achieve project success, it is subjected to various risks due to the unique features of construction activities, such as long period, complicated processes, abominable environment, financial intensity, and dynamic organizational structures (Zou, Zhang, & Wang, 2007; Akintoye & MacLeod, 1997). In addition, Husin, Ismail, & Memon (2013) stated that the construction industry is always faced with chronic problems such as time overrun, cost overrun, wastes generation, imposing negative impacts to the environment, and excessive resource consumption. Thus, risks in construction project have to be given serious attention so that the project is successfully accomplished.

Risk can be defined as a combination of the probability and the severity, and also the exposure of all hazards in the construction activity (Jannadi & Almishari, 2003). In managing risk, a systematic way is required to look into the areas of risk and consciously determining how to treat the risk. It is a management tool that aims at identifying sources of risk and uncertainty, determining their impact, and developing appropriate management responses (Uher, 2003). A process of risk management has been divided into three consecutive stages as stated by Perera et al. (2014) and KarimiAzari et al. (2011) which are;

- i. risk identification,
- ii. risk analysis and
- iii. risk response, where risk response has been further divided into four actions,
i.e. retention, reduction, transfer, and avoidance

For risk identification and risk analysis, it specifies and predicts the likelihood and adverse impacts of risks; whereas for risk response, it is concerns on the measures taken by project management to reduce the probability and effects of risks (Perera et al., 2014).

Risk identification is a significant step in the risk management process, as it attempts to identify the various risks affecting a construction project. In this stage, risk factors that influence the project are detected, classified and documented (Gohar, Khandazi & Farmani, 2012). Source of the knowledge for risk identification phase is vital to the success of this stage and should elicit the viewpoints of experts with extensive experience in directly dealing with similar construction projects (Ruthankoon & Ogunlana, 2003). In this study, risk identification was accomplished through literature review and pilot study. A total of 33 factors causing construction waste generation were identified through literature review. Then, the identified factors were classified into four phase of CPLC through pilot study. From that, it presented one factor in planning phase, five factors in design phase, 32 factors in construction phase and nine factors in finishing phase.

Risk analysis is important as it estimate risk by identifying the undesired event, the likelihood of occurrence of the unwanted event, and the consequence of such event. It involves measures which produce the estimation of significance level of the individual risk factors to the project, so as to produce the estimation of the risk of the potential factors to project success (KarimiAzari et al., 2011).

There are two approaches used in risk analysis, which are quantitative risk analysis and qualitative risk analysis (Ehsan et al., 2010). Quantitative analysis involves more sophisticated techniques and methods to investigate and analyze construction project risks. Additionally, this analysis represents risks in mathematical form to quantify them in terms of performance in quality, time and cost (Morledge, Smith, & Kashiwagi, 2006). Quantitative risk analysis attempts to estimate the frequency of risks and the magnitude of their consequences by different methods such as the sensitivity analysis, decision tree analysis, the cost risk analysis, and Monte Carlo simulation (Mahendra, Pitroda, & Bhavsar, 2013; Ehsan et al., 2010; Modarres, 2006)

Qualitative risk analysis assesses the impact and likelihood of the identified risks and develops prioritized lists of the risks for further analysis or direct mitigation. A common qualitative approach is the precedence diagramming method, which uses ordinal numbers to determine priorities and outcomes. Another way of employing qualitative approach is to make a list of the processes of a project in descending order, calculate the risks associated with each process and list the controls that may exist for each risk (Ehsan et al., 2010). A risk matrix (or a probability/impact matrix) also is a tool commonly used in qualitative risk analysis (Mahendra et al., 2013; Zhou & Leung, 2012; Modarres, 2006). It is a table that contains several regions that indicate risk level based on the scale of probability and scale of impact or severity. Risks are qualitatively assessed according to the region it mapped. In this study, the risk levels for the factors that have been identified were assessed by using risk matrix which has been explained in section 3.5.3.

Once the risks of a project have been identified and analyzed, appropriate **risk response** strategies must be adopted to cope with the risks in the project implementation. The treatment measures on each risk are based on the nature and impact of the risk (Zou et al., 2007). As mentioned by Mahendra et al. (2013), risk response can be done by several methods including risk avoidance, risk transfer, risk mitigation/reduction, risk exploit, risk share, risk enhance, risk acceptance, and contingency plan. In this study, to response the risk, mitigation measures for the risky factor were proposed. The mitigation measure may reduce the probability and/or impact of an adverse risk event to an acceptable level of risk. Taking early action to reduce the probability and/or impact of a risk is often more effective than attempting to repair the damage after the risk has passed (Mahendra et al., 2013).

Basically, eliminating construction risks seems hardly doable (Siew & Abdul-Rahman, 2013). However, risk management should be applied into any construction project at the initial stage of the project to get maximum benefit in managing the risk. This is because, the awareness of the risks and appropriate strategies for dealing with the risks are imperative and contributes to the success of the projects (Zou et al., 2007).

2.3 Construction Wastes

There are a lot of researches in construction wastes generation that have been carried out in various countries. It includes the types of construction wastes, factors causing construction wastes, the impacts, and the way of handling the wastes. This subtopic comprises the definition of construction wastes, construction wastes generation in other countries, wastes management, and the impact of the wastes.

2.3.1 Definition

Construction wastes have been defined in various ways. Skoyles & Skoyles (1987) stated that construction wastes is ‘a material which needed to be transported elsewhere from the construction site or used on the site itself other than the intended purpose of the project due to damage, excess or non-use or which cannot be used due to non-compliance with the specifications, or which is a by-product of the construction process’. In Hong Kong, the definition of construction wastes was established by Hong Kong Polytechnic (1993) as ‘by-product generated and removed from construction, renovation, and demolition work places or sites of building and civil engineering structures’. In another research, construction wastes was defined as ‘any material apart from earth materials, which needed to be transported elsewhere from the construction site or used on the site itself other than the intended specific purpose of the project due to damage, excess or non-use or which cannot be used due to non-compliance with the specifications, or which is a by-product of the construction process’ (Ekanayake & Ofori, 2004). Based on the Solid Wastes and Public Cleaning Management Act 2007 (Act 672), construction solid wastes are ‘any type of solid wastes that is produced from any construction activities or demolition or including accomplishment, arrangement, renovation or modification’.

According to Poon et al. (2013), construction waste is a mixture of inert and non-inert materials arising from various construction activities like excavation, demolition, construction, renovation, and roadwork. Based on all highlighted definitions, it should be understood that construction wastes is in the form of materials losses while the construction project was being carried out.

However, according to new production philosophy, Koskela (1992) stated that construction wastes 'includes both the incidence of material losses and the execution of unnecessary work, which generates additional costs but does not add value to the product. This was then supported by Formoso, Isatto, & Hirota (1999) whom defined construction wastes as 'any inefficiency that results in the use of equipment, materials, labour, or capital in larger quantities than those considered as necessary in the production of a building'. This means that, besides material wastes; time, cost, and process wastes also can be described as wastes. It can be generated due to any inefficiency of activities such as waiting time, over production, and processing but do not add any value to the project. However, this research only focuses on construction material wastes. Although construction wastes generation contributes to high economic losses than material wastes (Formoso et al., 1999), the most important thing that we have to be concerned with is the adverse impact on the environment (Masudi et al., 2011) which is contributed by material wastes. Table 2.1 summarizes the various definitions given for construction waste.



REFERENCES

- Abdullah, A. M., & Malik, S. A. (2012). Key indicators of SWOT analysis between Bumiputera and Non-bumiputera Industrialized Building System (IBS) contractors in Selangor. *2012 International Conference on Statistics in Science, Business and Engineering (ICSSBE)* (pp. 1–6). IEEE.
- Adeweyu, T. O., & Oтали, M. (2013). Evaluation of causes of construction material wastes - Case of Rivers State, Nigeria. *Ethiopian Journal of Environmental Studies and Management*, 6(6), 746–753.
- Agyekum, K., Ayarkwa, J., & Adinyira, E. (2012). Consultants' perspectives on materials wastes reduction in Ghana. *Engineering Management Research*, 1(1), 138–150.
- Akintoye, A. S., & Macleod, M. J. (1997). Risk analysis and management in construction. *International Journal of Project Management*, 15(1), 31–38.
- Al-Hajj, A., & Hamani, K. (2011). Material wastes in the UAE construction industry: Main causes and minimisation practices. *Architectural Engineering and Design Management*, 7(4), 221–235.
- Alshubbak, A., Pellicer, E., & Catalá, J. (2009). A collaborative approach to project life cycle definition based on the Spanish construction industry. *3RD Conference on Engineering Work in Palestine November 3-5, 2009* (pp. 1–19).
- Alwi, S., Hampson, K., & Mohamed, S. (2001). Effect of quality supervision on rework in the Indonesian context. *Asia Pacific Building and Construction Management Journal*, 1–9.
- Alwi, S., Hampson, K., & Mohamed, S. (2002a). Wastes in the Indonesian construction project. *Proceedings of the 1st International Conferences of CIB W107 – Creating a Sustainable Construction Industry in Developing Countries* (pp. 305–315).

- Abdullah, A. M., & Malik, S. A. (2012). Key indicators of SWOT analysis between Bumiputera and Non-bumiputera Industrialized Building System (IBS) contractors in Selangor. *2012 International Conference on Statistics in Science, Business and Engineering (ICSSBE)* (pp. 1–6). IEEE.
- Adeweyu, T. O., & Otali, M. (2013). Evaluation of causes of construction material wastes - Case of Rivers State, Nigeria. *Ethiopian Journal of Environmental Studies and Management*, *6*(6), 746–753.
- Agyekum, K., Ayarkwa, J., & Adinyira, E. (2012). Consultants' perspectives on materials wastes reduction in Ghana. *Engineering Management Research*, *1*(1), 138–150.
- Akintoye, A. S., & Macleod, M. J. (1997). Risk analysis and management in construction. *International Journal of Project Management*, *15*(1), 31–38.
- Al-Hajj, A., & Hamani, K. (2011). Material wastes in the UAE construction industry: Main causes and minimisation practices. *Architectural Engineering and Design Management*, *7*(4), 221–235.
- Alshubbak, A., Pellicer, E., & Catalá, J. (2009). A collaborative approach to project life cycle definition based on the Spanish construction industry. *3RD Conference on Engineering Work in Palestine November 3-5, 2009* (pp. 1–19).
- Alwi, S., Hampson, K., & Mohamed, S. (2001). Effect of quality supervision on rework in the Indonesian context. *Asia Pacific Building and Construction Management Journal*, 1–9.
- Alwi, S., Hampson, K., & Mohamed, S. (2002a). Wastes in the Indonesian construction project. *Proceedings of the 1st International Conferences of CIB W107 – Creating a Sustainable Construction Industry in Developing Countries* (pp. 305–315).

- Alwi, S., Hampson, K., & Mohamed, S. (2002b). Non value-adding activities in Australian construction projects. *Proceedings International Conference on Advancement in Design, Construction, Construction Management and Maintenance of Building Structure* (pp. 270–278).
- Alwi, S., Hampson, K., & Mohamed, S. (2002c). Non value-adding activities: A comparative study of Indonesian and Australian construction projects. *Proceedings 10th of the International Group of Lean Construction Conference* (pp. 627–638).
- Arnold, P., & Javernick-will, A. (2013). Projectwide Access: Key to effective implementation of construction project management software systems. *Journal of Construction Engineering and Management*, 139(5), 510–518.
- Augustine, S. (2011). *Managing wastes and cost in the construction industry: a case study of the road construction*. Kwame Nkrumah University of Science and Technology: Master's Thesis.
- Barron, M., & Barron, A. R., (2013). *Project management*. Rice University, Houston, Texas: Connexions.
- Bennet, F. L. (2007). *The management of construction: a project lifecycle approach*. Alaska: Routledge.
- Begum, R. A., & Pereira, J. J. (2011). C&D waste profile of the Malaysian construction industry: Need a centralized database. *Sustainable Technologies (WCST), 2011 World Congress on* (pp. 73-76). IEEE.
- Begum, R. A., Satari, S. K., & Pereira, J. J. (2010). Wastes generation and recycling : Comparison of Conventional and Industrialized Building Systems. *American Journal of Environmental Sciences*, 6(4), 383–388.
- Begum, R. A., Siwar, C., Pereira, J. J., & Jaafar, A. H. (2009). Attitude and behavioral factors in wastes management in the construction industry of Malaysia. *Resources, Conservation and Recycling*, 53(6), 321–328.
- Berg, R., & Hinze, J. (2005). Theft and vandalism on construction sites. *Journal of Construction Engineering and Management*, 131(7), 826–833.
- Bossink, B. A. G., & Brouwers, H. J. H. (1996). Construction wastes: Quantification and source evaluation. *Journal of Construction Engineering and Management*, 122(1), 55–60.
- Calvo, N., Varela-Candamio, L., & Novo-Corti, I. (2014). A dynamic model for construction and demolition (C&D) waste management in Spain: Driving

- policies based on economic incentives and tax penalties. *Sustainability*, 6(1), 416-435.
- Chandrakanthi, M., & Ruwanpura, J. Y. (2002). Optimization of the wastes management for construction projects using simulation. *Proceedings of the 2002 Winter Simulation Conference* (pp. 1771–1777). IEEE.
- Chan, D. W., & Kumaraswamy, M. M. (1997). A comparative study of causes of time overruns in Hong Kong construction projects. *International Journal of Project Management*, 15(1), 55-63.
- Chan, A. P. C., Yung, E. H. K., Lam, P. T. I., Tam, C. M. & Cheung, S. O. (2001). Application of Delphi method in selection of procurement systems for construction projects. *Construction Management and Economics*, 19 (7), 699 - 718.
- Dainty, A. R., & Brooke, R. J. (2004). Towards improved construction wastes minimisation: a need for improved supply chain integration? *Structural Survey*, 22(1), 20-29.
- Domingo, N., Osmani, M., & Price, A. D. F. (2008). Reducing construction wastes in healthcare facilities : A project lifecycle approach. *Association of Researches in Construction Management*, Cardiff, Wales.
- Egan, J. (1998). *Rethinking Construction*. The Report of the Construction Task Force to the Deputy Prime Minister, John Prescott. United Kingdom.
- Ehsan, N., Mirza, E., Alam, M., Ishaque, A. (2010). Risk management in construction industry. *Computer Science and Information Technology (ICCSIT)*, 2010 3rd IEEE International Conference, 9, 16-21.
- Ekanayake, L. L., & Ofori, G. (2004). Building wastes assessment score: Design-Based Tool. *Building and Environment*, 39(7), 851–861.
- Engert, P. A., & Lansdowne, Z. F. (1999). Risk Matrix User's Guide. *Bedford, MA: The MITRE Corporation*.
- Esin, T., & Cosgun, N. (2007). A study conducted to reduce construction wastes generation in Turkey. *Building and Environment*, 42(4), 1667–1674.
- Enshassi, A., Mohamed, S., & Abushaban, S. (2009). Factors affecting the performance of construction projects in the Gaza strip. *Journal of Civil Engineering and Management*, 15(3), 269-280.

- Ferguson, J., Kermodé, N., Nash, C. L., Sketch, W. A. J., & Huxford, R. P. (1995). *Managing and minimizing construction wastes - A practical guide*. London: Institution of Civil Engineers.
- Foo, L. C., Rahman, I. A., Asmi, A., Nagapan, S., & Khalid, K. I. (2013). Classification and quantification of construction wastes at housing project site. *International Journal of Zero Wastes Generation*, 1(1), 1–4.
- Formoso, C. T., Soibelman, L., Cesare, C. D., & Isatto, E. L. (2003). Material wastes in building industry: Main causes and prevention. *Journal of Construction Engineering and Management*, 128(4), 316–325.
- Formoso, C. T., Isatto, E. L., & Hirota, E. H. (1999). Method for wastes control in the building industry. *Proceedings of the 7th Annual Conference of the International Group for Lean Construction (1999)* (pp. 325–334).
- Frame, J. D. (2003). *Managing Risk in Organizations: A Guide for Managers*. 1st ed. Jossey-Bass: A Wiley Imprint, San Francisco.
- Frimpong, Y., Oluwoye, J., & Crawford, L. (2003). Causes of delay and cost overruns in construction of groundwater projects in a developing countries; Ghana as a case study. *International Journal of Project Management*, 21(5), 321-326.
- Gannet Flaming Inc. (2009). *Construction Project Management Handbook*. Washington DC: Federal Transit Administration.
- Garas, G. L., Anis, A. R., & Gammal A. (2001). Materials wastes in the Egyptian construction industry (pp. 1-8).
- Garas, G. L. (2003). *Estimating material wastes in the building construction industry using Artificial Intelligence*. Cairo University: Ph.D. Proceeding.
- Gavilan, R. M., & Bernold, L. E. (1995). Source evaluation of solid wastes in building construction. *Journal of Construction Engineering and Management*, 120(3), 536–552.
- Gharaibeh, H. M. (2013). Cost control in mega projects using the Delphi Method. *Journal of Management in Engineering*, 30(5), 1-24.
- Goh, K. C., Tey, J. S., Seow, T. W., & Goh, H. H. (2013). Importance of sustainability and engineering economics in wastes infrastructure projects, *International Conference on Sustainable Building Asia (SB13 SEOUL)*. Seoul, Korea: International Sustainability Council and Architectural Institute of Korea. pp. 352–358.

- Gohar, A. S., Khanzadi, M., & Farmani, M. (2012). Identifying and evaluating risks of construction projects in fuzzy environment: a case study in Iranian construction industry. *Indian Journal of Science and Technology*, 5(11), 3593-3602.
- Gündüz, M., Nielsen, Y., & Özdemir, M. (2013). Quantification of delay factors using the relative importance index method for construction projects in Turkey. *Journal of Management in Engineering*, 29(2), 133-139.
- Hallowell, M. R., & Gambatese, J. A. (2010). Qualitative research : application of the Delphi method to CEM Research. *Journal of Construction Engineering Management*, 136(1), 99–107.
- Hamatschek, E., Tee, S. S., & Faulstich, M. (2010). Current practice of municipal solid wastes management in Malaysia and the potential for Wastes-to-Energy implementation. *The International Solid Waste Association (ISWA) World Congress*, Hamburg, Germany.
- Hasan, A. B. C., Ridzuan, A. R. B. M., Yusof, Z. B., Noordin, B. B., Atan, I. B., & Ghani, A. H. B. A. (2013). Estimation model of construction waste materials in Malaysia: Steel. In *Business Engineering and Industrial Applications Colloquium (BEIAC), 2013 IEEE* (pp. 709-713). IEEE.
- Hassan, S. H., Ahzahar, N., Fauzi, M. A., & Eman, J. (2012). Wastes management issues in the Northern Region of Malaysia. *Procedia - Social and Behavioral Sciences*, 42, 175–181.
- Hong Kong Polytechnic. (1993). *Reduction of Construction wastes: final report*. Hong Kong: The Hong Kong Construction Association Limited.
- Hussin, J. M., Rahman, I. A., & Memon, A. H. (2013). The way forward in sustainable construction: issues and challenges. *International Journal of Advances in Applied Sciences*, 2(1), 15-24.
- Ikau, R., Tawie, R., & Joseph, C. (2013). Initial findings on perspectives of local contractors on wastes minimization barriers and incentives on construction sites. *2013 IEEE Business Engineering and Industrial Applications Colloquium (BEIAC)* (pp. 506–509). IEEE.
- Intan, S., Alifen, R. S., & Arijanto, L. (2005). Analisa dan evaluasi sisa material konstruksi. *Civil Engineering Dimension*, 7(1), 36–45.
- Jannadi, O. A., & Almishari, S. (2003). Risk assessment in construction. *Journal of Construction Engineering and Management*, 129(5), 492–500.

- Jiu-yan, W., Yi-kun, S., & Jin-xin, T. (2009). Study on the construction project life-cycle Integrated Management System. *2009 International Conference on Management Science & Engineering (16th)* (pp. 1976–1981).
- John, A. O., & Itodo, D. E., (2013). Professionals' views of material wastage on construction sites and cost overruns. *Organization, Technology & Management in Construction: An International Journal*. 5(1). (pp. 747-757).
- Jordan, E., & Javernick-Will, A. (2013). Indicators of community recovery: content analysis and Delphi approach. *Natural hazards review*, 14(1), 21-28.
- KarimiAzari, A., Mousavi, N., Mousavi, S. F., & Hosseini, S. (2011). Risk assessment model selection in construction industry. *Expert Systems with Applications*, 38(8), 9105-9111.
- Kartam, N. A. (1996). Making effective use of construction lessons learned in project life cycle. *Journal of Construction Engineering and Management*, 122(5913), 14–21.
- Kartam, N., Al-Mutairi, N., Al-Ghusain, I., & Al-Humoud, J. (2004). Environmental management of construction and demolition wastes in Kuwait. *Wastes management (New York, N.Y.)*, 24(10), 1049–59.
- Katz, A., & Baum, H. (2011). A novel methodology to estimate the evolution of construction wastes in construction sites. *Wastes management (New York, N.Y.)*, 31(2), 353–8.
- Khan, R. A., Liew, M. S., & Ghazali, Z. (2014). Malaysian construction sector and Malaysia Vision 2020 : Developed Nation Status. *2nd World Conference On Business, Economics And Management - WCBEM 2013* (Vol. 109, pp. 507–513). Elsevier B.V.
- Kofoworola, O. F., & Gheewala, S. H. (2009). Estimation of construction wastes generation and management in Thailand. *Wastes management (New York, N.Y.)*, 29(2), 731–8.
- Koskela, L. (1992). *Application of the new production philosophy to construction* (No. 72). (Technical Report No. 72, Center for Integrated Facility Engineering, Department of Civil Engineering). Stanford, CA: Stanford University.
- Kozlovská, M., & Spišáková, M. (2013). Construction wastes generation across construction project life-cycle. *Organization, Technology and Management in Construction an International Journal*, 5(1), 687–695.

- Kulatunga, U., Amaratunga, D., Haigh, R., & Rameezdeen, R. (2006). Attitudes and perceptions of construction workforce on construction wastes in Sri Lanka. *Management of Environmental Quality: An International Journal*, 17(1), 57–72.
- Laquatra, J. (2004). Wastes management at the construction site. *Proceedings of the NSF Housing Research Agenda Workshop, Feb. 12-14, 2004, Orlando, FL. Vol. 2*, pp. 45 - 50.
- Lester, A. (2007). *Project Management - Planning and Control*. 5th ed. New York: Elsevier Ltd.
- Ling, F. Y. Y., & Nguyen, D. S. A. (2013). Strategies for construction wastes management In Ho Chi Minh City, Vietnam. *Emerald Group Publishing Limited*.
- Linstone, H. A., & Turoff, M. (Eds.). (1975). *The Delphi method: Techniques and applications* (Vol. 29). Reading, MA: Addison-Wesley.
- Liu, Z., Osmani, M., Demian, P., & Baldwin, A. N. (2011). The potential use of BIM to aid construction wastes minimisation. *Proceedings of the CIB W78-W102 2011: International Conference –Sophia Antipolis, France, 26-28 October*.
- Lu, W., & Tam, V. W. Y. (2013). Construction wastes management policies and their effectiveness in Hong Kong: A longitudinal review. *Renewable and Sustainable Energy Reviews*, 23, 214–223.
- Lu, W., & Yuan, H. (2011). A framework for understanding wastes management studies in construction. *Wastes management (New York, N.Y.)*, 31(6), 1252–60.
- Lu, W., Yuan, H., Li, J., Hao, J. J. L., Mi, X., & Ding, Z. (2011). An empirical investigation of construction and demolition wastes generation rates in Shenzhen city, South China. *Wastes management (New York, N.Y.)*, 31(4), 680–687.
- Mahamid, I. (2011). Risk matrix for factors affecting time delay in road construction projects: owners' perspective. *Engineering, Construction and Architectural Management*, 18(6), 609–617.
- Mahendra, P. A., Pitroda, J. R., & Bhavsar, J. J. (2013). A Study of Risk Management Techniques for Construction Projects in Developing Countries. *International Journal of Innovative Technology and Exploring Engineering. Vol3*, (5), 139-142.

- Manoliadis, O., Tsolas, I., & Nakou, A. (2006). Sustainable construction and drivers of change in Greece: a Delphi study. *Construction Management and Economics*, 24(2), 113–120.
- Manowong, E. (2012). Investigating factors influencing construction wastes management efforts in developing countries: an experience from Thailand. *Wastes Management & Research: The Journal of the International Solid Wastess and Public Cleansing Association, ISWA*, 30(1), 56–71.
- Marzouk, M. M., & El-Rasas, T. I. (2014). Analyzing delay causes in Egyptian construction projects. *Journal of Advanced Research*, 5(1), 49-55.
- Marzouk, M., & Azab, S. (2014). Environmental and economic impact assessment of construction and demolition wastes disposal using System Dynamics. *Resources, Conservation and Recycling*, 82, 41–49.
- Masudi, A. F., Hassan, C. R. C., Mahmood, N. Z., Mokhtar, S. N., & Sulaiman, N. M. (2011). Construction wastes quantification and benchmarking: A study in Klang Valley, Malaysia. *Journal of Chemistry and Chemical Engineering*, 5(10), 909-916.
- Memon, A. H., Rahman, I. A., Asmi, A., & Azis, A. (2011). Preliminary study on causative factors leading to construction cost overrun. *International Journal of Sustainable Construction Engineering & Technology*, 2(1), 57–71.
- Memon, A. H., Rahman, I. A., & Azis, A. A. A. (2012). Time and cost performance in construction projects in Southern and Central Regions of Peninsular Malaysia. *International Journal of Advances in Applied Sciences*, 1(1), 45-52.
- Modarres, M. (2006). *Risk analysis in engineering: techniques, tools, and trends*. 1st ed. Boca Raton: CRC Press.
- Morledge, R., Smith, A. & Kashiwagi, D. T. (2006). *Risk. in building procurement*. Oxford: Blackwell.
- Nagapan, S., Rahman, I. A., & Asmi, A. (2011). A review of construction wastes cause factors. *Proceedings of the Asian Conference of Real Estate: Sustainable Growth Managing Challenges (ACRE), Johor, Malaysia*.
- Nagapan, S., Rahman, I. A., & Asmi, A. (2012a). Construction wastes management : Malaysian perspective. *International Conference on Civil and Environmental Engineering Sustainability (IConCEES), Malaysia* (Vol. 2, pp. 299–309).

- Nagapan, S., Rahman, I. A., & Asmi, A. (2012b). Factors contributing to physical and non-physical wastes generation in construction industry. *International Journal of Advances in Applied Sciences (IJAAS)*, 1(1), 1–10.
- Nagapan, S., Rahman, I. A., Asmi, A., Hameed, A., & Zin, R. M. (2012c). Identifying causes of construction wastes - case of Central Region of Peninsula Malaysia. *International Journal of Integrated Engineering*, 4(2), 22–28.
- Nagapan, S., Rahman, I. A., Asmi, A., Memon, A. H., & Latif, I. (2012d). Issues on construction wastes: The need for sustainable wastes management. *2012 IEEE Colloquium on Humanities, Science and Engineering (CHUSER)* (pp. 325–330). IEEE.
- Nagapan, S., Rahman, I. A., Asmi, A., & Adnan, N. F. (2013). Study of site's construction wastes in Batu Pahat, Johor. *Malaysian Technical Universities Conference on Engineering & Technology 2012, MUCET 2012 Part 3 - Civil and Chemical Engineering* (Vol. 53, pp. 99–103).
- Nasaruddin, F. H., & Ravana, S. D. (2008). E-Construction wastes exchange in Malaysia: A preliminary study issues in Malaysia management. *Information Technology, 2008. ITSIM 2008. International Symposium on*, 4, 1–7.
- Nazech, E. M., Zaldi, D., & Trigunaryah, B. (2008). Identification of construction wastes in road & highway construction projects. *Proceedings Eleventh East Asia-Pacific Conference on Structural Engineering and Construction (EASEC-11)* (pp. 1–7).
- Oladiran, & Joseph, O. (2009). Causes And minimization techniques of materials wastes in Nigerian construction process. *Fifth International Conference on Construction in the 21st Century (CITC-V) "Collaboration and Integration in Engineering, Management and Technology" May 20-22, 2009, Istanbul, Turkey*.
- Official Portal Solid Wastes and Public Cleansing Management Corporation (PPSPPA), (2013).
http://www.sisa.my/sisamy/index.php?option=com_content&view=article&id=201&Itemid=41 [retrieved on 19 March 2014]
- Oh, I. Y. (2014). Dispose of wastes at appointed site. The Star online,
<http://www.thestar.com.my/News/Community/2014/03/07/Dispose-of-wastes-at-appointed-sites-Ministry-planning-a-more-organised-construction-debris-disposal/> [accessed on 24 March 2014].

- Olawale, Y. A., & Sun, M. (2010). Cost and time control of construction projects: inhibiting factors and mitigating measures in practice. *Construction Management and Economics*, 28(5), 509-526.
- Osmani, M. (2012). Construction wastes minimization in the UK: Current pressures for change and approaches. *Procedia - Social and Behavioral Sciences*, 40, 37–40.
- Osmani, M., Glass, J., & Price, A. (2006). Architect and contractor attitudes to wastes minimisation. *Proceeding of Institution of Civil Engineering, Wastes and Resource Management 159 Issue WR2* (pp. 65–72).
- Osmani, M., Glass, J., & Price, A. D. F. (2008). Architects' perspectives on construction wastes reduction by design. *Wastes Management*, 28(7), 1147–1158.
- Panos, K., & Danai, G. I. (2012). Survey regarding control and reduction of construction wastes. *PLEA2012 - 28th Conference, Opportunities, Limits & Needs Towards an environmentally responsible architecture Lima, Perú*.
- Perera, B. A. K. S., Rameezdeen, R., Chileshe, N., & Hosseini, M. R. (2014). Enhancing the effectiveness of risk management practices in Sri Lankan road construction projects: A Delphi approach. *International Journal of Construction Management*, 14(1), 1-19.
- Pimenteira, C. P., Carpio, L. G. T., Rosa, L. P., & Tolmansquim, M. T. (2005). Solid wastess integrated management in Rio de Janeiro: input-output analysis. *Wastes Management (New York, N.Y.)*, 25(5), 539–53.
- Polat, G., & Ballard, G. (2004). Wastes in Turkish construction. *Proceedings of the 12th Annual Conference of the International Group for Lean Construction IGLC-12, August, Denmark* (pp. 488–501).
- Poon, C S. (2007). Reducing construction wastes. *Wastes Management*, 27(12), 1715–1716.
- Poon, C. S., Yu, A. T. W., & Jaillon, L. (2004). Reducing building wastes at construction sites in Hong Kong. *Construction Management and Economics*, 22(5), 461–470.
- Rahmat, N. R., & Ibrahim, A. H. (2007). Illegal dumping site : Case study in the district of Johor Bahru Tengah, Johor. *ICoSM* (pp. 89–91).
- RIBA Plan of Work 2013: Consultation document*. (2013). (pp. 1–6).

- Rowe, G., & Wright, G. (1999). The Delphi technique as a forecasting tool : Issues and analysis. *International Journal of Forecasting*, 15(4), 353–375.
- Ruthankoon, R., & Ogunlana, S. O. (2003). Testing Herzberg’s two-factor theory in the Thai construction industry. *Engineering, Construction and Architectural Management*, 10(5), 333-341.
- Saad A. (2011). Factors impacting the project's life cycle. *E-Leader Vietnam 2011*. (pp. 1-30)
- Seagle, E. D., & Iverson, M. (2001). Characteristics of the turfgrass industry in 2020: A Delphi study with implications for agricultural education programs. *Journal of Southern Agricultural Education Research*, 52(1), 1-13.
- Senaratne, S., & Wijesiri, D. (2008). Lean construction as a strategic option: Testing its suitability and acceptability in Sri Lanka. *Lean Construction Journal*,4(1), 34-48.
- Shen, L. Y., Tam, V. W. Y., Tam, C. M., & Ho, S. (2002). Material wastage in construction activities - A Hong Kong survey. *CIB W107: Creating a Sustainable Construction Industry in Developing Countries*.
- Siew G. C., & Abdul-Rahman, H. (2013). The identification and management of major risks in the Malaysian construction industry. *Journal of Construction in Developing Countries*, 18(1), 19–32.
- Skoyles, E.R. & Skoyles, J.R. (1987). *Wastes prevention on site*. Mitchell: London.
- Skulmoski, G., Hartman, F., & Krahn, J. (2007). The Delphi method for graduate research. *Journal of Information Technology Education: Research*,6(1), 1-21.
- Spies, S. (2009). 3R in construction and demolition wastes (CDW) – potentials and constraints. *GTZ – German Technical Cooperation Division for Environment, Resource Efficiency and Wastes Management*.
- Surve, R. B., & Kuljarni, S. S. (2013). “Construction wastes reduction – A case study”. *International Journal of Engineering Research & Technology (IJERT)*. 2(8). (pp. 870 - 875).
- Tam, V. W. Y., & Le, K. N. (2009). On implementation of wastes management systems in the Hong Kong construction industry using spectral methods. *2009 IEEE International Conference on Industrial Engineering and Engineering Management* (pp. 573–577). IEEE.

- Tam, V. W. Y., Shen, L. Y., Fung, I. W. H., & Wang, J. Y. (2007a). Controlling construction wastes by implementing governmental ordinances in Hong Kong. *Construction Innovation: Information, Process, Management*, 7(2), 149–166.
- Tam, V. W. Y., Shen, L. Y., & Tam, C. M. (2007b). Assessing the levels of material wastage affected by sub-contracting relationships and projects types with their correlations. *Building and Environment*, 42(3), 1471–1477.
- Uher, T. (2003) *Programming and Scheduling techniques*, UNSW Press, Sydney.
- Urio, A. F., & Brent, A. C. (2006). Solid wastes management strategy in Botswana : The reduction of construction wastes. *Journal of the South African Institution of Civil Engineering*, 48(2), 18–22.
- Van Teijlingen, E. R., & Hundley, V. (2010). The importance of pilot studies. *Social Research Update*, 34, 1-4.
- Wahab, A. B., & Lawal, A. F. (2011). An evaluation of wastes control measures in construction industry in Nigeria. *African Journal of Environmental Science and Technology*, 5(3), 246–254.
- Wan, S. K., Kumaraswamy, M. M., & Liu, D. T. (2009). Contributors to construction debris from electrical and mechanical work in Hong Kong infrastructure projects. *Journal of Construction Engineering and Management*, 135(7), 637–646.
- Wang, J., Li, Z., & Tam, V. W. Y. (2014). Critical factors in effective construction wastes minimization at the design stage: a Shenzhen case study, China. *Resources, Conservation and Recycling*, 82, 1–7.
- Wang, J.-Y., Kang, X.-P., & Tam, V. W.-Y. (2008). An investigation of construction wastess: an empirical study in Shenzhen. *Journal of Engineering, Design and Technology*, 6(3), 227–236.
- Wang, R., & Li, S. (2011). Talking about the production and disposing of construction wastes from the view of sustainable development. *Power and Energy Engineering Conference (APPEEC), 2011 Asia-Pacific, IEEE* (pp. 1–4).
- Wastes & Resources Action Programme (WRAP) (2009). *Achieving good practice wastes minimisation and management*. Oxon: Wastes & Resauces Action Programme.
- Westland, J. (2006). *The project management life cycle*. United Kingdom: Kongan Page.

- Wibiwo, M. A. (2003). *The contribution of the construction industry to the economy of Indonesia: a systemic approach*. Civil Engineering Department, Diponegoro University, Indonesia.
- Xia, B., & Chan, A. P. C. (2010). Key competences of design-build clients in China. *Journal of Facilities Management*, 8(2), 114–129.
- Yang, Y. B., & Ou, S. F. (2008). Using structural equation modeling to analyze relationships among key causes of delay in construction. *Canadian Journal of Civil Engineering*. (35), 321–332.
- Yeheyis, M., Hewage, K., Alam, M. S., Eskicioglu, C., & Sadiq, R. (2012). An overview of construction and demolition wastes management in Canada: a lifecycle analysis approach to sustainability. *Clean Technologies and Environmental Policy*, 15(1), 81–91.
- Yeung, J. F. Y., Chan, A. P. C., & Chan, D. W. M. (2009). Developing a performance index for relationship-based construction projects in Australia: Delphi Study. *Journal of Management in Engineering*, 25(2), 59–68.
- Yu, A. T. W., Poon, C. S., Wong, A., Yip, R., & Jaillon, L. (2013). Impact of construction wastes disposal charging scheme on work practices at construction sites in Hong Kong. *Wastes Management (New York, N.Y.)*, 33(1), 138–46.
- Yuan, H. (2012). A model for evaluating the social performance of construction wastes management. *Wastes management (New York, N.Y.)*, 32(6), 1218–28.
- Yunpeng, H. (2011). Minimization management of construction wastes. *2011 International Symposium on Water Resource and Environmental Protection (ISWREP), China* (pp. 2769–2772). IEEE.
- Zhao, Y., & Chua, D. K. H. (2003). Relationship between productivity and non value-adding activity. *11th Annual Conference of the International Group for Lean Construction*.
- Zhou, H., & Zhang, H. (2011). Risk assessment methodology for a deep foundation pit construction project in Shanghai, China. *Journal of Construction Engineering and Management*, 137(12), 1185–1194.
- Zhou, P., & Leung, H. K. (2012). An integrated risk analysis method using spatial interpolation. In *Software Engineering Conference (APSEC), 2012 19th Asia-Pacific* (Vol. 1, pp. 452-461). IEEE.

Zou, P. X., Zhang, G., & Wang, J. (2007). Understanding the key risks in construction projects in China. *International Journal of Project Management*, 25(6), 601-614.

