

**A STUDY ON STRYHCNOS POTATORIUM AND PISUM SATIVUM AS  
NATURAL COAGULANTS FOR MEAT FOOD PROCESSING  
WASTEWATER**

**NOR FADZILAH BINTI PAHAZRI**



**UNIVERSITI TUN HUSSIEN ONN MALAYSIA**

A STUDY ON STRYHCNOS POTATORUM AND PISUM SATIVUM  
AS NATURAL COAGULANTS FOR MEAT FOOD PROCESSING  
WASTEWATER

NOR FADZILAH BINTI PAHAZRI

A thesis submitted in  
fulfillment of the requirement for the award of the  
Degree of Master of Civil Engineering

Faculty of Civil and Environmental Engineering  
UNIVERSITI TUN HUSSEIN ONN MALAYSIA  
86400 Parit Raja, Johor

JULY, 2018

## DEDICATION

**To Maa and Abah,  
The reason of what I became today.  
Thanks for the endless love and great support.**

**To lecturers,  
Thanks a lot for the guidance and helping.**

**To my beloved brothers and sisters,  
Thanks for making me happy and support.**

**To the friends,  
I will always remember you,**

**Thank you all...**

**Love,  
-Fadzillah Pahazri-**



PTTA  
PERPUSTAKAAN TUN AMINAH

## ACKNOWLEDGEMENT

I acknowledge with my sincere thanks to my supervisor Assoc. Prof. Dr. Radin Maya Saphira bt Radin Mohamed for the opportunity, guidance, invaluable advice and support during the period of my studies. I have learned a lot of things about the study and life as a student.

A million thanks to our research team members for the guidance and constructive comments during the period of this research.

My special thanks go to the Universiti Tun Hussein Onn Malaysia for the grant of this study.

I would like to offer my sincere appreciation to my family and friends for their support and encouragement to finish this thesis.

Finally, I hope this study may be blessed by Him and be beneficial in the future.

Nor Fadzilah Binti Pahazri,  
Master of Civil Engineering



## ABSTRACT

Wastewater generated from meat food processing industry has significant effects on the environment. Many methods have been reported for removing turbidity, total suspended solids (TSS), chemical oxygen demand (COD), oil and grease (O&G) and colour from meat food processing wastewater (MFPW). The most common method among them is flocculation-coagulation process which is widely used. Although inorganic coagulants are prominent in wastewater treatments, its application may cause toxic residual. In this study, the attempt has been made to study the performance of *S. Potatorum* (nirmali) and *P. Sativum* (pea) seed as natural coagulants in the flocculation process. A further aim is to determine the optimum conditions for the treatment of MFPW effluents such as coagulant dosage, mixing rate and pH. An adsorption study was also carried out to study the adsorption potential of these coagulants to treat MFPW. A lab-scale treatment tank was developed to evaluate the effectiveness in MFPW treatment. Jar test results showed that optimum dosage, pH and mixing rate for *S. Potatorum* were pH 8 with dosage of 150 mg/L and 150 rpm mixing rate with the removal of turbidity, TSS, COD, O&G and colour are 91%, 97.6%, 58.4%, 79.9% and 84.3% respectively. Meanwhile, for *P. Sativum*, the optimum condition were observed at pH 8 with dosage of 150 mg/L and 150 rpm mixing rate with the removal of turbidity, TSS, COD, O&G and colour 87.8%, 97.3%, 65.5%, 77.9% and 76.5% respectively. The adsorption study was found that the analysis fitted well to the Langmuir isotherm for both natural coagulants. Results show that the percentage of turbidity, TSS, COD, O&G removal by chemical coagulants are quite similar than natural coagulants when lab-scale treatment tank was used to treat the MFPW. This indicated that these natural coagulants have a potential to use as alternative in wastewater treatment.

## ABSTRAK

Air sisa yang dihasilkan daripada industri pemprosesan makanan berasaskan daging mempunyai kesan yang ketara terhadap alam sekitar. Banyak kaedah telah dilaporkan untuk merawat kekeruhan, jumlah pepejal terampai (TSS), keperluan oksigen kimia (COD), minyak dan gris (O&G) dan warna dari air sisa pemprosesan makanan daging (MFPW). Kaedah yang paling umum adalah proses pengumpulan dan pengelompokan yang digunakan secara meluas. Walaupun penggunaan penggumpal bukan organik terkenal dalam rawatan air sisa, namun ianya boleh menyebabkan sisa toksik berbahaya. Dalam kajian ini, eksperimen telah dijalankan untuk mengkaji prestasi *S. Potatorum* dan *P. Sativum* sebagai koagulan semulajadi dalam proses pengelompokan menggunakan ujian Jar. Tujuan lain kajian ini adalah untuk menentukan keadaan optimum bagi rawatan MFPW iaitu kadar percampuran, pH dan halaju pengacauan. Kajian penjerapan juga dijalankan untuk mengkaji potensi penjerap penggumpal ini untuk merawat air sisa pemprosesan daging. Sebuah tangki rawatan makmal juga direka untuk menilai keberkesanan rawatan air sisa pemprosesan daging. Keputusan ujian Jar menunjukkan bahawa dos yang optimum, pH dan halaju pengacauan untuk *S. Potatorum* adalah pada pH 8 dengan dos campuran 150 mg/L dan 150 rpm dengan penyingkiran kekeruhan, pepejal terampai (TSS), keperluan oksigen kimia (COD), minyak dan gris (O & G) dan warna ialah 91%, 97.6% 58.4%, 79.9% dan 84.3%. Sementara itu, untuk *P. Sativum*, optimum proses adalah pada pH 8 dengan dos 150 mg/ L dan 150 rpm halaju pengacauan, memberikan kadar pengurangan jumlah pepejal terampai (TSS), keperluan oksigen kimia (COD), minyak dan gris (O&G) dan warna masing-masing 87.8%, 97.3%, 65.5%, 77.9% dan 76.5 %. Kajian penjerapan mendapati bahawa analisis itu sesuai dengan isoterm Langmuir untuk kedua-dua bahan penggumpal semula jadi. Keputusan menunjukkan bahawa peratusan kekeruhan, jumlah pepejal terampai (TSS), keperluan oksigen kimia (COD), minyak dan gris (O&G) dan warna daripada

eksperimen koagulan kimia tidak jauh berbeza daripada koagulan semulajadi apabila tangki rawatan makmal digunakan untuk merawat air sisa pemprosesan daging. Ini menunjukkan bahawa sistem tangki pembekuan rawatan makmal ini boleh digunakan untuk mengurangkan bahan pencemar dari air sisa pemprosesan daging.







2.4	Coagulants	12
2.4.1	Inorganic Coagulants	12
2.4.2	Organic Coagulants	13
2.5	Factors Influence the Coagulation-Flocculation Process	18
2.5.1	Effect of coagulant dosage	18
2.5.2	Effect of pH	18
2.5.3	Effect of Mixing Rate	19
2.6	Previous Studies of Coagulation-Flocculation Process in Different Wastewater Treatment	20
2.7	Adsorption Isotherms	22
2.7.1	Adsorption Models	23
2.7.2	Factors Influence the Adsorption Process	27
2.8	Key Findings of Literature Review	27
<b>CHAPTER 3 METHODOLOGY</b>		<b>29</b>
3.1	Introduction	29
3.2	Problem Identifications and Site Location	31
3.3	Sampling of Meat Food Processing Wastewater (MFPW)	32
3.3.1	Sampling Preservation and Storage	32
3.4	Testing and Equipment	33
3.5	Coagulation and Flocculation Method	34
3.5.1	Preparation of Alum and Ferrous Sulphate Stock Solution as Coagulants	34
3.5.2	Preparation of <i>S. Potatorum</i> and <i>P. Sativum</i> Stock Solution as Coagulants	35
3.5.3	Coagulation-Flocculation Process with Jar Test	36
3.6	Adsorption Experiments	36
3.6.1	Preparation of <i>S. Potatorum</i> and <i>P. Sativum</i>	

**CHAPTER 3****METHODOLOGY****29**

3.1	Introduction	29
3.2	Problem Identifications and Site Location	31
3.3	Sampling of Meat Food Processing Wastewater (MFPW)	32
3.3.1	Sampling Preservation and Storage	32
3.4	Testing and Equipment	33
3.5	Coagulation and Flocculation Method	34
3.5.1	Preparation of Alum and Ferrous Sulphate Stock Solution as Coagulants	34
3.5.2	Preparation of <i>S. Potatorum</i> and <i>P. Sativum</i> Stock Solution as Coagulants	35
3.5.3	Coagulation-Flocculation Process with Jar Test	36
3.6	Adsorption Experiments	36
3.6.1	Preparation of <i>S. Potatorum</i> and <i>P. Sativum</i>	

	Stock Solution as Adsorbent	36
3.6.2	Determination of Turbidity, TSS, COD, O&G and Colour Removal	37
3.6.3	Determination of Adsorption Isotherms	37
3.7	Lab-scale Wastewater Treatment	38
<b>CHAPTER 4</b>	<b>RESULTS AND DISCUSSION</b>	<b>40</b>
4.1	Introduction	<b>Error! Bookmark not defined.</b>
4.2	MFPW Characteristics	41
4.3	Effects of Coagulant Dosage, pH and Mixing Rate	42
4.3.1	Effect of Dosage	43
4.3.2	Effect of pH	47
4.3.3	Effect of Mixing Rate	51
4.4	Summary of the Comparison among Coagulants	54
4.5	Kinetics of Adsorption Studies	56
4.5.1	Effect on Adsorbent Dosage on Colour removal	57
4.5.2	Effect of pH on Colour Removal	58
4.5.3	Effect on Contact Time on Colour Removal	59
4.5.4	Adsorption Isotherms for <i>S. Potatorum</i> Sorbent	61
4.5.4.1	Adsorption Isotherms of Colour	61
4.5.5	Adsorption Isotherms for <i>P. Sativum</i> Sorbent	63
4.5.5.1	Adsorption Isotherms of Colour	63
4.6	Application of Lab Scale Treatment System	65
<b>CHAPTER 5</b>	<b>CONCLUSION</b>	<b>69</b>
5.1	Introduction	69
5.2	Conclusion	69
5.3	Recommendation	72



PT TAJUK TUN AMINAH  
PERPUSTAKAAN TUN AMINAH

<b>REFERENCES</b>	<b>73</b>
<b>APPENDIX A DATA OF TURBIDITY REMOVAL USING COMMERCIAL COAGULANTS</b>	<b>81</b>
<b>APPENDIX B DATA OF TURBIDITY REMOVAL USING NATURAL COAGULANTS</b>	<b>83</b>
<b>APPENDIX C DATA OF ORGANIC REMOVAL PERCENTAGE USING LAB-SCALE SYSTEM TREATMENT</b>	<b>85</b>
<b>APPENDIX D DATA OF ADSORPTION ISOTHERMS FOR TURBIDITY AND TSS</b>	<b>87</b>



## LIST OF TABLES

2.1	Characteristics of MFPW derived from previous studies	9
2.2	Review of coagulation-process using natural coagulant versus commercial coagulant	16
2.3	Previous studies of coagulation-flocculation process set-up	21
2.4	Previous study on the adsorption kinetics	26
3.1	Storage and maximum holding time of samples (APHA 2012)	33
3.2	Wastewater characteristics, methods and equipment	34
4.1	Range of characteristics of meat food processing wastewater and Standard A and B for effluent discharge in Malaysia	41
4.2	Summary of the optimum percentage removal (%) of turbidity analysis	55
4.3	Summary of the optimum percentage removal (%) of TSS analysis	55
4.4	Summary of the optimum percentage removal (%) of COD analysis	55
4.5	Summary of the optimum percentage removal (%) of O&G analysis	56
4.6	Summary of the optimum percentage removal (%) of colour analysis	56
4.7	The optimum results for coagulants to be apply in lab-scale treatment system.	56
4.8	Estimated constants of Langmuir and Freundlich isotherm for the adsorption of meat food processing wastewater parameters sorption onto <i>S.potatorum</i>	63
4.9	Estimated constants of Langmuir and Freundlich isotherm for the adsorption of meat food processing wastewater parameters sorption onto <i>P.sativum</i>	65
4.10	Summary of organic removal percentage and the concentrations value compared to standard effluent discharge in Malaysia	67

## LIST OF FIGURES

2.1	Coagulation via charge neutralization and flocculation mechanism of the colloidal particles present in water	12
3.1	Flow chart of methodology	30
3.2	Meat food processing small industry in Parit Raja	31
3.3	Satellite image of site study	31
3.4	Sampling location and the effluent discharge flow	32
3.5	<i>S. potatorum</i> and <i>P. sativum</i> coagulants stock solution	35
3.6	Lab-scale treatment system diagram	38
3.7	Lab-scale treatment system	39
4.1	Removal percentage of turbidity, TSS, COD, O&G and colour using alum with different dosage at pH 7, rapid mixing rate 150 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes	44
4.2	Removal percentage of turbidity, TSS, COD, O&G and colour using ferrous sulphate with different dosage at pH 7, rapid mixing rate 150 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes	45
4.3	Removal percentage of turbidity, TSS, COD, O&G and colour using <i>S. Potatorum</i> with different dosage at pH 7, rapid mixing rate 150 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes	46
4.4	Removal percentage of turbidity, TSS, COD, O&G and colour using <i>P. Sativum</i> with different dosage at pH 7, rapid mixing rate 150 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes	47
4.5	Removal percentage of turbidity, TSS, COD, O&G and colour using alum with different pH at 150 mg/L dosage with rapid mixing rate 150 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes	48

- 4.6 Removal percentage of turbidity, TSS, COD, O&G and colour using ferrous sulphate with different pH at 150 mg/L dosage with rapid mixing rate 210 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes 49
- 4.7 Removal percentage of turbidity, TSS, COD, O&G and colour using *S. Potatorum* with different pH at 150 mg/L dosage with rapid mixing rate 210 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes 50
- 4.8 Removal percentage of turbidity, TSS, COD, O&G and colour using *P. Sativum* with different pH at 150 mg/L dosage with rapid mixing rate 210 rpm at 5 minutes and slow mixing rate 30 rpm at 25 minutes 50
- 4.9 Removal percentage of turbidity, TSS, COD, O&G and colour using alum with different rapid mixing rate, slow mixing 20 minutes at 30 rpm with pH 7 and 150 mg/L coagulant dosage 52
- 4.10 Removal percentage of turbidity, TSS, COD, O&G and colour using ferrous sulphate with different rapid mixing rate, slow mixing 20 minutes at 30 rpm with pH 8 and 210 mg/L coagulant dosage 52
- 4.11 Removal percentage of turbidity, TSS, COD, O&G and colour using *S. Potatorum* with different rapid mixing, slow mixing 20 minutes at 30 rpm with pH 8 and 210 mg/L coagulant dosage 53
- 4.12 Removal percentage of turbidity, TSS, COD, O&G and colour using *P. Sativum* with different rapid mixing, slow mixing 20 minutes at 30 rpm with pH 9 and 150 mg/L coagulant dosage 54
- 4.13 Removal percentage colour using *S. potatorum* as adsorbent at different amount of dosage at pH 7 and contact time 60 minute 57
- 4.14 Removal percentage of colour using *P. sativum* as adsorbent at different amount of dosage at pH 7 and contact time 60 minute 58
- 4.15 Effect of pH in the range between 4 to 9 on percent reduction of colour using 2.1 g of *S. potatorum* dosage and contact time 60 minute 59
- 4.16 Effect of pH in the range between 4 to 9 on percent reduction of

	colour using 2.1 g of <i>P. sativum</i> dosage and contact time 60 minute	59
4.17	Effect of contact time from 10 to 80 minutes on colour removal, using 2.1 g of <i>S. potatorum</i> at pH 7	60
4.18	Effect of contact time from 10 to 80 minutes on colour removal, using 2.1 g of <i>P. sativum</i> at pH 7	61
4.19	Langmuir isotherms of colour of <i>S.potatorum</i>	62
4.20	Freundlich isotherms of colour of <i>S.potatorum</i>	62
4.21	Langmuir isotherms of colour of <i>P. sativum</i>	64
4.22	Freundlich isotherms of colour of <i>P. sativum</i>	64
4.23	Percentage of turbidity, TSS, BOD, COD, O&G and colour removal by chemical coagulants using lab-scale treatment system	67



**LIST OF APPENDICES**

A	Data Of Turbidity Removal Using Commercial Coagulants	94
B	Data Of Turbidity Removal Using Natural Coagulants	96
C	Data Of Organic Removal Percentage Using Lab-Scale System Treatment	98
D	Data Of Adsorption Isotherms For Turbidity And Tss	100



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH



**LIST OF ABBREVIATIONS**

°C	Degree Celsius
µm	Micrometer
APHA	American Public Health Association
BOD <sub>5</sub>	Biochemical oxygen demand
COD	Chemical oxygen demand
GPS	Global Positioning System
H <sub>2</sub> SO <sub>4</sub>	sulphuric acid
MFPW	Meat food processing wastewater
mg/L	Milligram/Liter
mm <sup>3</sup> /y	Milimeter cubic/Year
N	Nitrogens
NaOH	sodium hydroxide
NTU	Nephelometric Turbidity Unit
TN	Total Nitrogen
O&G	Oil and grease
P	Phosphorus
PAC	Polyaluminium chloride
PET	Polyethylene Terephthalate
Pt.Co	Platinum-Cobalt Scale
rpm	Revolutions per minute
TDS	Total dissolved solids
TP	Total Phosphorus
TSS	Total suspended solid

## CHAPTER 1

### INTRODUCTION

#### 1.1 Background of Study

Environment pollution is seriously increasing throughout the world because of economic growth and increased human activity. Wastewater is one of the major pollution problems that give effects to the water bodies and also human health. Wastewater originates from household wastes human and animal wastes, industrial wastewaters and groundwater infiltration. Wastewater basically is the flow of used water from a community. The nature of wastewater includes physical, chemical and biological characteristics which depend on the industrial contributions, weather and infiltration. It is 99.94 percent water by weight and the remaining 0.06 percent is material dissolved or suspended in the water. The dissolved and suspended solids in wastewater contain organic and inorganic material (Lee and Lin, 2000).

One of the wastewater that has raised environmental concern is the discharge from the food industries activities. Meat food processing industry is considered highly polluted wastewater due to the level contents from fats, bloods and also scraps of meat from the operation process (Bickers and Oostrom, 2000). Sena *et al.* (2008), had shown that the effluent of meat processing industry in Brazil having a high pollutant load due to the high concentrations of total solids (TS), turbidity, oils and greases (O&G), high biochemical oxygen demands (BOD<sub>5</sub>) and chemical oxygen demands (COD). This wastewater was dark brown in color, with a strong and putrefied smell. Meanwhile Bohdziewicz *et al.* (2003), reported that the effluent from meat processing industry in Poland was characterized by considerable pollutant

load, substantial amounts of suspended matter and high concentrations of total nitrogen varying from 49 to 287 mg/L and phosphorus 15 to 27 mg/L.

Activities in meat food processing require a lot of water. About 62 mm<sup>3</sup>/y of water was used to watering and washing livestock, cleaning vehicles, and rinsing carcasses and by-products (Sroka *et al.*, 2004). In addition, water is also used for cleaning purposes during the meat processing activities. Wastewater generated from these industries has significant effects on the environment. The nature of the processes involved in the processing industry greatly affects the type, composition and concentration of contaminants in wastewater (Rahman *et al.*, 2014). In addition, the pollution loads of waste water discharge from the meat processing industry vary according to season, day or shift. No matter whether direct or indirect discharge of wastewater meat industry, the majority of the dissolved organic matter and particles must be removed before discharge into drains or rivers (Thirugnanasambandham *et al.*, 2015). According to Caixeta *et al.* (2002), the city of Uberlândia in Brazil has 10 enterprises in area of meat food processing and slaughterhouses which in most of them, the wastewaters are not treated and the effluent was directly discharged to the receiving waterways. Consequently, this discharge of wastewaters into the receiving waterways has caused problems of bad smell and proliferation of vectors in the population of the region.

Many methods have been reported for removing COD, TSS, O&G and colour from meat food processing wastewater (MFPW), for instance upflow anaerobic sludge blanket (UASB), column flotation, anaerobic treatment, ultrafiltration and reverse osmosis and sequencing batch reactor (Caixeta *et al.*, 2002; Bohdziewicz *et al.*, 2003; Baskar and Sukmaran, 2015). The most common method among them is flocculation-coagulation process which is a widely used due to its relatively simple operation and low cost (Daud *et al.*, 2015). Coagulation, flocculation and sedimentation are the three major processes in wastewater treatment process. These processes were considered in order to achieve the full capacity of the wastewater treatment process (Kumar *et al.*, 2014).

The most commonly used coagulants in wastewater treatment are aluminium and ferric salts. However, there are some disadvantages with those in-coagulants (Gao *et al.*, 2007; Chen *et al.*, 2010). Recent studies have reported that component of aluminium salts could lead to human health implications, such as Alzhemeir's disease and the cause of cancer (Devrimci *et al.*, 2012; Hamid *et al.*, 2014). There

were also the problem of reaction of alum with the alkalinity present in the water leading to a reduction of pH and low efficiency in coagulation in cold water (Ramavandi, 2014). Due to this problem, presently there is an increasing interest to utilise the natural and cheaper materials to remove organic pollutants from wastewaters.

To ease the problems associated with chemicals coagulants, several studies have pointed out the introduction of natural coagulants. For example, Mishra *et al.*, (2002), used the plantago *pysllium mucilage* to treat the sewage and tannery effluent. Hamadani *et al.* (2011), also use the same coagulant in semi-aerobic landfill leachate treatment. The use of natural coagulants had shown high efficiency of pollutants removal in the effluent treatment.

Natural polymer based flocculants have started gaining importance for their eco-friendly nature. In this case study, the potential of *Strychnos potatorum* and *Pisum sativum* will be evaluated as a natural coagulant. The removal efficiency of COD, TSS, O&G and colour will be assessed by using *Strychnos potatorum* and *Pisum sativum* and also the presence of aluminium sulphate and ferrous sulfate as the chemical coagulants. The development of the pilot scale treatment system will be established and the efficiency of the removal of COD, TSS, O&G and colour will be assessed.

## 1.2 Problem Statement

Most of the industries choose to discharge the effluent with the cheapest way which is to release directly into the drain and river. In Malaysia, public wastewater treatment plants are insufficiently provided and due to that, wastewater is discharged directly from factories and industries to such public waters such as drains and rivers. Industrial wastewaters can be very strong in terms of pollutant concentrations and hence can contribute significantly to the overall pollution load imposed on the environment (Ng, 2005). Discharge of effluent into water bodies can cause water depletion and results in aquatic pollution (Dohare and Meshram, 2014). The food industry is one of the industries that have highest consumptions of water and is one of the biggest producers of effluents per unit of production (Singh *et al.*, 2014).

Among various kinds of food industries, meat processing is one of the industries that contributed to the degradation of environment.

One of the meat food processing industries is located in small and medium industry in Parit Raja, Batu Pahat, Johor, Malaysia. It produces whole meal pita bread, kebab frozen, marinated beef, chicken and mutton, beef, and chicken and mutton satay. As the industry that doing business based on the meat food processing, this industry requires large amounts of water for carrying out activities during the processing of the food. Based from the site investigation, wastewater from this industry was discharged into drains without any prior treatment. In addition, during the rainy season, the effluent will be flowing into the nearest water bodies. Consequently, the drain adjacent to the industrial area has been contaminated with pollutants contained in wastewater from the meat food processing. In addition, the villagers here complained about the smell come from the river. It was uncomfortable to them to live with the smell comes from the river.

The wastewater flow directly into the drains also may cause drainage pollution. Meat food processing industry produces wastewater with loads of fat, oil, grease and solids. Meat processing wastewater usually contains high concentrations of nitrogen, which must be removed before discharge to water bodies (Bickers and Oostrom, 2000). In addition, presence of plenteous amount of biodegradable organic materials in the meat processing wastewater binds oxygen and reduces its availability which ultimately causes death of aquatic animals. This wastewater also contains several toxic compounds including unionized ammonia, chromium and tannins that are directly involved in the deaths of aquatic animals (Rahman *et al.*, 2014).

Coagulation-flocculation process has been widely used wide world for wastewater treatment and aluminium and ferric salts are commonly used as coagulants. This process is known as low cost and efficient in removal organic pollutants from wastewaters. However, the using of aluminium and ferric salts in wastewater treatment can bring harm to environment and human healths other than the cost are quite expensive. There are many advantages of using natural coagulants in wastewater treatment. *S. Potatorum* and *P. Sativum* especially high contains in polysaccharide, starch and albumin proteins (Yadav *et al.*, 2014) as an active agents which makes it suitable as coagulants. Therefore this research is using natural coagulants in order to fill the gap of previous process and experiments.

### 1.3 Objectives of Study

The aim of this study was to investigate the efficiency of coagulation-flocculation process removal of turbidity, COD, TSS, colour and O&G from MFPW. The specific objectives of the study can be outlined as follows:

1. To study the effectiveness of *S. potatorum* and *P. sativum* as a natural coagulant for removing turbidity, TSS, COD, O&G and colour from MFPW and the influence of operating parameters; mixing rate, dosage and pH during the coagulation-flocculation process.
2. To investigate the adsorptions capacity of *S. potatorum* and *P. sativum* to remove COD, turbidity, colour and O&G from MFPW along with the parameters that affected the sorption process.
3. To evaluate the efficiency of the lab-scale system to treat the MFPW.

### 1.4 Research Questions

On the basis of objective of study, there are some research questions was developed to guide the study.

- 1) How much percentage of organic pollutants from MFPW can be removing by using the natural coagulants?
- 2) What is the optimum condition of mixing rate, dosage and pH that suitable for coagulation-flocculation process?
- 3) How good are the adsorption capacity of the natural coagulants in the coagulation process?
- 4) What is the parameters that effected the adsorption process?
- 5) How effective the coagulation-flocculation system to treat meat food processing wastewater in lab-scale process?

## 1.5 Scope of Study

The MFPW was collected from a meat processing industry in Parit Raja, Batu Pahat Johor, Malaysia. The raw meat processing wastewater was analyzed for the parameters such as pH, BOD, COD, TSS, turbidity, O&G, and colour.

The effectiveness of the use of *S. potatorum* and *P. sativum* as natural coagulants was measured through the removal of the five parameters of pollutants in meat food processing wastewater which are turbidity, TSS, COD, colour and O&G. Various dosages of different coagulant were tested to find the optimum dosage and their environmental factors such as pH effects were evaluated. The adsorption test was conducted by varying the amount of adsorbent, pH and contact time in jar test to investigate the potential adsorption of these sorbent and the factors that affecting the capacity of adsorption. Finally, the coagulation-flocculation system was set-up in a lab-scale to simulate the treatment process by using optimum value from all the above experimental works.

## 1.6 Significant of Study

Environment pollution is seriously increasing throughout the world because of economic growth and increased human activity. In order to control the environment pollution, the wastewater from industry need to be treated before discharged into rivers. This pollution is greatly affected human health and the environment if it is not properly treated. These impacts can include harm to fish and wildlife populations, oxygen depletion and contamination of drinking water. Through this study, the process that selected to treat meat food processing wastewater can reduced the cost and environmental friendly. This purpose can be achieved by using natural coagulation as coagulants in coagulation-flocculation process. Natural coagulants is non-toxic and locally available makes treatment cost is cheaper. The use of *S. potatorum* and *P. sativum* is not explored by many researchers especially in meat food processing wastewater. This study is important since this study was lead to an environmentally coagulation-flocculation system by using natural coagulant as an alternative to replace the chemical coagulant.

## CHAPTER 2

### LITERATURE REVIEW

#### 2.1 Introduction

This chapter describes overview of related theory and previous research relevant to the study of removal of pollutants using flocculation-coagulation process. This chapter discuss about wastewater, characteristics of meat food processing wastewater (MFPW), coagulation and flocculation process details and also factors that influence the coagulation-flocculation processes. This chapter also gives explanation about the chemical and natural coagulant that was used in wastewater treatment and the efficiency of these coagulants. In this chapter also, the adsorption process and the adsorption isotherm for wastewater was discussed. Finally, the key findings of literature review will be discussed and gaps of research will be highlighted.

#### 2.2 Meat Food Processing Wastewater (MFPW)

Waste in the food industry mainly include residual organic raw material after processing. Disposal and use of waste materials is a difficult task because of poor biological stability, high water activity, poor oxidative stability, pathogenicity and optimum enzyme activity. Industrial waste generated by different foods can be determined by the level of their production (Rahman *et al.*, 2014). One of the branches of the food industry which has the greatest impact on the degradation of the natural environment is the meat industry (Bohdziewicz *et al.*, 2003). Activities in



## REFERENCES

- Ahmad, A., Mat Yasin, N., Derek, C. & Li, J., 2011. Optimization of microalgae coagulation process using chitosan. *Chemical Engineering Journal*, Issue 173, p. 879– 882.
- Altaher, H., Elqada, E. & Omar, W., 2011. Pretreatment of Wastewater Streams from Petroleum/Petrochemical Industries Using Coagulation. *Advances in Chemical Engineering and Science*, Volume 1, pp. 245-251.
- Amuda, O. & Ibrahim, A., 2006. Industrial wastewater treatment using natural material as adsorbent. *African Journal of Biotechnology*, 5(16), pp. 1483-1487.
- Aygun, A. & Yilmaz, T., 2010. Improvement of coagulation-flocculation process for treatment of detergent wastewaters using coagulant aids. *International Journal of Chemical and Environmental Engineering* , 1(2), pp. 97 - 101.
- Baskar , M. & Sukmaran, B., 2015. Effective Method of Treating Wastewater from Meat Processing Industry Using Sequencing Batch Reactor. *International Research Journal of Engineering and Technology*, 2(2), pp. 27-31.
- Babarao, D. T. & Verma, S., 2013. Coal washery wastewater treatment using natural coagulants and chemical precipitation. *International Journal of Science and Research*, 4(6), pp. 1877-1881.
- Bidhendi, G. N., Shahriari, T. & Shahriari, S., 2009. Plantago ovata efficiency in elimination of water turbidity. *Journal of Water Resource and Protection* , Volume 2, pp. 90-98.
- Bohdziewics, J. & Ewa, S., 2006. Application of hybrid systems to the treatment of meat industry wastewater. *Desalination*, Issue 198, p. 33–40.
- Bohdziewicz, J., Sroka, E. & Korus, I., 2003. Application of Ultrafiltration and Reverse Osmosis to the Treatment of the Wastewater Produced by the Meat Industry. *Polish Journal of Environmental Studies*, 12(3), pp. 269-274.

- Caixeta , C. E., Cammarota, M. C. & Xavier, A. M., 2002. Slaughterhouse wastewater treatment: evaluation of a new three-phase separation system in a UASB. *Bioresource Technology*, Volume 81, pp. 61-69.
- Chen, T., Yue, Q. & Gao, B., 2010. Effect of dosing method and pH on color removal performance and floc aggregation of polyferric chloride–polyamine dual coagulant in synthetic dyeing wastewater treatment. *Colloids Surf. A*, Volume 355, pp. 121-129.
- Cosmin, . M. & Alexe, . F., 2014. Assessing the power generation solution by thermal-chemical conversion of meat processing industry waste. *Energy Procedia* 50, pp. 728-743.
- Choy, S., Prasad , K., Wu, T. & Ramanan, R., 2015. A review on common vegetables and legumes as promising plant-based natural coagulants in water clarification. *International Journal Environment Science and Technology*, pp. 367-390.
- Dada, A., Olalekan , A., Olantunya, A. & Dada, O., 2012. Langmuir, Freundlich, Temkin and Dubinin–Radushkevich Isotherms Studies of Equilibrium Sorption of  $Zn^{2+}$  Unto Phosphoric Acid Modified Rice Husk. *IOSR Journal of Applied Chemistry* , 3(1), pp. 38 - 45.
- Daud, Z. et al., 2015. Suspended solid, color, COD and Oil and Grease removal from biodiesel wastewater by coagulation and flocculation processes. *Social and Behavioral Sciences*, Volume 195, pp. 2407-2411.
- Devrimci, H. A., Yuksel, A. & Sanin, F. D., 2012. Algal alginate: a potential coagulant for drinking water treatment. *Desalination*, Volume 299, pp. 16-21.
- Deshmukh, B. S., Pimpalkar, S. N., Rakhunde, R. M. & Joshi, V. A., 2013. Evaluation Performance of Natural Strychnos Potatorum over the Synthetic Coagulant Alum, for the Treatment of Turbid Water. *International Journal of Innovative Research in Science, Engineering and Technology*, 2(11), pp. 6183 - 6189.
- Desta, M. B., 2013. Batch Sorption Experiments: Langmuir and Freundlich Isotherm Studies for the Adsorption of Textile Metal Ions onto Teff Straw (Eragrostis tef ) Agricultural Waste. *Journal of Thermodynamics*, Volume 2013, pp. 1-6.
- Dohare, D. & Meshram, R., 2014. Biological Treatment of Edible Oil Refinery Wastewater using Activated Sludge Process and Sequencing Batch Reactors - A Review. *International Journal Of Engineering Sciences & Research Technology*, 3(12), pp. 251-260.
- Farajnezhad, H. & Gharbani, P., 2012. Coagulation treatment of wastewater in petroleum industry using poly aluminium chloride and ferric chloride.

*International Journal of Research and Reviews in Applied Sciences*, 113(1), pp. 306-310.

Farhan, A. M., Salem, N. M., Al-Dujaili, A. H. & Awwad, A. M., 2012. Biosorption Studies of Cr(VI) Ions from Electroplating. *American Journal of Environmental Engineering*, 2(6), pp. 188-195.

Fattah , A. & Azhar, A., 2014. *Treatment of Automotive Wastewater by Coagulation-Flocculation Using Poly-aluminum Chloride (PAC), Ferric Chloride (FeCl<sub>3</sub>) and Aluminum Sulfate (alum)*. UKM, AIP Publishing.

Fatehah , O. M., Hossain, S. & Teng, T. T., 2013. Semiconductor wastewater treatment using tapioca starch as a natural coagulant. *Journal of Water Resource and Protection* , Volume 5, pp. 1018-1026.

Gao, B. et al., 2007. Color removal from simulated dye water and actual textile wastewater using a composite coagulant prepared by polyferric chloride and polydimethyldiallylammonium chloride. *Sep. Purif. Technology*, Volume 54, pp. 157-163.

Ha, B. M. & Huong, D. T. G., 2017. Coagulation In Treatment Of Swine Slaughterhouse Wastewater. *GeoScience Engineering*, 63(1), pp. 15 - 21.

Hamid, S. H., Lananan, F., Din, W. N. S. & Su, . S. L., 2014. Harvesting microalgae, *Chlorella* sp. by bio-flocculation of *Moringa oleifera* seed derivatives from aquaculture wastewater phytoremediation. *International Biodeterioration & Biodegradation*, pp. 270-275.

Hamadani, Y. A., Yusoff, M. S., Umar, M. & Bashir, M. J., 2011. Application of psyllium husk as coagulant and coagulant aid in semi-aerobic landfill leachate treatment. *Journal of Hazardous Materials*, Volume 190, pp. 582-587.

Hamawand , I. et al., 2017. A Critical Review on Processes and Energy Profile of the Australian Meat Processing Industry. *Energies*, 10(731), pp. 1-29.

Hassan, M., Vivek, S. & Unnisa, S. A., 2012. Purification of turbid water with *Pisum Sativum* seeds and solar energy. *International Journal of Green and Herbal Chemistry*, 1(3), pp. 296-301.

Hosny, R. et al., 2016. Treatment of the oily produced water (OPW) using coagulant mixtures. *Egyptian Journal of Petroleum*, Volume 25, pp. 391 - 396

Kan, C., Huang, C. & Pan , J., 2002. Coagulation of high turbidity water: the effects of rapid mixing. *Journal of Water Supply: Research and Technology*, 51(2), pp. 77 - 85.

- Kokila, A., Prajapati, S., Patel, R. & Dabhi, Y., 2011. Effective use of Ferrous sulphate and alum as coagulant in treatment of dairy industry wastewater. *ARPN Journal of Engineering and Applied Science*, 6(9), pp. 42 - 45.
- Kyzas, G. Z. & Kostoglou, M., 2014. Green adsorbents for wastewater: A critical review. *Materials*, Volume 7, pp. 333-364.
- Kumar, J., Poongodi, P., Jayakumar, J. & Raj, K., 2014. Modelling and development of laboratory based portable water treatment plant. *Journal of Chemical and Pharmaceutical Research*, 6(2), pp. 410-415.
- Kumar, P. S., Vaibhav, K., Rekhi, S. & Thyagarajan, A., 2016. Removal of turbidity from washing machine discharge using *Strychnos potatorum* seeds: Parameter optimization and mechanism prediction. *Resource-Efficient Technologies*, Volume 2, pp. 171-176.
- Kushwaha, J., Chandra, S. V. & Mall, I., 2010. Treatment of dairy wastewater by inorganic coagulants: Parametric and disposal studies. *Water Resource*, Volume 44, pp. 5867-5874.
- Langmuir I. (1918). *J. Am. Chem. Soc.* 40: 1362.
- Lee, C.C. and Lin, S.D. 2000. *Handbook of environmental engineering calculations*, McGraw-Hill Professional.
- Mishra, A. et al., 2002. Plantago Psyllium Mucilage for Sewage and Tannery Effluent Treatment. *Iranian Polymer Journal*, 11(6), pp. 381-386.
- Miller, S., J.Fugate, E., Craver, V. O. & B.Zimmerman, J., 2008. Toward understanding the efficacy and mechanism of *Opuntia* spp. as a natural coagulant for potential application in water treatment. *Environmental Science & Technology*, Volume 42, pp. 4272-4279.
- Matouq, M., Jildeh, N., Qtaishat, M. & Hindayeh, M., 2015. The adsorption kinetics and modeling for heavy metals removal from wastewater by *Moringa* pods. *Journal of Environmental Chemical Engineering*, 3(2), p. 775-784.
- Mittal, A., 2006. Adsorption kinetics of removal of a toxic dye, Malachite Green, from wastewater by using hen feathers. *Journal of Hazardous Materials*, Volume 133, pp. 196-202.
- Muralimohan, N., Palanisamy, T. & Vimaladewi, M., 2014. Experimental study on removal efficiency of blended coagulants in textile wastewater treatment. *International Journal of Research in Engineering & Technology*, 2(2), pp. 15-20.
- Ng, W. J., 2005. *Industrial Wastewater Treatment*. London: Imperial College Press.

- Nirmala , C. R. & Jadhav, M., 2012. Enhancing filtrate quality of turbid water incorporating seeds of *Strychnos Potatorum*, pads of cactus *Opuntia* and mucilage extracted from the fruits of *Coccinia indica* as coagulants. *Journal of Environmental Research And Development*, 7(2), pp. 668-674.
- Okolo, B. I., Menkiti , M. C., Nnaji, C. P. & Onukwuli, O. D., 2014. The performance of Okra seeds extract in removal of suspended particles from brewery effluent by coag-flocculation process. *British Journal of Applied Science and Technology*, 34(4), pp. 4791-4806.
- Ozer, A. & Pirincci, H., 2006. The adsorption of Cd(II) ions on sulphuric acid-treated wheat bran. *Journal of Hazardous Materials* , 137(2), pp. 849-855.
- Pitakpoolsil, W. & Hunson, M., 2013. Adsorption of pollutants from biodiesel wastewater using chitosan flakes. *Journal of the Taiwan Institute of Chemical Engineers*, Volume 44, pp. 963-971.
- Pallavi, N. & Mahesh , S., 2013. Feasibility Study of *Moringa Oleifera* as a Natural Coagulant for the Treatment of Dairy Wastewater. *International Journal of Engineering Research*, 2(3), pp. 200-202.
- Prakash, N. B., Sockan, V. & Jayakaran, P., 2014. Waste Water Treatment by Coagulation and Flocculation. *International Journal of Engineering Science and Innovative Technology*, 3(2), pp. 479 - 484.
- Rahman, U., Sahar, A. & Khan, M. A., 2014. Recovery and utilization of effluents from meat processing industries. *Food Research International*, Issue 65, p. 322–328.
- Rani , C. N. & Jadhav , M. V., 2012. Enhancing Filtrate Quality Of Turbid Water Incorporating Seeds Of *Strychnos Potatorum*, Pads Of Cactus *Opuntia* And Mucilage Extracted From The Fruits Of *Coccinia Indica* As Coagulants. *Journal of Environmental Research And Development* , 7(2), pp. 668-674.
- Ramavandi, B., 2014. Treatment of water turbidity and bacteria by using coagulant extracted from *Plantago Ovata*. *Water Resources and Industry*, Volume 6, pp. 36-50.
- Renault, F., Sancey, B., Badot, P. & Crini, G., 2009. Chitosan for coagulation/flocculation process-An economical approach. *European Polymer Journal*, 45(5), pp. 1337-1348.
- Syafalni, Abdullah, R., Abustan , I. & Ibrahim, A. N., 2013. Wastewater treatment using bentonite, the combinations of bentonitezeolite, zeolite, bentonite-alum, and bentonite-limestone as adsorbent and coagulant. *International Journal Of Environmental Sciences*, 4(3), pp. 379 -391.

- Saritha, V., Srinivas, N. & Vuppala, N. S., 2017. Analysis and optimization of coagulation and flocculation process. *Applied Water Science*, 7(1), pp. 451 - 460.
- Sarkar, B., Chakrabarti, P. & Kale, V., 2006. Wastewater treatment in dairy industries - possibility of reuse. *Desalination*, Volume 195, pp. 141-152.
- Sroka, E., Kaminski, W. & Bohdziewicz, J., 2004. Biological treatment of meat industry wastewater. *Desalination*, Volume 162, pp. 85-91.
- Salh, D. M., Aziz, B. K. & Faraidoon, K., 2015. Adsorbition of Crystal Violet on Walnut Shell from Aqueous Solution. *International Journal of Basis & Applied Science*, 15(4), pp. 4-7.
- Sena, R. F. d., Moreira, . R. F. & José, H. J., 2008. Comparison of coagulants and coagulation aids for treatment of meat processing wastewater by column flotation. *Bioresource Technology*, p. 8221–8225.
- Sheng, W., Peng, X., Lee, D. & Su, A., 2006. Coagulation of particles through rapid mixing. *Drying Technology*, Volume 24, pp. 1271-1276.
- Thirugnanasambandham, K., Sivakumar, V. & Maran, J. P., 2015. Response surface modelling and optimization of treatment of meat industry wastewater using electrochemical treatment method. *Journal of the Taiwan Institute of Chemical Engineers*, Issue 46 , p. 160–167.
- Tansengco, M. et al., 2015. Biological Treatment of Meat Processing Wastewater using Anaerobic Sequencing Batch Reactor (ASBR). *International Research Journal of Biological Sciences*, 4(3), pp. 66-75.
- Tatsi, A., Zouboulis, A., Matis, K. & Samaras, P., 2003. Coagulation-Flocculation Pretreatment of Sanitary Landfill Leachates. *Chemosphere*, 53(7), pp. 737-744.
- Vafajoo, L., Ghanaat, F. & Ghalebi, A., 2014. An Investigation of a Petrochemical Wastewater Treatment utilizing GAC: A Study of Adsorption Kinetics. *APCBEE Procedia 10*, pp. 131-135.
- Vandamme, D., Foubert, I., Meesschaert, B. & Muylaert, K., 2010. Flocculation of microalgae using cationic starch. *J Appl Phycol*, Issue 22, p. 525–530.
- Vandamme, D., Imogen, . F. & Koenraad , M., 2013. Flocculation as a low-cost method for harvesting microalgae for bulk biomass production. *Trends in Biotechnology*, 4(31), pp. 233-239.
- Vieira, A. M. S., Vieira, M. F., Silva, G. F. & Aroujo, A. A., 2010. Use of Moringa Oleifera Seed as a Natural Adsorbent for Wastewater Treatment. *Water Air Soil Pollution*, Issue 206, pp. 273 - 281.

- Vijayaraghavan, G., Sivakumar, T. & Kumar, A. V., 2011. Application Of Plant Based Coagulants For Waste Water Treatment. *International Journal of Advanced Engineering Research and Studies*, 1(1), pp. 88-92.
- Vanerkara, A., Satyanarayan, S. & Satyanarayan, S., 2013. Treatment of Food Processing Industry Wastewater by a Coagulation/ Flocculation Process. *International Journal of Chemical and Physical Sciences*, Volume 2, pp. 63 - 72.
- Vishali, S. & Karthikeyan, R., 2014. A Comparative Study of Strychnos potatorum and Chemical Coagulants in the Treatment of Paint and Industrial Effluents: An Alternate Solution. *Separation Science and Technology*, Volume 49, pp. 2510-2517.
- Vikashni , N., Matakite, . M., Kanayathu, K. & Subramaniam, S., 2012. Water Purification using Moringa oleifera and Other Locally Available Seeds in Fiji Water Purification using Moringa oleifera and Other Locally Available Seeds in Fiji. *International Journal of Applied Science and Technology*, 2(5), pp. 125-129.
- Wang , J., Chen, Y., Ge, X. & Yu, H., 2007. "Optimization of Coagulation-Flocculation Process for a Paper-Recycling Wastewater Treatment Using Response Surface Methodology. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 302(1), pp. 204-210.
- Yadav, K. N., Kadam , P. V., Patel, J. A. & Patil, M. J., 2014. Strychnos potatorum: Phytochemical and pharmacological review. *Pharmacognosy Review*, 8(15), pp. 61-68.
- Yin, C. Y., 2010. Emerging usage of plant-based coagulants for water and wastewater treatment. *Process Biochemistry*, Volume 45, pp. 1437-1444.

