


PROPERTIES AND ENVIRONMENTAL IMPACT FROM MOSAIC SLUDGE  
INDUSTRY INCORPORATED INTO FIRED CLAY BRICKS

AHMAD SHAYUTI BIN ABDUL RAHIM



Faculty of Civil and Environmental Engineering  
Universiti Tun Hussein Onn Malaysia

FEBRUARY 2016

*To my loving family and friends  
My love to you all will always remain...*



## ACKNOWLEDGEMENT

بِسْمِ اللَّهِ الرَّحْمَنِ الرَّحِيمِ

Praised to Allah S.W.T, the Most Gracious and Most Merciful who has created the mankind with knowledge, wisdom and power. Thank to Allah S.W.T because I finally accomplish my research for Master Degree in Civil Engineering at University of Tun Hussein Onn Malaysia.

Special thanks to my supervisor Associate Professor Dr Aeslina Abdul Kadir for her guidance, support and encouragement during my research study.

I would like to thank and express my greatest appreciation to my parent, Abdul Rahim Abdullah and Saleha Razali who never give up on giving me support, their prayers and always understanding my study.

I also acknowledge to Biasiswa Kerajaan Negeri Sabah for the scholarship and financial support. Not to forget, Hap Seng Consolidated Berhad for the facilities and assistance to accomplish this research.

Besides, I would like to extend our heartiest thanks to all the lectures, technicians and friends, who have been supportive and help me to finish my research. At last but not least gratitude goes to all who directly or indirectly helped me to complete this research. May all the good deeds that were done will be blessed by Allah. Wassalam

## ABSTRACT

Brick is one of the most common masonry units used as building material. Due to the demand recently, different types of waste materials have been investigated to be incorporated into bricks. The utilization of these waste materials in fired clay bricks usually has positive effects on the properties such as lightweight bricks with improved shrinkage, porosity, and strength. The main objective of this study is to focus on the properties and environmental impact of the mosaic sludge incorporated into fired clay bricks. The characteristics of raw materials obtained by using the X-Ray Fluorescence Spectrometer showed that the chemical composition of the raw materials of clay soil and mosaic sludge was high with silicon dioxide and aluminium oxide and with the same chemical composition BS and PS are suitable to replace clay soil as raw materials. The recommended percentage of BS and PS incorporation was up to 30% with better physical and mechanical properties. The results showed that the utilization of BS and PS brick obtained higher compressive strength up to  $25 \text{ N/mm}^2$  and low initial rate of suction under the limit of  $5 \text{ g/mm}^2$ . The leachability tests such as Toxicity Characteristic Leaching Procedure (TCLP), Synthetic Precipitation Leaching Procedure (SPLP) and Static Leachate Procedure (SLT) were conducted to determine the results which complied with the United State Environment Protection Agency (USEPA) and Environment Protection Agency Victoria (EPAV). As for the indoor air quality, BS sludge and PS sludge could be incorporated up to 30% in the fired clay bricks for good physical and mechanical properties that complied standard requirements for heavy metals with better indoor air quality based on the Industry Codes of Practice on Indoor Air Quality (ICOP-IAQ) standards. Therefore, BS and PS wastes can be an alternative low cost material that provides an environmentally friendly disposal method.

## ABSTRAK

Bata merupakan satu unit masonri yang biasa digunakan sebagai bahan binaan. Berdasarkan permintaan, beberapa jenis sisa yang berbeza telah dikaji dan dimasukkan ke dalam batu bata. Penggunaan sisa ini di dalam bata tanah liat kebiasaannya mempunyai kesan yang positif terhadap sifatnya seperti batu-bata ringan yang diperbaik dari segi penyusutan, keliangan, dan kekuatan. Objektif utama kajian ini untuk memfokuskan ciri-ciri dan kesan terhadap alam sekitar dengan menggunakan sisa *Bodymill Sludge* (BS) dan *Polishing Sludge* (PS) ke dalam bata tanah liat. Ciri-ciri yang telah diperoleh dengan menggunakan Spektrometer Pendarfluor Sinar-X (XRF) menunjukkan komposisi kimia bahan mentah daripada tanah liat dan enap cemar mozek mengandungi silikon dioksida dan aluminium oksida yang tinggi dengan komposisi ciri yang sama BS dan PS sesuai menggantikan tanah liat sebagai bahan mentah. Peratusan PS dan BS yang disyorkan sehingga 30% dengan sifat fizikal dan mekanikal yang lebih baik. Penggunaan enap cemar sepenuhnya daripada bata BS dan PS memperolehi kekuatan mampatan yang paling tinggi dengan  $25 \text{ N/mm}^2$  dan kadar awal ujian sedutan dibawah had  $5 \text{ g/mm}^2$ . Semua ujian pengurasan untuk Prosedur Pengurasan Ciri Ketoksiakan (TCLP), Prosedur Pengurasan Hujan Tiruan (SPLP) dan Ujian Pengurasan Statik (SLT) ditentukan dan secara amnya mematuhi Agensi Perlindungan Alam Sekitar Amerika Syarikat (USEPA) dan Agensi Perlindungan Alam Sekitar Victoria (EPAV). Sementara itu kualiti udara dalaman, enapcemar BS dan enapcemar PS boleh digunakan sehingga 30% di dalam bata tanah liat kerana sifat fizikal dan mekanikal yang baik yang mematuhi piawaian bagi logam berat dan dengan kualiti udara dalaman yang lebih baik berdasarkan piawaian Kod Amalan Industri Kualiti Udara Dalaman (ICOP-IAQ). Oleh itu, enap cemar BS dan enap cemar PS boleh menjadi alternatif sebagai bahan berkos rendah dalam menyediakan kaedah pelupusan yang mesra alam sekitar.

## CONTENTS

<b>TITLE</b>	i
<b>DECLARATION</b>	ii
<b>DEDICATED</b>	iii
<b>ACKNOWLEDGEMENT</b>	iv
<b>ABSTRACT</b>	v
<b>ABSTRAK</b>	vi
<b>CONTENTS</b>	vii
<b>LIST OF TABLES</b>	xiii
<b>LIST OF FIGURES</b>	xv
<b>LIST OF SYMBOL AND ABBREVIATIONS</b>	xxi
<b>LIST OF APPENDICES</b>	xxvi
<b>INTRODUCTION</b>	
1.1    Background Study	1
1.2    Problem statement	3
1.3    Objective	4
1.4    Scope of work	4



<b>CHAPTER 2</b>	<b>LITERATURE REVIEW</b>	
2.1	Introduction	5
2.2	Mosaic	5
2.2.1	Mosaic manufacturing	6
2.2.2	Types of mosaic	7
2.2.2.1	Ceramic	7
2.2.2.2	Vitreous glass	8
2.2.2.3	Smalti glass	8
2.2.2.4	Organic tiles	8
2.3	Mosaic sludge	8
2.3.1	Bodymill sludge	9
2.3.2	Polishing sludge	9
2.4	Fired clay brick	10
2.4.1	Raw material	10
2.4.2	Fired clay brick manufacturing process	11
2.4.2.1	Mining, storage and clay preparation	12
2.4.2.2	Forming and cutting	12
2.4.2.3	Drying	13
2.4.2.4	Firing	13
2.4.3	Types of brick	13
2.4.3.1	Common brick	14
2.4.3.2	Face brick	14
2.4.3.3	Engineering brick	14
2.4.3.4	Firebricks	14
2.4.3.5	Sand-lime brick	15
2.4.3.6	Concrete brick	15
2.4.4	Properties of fired clay brick	15
2.4.4.1	Density	15
2.4.4.2	Compressive strength	15

2.4.4.3 Initial rate of suction	16
2.4.4.4 Firing shrinkage	17
2.4.5 Leachability	17
2.4.5.1 Impact of heavy metals towards the environment and human health	18
2.4.5.1.1 Arsenic (As)	19
2.4.5.1.2 Barium (Ba)	19
2.4.5.1.3 Cadmium (Cd)	19
2.4.5.1.4 Chromium (Cr)	20
2.4.5.1.5 Lead (Pb)	20
2.4.5.1.6 Mercury (Hg)	20
2.4.6 Indoor Air Quality	21
2.4.6.1 Impact of gas emissions towards the environment and human health	22
2.4.6.1.1 Total volatile organic compounds (TVOC)	23
2.4.6.1.2 Carbon dioxide (CO <sub>2</sub> )	23
2.4.6.1.3 Carbon monoxide (CO)	23
2.4.6.1.4 Ozone (O <sub>3</sub> )	23
2.4.6.1.5 Formaldehyde (HCHO)	24
2.4.6.1.6 Particulate matter (PM <sub>10</sub> )	24
2.4.7 Overview of sludge waste incorporated in fired clay brick	24
2.4.7.1 Textile sludge	25
2.4.7.2 Water treatment sludge	25
2.4.7.3 Sewage sludge	27
2.4.7.4 Other sludge waste	30
2.4.8 Summary and research gap	37
<b>CHAPTER 3</b>	<b>METHODOLOGY</b>
3.1 Introduction	40
3.2 Stage I :Raw materials	43

3.2.1	Collection	43
3.2.1.1	Mosaic sludge and clay collection	43
3.2.2	Preparation	44
3.2.2.1	Preparation of mosaic and clay soil	44
3.2.3	Characterization of raw materials	45
3.2.3.1	Chemical composition and heavy metal concentration	45
3.2.3.2	The procedure of making pellet and XRF analysis	46
3.2.4	Classification	47
3.2.4.1	Compaction test	47
3.2.4.2	Atterberg limit	50
3.2.4.3	Specific gravity	53
3.3	Stage II : Brick manufacturing	55
3.3.1	Control brick	55
3.3.2	Mosaic sludge brick	55
3.4	Stage III: Physical and mechanical tests	57
3.4.1	Firing shrinkage	57
3.4.2	Density	58
3.4.3	Compressive strength	59
3.4.4	Initial rate of suction	60
3.4.5	Microstructure characteristics	61
3.4.6	Surface area characterization	62
3.5	Stage IV: Leachability	62
3.5.1	Toxicity Characteristic Leaching Procedure (TCLP)	62
3.5.2	Synthetic Precipitation Leaching Procedure (SPLP)	64
3.5.3	Static Leachate Test (SLT)	65
3.6	Stage V: Indoor air quality	66

3.6.1	Indoor air quality	66
3.6.2	Walk in stability chamber (WiSC)	68
3.6.3	Experimental procedure	68
3.6.4	Measurement of instrument	71
3.6.4.1	Indoor air quality monitor (IAQ monitor)	71
3.6.4.2	Toxicity gas test instrument Graywolf	72
3.6.4.3	Formaldemeter <i>htV</i>	73
3.6.4.4	Aeroqual series 500	73
3.6.4.5	DustTrak aerosol monitor	74
<b>CHAPTER 4</b>	<b>RESULT AND DISCUSSION</b>	
4.1	Introduction	75
4.2	Stage I : Raw Material	75
4.2.1	Characteristic of clay soil and mosaic sludge wastes	75
4.2.2	Chemical properties of clay soil and mosaic sludge	76
4.2.2.1	Chemical composition and concentration analysis	76
4.2.3	Soil classification	79
4.2.3.1	Compaction test	79
4.2.3.2	Atterberg limit	80
4.3	Stage III : Physical and mechanical properties	81
4.3.1	Firing shrinkage	81
4.3.2	Density	83
4.3.3	Compressive strength	84
4.3.4	Initial rate of suction	86
4.3.5	Microstructure analysis	88
4.3.6	Summary of physical and mechanical properties	92

**CHAPTER 5**

4.4	Stage IV : Leachability	94
4.4.1	Toxicity Characteristic Leaching Procedure (TCLP)	95
4.4.2	Synthetic Precipitation Leaching Procedure (SPLP)	98
4.4.3	Static leachate test (SLT)	101
4.4.4	Summary of TCLP, SPLP and SLT	112
4.5	Stage V: Indoor air quality	115
4.5.1	Total volatile organic compound (TVOC)	117
4.5.2	Carbon dioxide (CO <sub>2</sub> )	119
4.5.3	Carbon monoxide (CO)	121
4.5.4	Ozone (O <sub>3</sub> )	123
4.5.5	Formaldehyde (HCHO)	125
4.5.5	Particulate matter (PM <sub>10</sub> )	127
4.5.7	Summary of indoor air quality (IAQ)	129
<b>CONCLUSION</b>		
5.1	Introduction	131
5.2	Conclusion	132
5.3	Recommendation for future research	134
<b>REFERENCES</b>		
<b>APPENDICES</b>		
		135
		150

## LIST OF TABLES

2.1	Sizes of bricks (BS 3291:1985)	13
2.2	Compressive strength (BS 3921:1985)	16
2.3	Water absorption / initial rate of suction (BS 3921:1985)	17
2.4	Maximum concentration of contaminants for the toxicity characteristic (Environmental Protection Agency, 2009)	18
2.5	Acceptable range of specific physical parameters (ICOP-IAQ, 2010)	21
2.6	List of indoor air contaminants and the acceptable limits (ICOP-IAQ, 2010)	22
2.7	Overview of physical and mechanical of sludge waste incorporated with clay bricks	33
2.8	Overview of leachability of sludge waste incorporated with clay bricks	36
3.1	Classification of soil according to plasticity (BS 1377:1990)	53
3.2	Ratio mixture	55
3.3	Specification of WiSC size	68
4.1	Composition of heavy metals	77

4.2	Concentration of heavy metals	78
4.3	Percentages of water content	80
4.4	Classification of soil	80
4.5	Firing shrinkage for BS and PS brick	81
4.6	Density of BS and PS brick	83
4.7	Compressive strength of BS and PS brick	85
4.8	Initial rate of suction for BS and PS brick	87
4.9	Heavy metals leachability concentration by using TCLP	96
4.10	Heavy metals leachability concentration by using SPLP	99
4.11	Summary of indoor air quality data	116
4.12	Emissions of total volatile organic compound (TVOC)	117
4.13	Emissions of carbon dioxide ( $\text{CO}_2$ )	119
4.14	Emissions of carbon monoxide (CO)	121
4.15	Emissions of ozone ( $\text{O}_3$ )	123
4.16	Emissions of formaldehyde (HCHO)	125
4.17	Emissions of particular matter ( $\text{PM}_{10}$ )	127

## LIST OF FIGURES

2.1	Mosaic manufacturing process (Admeg, 2015)	7
2.2	Bodymill process	9
2.3	Polishing process	10
2.4	Brick manufacturing process (Bender <i>et al</i> , 2011)	11
3.1	Flowchart in this study	41
3.2a	Mosaic sludge location	43
3.2b	Mosaic sludge main building	43
3.2c	Sludge was collected	44
3.3	Clay soil factory	44
3.4	S4- Pioneer Brunker- AXS, Germany	45
3.5a	Set of apparatus	46
3.5b	Electronic weight scale	46
3.5c	Preparation of the samples	47
3.5d	Steel pellet	47
3.5e	Compactor	47

3.5f	Pellet was put inside the incubator	47
3.6	Compaction test apparatus	49
3.7	Process of compaction test	49
3.8a	Sieved soil	51
3.8b	Soil mixed with distilled water	51
3.8c	Mixed soil in cup	51
3.8d	Smooth soil surface	51
3.8e	Cone penetration test	51
3.8f	Samples on petri dish	51
3.9a	Soil sample on glass plate	52
3.9b	Divided sample	52
3.9c	Threads sample	52
3.9d	Samples on petri dish	52
3.10a	Pyknometer	54
3.10b	Filled with distilled water	54
3.10c	Vacuum desiccator	54
3.10d	Samples weigh	54
3.11a	Sieved clay soil	56
3.11b	Clay soil with sludge mixture	56
3.11c	Mixed clay soil	56
3.11d	Layering clay soil in mould	56

3.11e	Brick compaction	56
3.11f	Dried bricks	56
3.12	Length measurement of brick	57
3.13	Brick measurement	58
3.14	Compressive strength test	59
3.15	Initial rate of suction test	61
3.16	SEM machine at Analytical Environment laboratory (ZEISS EVO LS10, Germany)	61
3.17	Brunauer Emmett Teller (BET) Machine (Micrometric ASAP 2020, USA)	62
3.18a	Samples were crushed and sifted through 9.5mm sieve	63
3.18b	Samples were placed in a rotary extractor at 30rpm	63
3.18c	Sample filtration with $0.7\mu\text{m}$ of glass microfiber filter	63
3.18d	Heavy metals analysis	63
3.19	Summary procedure of TCLP test	64
3.20	SLT set-up diagram	65
3.21	Cube form	66
3.22	Wall form	67
3.23	Column form	67
3.24	Walk in stability chamber	68
3.25	Cube form arrangement	69

3.26	Wall form arrangement	70
3.27	Column form arrangement	70
3.28	Equipments used for IAQ	71
3.29	IAQ detector	72
3.30	Toxic gas detector	72
3.31	Formaldemeter <i>htV</i> device	73
3.32	Aeroqual	74
3.33	DustTrak aerosol	74
4.1	Optimum moisture content	79
4.2	Shrinkage between different percentages of BS brick	81
4.3	Shrinkage between different percentages of PS brick	82
4.4	Density between different percentages of BS brick	84
4.5	Density between different percentages of PS brick	84
4.6	Compressive strength between different percentages of BS brick	86
4.7	Compressive strength between different percentages of PS brick	86
4.8	Initial rate of suction between different percentages of BS brick	88
4.9	Initial rate of suction between different percentages of PS brick	88
4.10a	Control brick	89
4.10b	BS brick (1%)	89

4.10c	BS brick (5%)	89
4.10d	BS brick (10%)	89
4.10e	BS brick (20%)	89
4.10f	BS brick (30%)	89
4.10g	PS brick (1%)	90
4.10h	PS brick (5%)	90
4.10i	PS brick (10%)	90
4.10j	PS brick (20%)	90
4.10k	PS brick (30%)	90
4.11	Heavy metals concentration in BS brick by using TCLP	97
4.12	Heavy metals concentration in PS brick by using TCLP	97
4.13	Heavy metals concentration in BS brick by using SPLP	100
4.14	Heavy metals concentration in PS brick by using SPLP	100
4.15	Heavy metals concentration for control brick	102
4.16	Heavy metals concentration of BS brick (1%)	103
4.17	Heavy metals concentration of BS brick (5%)	104
4.18	Heavy metals concentration of BS brick (10%)	105
4.19	Heavy metals concentration of BS brick (20%)	106
4.20	Heavy metals concentration of BS brick (30%)	107
4.21	Heavy metals concentration of PS brick (1%)	108
4.22	Heavy metals concentration of PS brick (5%)	109

4.23	Heavy metals concentration of PS brick (10%)	110
4.24	Heavy metals concentration of PS brick (20%)	111
4.25	Heavy metals concentration of PS brick (30%)	112
4.26	Total Volatile Organic Compound (TVOC) emissions from different types of sludge bricks	118
4.27	Carbon dioxide ( $\text{CO}_2$ ) emissions from different types of fired clay bricks	120
4.28	Carbon monoxide (CO) emissions from different types of fired clay bricks	122
4.29	Ozone ( $\text{O}_3$ ) emissions from different types of fired clay bricks	124
4.30	Formaldehyde (HCHO) emissions of different types of fired clay bricks	126
4.31	Particulate Matter ( $\text{PM}_{10}$ ) emissions from different types of fired clay bricks	128



PTI AUTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

A large, semi-transparent watermark is positioned diagonally across the page. The text "PTI AUTHM" is at the top, followed by "PERPUSTAKAAN TUNKU TUN AMINAH" below it. Both parts of the watermark are written in a light purple or grey color.

## LIST OF SYMBOLS AND ABBREVIATIONS

%	- Percent
$\leq$	- Less-than or Equal to
$\geq$	- Greater-than or Equal to
$^{\circ}\text{C}$	- Degree Celsius
$^{\circ}\text{C}/\text{min}$	- Degree Celsius per minute
$\mu$	- micro
$\mu\text{m}$	- Micro meter
A	- Area
AAS	- Atomic Absorption Spectroscopy
Al	- Aluminium
$\text{Al}_2\text{O}_3$	- Aluminum oxide
As	- Arsenic
Ba	- Barium
BS	- Bodymill Sludge
C	- Ceiling limit
CaO	- Calcium oxide
Cd	- Cadmium
Ce	- Cerium
$\text{Cfu}/\text{m}^3$	- Colony Forming Unit per Cubic Meter

$\text{cm}^3$	- Cubic centimeter
CO	- Carbon Monoxide
Co	- Cobalt
$\text{CO}_2$	- Carbon Dioxide
Cr	- Chromium
Cs	- Cesium
Cu	- Copper
$\text{CuO}$	- Copper(II) oxide
D	- Diameter
EN	- European Standard
EPA	- Environmental Protection Agency
EPAV	- Environmental Protection Agency Victoria
ER	- Empty Room
et al	- And others
Fe	- Ferum
$\text{Fe}_2\text{O}_3$	- Ferric oxide
FKAAS	- Fakulti Kejuruteraan awam dan alam sekitar
g	- Gram
$\text{g}/\text{cm}^3$	- Gram per cubic meter
Ga	- Gallium
HCHO	- Formaldehyde
IAQ	- Indoor Air Quality
ICOP-IAQ	- Industry Code of Practice on Indoor Air Quality
ISO	- International Organization for Standardization
$\text{K}_2\text{O}$	- Potassium oxide
kg	- Kilogram
$\text{kg}/\text{m}^3$	- Kilogram per cubic meter

kN	- Kilo newton
L	- Length
L/min	- Liter per minute
La	- Lanthanum
LL	- Liquid Limit
LLD	- Lower Level Detection
LOI	- Loss on Ignition
Ls	- Actual Length – Dry Length
$L_{wet}$	- Wet Length
$L_{dry}$	- Dry Length
M	- mass
M1	- Dry Mass
m1	- Mass of wet brick
M2	- Wet Mass
m2	- Submerged mass of brick
mg/L	- Milligram per litre
mg/m <sup>3</sup>	- Milligram per cubic meter
MgO	- Magnesium oxide
mm	- milimeter
MMB	- Malaysia Mosaic Berhad
Mn	- Mangan
MnO	- Manganese(II) oxide
mo	- Ambient mass
Mo	- Molybderium
MPa	- Megapascal
N/mm <sup>2</sup>	- Newton per millimeter square
NA	- Not Available

Na <sub>2</sub> O	- Sodium oxide
Nb	- Niobium
ND	- Not Detectable
Ni	- Nickel
O <sup>3</sup>	- Ozone
OMC	- Optimum Moisture Content
P <sub>2</sub> O <sub>5</sub>	- Phosphorus pentoxid
Pb	- Lead
PI	- Plasticity Index
PL	- Plastic Limit
PM10	- Particulate Matter
ppm	- part per million
PS	- Polishing Sludge
psi	- Pounds per square inch
Rb	- Rubidium
RECESS	- Research Centre for Soft Soil
RH	- Relative humidity
Sb	- Antimony
Sc	- Scandium
SEM	- Scanning Electron Microscope
SiO <sub>2</sub>	- Silicon dioxide
SLT	- Static Leachate Test
Sn	- Tin
SO <sub>3</sub>	- Sulphur trioxide
SPLP	- Synthetic Precipitation Leaching Procedure
Sr	- Strontium
SrO	- Strontium oxide

TCLP	- Toxicity Characteristic Leaching Procedure
TEL	- Thermal Environmental Laboratory
Th	- Thorium
Ti	- Thallium
TiO <sub>2</sub>	- Titanium dioxide
TVOC	- Total volatile organic compounds
twa	- time-weighted average
U	- Uranium
USEPA	- Unites States Environmental Protection Agency
UTHM	- Universiti Tun Hussein Onn Malaysia
V	- Vanadium
VOCs	- Volatile organic compound
WHO	- World Health Organization
WiSC	- Walk in Stability Chamber
wt.	- Weight
XRF	- X-Ray Fluorescence
Y	- Yttrium
Zn	- Zinc
ZnO	- Zinc oxide
Zr	- Zirconium
ZrO <sub>2</sub>	- Zirconium dioxide
$\Delta T$	- temperature gradient
$\rho$	- Density
$\pi$	- Pi

## REFERENCES

- Abdul Kadir, A. & Abbas Mohajerani. Bricks: An excellent building material for recycling wastes. *Proceedings of the Lasted International Conference Environmental Management and Engineering (EME 2011)*, July 4-6, Calgary, AB, Canada. 2011: pp. 108-115.
- Abdul Kadir, A. & Noor Amira Sarani. An overview of wastes recycling in fired clay bricks. *International Journal of Integrated Engineering*. 2012. 4(2):53-69.
- Abdul Latif, A. A. B. Ahmad Tarmizi Abd.Karim, Ahmad Shukri Ahmad, Mohd Baharudin Ridzuan and Yung-Tse Hung. Phytoremediation of Metals in Industrial Sludge by Cyperus Kyllingia-Rasiga, Asystassia Intrusa and Scindapsus Pictus Var Argyaeus Plant Species. *International Journal of Integrated Engineering*. 2012. 4(2) : 1-8.
- Advameg (2015). *How Products are Made Ceramic Tile*. Retrieved on May 27, 2015, from: <http://www.madehow.com/Volume-1/Ceramic-Tile.html>.
- Aeroqual (2014). *Gas Sensor Specification*. Retrieved on May 26, 2015. from: <http://www.aeroqual.com/wp-content/uploads/Aeroqual-Gas-Sensor-Specifications-V4.pdf>
- Agrawal, A., Loya, M. I. M., Rawani, A. M. An Empirical Study on Influence of Quality on Adoption of Fly Ash Bricks. *International proceedings of Economics Development and Research (IPEDR)*. 2014. vol. 75(8) : pp 33-35.
- Alleman, J. E. Beneficial use of sludge in building components, 1. Concept review and technical background. *Interbrick* 3. 1987. Vol. 2: 14-18.
- Alleman, J. E. Beneficial use of sludge in building components. 2. Full-scale production of sludge-amended bricks. *Interbrick* 5. 1989. Vol. 1: 28-32.

- Alonso, S. R., Coz, A., Viguri, J. R., Andres, A. Recycling of foundry by-product in the ceramic industry: Green and core sand in clay bricks. *Construction and building materials.* 2012. 27: 97-106.
- American National Standards Institution. *Measurement Of The Leachability Of Solidified Low-Level Radioactive Wastes By A Short-Term Test Procedure.* United State of America (USA). ANSI/ANS 16.1. 2003.
- Amrhein, J. E. *Reinforced Masonry Engineering Handbook: Clay and Concrete masonry.* 5<sup>th</sup> Edition. United states of America: CRC Press LLC. 1998.
- Anjum, N. A., Ahmad, I., Pereira, M. E., Duarte, A. C., Umar, S., Khan, N. A. *The Plant family Brassicaceae: Contribution Towards Phytoremediation: Volume 21.* New York, London: Springer. 2012.
- Arya, C. *Design of Structural Elements.* 2<sup>nd</sup> edition, Great Britain by Alden Press, Oxford. 1994.
- Asokan, P., Saxena, M., Asolekar, S. R. Hazardous Jarosite used in developing non-Hazardours for engineering application. *Journal of Hazardous Materials.* 2006. Vol 137 (3): 1589-1599.
- ASTM (American Society of Testing Materials), *ASTM C67 Standard Test Method for Sampling and Test Brick and Structural Clay Tile, Annual Book of ASTM Standards, Section 4, Construction, 04. 08, 04. 09, Soil and rock (I) and (II), ASTM, West Conshohocken, Pa, USA,* 1998.
- Azeez, O., Ogundare, O., Oshodin, T. E., Olasupo, O. A., Olunlade, B. A.. Evaluation of the Compressive Strength of Hybrid Clay Bricks. *Journal of Minerals & Materials Characterization & Engineering.* 2011. Vol 10 (7): 609-615.
- Azo Material. *Brick Walls and Brickwork – Vanadium Staining.* 2013. Retrieved on May 21, 2015. from : <http://www.azom.com/article.aspx?ArticleID=1399>.
- Babu R. G. & Ramana V. N. Durability of Bricks Cast with Industrial Sludge. *IOSR Journal of Machanical and Civil Engineering (IOSR-JMCE).* 2013. 6(4): 43-46.
- Baskar, R., Meera, S. B. K. M., Sundaram, S. Characterization and Reuse of Textile Effluent Treatment Plant Waste Sludge In Clay Bricks. *Journal of the University of Chemical Technology and Metallurgy.* 2006. vol. 41(4): 473-478.

- Bearg, D. W. *Indoor Air Quality and HVAC Systems*. United States of America: Lewis Publishers. 1993.
- Bender, Joel, Hadley, John, G., Hellerstein, Jon, P., Hohman, Charles, M. Glass, (2011). *Ceramics and Related Materials*. In Encyclopedia of Occupational Health and Safety. Retrieved on May 27, 2015. from : <http://www.iloencyclopaedia.org/part-xiii-12343/glass-pottery-and-related-materials/138-84-glass-pottery-and-related-materials/glass-ceramics-and-related-materials>.
- Bettelheim, F., Brown, W., Campbell, M., Farrell, S. *Introduction to General, Organic and Biochemistry*. 9<sup>th</sup> Edition . United State of America: Brooks/Cole Cangage Learning. 2000.
- Blythe, L. J. and Arniella, E. F. Leachate Tests for Solidified Hazardous Wastes. *Proceeding of the 1991 Georgia Water Conference*. The University Of Georgia, Athens, Gerogia. 1991. pp. 341-343.
- Boch, P. and Nipce, J. C. *Ceramic Materials Processes, Properties and Applications*. London: ISTE LTD. 2007
- Boesmans, B., Colon, F. J., Velden, V. D. J. H. Laterizi prodotti con argilla e rifiuti urbani. *Proc. 5th CERP Conference*. 1983. pp. 26-29.
- Brosnan, D. A. & Hochlretner, W. Additions of oxidized sewage sludge in brick manufacture as a means of revenue generation. *Journal of the Canadian Ceramic Society*. 1992. vol. 61(2), pp. 128-134.
- Branis, M., Hovorka, J., Smolik, J. & Lazaridis, M. The Effect of Outdoor Air and Indoor Human Activity on Particulate Matter Concentrations in a Experimental Flat. *Proceeding of Healthy Building*. Lisboa, 2005. vol 2, pp. 451-454.
- British Standard Institution. *Specification for Clay Bricks*. London, BS3921. 1985.
- British Standard Institution. *Proctor Test*. London, BS1377: Part 4. 1990.
- British Standard Institution. *Soil or Civil Engineering Purposes*. London, BS 1377: Part 2. 1990
- Brick Industry Association. *Manufacturing of brick* . Reston Virginia: Technical Notes. 2006. Retrieved on May 10, 2013. from: <http://www.gobrick.com/portals/25/docs/technical%20notes/tn9.pdf>
- Campbell, J. W. P. and Pryce. *Brick A World History*. Thames and Hudson: New York, NY. 2003.

- Carson (2014). *Brick houses- Solid Masonry VS. Brick Veneer*. Retrieved on May 27, 2015. from: <http://www.carsondunlop.com/resources/articles/brick-houses-solid-masonry-vs-brick-veneer/>
- Carter, C. B. and Norton, M. G. *Ceramic materials: Science and Engineering*. London: Springer Science business Media. 2013.
- Charles, R. S. *Bricklaying: A homeowner's illustrated Guide*, 1<sup>st</sup> edition, United States of America: McGraw-Hill Inc.1992.
- Churchill, M. Aspects of sewage sludge utilization and its impact on brick making. *Global Ceramic, Review*. 1994. Vol.1:18-21.
- Construction Industry Development Board Malaysia (CIDB), (2013). *List of Construction Materials Manufacturers 2013*. Retrieved on April 1, 2015. from: [https://www.cidb.gov.my/cidbv4/images/pdf/material/senarai\\_kilang\\_1.pdf](https://www.cidb.gov.my/cidbv4/images/pdf/material/senarai_kilang_1.pdf)
- Consumer Product Safety Commission. (2015). *United States Consumer Product Safety Commission-carbon Monoxide Information Centre*. Retrieved on May 20, 2015. from: <http://www.cpsc.gov/en/Safety-Education/Safety-Education-Centers/Carbon-Monoxide-Information-Center/20/5>
- Critical Environment. (2012). *Portable Indoor Air Quality Smart Sensor Specifications*. Retrieved on May 26, 2015. from: [http://www.critical-environment.com/media/Miscellaneous/1210-IAQ-Sensor-Specification\\_web.pdf](http://www.critical-environment.com/media/Miscellaneous/1210-IAQ-Sensor-Specification_web.pdf)
- Cusick, D. and Kirby, M. *The Michaels Book of Arts & Crafts*. New York: Sterling Publishing Co. Inc. 2003.
- Cultrone, G., Sebastian, E., Elert, K., Torre, M. J. D. L., Cazalla, O., Navarro, C. R. Influence of Mineralogy and Firing Temperature on Porosity of Bricks. *Journal of The European Ceramic Society*. 2004. Vol 24: 547-564.
- Darwish, L. *Earth repair: A grassroots guide to healing toxic and damaged landscapes*. Canada: New Society publishers. 2013.
- Department of Environment, Malaysia (2015). *Environmental Quality Act 1974. Environmental Quality (Scheduled Wastes) Regulations 2005*. Retrieved on May 25 2015. from: [http://www.env.go.jp/en/recycle/asian\\_net/Country\\_Information/Law\\_N\\_Regulation/Malaysia/Malaysia%20EQA%20Scheduled%20Waste%202005.pdf](http://www.env.go.jp/en/recycle/asian_net/Country_Information/Law_N_Regulation/Malaysia/Malaysia%20EQA%20Scheduled%20Waste%202005.pdf)

- Department of Environment, Malaysia (2014), *Malaysia Environmental Quality Report 2012*, Selangor Darul Ehsan: OMR Press Sdn. Bhd.
- Dikshith, T. S. S. *Safe Use of Chemicals: A Practical Guide*. United States of America: Taylor & francis group, LLC. 2009.
- Dikshith, T. S. S. *Handbook of Chemicals and Safety*. United States of America: Taylor & francis group, LLC. 2011.
- Dixon, C. J. *Atlas of Economic Mineral Deposits*. 7<sup>th</sup> Edition. London: Chapman and Hall. 2012.
- Dondi, M., Marsigli, M. & Fabbri, B.. Recycling of industrial and urban wastes in brik production- A review (Part 1). *Tile & Brick International*. 1997a. 13(3): 218-225.
- Duruibe, J. O., Ogwuegbu, M. O. C. and Egwurugwu, J. N. Heavy metal pollution and human biotoxic effects. *International Journal of Physical Sciences*. 2007. 2(5): 112-118.
- Environment Protection Agency (EPA). *Toxicity Concentration Leaching Procedure (TCLP)*. Method 1311. 1992. Retrieved on April 1 2014 from: <http://www.epa.gov/osw/hazard/testmethods/sw846/pdfs/1311.pdf>
- Environment Protection Agency (EPA). *Synthetic Precipitation Leaching Procedure (SPLP)*. Method 1312. 1994. Retrieved on April 1 2014 from: <http://www.epa.gov/osw/hazard/testmethods/sw846/pdfs/1312.pdf>
- Environment Protection Agency (EPA). 1997. Retrieved on May 23 2015 from: <http://www.epa.gov/ttnchie1/ap42/ch11/final/c11s03.pdf>
- Environment Protection Agency (EPA). Hazardous Waste Characteristics. 2009.
- European Commission. (2015). *Cut and Polished Tiles don't have mean Waste Water Sludge*. Retrieved on April 3 2015 from: <https://ec.europa.eu/easme/en/news/cut-and-polished-tiles-don-t-have-mean-wasted-water-and-sludge>.
- Fadaly, E. A. E. and Enany, A. E. Lead free Ceramic Cooking ware from Egyptian Raw Materials. *International Journal of Current Microbiology and Applied Sciences*. 2015. vol 4(4). pp. 474-487.
- Ferraz, E., Coroado, J., Silva, J., Gomes, C. and Rocha, F.. Manufacture of Ceramic Bricks using Recycled Brewing Spent Kieslguhr. *Material and Manufacturing Processes*. 2011. 26.:1319-1329.

- Fernandes, F. M., Lourenco P. B., Castro, Fernando. Ancient Clay bricks: Manufacture and Properties. In Bostenaru, D., Maria, Poikrl, Richad, Torok, Akos. (2010) *Materials, Technologies and Practice in Historic Heritage Structures*. Romania: Springer Science Business Media. 2009.: 1-20.
- Fonseca, B. S. D., Simao, J. A. R., Galhano, C.. Effect of coastal environment in clay facing bricks and roof tiles. *1<sup>st</sup> Annual International Interdisciplinary Conference*. AIIC. 2013. : 432-440.
- Fu, F. and Wang, Q.. Removal of heavy metal ions from wastewater: A review. *Journal of Environmental Management*. 2011. Vol 92 : 407-418.
- Garbarino J. R., Hayes, H., Roth, D., Antweider, R., Brinton T. I., Taylor, H. 1995. *Contaminants in the Mississippi River, U.S. Geological Survey Circular 1133*. Retrieved on May 12, 2015 from: www.pubs.usgs.gov/circ/circ1133
- Geric M., Gajski, G., Orescanin, V., Kollar, R. Chemical and Toxicological Characterization of The Bricks Produced from Clay/Sewage sludge Mixture. *Journal of Environmental Science and Health, part A*. 2012. Vol 47: 1521-1527.
- Godish, T. *Sick Building: Definition, Diagnosis and Mitigation*. Lewis Publishers, Boca Raton, Fl. 1995.
- Gonzalez, G. M. M, and Islas, H. J. Experimental study of the firing of red clay bricks using liquefied petroleum gas. *Journal of Scientific & Industrial Research*. 2014. Vol 73: 661-666.
- Graywolf. (2014). *Graywolf Sensing Solution*. Retrieved on May 26, 2015. from: <http://www.wolfsense.com/directsense-iaq-indoor-air-quality-monitor.html>
- Guo, H., & Murray, F. Determination of Total Volatile Organic Compound Emission from Furniture Polishes. *Clean Products and Processes*. 2001. 3(1): 42-48.
- Hariprasad N. V. and Dayananda H. S. Environmental Impact due to Agricultural runoff containing Heavy Metals- A Review. *International Journal of Scientific and Research Publication*. 2013. 3(5):1-6
- Harwell, S. Overview of current approaches – Public Meeting on waste leaching Session III-leaching Science, *Proceedings of the Environment Protection Agency*. 1999.
- Hashemi, H., Pourzamani, H., Samani, B. R. Comprehensive Planning for Classification and Disposal of Solid Waste at the Industrial Parks regarding

- Health and Environmental Impacts. *Journal of Environmental and Public Health*. 2014 from Doi: <http://dx.doi.org/10.1155/2014/230163>.
- Hegazy, B. E., Hanan, A. F., and Ahmed, M. H. Brick Manufacturing from Water Treatment Sludge and Rice Husk Ash. *Australian Journal of Basic and Applied Sciences*. 2012. 6(3): 453-461.
- Hegazy, B. E., Hanan, A. F., and Ahmed, M. H. Incorporation of Water Sludge, Silica Fume and Rice Husk Ash in Brick Making. *Advances in Environmental Research*. 2012. 1(1): 83-96.
- Henze, M., Amy, G., Brdjanovic, D., Comeau, Y., Ekama, G. A., Garcia, J. H. O., Gerba, C. P., Hooijmans, C. M., Judd, S., Kim, B., Lier, J. B. V., Mahmoud, N., Martins, A. M., Morgenroth, E. F., Olsson, G., Rosso, D., Stenstrom, M. K., Takacs, I., Loosdrecht, M. C. M. V., Wentzel, M. C., Zeeman, G. *Biological wastewater treatment*. London: Cambridge University Press. 2008.
- Herek, L. C. S., Hori, C. E., Reis, M. H. M., Mora, N. D., Tavares C. R. G., Bergamasco R. Characterization of ceramic bricks incorporated with textile laundry sludge. *Ceramics International*. 2012. 38: 951-959.
- Hesskosa, K.. *Indoor Air quality: The Latest Sampling and Analytical Methods*. 2<sup>nd</sup> Edition. Boca Raton: Taylor & Francis group, LLC. 2011.
- Hii, Kevin., Mohajerani, A., Slatter, P. and Eshtiaghi, N. Reuse of Desalination Sludge for Brick Making. *Chemeca 2013:Challenging Tomorrow*. Borton , ACT: Engineers Australia,.2013. 485-490.
- Horstmeyer, S. L. (2013). *Cape Cod Coaching*. Retrieved on August 25, 2014. from: <http://www.capecodcoaching.com/blog/training-9213>.
- ICOP-IAQ. *Industrial Code of practice on Indoor Air Quality*. Department of Occupational Safety and Health, Ministry of human Resources Malaysia. 2010.
- Ingunza, D. M. P., Anazsandra C. L. Duarte and Nascimento R. M. Use of Sewage Sludge as Raw Material in the Manufacture of Soft-Mud Bricks. *Journal of Materials in Civil Engineering*. 2011. 852-856.
- Ismail, M., Ismail, M. A., Lau, S. K., Muhammad, B. and Majid, Z. Fabrication of Bricks from Paper Sludge and Palm Oil Fuel Ash. *Concrete Research Letters*. 2010. 1(2):60-66.

- Jacobsen, R. A. *Mosaics For The First Time*. New York: Sterling publishing Co. Inc. 2005.
- Jahagirdar, S., Shrihari, S., Manu, B. Reuse of Textile Mill Sludge in Burnt Clay Bricks. *International Journal of Advanced Technology in Civil Engineering*. 2013. 2(1): 96-99.
- Jantunen, M. J. Indoor Air Exposure. *Proceeding of the 10th International Conference on Indoor Air Quality and Climate*. Beijing, China .2005. pp. 23-30.
- Jimoda, L. A. Effects of Particulate Matter on Human Health, the Ecosystem, Climate and Materials: A Review. *Working and Living Environmental Protection*. 2012. 9(1): 27-44.
- Johari, I., Said, S., Hisham, B., Bakar, A., Ahmad, Z. A. Effect of the Change of Firing Temperature on Microstructure and Physical Properties of Clay Bricks from Beruas (Malaysia). *Science of Sintering*, 2010. vol 42: 245-254.
- John, V. M. & Zordan, S. E. Research and development methodology for recycling residues as building materials - a proposal. *Waste Management*, (2001) vol.21: 213-219.
- Karaman, S., Ersahin, S. and Gunal, H. Firing temperature and firing time influence on mechanical and physical properties of clay bricks. *Journal of Scientific & Industrial Research*. 2006. 65:153-159.
- Kayali, O.. High Performance Bricks from Fly Ash. *World of Coal Ash (WOCA)*. 2005. 1-13.
- Kelly, N. and Trebilcock, M. J. *The Making of the Mosaic: A History of Canadian Immigration Policy*. 2<sup>nd</sup> edition. Canada: University of Toronto Press Incorporated. 2000.
- Kerkez, V., Tomin, M. R. B., Dalmacija, M. B., Tomasevic, D. D., Roncevic, S. D., Pucar, G. V., Dalmacija, B. D. Leachability and physical stability of solidified and stabilized pyrite cinder sludge from dye effluent treatment. *Hem. Ind.* 2015. Vol 69(3): 231-239.
- Khezri, S. M., Poshtegal, M. K., Khoramipour, S. and Ghafori, P. Use of Aluminium Anodizing Sludge Cake In manufacture of Bricks. *Journal of Food, Agriculture & Environment*. 2010. 8(3&4):1158-1161.
- Kim, H.B.(Ed.),. *Handbook of Stability Testing in Pharmaceutical Development*. New York, USA: Springer. 2009.

- Kogel, J. E., Trivedi, N. C., Barker, J. M., Krukowski, S. T. Industrial Minerals & Rocks: Commodities, Markets, and Uses. 7<sup>th</sup> edition. Society for mining, Metallurgy, and Exploration, Inc. (SME). United States of America.
- Koratich, D. (2009). *Dry shrinkage*. Retrieved on 20 November, 2013 from : <http://www.engr.psu.edu/ce/courses/ce584/concrete/library/cracking/dryshrinkage/dryingshrinkage.html>
- Kosson, D. S., Sloot, H. A. V. D., Scanhez, F., Garrabrants, A. C. An Integrated Framework for Evaluating Leaching In Waste Management and Utilization of Secondary Materials. *Environmental Engineering Science*. 2002. Vol. 19(3): 154-204.
- Kreh, R. T. *Masonry Skills*, 7<sup>th</sup> edition. United States of America: Cengage learning. 2015.
- Kudakwashe, K. S. and Gumbo J. R. Assessment of Heavy Metals in Municipal Sewage Sludge: A Case Study of Limpopo Province, South Africa. *International Journal of Environmental Research and Public Health*. 2014. 11:2569-2579.
- Kulkarni, A., Raje, S., Peerzada, S., and Rajgor, M.. A Minuscule Endeavour for Accomplishing Hypo Sludge Fly Ash Brick in Indian Context. *International Journal of Engineering Trends and Technology (IJETT)*. 2014. 10(7):361-365.
- Kuo, Y. M., Lin, T. C., Tsai, P. J.. Effect of SiO<sub>2</sub> on Immobilization of Metals and Encapsulation of a Glass Network in Slag. *J. Air Waste Manage. Assoc.* 53 (2003). 1412-1416.
- Kuokkanen, T., Poykio, R., Nurmesniemi, H., and Ramo, J. Sequential leaching of heavy metals and sulfur in bottom ash and fly ash from the co-combustion of wood and peat at a municipal district heating plant. *Chem. Speciat. Bioavail.*, (2006) 18: 131 – 141.
- Labrincha, J. A., Hajjaji, W., Sneff, L., Zanelli, C., Dondi, M., Rocha, F. Novel inorganic products based on industrial wastes. *3<sup>rd</sup> International Slag Valorisation Symposium*. 2013. 279-288.
- Lateef, E. M., Hall, J. E., Smith, S. R., Bakry, B. A., Elewa, T. A. A Survey of Heavy Metals content of Soil and plants As Affected by Long-Term Application of Sewage Water. A Case Study. *E3S Web of conferences* 1. 2013.

- Lau, H. H., Whyte, A., Law, P. L., Composition and Characteristic of Construction Waste Generated By Residential Housing Project. *International journal of Environmental Research*. 2008. 2(3): 61-268.
- Levin, H. The Big Indoor Air Emissions Threat – Secondary Emission, *World Sustainable Building Conference*. Melbourne. 2008.
- Liew, A. G., Idris, A., Samad, A. A., Calvin., Wong, H. K., Jaafar, M. S., & Aminuddin, M. B. Incorporating of Sewage in Clay Brick and its Characterization. *Waste Management & Research*. 2004. Vol. 24: 226-233.
- Lin, D. F. and Weng, C. H.. Use of Sewage Sludge Ash as Brick Material. *Journal of Environmental Engineering*. 2001. 127(10).
- Lin, K. L., Huang, L. S., Shie, J. L., Cheng, C. J., Lee, C. H., Chang T. C. Elucidating the effects of solar panel waste glass substitution on the physical and mechanical characteristic of clay bricks. *Environment Technologies*. 2013. Vol 34(1-4): 15-24.
- Liu, B., Ray, A. and Thomas, P. S. Drying Shrinkage of Hydrothermally Cured Cements With Reactive Magnesia and Clay Brick Waste. *International Inorganic Banded Fiber Composites Conference*. 2010.: 90-95.
- Majid, N. M., Islam, M. M. and Mathew, L. Heavy metal uptake and translocation by mangium (Acacia Mangium) from sewage sludge contaminated soil. *Australian Journal of Crop Science*. 2012. 6(8): 1228-1235.
- Malaysia Mosaic Berhad (MMB). *Welcome to Malaysia Mosaic Berhad: Enhancing Human Spaces Ecologically*. Johor, Malaysia. 2015.
- Malhotra, V. M. and Chugh Y. P. Tile, Countertops and Strutural Materials from Sulfate-Rich FGD Scrubber Sludge. *Combustion Byproduct Recycling Consortium*. 2005. 6(1): 1-8.
- Marangoni, M., Ponsot, I., Kuusik, R., Bernardo, E. Strong and Chemically inert sinter crystallised glass ceramics based on Estonian oil shale ash. *Institute of Materials, Minerals and Mining*. 2014. Vol 113(2): 120-128.
- Masirin, M. I. Ridzuan, M.B. Mustapha, S. Don, R. An Overview of Landfill Management and Technologies: A Malaysian Case Study At Ampar Tenang, *Proceedings 1<sup>st</sup> National Seminar on Environment, Development & Sustainability: Ecological, Economical and Social Aspects*. (2008)
- Mckay, W. B., *Brickwork*. 3<sup>rd</sup> edition. United States of America: Longman Inc. New York. 1976.

- Mesaros, R. Use of sludge from the manucipal sewage system for brick making. *New life for an obsolescent brickworks, Ziegel industries International* 5. 1989. 251-254.
- Michael, S. M. and John, P. Z. *Material For Civil and Construction Engineers*. 2<sup>nd</sup> Edition. New Jersey: Pearson, Prentice Hall. 2006.
- Min, X., Qianwen S., Xiaobo, L., Yumei, D. Experimental Study On Production Of Common Sintered Bricks Containing High Volume Of Waterworks Sludge. *International Conference on Computer Distributed and Intelligent Environmental Monitoring*. 2011.794-796.
- Montanaro, L., Bianchini, N., Rincon, J. Ma., Romero, M. Sintering Behaviour of Pressed Red Mud Wastes from Zinc Hydrometallurgy. *Ceramics International*. 2001. vol 27 (1): 29-37.
- Morais, S., Costa, F. G. and Pereira, M. L. *Heavy Metals and Human Health*. In Jacques Oosthuizen. Environmental Health- Emerging Issues and Practice. Crotia. InTech Europe. 2012.
- Morani, M., Seifert, T., & Lindvall. *Indoor Air Quality. A Comprehensive Reference Book*. Amsterdam-Laussane-New York-Oxford-Shannon-Tokyo, pp. 1049. 1995.
- Morrison, G. C. & Nazaroff, W. W. Ozone Interaction with Carpets: Secondary Emissions of Aldehydes, *Environment Science & Technolgy*. 2002. 36 (10): 2185-2192.
- Nash, W. G. *Brickwork 1*. 3<sup>rd</sup> edition. Great Britain: Anchor Brendon Ltd, Tiptree , Essex. 1966.
- Nouri, J., Khorasani, N., Lorestani, B., Karami, M., Hassani, A.H. and Yousefi, N. Accumulation of Heavy Metals in Soil and Uptake by Plant Species with Phytoremediation Potential. *Environment. Earth Science*. 2009. 59: 315–323.
- Ngoc, UN., Schintzer, H. Sustainable solution for solid waste management in south East Asian Countries. *Waste Management and Research* 2009, 2(9):1982-95.
- Nwoye, C. I., Obidiegwu, E. O. and Mbah, C. N. Production of Bricks for Building Construction and Predictability of its Post-Fired Volume Shrinkage Based on Apparent Porosity and Water Absorption Capacity. *Research and Reviews Journal of Material Sciences*. 2014. vol 2 (3):17-26.

- Oliveira, A. S., Bocio, A., Trevilato, T. M., Takayanagui, A. M., Domingo, J. L., Segura-Munoz, S. L. Heavy metals in untreated/treated urban effluent and sludge from a biological wastewater treatment plant. *Environment Science Pollution Research International*. 2007. 14(7): 483-489.
- Pacyga, D. A. and Shanabruch, C. *The Chicago Bungalow*. Great Britain: Arcadia Publishing. 2003.
- Pavia, S. and Hanley, R. Flexural bond strength of natural hydraulic lime mortar and clay brick. *Material and Structures*. 2010. Vol 43: 913-922.
- Perbadanan Pengurusan Sisa Pepejal dan Pembersihan Awam (PPSPPA). *Buku Poket :Maklumat Asas Pengurusan dan Pengoperasian Sisa Pepejal & Pembersihan Awam di Malaysia*. Kuala Lumpur, Malaysia. 2014.
- Petrucci, E. G. R. *Construction materials*, 11<sup>th</sup> Edition. Globo: Porto Alegre. 1998.
- Posudin, Y. *Volatile Organic Compounds in Indoor Air: Scientific, Medical and Instrumental Aspects*. National University of Life and Environmental Sciences of Ukraine. 2008.
- Preez, A. *FCS Civil & Construction Technology L4*. 1<sup>st</sup> Edition. South Africa: Pearson Education South Africa (Pty) Ltd. 2009.
- Punmia, B. C., Jain, A. K., Jain. A. K. *Basic Civil Engineering*. 5<sup>th</sup> edition, New Delhi: Laxmi Publications (p) LTD. 2003.
- Qiang, X. *Nanoporous Materials: Synthesis and Applications*. United States of America: CRC Press, Taylor & Francais Group. 2013.
- Qio , L. and Ho, G. The Effects of Clay Amendment and Composting On Metal Speciation in Digested Sludge. *Water Research*. 1997. Vol 31(5): 951-964.
- Rajgor, M., Pitroda. J. Stone Sludge: Economical Solution for Manufacturing of Bricks. *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*. 2013. 2(5): 16-20.
- Ramadan, M. O., Hanan, A. F. and Ahmed, M. H. Reuse of Water Treatment Plant Sludge in Brick Manufacturing. *Journal of Applied Sciences Research*. 2008. 4(10):1223-1229.
- Reena, S., Gautam, N., Mishra, A. and Gupta, R. Heavy metals and living systems: An overview. *Indian Journal of Pharmacology*. 2011. 43(3): 246-253.
- Reeves, G. M., Sims, I., Cripps, J.C.. *Clay Materials Used in Construction*. London: The Geological Society. 2006.

- Riza, F. V., Rahman, I. A. Zaidi, A. M. A. A Brief Review of Compressed Stabilized Earth Brick (CSEB). *International Conference on Science and Social Research (CSSR 2010)*, 2010. 1011- 1016.
- Rouf, M. A. & Hossain, M. D. Effects of using arsenic iron sludge in brick making. Fate of Arsenic in the Environment, *Proceedings of the BUET-UNU International Symposium*, 5–6 February, Dhaka, Bangladesh, 2003, 193-208.
- Saijun Z. Experiment on Making Autoclaved Sludge Bricks with Water-Treatment Plant Sludge. *Scientific Research Fund of Human Provincial Education Department. IEEE*. 2011. 6568-6571.
- Salthammer, T., Mentese, S., & Marutzky, R.. Formaldehyde in the Indoor Environment. *Chemical. Review*. 2010. 110(4): 2536-2572.
- Segadaes, A. M., Carvalho, M. A., Acchar, W. Using Marble and granite rejects to enhance the processing of clay product. *Applied Clay Science*. 2005. 30(1): 42-52.
- Seneviratne, M.. *A Practical Approach to Water Conservation for Commercial and Industrial Facilities*. Great Britain: Elsevier Ltd. 2007.
- Sengupta, P., Saikia, N. Borthakur, P. C. Bricks from Petroleum Effluent treatment plant Sludge: Properties and Environmental Characteristics. *Journal of Environmental Engineering*. 2002. 28(11): 1090-1094.
- Sengupta, P., Dutta, D. K., Goswamee, R. L., Saikia, N., Borthakur, P. C. Combating hazardous Sludge Disposal Problem at Lakwa (India) Oil Field Effluent. *SPE No. 39533, Proc, SPE Oil and Natural Gas Conf. And Exhibiton, Society of Petroluem Engineers*. 1998. pp. 279-284.
- Sidrak F. G., Biofly Engineering Reuse of Fly Ash and Sewage Sludge Brick. Ph.D. Thesis. *University of Wolonggong (Australia)*, 1996.
- Sieckhaus, J. F. *Chemicals, Human Health, and the Environment: A Guide to the Development and Control of Chemical and Energy Technology*. United states of America : Xlibris corporation. 2009.
- Siefers, A. M.. *A novel and cost-effective hydrogen sulfide removal technology using tire derived rubbe particles*. Master Thesis. Iowa State University: 2010.
- Silva M. D. M., Araujo, A. S. F., Nunes, L. A. P. L., Melo, W. J. D., Singh, R. P. Heavy metals in cowpea (*Vigna unguiculata* L.) after tannery sludge

- compost amendment. *Chilean Journal of Agricultural Research*. 2013 vol. 73(3).
- Slim, J. A., Wakefield, R. W. The utilization of sewage sludge in manufacture of clay bricks. *Water SA*. 1991. vol. 17(3).
- Stringfellow, A., Banks, C. J., Hillman, P. F. (2001). *The Influence of Composing on Heavy metal Extractability from Two Sewage Sludges*. In Dhir R. K., Limbachiya M. C., McCarthy M. J. Recycling and Reuse of sewage sludge. London: Thomas Telford Publishing. pp 118-124.
- Struck, T. P.. (2009). *Mosaic*. Retrieved on 14 April, 2013 from: <http://www.classics.upenn.edu/myth/php/tools/dictionary.php>.
- Tay, J. H. Bricks manufactured from sludge. *Journal Environment Engineering*. 1987. Vol. 113(2): 278.
- Tay, J. H. Show, K. Y. and Hong, S. Y. The Application of Industrial Sludge and Marine Clay in Brick-Making. *Journal of the Chinese Institute of Environmental Engineering*. 2001. 11(3): 203-208.
- Varghese, P. C., *Building materials*. 2<sup>nd</sup> edition. Delhi: PHI Learning Private Limited. 2015.
- Victoria A. N. Characterisation and Performance Evaluation of Water Works Sludge As Brick Material. *International Journal of Engineering and Applied Science*. 2013. 3(3): 69-79.
- Violante, A., Cozzolino, V., Perelomov, L., Caporale, A. G. and Pigna, M. Mobility and BioAvailability of Heavy Metals and Metalloids in Soil Environment. *Journal of Soil Science and plant Nutrition*. 2010. vol 10(30): 268-292.
- Virdi, S. *Construction Science and Materials*. 1<sup>st</sup> Edition. United States of America: John Wiley & Sons, Ltd. 2012.
- Vitez, T. & Travnicek, P. Particle Size Distribution of Sawdust and Wood Shavings Mixture. *Research Agriculture Engineering*. 2010. 56(4): 154-158.
- Sakr, W., Weschler, C. J., & Fanger, P. O. (2005). The impact of Sorption on perceived air quality. *International Journal of Indoor Environment and Health*. 2006. 6(2): 98-110.
- Wang, L. K., Chen, J. P., Hung, Y., Shammas, N. K. *Heavy Metals in the Environment*. United States of America: Taylor & Francis Group.LLC. 2009.

- Weldemarian, M. M.. Heavy Metal (Pb, Cd, Zn, Cu, Cr and Fe) Content in Almeda Textile Industry Sludge, Northern Tigrai, Ethiopia. *International Journal of scientific and Research Publications*. 2014. vol 4(1). pp. 1-3.
- Weng, C.H., Lin, D. F., Chiang, P. C. Utilization of Sludge as brick materials. *Advance in environment research*. 2003. 7(1): 679-685.
- Werle, S. and Dudziak, M. Analysis of organic and Inorganic Contaminants in Dried Sewage Sludge and By Products of Dried Sewage Sludge Gasification. *Journal Energies*. 2014. 462-476.
- Xu, G., Liu, M., Li G. Stabilization of heavy metals in lightweight aggregate made from sewage sludge and river sediment. *Journal of Hazardous Materials*. 2013. Vol 260: 74-81.
- Zaidi, A., Wani, P. A., Khan, M. S. *Toxicity of Heavy Metals to Legumes and Bioremediation*. India: Springer Verlag Wien. 2012.
- Ziemacki, G. Viviano, G. and Merli, F. Heavy metals: Sources and Environment Presence. *Ann. 1<sup>st</sup> Super Sanita*. 1989. 25(3): 531-536.
- Zorpas, A. Heavy Metals Removal from Sewage Sludge Compost Using Natural Zeolite- A Function of Temperature and Contact Time. In Dhir, R. K., Limbachiya, M. C., McCarthy, M. J. *Recycling and Reuse of sewage sludge*. London. Thomas Telford Publishing. pp. 112-117. 2001.
- Zumdahl, S. and Zumdahl, S. *Chemistry*. 8<sup>th</sup> Edition. United State of America: Nelson Education Ltd. 2010.