

THE POTENTIAL USE OF LIGHT PIPE SYSTEM AS ILLUMINATION  
ELEMENT FOR ONE STOREY BUILDING IN MALAYSIA

ASLILA BINTI ABD. KADIR

A thesis submitted in partial  
fulfilment requirements for the award of the  
Degree of Doctor of Philosophy



Faculty of Civil Engineering and Built Environment  
Universiti Tun Hussein Onn Malaysia

JULY 2022

*To Allah the Almighty*

*For my beloved mother, my husband and children*



## ACKNOWLEDGEMENT

I believe that I would not have been able to complete this PhD journey without the support and cooperation of countless people over the years. My special thanks to Assoc. Prof Dr Mohamad Zaky bin Noh, former Dean of Centre For Diploma Studies (CeDS) who allowed and encouraged me to pursue this PhD journey.

Hereby, I would like to express my sincere gratitude to my supervisor, Prof. Sr. Ts. Dr. Hj. Lokman Hakim Bin Ismail and Co-Supervisor Assoc Prof. Ts. Dr. Narimah Binti Kassim for their excellent guidance, patience and providing me motivation to complete the research. My gratitude also goes to Tn Hj Amir Khan former Deputy Dean (Academic) CeDS, Assoc Prof Hj Masiri Kaamin former Deputy Dean (Research, Development & Publication) CeDS and Dr Norhayati Binti Ngadiman Head of Civil Engineering Department for patiently allowing me juggling my task under the department and my commitment to complete this research.

Special thanks also goes to Mr Osman Abd Rahman Assistant Engineer for Building Services Laboratory and Mr Suhaimi Harun Assistant Engineer for Advanced Materials Engineering Laboratory for assistance with the research equipment.

Appreciation also goes to everyone involved directly or indirectly towards this Phd journey. Last but not least, my foremost gratitude is to my husband, Amran Bin Muharam for being there persistently encouraging me always and to my children, Amran Afieq, Amran Hazeem and Nureen Qistina for their patience and understanding. Similar gratitude also goes to my beloved mother, Hajjah Fatimah Binti Hj Adnan for her endless love and prayers. To my family, I thank you for your fullest support.

## ABSTRACT

Daylighting is an efficient and practical strategy for illuminating the interiors of buildings with natural light during the day. Natural light is extremely beneficial for energy conservation, the occupants' health and psychological well-being, and the environment. Light pipe system (LPS) is a lighting device that can capture sunlight from the rooftop and transmits into the low light area or into rooms with insufficient daylight. The purpose of this study was to determine the potential of a light pipe system for interior illumination in single storey building spaces in Malaysia. The physical experiment was conducted in a test room to determine the light pipe system's overall potential. Meanwhile, a computer simulation was used to determine the illuminance distribution of the LPS and artificial lighting in order to calculate energy savings. The simulation was conducted in three scenarios, (1) with one LPS, (2) with two LPS, and (3) with three LPS. The results indicate that the LPS performed admirably under intermediate sky and met the building's minimum illuminance (100 lux) requirements, as recommended by MS 1525:2014. Furthermore, the analysis of the daylight performance results was based on Work Plane Illuminance (WPI), the daylight penetration factor (DPF) and illuminance uniformity. The results illustrated that the LPS performance was reasonable, but the presence of clouds disrupted the capacity of the LPS to achieve the illuminance recommended. As a result, artificial lighting was used as a source of power. By combining a light pipe system with artificial lighting, it is possible to achieve an adequate level of illumination in a room while reducing electricity consumption. The simulation results indicate that using two LPS is more beneficial in a 15 m<sup>2</sup> space than using one or three LPS. Using two LPS for the test room with the artificial lighting system and applying the dimming control, the reduction was up to 25 per cent per day, suggesting that 114 kWh could be saved annually. In parallel, the CO<sub>2</sub> emissions produced from the energy usage could be reduced to 80 kg per year. Both reductions would contribute to saving to the environment. This discovery provide useful information to building designers intending to implement LPS and this system will be widespread use of LPS in Malaysia.

## ABSTRAK

Cahaya siang merupakan sumber pencahayaan semulajadi dalam bangunan yang efisien dan praktikal. Ia bermanfaat kepada penjimatan tenaga, kesihatan dan psikologi penghuni serta penjagaan alam sekitar. Sistem Paip Cahaya (LPS) merupakan sistem pencahayaan semulajadi yang dapat membawa cahaya siang daripada atas bumbung ke ruang dalaman bangunan, terutamanya ruang yang memperolehi cahaya siang yang rendah seperti ruang yang jauh daripada tingkap atau ruang yang terhalang dengan dinding sesekat. Tujuan kajian ini adalah untuk menentukan potensi LPS sebagai kaaedah pencahayaan semulajadi pada bangunan setingkat di Malaysia. Kajian fizikal secara eksperimen telah dijalankan di dalam bilik ujian. Manakala simulasi komputer dijalankan bagi menentukan corak pencahayaan daripada LPS dan lampu elektrik. Hasil simulasi ini digunakan untuk pengiraan penjimatan tenaga yang diperolehi dengan menggunakan LPS dan lampu elektrik. Simulasi dijalankan dalam tiga senario iaitu; (1) dengan satu LPS, (2) dengan dua LPS dan (3) dengan tiga LPS. Keputusan kajian menunjukkan LPS berupaya memenuhi keperluan minimum pencahayaan (100lux) sebagaimana yang dicadangkan dalam MS 1525 :2014. Selain itu, penilaian faktor penembusan cahaya (DPF) dan keseragaman pencahayaan ( $U_o$ ) juga dapat dipenuhi oleh LPS ketika keadaan langit sederhana. Namun kehadiran awan telah mempengaruhi kapasiti cahaya. Menggabungkan LPS dan lampu elektrik adalah bagi mendapatkan tahap pencahayaan yang mencukupi dalam bangunan. Melalui simulasi komputer mendapati penggunaan dua LPS yang digabungkan dengan lampu elektrik adalah lebih sesuai untuk ruang  $15m^2$  berbanding dengan satu atau tiga LPS. Dengan menjadikan LPS sebagai sumber utama pencahayaan dan lampu elektrik sebagai sandaran, tenaga elektrik untuk tujuan pencahayaan dapat dijimatkan sebanyak 25% sehari dan mencecah 114kWh setahun. Disamping itu, pelepasan  $CO_2$  juga dapat dikurangkan sebanyak 80kg setahun. Kajian ini dapat memberi maklumat kepada perekabentuk bangunan terhadap penggunaan LPS dan ia akan meluaskan penggunaan sistem ini di Malaysia.

## CONTENTS

	<b>TITLE</b>	<b>i</b>
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>CONTENTS</b>	<b>vii</b>
	<b>LIST OF TABLES</b>	<b>xii</b>
	<b>LIST OF FIGURES</b>	<b>xv</b>
	<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xix</b>
	<b>LIST OF APPENDICES</b>	<b>xxi</b>
<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Research background	1
	1.2 Problem statement	3
	1.3 Research questions	5
	1.4 Research objectives	5
	1.5 Scope of the research	5
	1.6 Significance of the research	6
	1.7 Thesis outline	7
	1.8 Summary	8

<b>CHAPTER 2</b>	<b>DAYLIGHTING OPTIMISATION IN BUILDINGS</b>	<b>9</b>
2.1	Introduction	9
2.2	Daylight	9
	2.2.1 Source of daylight	10
	2.2.2 Photometrical units and measures	12
2.3	Daylight in the Malaysian climate	13
	2.3.1 Sky condition	15
	2.3.2 Determination of sky type	16
2.4	Benefits of daylight	22
	2.4.1 Health and well-being	23
	2.4.2 Performance and productivity	25
2.5	Energy-saving potential	26
	2.5.1 Energy consumption	28
	2.5.2 CO <sub>2</sub> emissions mitigation	30
2.6	Daylighting strategies	31
	2.6.1 Conventional daylighting strategies	31
	2.6.2 Innovative daylighting strategies	34
2.7	Light pipe systems	38
	2.7.1 Development of light pipe systems	39
	2.7.2 Components of light pipe systems	44
2.8	Previous research into light pipe systems	47
	2.8.1 Experimental research of light pipe systems	48
	2.8.2 Computer simulation	56



2.9	Daylight performance criteria	58
2.9.1	Work plane illuminance	58
2.9.2	Daylight ratio	59
2.9.3	Illuminance uniformity	61
2.10	Research gap	62
2.11	Summary	64
<b>CHAPTER 3</b>	<b>RESEARCH METHODOLOGY</b>	<b>65</b>
3.1	Introduction	65
3.2	Research approach	65
3.3	Instruments in the test room	67
3.4	Data collection	69
3.4.1	The field measurement method	69
3.4.1.1	Preparation of field measurement	69
3.4.1.2	Light pipe configuration	73
3.4.1.3	Placement of light sensors	76
3.4.1.4	Data acquisition	78
3.4.2	Computer simulation	81
3.4.2.1	Illuminance data source for light pipe systems	81
3.4.2.2	Illuminance data source for artificial lighting	88
3.5	Data analysis techniques	89
3.5.1	Examination of the illuminance level obtained by the light pipe system	90



3.5.2	Investigation of the optimum performance of the light pipe system	90
3.5.3	Evaluation of the potential energy savings and CO <sub>2</sub> mitigation	90
3.6	Summary	92
<b>CHAPTER 4</b>	<b>DATA ANALYSIS AND DISCUSSION</b>	<b>93</b>
4.1	Introduction	93
4.2	Results of field study	93
4.3	Illuminance level obtained by light pipe systems	96
4.3.1	External illuminance	98
4.3.2	Solar altitude	101
4.3.3	Discussion	105
4.4	Performance of the light pipe system	106
4.4.1	Work plane illumination	108
4.4.2	Daylighting penetration factor	117
4.4.3	Illuminance uniformity	123
4.4.4	Discussion	124
4.5	Potential electrical energy savings	127
4.5.1	Artificial lighting distribution	128
4.5.2	Light pipe system distribution	130
4.5.3	Energy savings	134
4.5.4	CO <sub>2</sub> mitigation	145
4.5.5	Discussion	146
4.6	Summary	150



<b>CHAPTER 5</b>	<b>CONCLUSION</b>	<b>152</b>
5.1	Introduction	152
5.2	Conclusion	152
5.2.1	Objective 1: To examine the illuminance level obtained by a light pipe system	153
5.2.2	Objective 2: To investigate the optimum performance of a light pipe system in a building	153
5.2.3	Objective 3: To evaluate the potential electrical energy savings and carbon dioxide (CO <sub>2</sub> ) mitigation	154
5.3	Limitations of the research	154
5.4	Contributions of the research	155
5.5	Recommendations for future research	156
	<b>REFERENCES</b>	<b>157</b>
	<b>APPENDIX</b>	<b>172</b>
	<b>VITA</b>	<b>177</b>



PTTA UTHM  
PERPUSTAKAAN TUN AMINAH

## LIST OF TABLES

2.1	Sky types in the Malaysian climate	16
2.2	Classification of sky condition	17
2.3	Cloud cover (oktas) categorisation by World Meteorological Organization	18
2.4	Monthly Nebulosity Index (NI) in Subang, Malaysia	19
2.5	Hourly frequency of Nebulosity Index (NI)	20
2.6	Frequency of Nebulosity Index (NI) at Kota Kinabalu	20
2.7	Mean daily hours of sunshine for five major stations in Malaysia	21
2.8	Sky condition in tropical sky	21
2.9	Research on the effects of daylighting on health and wellbeing	24
2.10	Researcher on performance and productivity	26
2.11	Research on energy savings by using daylight	27
2.12	Application of light pipe systems	43
2.13	Research on light pipe systems	49
2.14	Recommended illuminance in buildings	58
2.15	Recommended average illuminance by MS 1525:2014	59
2.16	DPF values suggested by previous researchers	61
2.17	Illuminance uniformity for offices with different types of area	62
2.18	Summary of previous studies of light pipe systems	63
3.1	The instruments used to measure daylight illuminance	67

3.2	Configuration of the test room	73
3.3	Measurement and simulation readings	82
3.4	Result from simulation	83
3.5	Simulation parameters	87
4.1	Coefficient of determination for external weather conditions	96
4.2	F test between external illuminance and solar altitude to internal illuminance	97
4.3	Linear regression model for external illuminance and solar altitude to internal illuminance	97
4.4	Coefficient of determination for external illuminance	99
4.5	F test between external illuminance and internal illuminance	100
4.6	Linear regression model for external illuminance	100
4.7	Internal illuminance and external illuminance crosstabulation	101
4.8	Kendall's Tau-b test of external illuminance to internal illuminance	101
4.9	Coefficient of determination for solar altitude	102
4.10	F-test for solar altitude and internal illuminance	103
4.11	Linear regression model for solar altitude	103
4.12	Internal illuminance and solar altitude cross tabulation	104
4.13	Kendall's Tau-b test of solar altitude to internal illuminance	104
4.14	Summary statistical analysis	106
4.15	Average external illuminance data during the monitoring period	106
4.16	Selected dates for analysis	107
4.17	Average daylight penetration factor	117
4.18	Illuminance uniformity ( $U_0$ )	123
4.19	Summary of simulation results for artificial lighting	129

4.20	Illuminance distribution using the one light pipe system	131
4.21	Illuminance distribution using a two light pipes system	132
4.22	Illuminance distribution using a three light pipes system	133
4.23	Illuminance level of each zone	136
4.24	Comparison of artificial lights and the one light pipe system	138
4.25	Power consumption using the one light pipe system	139
4.26	Comparison of artificial lights and the two light pipes system	141
4.27	Power consumption using the two light pipes system	141
4.28	Comparison of artificial lights and the three light pipes system	144
4.29	Power consumption using the three light pipes system	144
4.30	Energy consumption and savings	145
4.31	CO <sub>2</sub> mitigation	146
4.32	Potential energy saving and CO <sub>2</sub> mitigation	148
4.33	Overall energy consumption cost in the test room	149



PERPUSTAKAAN TUN AMINAH

## LIST OF FIGURES

2.1	Wavelength of natural sunlight	10
2.2	Solar altitude and solar azimuth	11
2.3	Sun path diagrams of Johor Bahru	11
2.4	Relationship between luminous flux, intensity and illuminance	13
2.5	Maps of Malaysia	14
2.6	Daylight availability in Malaysia	14
2.7	The seventeen Sustainable Development Goals (SDGs)	23
2.8	Energy consumption in buildings in Malaysia	28
2.9	Sidelighting strategies	32
2.10	Perimeter offices blocking light from window	32
2.11	Enclosed corridor layout	33
2.12	Enclosed corridor rely on artificial lighting	33
2.13	Path of light through a light shelf system	35
2.14	Sunlight passing through the light pipe	36
2.15	Application of the fibre optic daylighting system	37
2.16	Application of a light pipe system	39
2.17	Invention by Hanneborg in 1900	40
2.18	Patented light pipes	42
2.19	Schematic of typical light pipe	44
2.20	Collectors used by previous researchers	45
2.21	Aspect ratio for light pipe systems	46
2.22	Different diffuser surfaces	46
2.23	Light pipe system in Athens	51

2.24	Light pipe system experiment in Seoul, Korea	52
2.25	Light pipe system experiment in Ancona, Italy	53
2.26	Light pipe experiment in Beijing, China	54
2.27	Light pipe experiment in Istanbul, Turkey	54
2.28	Light pipe experiment in IIT New Delhi	55
3.1	Research process flowchart	66
3.2	KYOWA UCAM 60B data logger and computer software	68
3.3	Methodology flowchart for field measurement	70
3.4	Test room layout	71
3.5	Location for the test room	72
3.6	Light pipe configuration	74
3.7	Proposed acrylic dome	74
3.8	UV-Vis Spectro Photometer	75
3.9	Proposed light pipe system	76
3.10	Interior view of a diffuser	76
3.11	Position of lux sensors	77
3.12	Measurement position for illuminance uniformity	78
3.13	External lux sensor LSI-Lastem ESR003#C	79
3.14	Solar altitude results from NOAA Solar Calculator	79
3.15	Internal lux sensor LSI-Lastem ESR001.1#C	80
3.16	Manual data collection	80
3.17	Setting up the sun position and sky model	81
3.18	Relationship between measurement and simulation	83
3.19	Main interface in HOLIGILM	84
3.20	Simulation steps	85
3.21	Proposed light pipe positions	86
3.22	Importing image and setting the scale	88
3.23	Digitised data points by manual selection	88
3.24	Baseline reading	89

3.25	Relative power load to light output for two fluorescent tubes	91
4.1	Average external illuminance in daylight during the monitoring period	94
4.2	Frequency of external illuminance distribution	95
4.3	Scattered plot of internal illuminance against external illuminance	99
4.4	Scattered plot of internal illuminance against solar altitude	102
4.5	WPI under intermediate sunny sky	109
4.6	Cumulative frequency distribution for intermediate sunny sky	110
4.7	Regression analysis between WPI and external illuminance under intermediate sunny sky	111
4.8	Regression analysis between WPI and solar altitude under intermediate sunny sky	111
4.9	View inside the test room under intermediate sunny sky	112
4.10	WPI under intermediate overcast sky	114
4.11	Cumulative frequency distribution for intermediate overcast sky	115
4.12	Regression analysis WPI and external illuminance under intermediate overcast sky	116
4.13	Regression analysis WPI and solar altitude under intermediate overcast sky	116
4.14	View inside the test room under intermediate overcast sky	117
4.15	DPF in intermediate sunny sky	119
4.16	Average DPF in intermediate sunny sky	120
4.17	Frequency of DPF in intermediate sunny sky	120
4.18	DPF in intermediate overcast sky	121
4.19	Average DPF in intermediate overcast sky	122
4.20	Frequency of DPF in intermediate overcast sky	122
4.21	Frequency of work plane illuminance during the monitoring period	124



4.22	Average internal illuminance	125
4.23	Daylight penetration factor comparison between types of sky	126
4.24	Floor plan and luminaires arrangement	128
4.25	Simulated illuminance level of the test room	129
4.26	Labels for artificial lighting	134
4.27	Arrangement for optimisation based on the scenario	135
4.28	Zoning each luminaire	136
4.29	Illuminance distribution for the one light pipe system	137
4.30	Illuminance distribution for the two light pipes system	140
4.31	Illuminance distribution for the three light pipes system	143
4.32	Potential energy savings	147
4.33	Potential energy savings and illuminance uniformity	149



## LIST OF SYMBOLS AND ABBREVIATIONS

$A_r$	-	Rayleigh scattering coefficient
$E_d$	-	Diffuse irradiance
$E_{avg}$	-	Average illuminance level
$E_{external}$	-	External illuminance
$E_{internal}$	-	Internal illuminance
$E_{min}$	-	Minimum illuminance level
$EC_{existing}$	-	Energy consumption of existing
$EC_{retrofiting}$	-	Energy consumption of proposed system
$E_g$	-	Global irradiance
GWh	-	Gigawatt per hour
$I_d$	-	Diffuse irradiance
$I_G$	-	Global irradiance
klx	-	Kilo lux
kWh	-	Kilowatt per hour
lx	-	Lux
$n$	-	Duration of sunshine
$NI$	-	Number of lamp
$no$	-	Daylength
$P$	-	Power
$R$	-	Correlation coefficient
$R^2$	-	Coefficient of Determination
$S$	-	Sunshine duration
$U_o$	-	Illuminance uniformity
$U_{o\ max}$	-	Maximum illuminance uniformity
$U_{o\ min}$	-	Minimum illuminance uniformity
$W$	-	Watt
$m$	-	Optical air mass

$\alpha$	-	Solar altitude
ACEM	-	Association of Consulting Engineers Malaysia
ALOS	-	Average Length of Stay
APEC	-	Asia pacific energy research centre
BC	-	Billing cost
BREEAM	-	Building research establishment environmental assessment method
CASBEE	-	Comprehensive Assessment System for Building Environmental Efficiency
CH <sub>4</sub>	-	Methane
CIDB	-	Construction Industry and Development Board
CO <sub>2</sub>	-	Carbon dioxide
CR	-	Cloud cover ratio
DF	-	Daylight factor
DPF	-	Daylight penetration factor
EC	-	Energy consumption
EE	-	Energy efficiency
EF	-	Emissions factor
ES	-	Energy saving
ET	-	Electricity tariff
GHG	-	Greenhouse gas
HOLIGILM	-	Hollow light guide interior illumination method
IESNA	-	The Illuminating Engineering Society of North America
LPS	-	Light pipe system
MS	-	Malaysian standard
N <sub>2</sub> O	-	Nitrous oxide
NI	-	Nebulosity index
NOAA	-	National Oceanic and Atmospheric Administration
OH	-	Operating hour of the luminaire per year
PAM	-	Malaysian Institute of Architect
RE	-	Renewable energy
SCN	-	Suprachiasmatic nucleus
SF <sub>6</sub>	-	Sulphur hexafluoride

- UV - Ultra violet
- WPI - Work plane illuminance



**LIST OF APPENDICES**

A	LSI-Lastem ESR003#S	167
B	LSI-Lastem ESR001	168
C	Data intermediate sunny sky	169
D	Data for intermediate overcast sky	170
E	List of publications	171



**PTTA UTHM**  
PERPUSTAKAAN TUNKU TUN AMINAH

# CHAPTER 1

## INTRODUCTION

### 1.1 Research background

Daylighting is the introduction of natural light to provide illumination in buildings during the daytime. It was the predominant source of light since the first built dwellings, even though oils lamps and gas lighting were invented thousands of years ago (Baker & Steemers, 2014). Due to their high fuel prices and environmental problems, oils and gas lamps do not make viable alternatives (Baker & Steemers, 2014; Mayhoub, 2011). The invention of electric lighting in the late 19th century rapidly replaced daylight in buildings due to its ability to keep the interior well-lighted and comfortable for the occupants. The development of electrical lighting transformed life in indoor environments by providing occupants with their lighting needs.

With the building sector and economic demand booming, people spend most of their lives in buildings such as offices, houses, factories, schools and supermarkets. For this reason, much energy consumption is associated with creating indoor environmental conditions that ensure the comfort of occupants. Besides that, the building envelope consequently became enclosed, fully air-conditioned and artificially lit. This situation has contributed to electrical lighting becoming the second most used type of electrical power consumption after air conditioning, and this rate is increasing every year. Although electrical lighting provides sufficient levels of illumination, it cannot provide the physiological benefits of natural light (Garcia-Hansen, 2006; Turan *et al.*, 2020). The use of electricity during the day not only contributes to electricity consumption but is also a waste of most natural light. Thus, it is not impossible that the peak demands for electrical lighting occur at the same time as the peak availability of daylight (Callow, 2003; Dortans *et al.*, 2020). Furthermore, with the increasing cost

of electricity, people have become more environmentally responsible about reducing their electricity use (Ismail, 2007; Patil, Kaushik & Garg, 2018).

Daylighting is a passive strategy that can be implemented by architects and designers in building design. Recently, several studies have shown that incorporating daylight is a way to reduce energy consumption in buildings (Chen *et al.*, 2014; Ihm, Nemri, & Krarti, 2009; Krarti, Erickson, & Hillman, 2005; Reffat & Ahmad, 2020; Srisamranrungruang & Hiyama, 2020; Yun *et al.*, 2012). These studies indicated that the need for artificial lighting in buildings can be reduced effectively, efficiently and sustainably through daylighting. It is possible to save as much as 27% and 10% of the energy usage as mentioned by Wagiman *et al.* (2021) and Zain-Ahmed *et al.* (2002) respectively. In addition, spaces illuminated by daylight give occupants the best colour rendering and most closely match human visual responses to provide high visual satisfaction (Edmonds & Pearce, 1999; Li & Lam, 2003; Osibona, Solomon, & Fecht, 2021).

As a way to reduce energy consumption in buildings, the incorporation of daylighting has increased over the last thirty years, along with the popularity of green building rating systems. In 1990, the Building Research Establishment Environmental Assessment Method (BREEAM) was first employed, since when the global application of green building appraisals has expanded. Assessment systems have been introduced and promoted by many countries, including Australia, with Green Star; Japan, with the Comprehensive Assessment System for Building Environmental Efficiency (CASBEE); Canada, with the Building and Environmental Performance Assessment Criteria (BEPAC) and the United States, with Leadership in Energy and Environmental Design (LEED).

In Malaysia, awareness of, and concern for, this issue has been growing within the government since the 2000s. The Construction Industry and Development Board (CIDB), a regulatory body entrusted with the responsibility for coordinating the needs of the Malaysian construction industry, has created an objective to promote green building projects. Besides that, the Malaysian Institute of Architects (PAM) and Association of Consulting Engineers Malaysia (ACEM) has introduced the Green Building Index (GBI) as a rating tool. The index is intended to promote sustainability in the built environment and enhances awareness of environmental issues and our collective responsibility to future generations among several parties. These include developers, architects, engineers, planners, designers, contractors and the public.

Malaysia experiences long sunshine hours during the daytime and sun is available throughout the year (Heng *et al.*, 2019; Munaaim *et al.*, 2014). Yet the conditions of the Malaysian sky are average or intermediate; in other words, the sky is not clear but not overcast (Zain-Ahmed *et al.*, 2002). These weather conditions are considered an advantage for daylighting. Therefore, the utilisation of innovative daylighting strategies could help in capturing daylight and delivering it into a building into which daylight cannot reach due to the building layout. This research examines the potential of using light pipes as innovative daylighting strategies in order to illuminate building interiors, which could be a contribution to sustainable solutions, i.e., the environment, society and economy could benefit.

## 1.2 Problem statement

The electricity demand in Malaysia is increasing every year due to increased population growth as well as economic growth. It rose from 110,119GWh in 2016, to 110567GWh in 2017 and 133,446GWh in 2018 (Suruhanjaya Tenaga, 2019). About 48% of the electricity generated is consumed by the building sector and by the year 2030, the consumption is expected to have increased by 50% (Hassan *et al.*, 2014). Artificial lighting contributes approximately 20% to 25% of the total building electricity consumption, for operational or aesthetic reasons (Tang & Chin, 2017; Zakaria *et al.*, 2013). More than 75% electricity generation in Malaysia dependant on fossil fuels compare to water power and renewable energy (Mohd Chachuli *et al.*, 2021; Worlddata, 2021). Due to that, CO<sub>2</sub> contributes the largest volume of gas emission resulting from the generation and this level is increasing day by day in develop and developing country such as Malaysia (Babatunde *et al.*, 2021; Ganandran *et al.*, 2014). CO<sub>2</sub> emissions have resulted in changes in temperature and also serious environmental issues related to the climate change. Nowadays, most countries around the world, making a significant effort to reduce CO<sub>2</sub> emissions percent. Malaysia on the other hand expected to reduce their percentage to 45% by 2030 (Ministry of Energy Green Technology and Water, 2017; Unit Perancang Ekonomi, 2021)

This has led designers to reconsider the use of daylight as an electric lighting substitute. Daylight is an essential resource that is readily available and its use is an effective and efficient sustainable approach that enhances visual comfort, energy



## REFERENCES

- Abdul-Azeez, I. A. (2016). Measuring and Monitoring Carbon Emission To Promote Low-Carbon Development in Johor Bahru. In *Malaysia Sustainable Cities Program, Working Paper Series*.
- Abimaje, J., Kandar, M. Z., & Yakubu Aminu, D. (2018). Light Shelf as a Daylighting System in a Tropical Climate Office Space. *International Journal of Engineering & Technology*, 7(2.29), 798.
- Ahadi, A. A., Saghafi, M. R., & Tahbaz, M. (2017). The study of effective factors in daylight performance of light-wells with dynamic daylight metrics in residential buildings. *Solar Energy*, 155, 679–697.
- Ahmed, S., Zain-Ahmed, A., Rahman, S. A., & Sharif, M. H. (2006). Predictive tools for evaluating daylighting performance of light pipes. *International Journal of Low-Carbon Technologies*, 1(4), 315–328.
- Al-Ashwal, N. T., & Hassan, A. S. (2018). The Impact of Daylighting-Artificial Lighting Integration on Building Occupants ' Health. *International Transaction Journal of Engineering, Management, & Applied Sciences & Technologies*, 9(2), 97–105.
- Al-Marwaei, M., & Carter, D. J. (2006). Tubular Guidance Systems for Daylight: Achieved and Predicted Installation Performances. *Applied Energy*, 83(7), 774–788.
- Al-Obaidi, K. M., Ismail, M. A., & Abdul Rahman, A. M. (2015). Assessing the allowable daylight illuminance from skylights in single-storey buildings in Malaysia: a review. *International Journal of Sustainable Building Technology and Urban Development*, 6(4), 236–248.
- Al-Obaidi, K. M., Ismail, M. A., Munaaim, M. A. C., & Abdul Rahman, A. M. (2017). Designing an integrated daylighting system for deep-plan spaces in Malaysian low-rise buildings. *Solar Energy*, 149(2017), 85–101.

- Alrubaih, M. S., Zain, M. F. M., Alghoul, M. A., Ibrahim, N. L. N., Shameri, M. A., & Elayeb, O. (2013). Research and development on aspects of daylighting fundamentals. *Renewable and Sustainable Energy Reviews*, *21*, 494–505.
- Alzoubi, H. H., & Al-Zoubi, A. H. (2010). Assessment of building façade performance in terms of daylighting and the associated energy consumption in architectural spaces: Vertical and horizontal shading devices for southern exposure facades. *Energy Conversion and Management*, *51*(8), 1592–1599.
- Ander, G. D. (2003). *Daylighting performance and design*. New Jersey: John Wiley & Sons, Inc.,.
- Asia Pacific Energy Research Centre. (2013). APEC Energy Demand and Supply Outlook 5th Edition. In *Asia Pacific Energy Research Centre*.
- Ayoub, M. (2019). 100 Years of daylighting: A chronological review of daylight prediction and calculation methods. *Solar Energy*, *194*(August), 360–390.
- Azad, A. , Salman, M., Kaushik, S., & Rakshit, D. (2019). Energy saving potential of tubular light pipe system with different colors on internal surfaces. *International Journal of Energy Sector Management*, *14*(4), 793–837.
- Babatunde, K. A., Said, F. F., Md Nor, N. G., Begum, R. A., & Mahmoud, M. A. (2021). Coherent or conflicting? Assessing natural gas subsidy and energy efficiency policy interactions amid CO2 emissions reduction in Malaysia electricity sector. *Journal of Cleaner Production*, *279*, 123374.
- Baker, N., & Steemers, K. (2014). *Daylight Design of Buildings* (3rd ed.). New York: Earthscan.
- Baloch, R. M., Maesano, C. N., Christoffersen, J., Mandin, C., Csobod, E., De Oliveira Fernandes, E., & Annesi-Maesano, I. (2021). Daylight and school performance in european schoolchildren. *International Journal of Environmental Research and Public Health*, *18*(1), 1–12.
- Baoubekri, M. (2008). *Daylighting, Architecture and Health* (First edit). Oxford: Architectural Press.
- Baroncini, C., Boccia, O., Chella, F., & Zazzini, P. (2010). Experimental analysis on a 1:2 scale model of the double light pipe, an innovative technological device for daylight transmission. *Solar Energy*, *84*(2), 296–307.
- Begum, R. A., Syed Abdullah, S. ., & Kabir Sarkar, M. . (2017). Time Series Patterns and Relationship of Energy Consumption and CO2 Emissions in Malaysia. *Asian Journal of Water, Environment and Pollution*, *14*(2), 41–49.

- Bellia, L, Bisegna, F., & Spada, G. (2011). Lighting in Indoor Environments: Visual and Non-Visual Effects of Light Sources With Different Spectral Power Distributions. *Building and Environment*, 46(10), 1984–1992.
- Bellia, Laura, Musto, M., & Spada, G. (2011). Illuminance Measurements Through HDR Imaging Photometry in Scholastic Environment. *Energy and Buildings*, 43(10), 2843–2849.
- Blume, C., Garbazza, C., & Spitschan, M. (2019). Effects of light on human circadian rhythms, sleep and mood. *Somnologie*, 23(3), 147–156.
- Boccia, O., & Zazzini, P. (2015). Daylight in buildings equipped with traditional or innovative sources : A critical analysis on the use of the scale model approach. *Energy & Buildings*, 86, 376–393.
- Bouchet, B., & Fontoynt, M. (1996). Day-lighting of underground spaces: Design rules. *Energy and Buildings*, 23(3), 293–298.
- Boyce, P., Hunter, C., & Howlett, O. (2003). The Benefits of Daylight through Windows. *Lighting Research Centre*, 1, 1–88.
- Bunjongjit, S., & Ngaopitakkul, A. (2018). Feasibility study and impact of daylight on illumination control for Energy-saving lighting systems. *Sustainability*, 10(4075), 2–22.
- Caicedo, D., & Pandharipande, A. (2016). Daylight and occupancy adaptive lighting control system: An iterative optimization approach. *Lighting Research and Technology*, 48(6), 661–675.
- Callow, J. (2003). *Daylighting Using Tubular Light Systems*. University of Nottingham.
- Canziani, R., Peron, F., & Rossi, G. (2004). Daylight and Energy Performances of A New Type of Light Pipe. *Energy and Buildings*, 36(11), 1163–1176.
- Carter, D. (2014). Tubular daylight guidance systems. *Lighting Res. Technology*, 46, 369–387.
- Carter, D. J. (2002). The measured and predicted performance of passive solar light pipe systems. *Lighting Research & Technology*, 34(1), 39–51.
- Carter, D. J. (2004). Developments in Tubular Daylight Guidance Systems. *Building Research & Information*, 32(3), 220–234.
- Carter, D. J. (2005). Developments in tubular daylight guidance systems. *Building Research & Information Reserach*, 78(6), 772–780.

- Carter, D. J., & Al Marwae, M. (2009). User Attitudes Toward Tubular Daylight Guidance Systems. *Lighting Research and Technology*, 41(1), 71–88.
- Chen, Y., Liu, J., Pei, J., Cao, X., Chen, Q., & Jiang, Y. (2014). Experimental and simulation study on the performance of daylighting in an industrial building and its energy saving potential. *Energy & Buildings*, 73, 184–191.
- Chirarattananon, S., Chaiwiwatworakul, P., & Patanasethanon, S. (2003). Challenges of daylighting with the luminosity and variability of the tropical sky. *Lighting Research & Technology*, 35(1), 3–10.
- Chirarattananon, S., Chedsiri, S., & Renshen, L. (2000). Daylighting Through Light Pipes in The Tropics. *Solar Energy*, 69(4), 331–341.
- Choi, J.-H., Beltran, L. O., & Kim, H.-S. (2012). Impacts of indoor daylight environments on patient average length of stay (ALOS) in a healthcare facility. *Building and Environment*, 50(0), 65–75.
- CIBSE. (2006). *Energy Assessment and Reporting Methodology: Office Assessment Method, United Kindom: CIBSE TM 22*.
- Ciugudeanu, C., & Beu, D. (2016). Passive Tubular Daylight Guidance System Survey. *Procedia Technology*, 22, 690–696.
- D.Philips. (2004). *Daylighting: Natural Light in Architecture*. Architectural Press.
- Darula, S., Kittler, R., & Kocifaj, M. (2010). Luminous effectiveness of tubular light-guides in tropics. *Applied Energy*, 87(11), 3460–3466.
- Darula, S., Kocifaj, M., & Mohelníková, J. (2013). Hollow light guide efficiency and illuminance distribution on the light-tube base under overcast and clear sky conditions. *Optik - International Journal for Light and Electron Optics*, 124(17), 3165–3169.
- Dayou, J., Hian, J., Chang, W., Yusoff, R., Sufiyan, A., Hamid, A., & Sulaiman, F. (2013). Development of Perez-Du Mortier Calibration Algorithm for Ground-Based Aerosol Optical Depth Measurement with Validation using SMARTS Model. *International Journal of Mathematical and Computational Sciences*, 7(10), 1019–1024.
- Delvaeye, R., Ryckaert, W., Stroobant, L., Hanselaer, P., Klein, R., & Breesch, H. (2016). Analysis of energy savings of three daylight control systems in a school building by means of monitoring. *Energy and Buildings*, 127, 969–979.

- Djamila, H., Ming, C. C., & Kumaresan, S. (2011). Estimation of exterior vertical daylight for the humid tropic of Kota Kinabalu city in East Malaysia. *Renewable Energy*, 36(1), 9–15.
- Dortans, C., Jack, M. W., Anderson, B., & Stephenson, J. (2020). Lightening the load: quantifying the potential for energy-efficient lighting to reduce peaks in electricity demand. *Energy Efficiency*, 13(6), 1105–1118.
- Dubois, M. (2001). Impact of Solar Shading Devices on Daylight Quality. In *Lund, Lund University*.
- Dutton, S., & Shao, L. (2007). Raytracing simulation for predicting light pipe transmittance. *International Journal of Low-Carbon Technologies*, 2(4), 339–358.
- Edmonds, I. R., & Pearce, D. J. (1999). Enhancement of crop illuminance in high latitude greenhouses with laser-cut panel glazing. *Solar Energy*, 66(4), 255–265.
- Edwards, L., & Torcellini, P. (2002). A Literature Review of the Effects of Natural Light on Building Occupants. In *National Renewable Energy Laboratory*.
- Ekren, N., & Gorgulu, S. (2012). An investigation into the usability of straight light-pipes in Istanbul. *Energy Education Science and Technology Part A: Energy Science and Research*, 30(1), 637–644.
- European Standard. (2011). *European Standard EN 12464-1: Light and lighting - Lighting of work places - Part 1: Indoor work places*.
- Fontoynt, M. (2002). Perceived performance of daylighting systems: Lighting efficacy and agreeableness. *Solar Energy*, 73(2), 83–94.
- Freewan, A. A., Shao, L., & Riffat, S. (2009). Interactions between louvers and ceiling geometry for maximum daylighting performance. *Renewable Energy*, 34(1), 223–232.
- Ganandran, G. S. B., Mahlia, T. M. I., Ong, H. C., Rismanchi, B., & Chong, W. T. (2014). Cost-benefit analysis and emission reduction of energy efficient lighting at the Universiti Tenaga Nasional. *Scientific World Journal*, 2014.
- Garcia-Hansen, V. (2006). *Innovative Daylighting Systems For Deep-Plan Commercial Buildings*. Queensland University of Technology.
- Gashniani, M. G., Saradj, F. M., & Faizi, M. (2018). Integration Issues for Using Innovative Daylighting Strategies in Light Wells. *Journal of Applied Engineering Sciences*, 7(2), 31–38.

- Ghisi, E., & Tinker, J. A. (2006). Evaluating the potential for energy savings on lighting by integrating fibre optics in buildings. *Building and Environment*, 41, 1611–1621.
- Google (2021). [*Google Maps Malaysia*]. Retrieved on April 21, 2021, From <https://www.google.com/maps/@3.8935379,99.5171002,5.01z>
- Hansen, G., & Ises, I. (2003). Natural illumination of deep-plan office buildings: light pipe strategies. *ISES Solar World Congress 2003*, (June), 14–19.
- Hassan, J. S., Zin, R. M., Majid, M. Z. A., Balubaid, S., & Hainin, M. R. (2014). Building energy consumption in Malaysia: An overview. *Jurnal Teknologi*, 70(7), 33–38.
- Hawes, B. K., Brunyé, T. T., Mahoney, C. R., Sullivan, J. M., & Aall, C. D. (2012). Effects of four workplace lighting technologies on perception, cognition and affective state. *International Journal of Industrial Ergonomics*, 42(1), 122–128.
- He, Z., Hong, T., & Chou, S. K. (2021). A framework for estimating the energy-saving potential of occupant behaviour improvement. *Applied Energy*, 287(April 2020), 116591.
- Heng, S. Y., Asako, Y., Suwa, T., Tan, L. K., Sharifmuddin, N. B., & Kamadinata, J. O. (2019). Performance of a small-scale solar cogeneration system in the equatorial zone of Malaysia. *Energy Conversion and Management*, 184, 127–138.
- Heschong Mahone Group. (1999). Daylighting in Schools An Investigation into the Relationship Between Daylighting and Human Performance. In *California Board for Energy Efficiency Third Party Program* (Vol. 1999). Fair Oaks, CA 95628.
- Hirning, M., Garcia Hansen, V., & Bell, J. (2010). Theoretical comparison of innovative window daylighting devices for a sub-tropical climate using radiance. *Proceedings of IE ECB'10*.
- Holick, M. F. (2004). Sunlight and vitamin D for bone health and prevention of autoimmune diseases, cancers, and cardiovascular disease. *The American Journal of Clinical Nutrition*, Vol. 80, pp. 1678–1688.
- Huvco (2019) <http://www.huvco.com/products.php?product=parans>

- Ibrahim, N. (2007). Daylight Availability in an Office Interior Due to Various Fenestration Options. *2nd PALENC Conference and 28th AIVC Conference on Building Low Energy Cooling and Advance Ventilation Technologies in the 21st Century, 1*(September), 436–440. Crete Island, Greece.
- IESNA. (2000). *The IESNA Lighting Handbook 9th Edition*. IESNA Publication Department.
- Ihm, P., Nemri, A., & Krarti, M. (2009). Estimation of lighting energy savings from daylighting. *Building and Environment, 44*(3), 509–514.
- Islam, Z., & Uddin, M. S. (2016). Threat Mitigation Through Design : Designing Out Threat in Educational Environment. *2016 Design Communication European Conference*.
- Ismail, L. H. (2007). *An Evaluation of Bioclimatic High Rise Office Building in A Tropical Climate : Energy Consumption and Users' Satisfaction in Selected Office Building in Malaysia*. University of Liverpool, UK.
- Jabatan Standard Malaysia. (2014). *MS 1525 : 2014 Efficiency and Use of Renewable Energy For Non-Residential Buildings - Code of Practise (third Revision)* (Vol. 2014).
- Jenkins, D., & Muneer, T. (2003). Modelling light-pipe performances—a natural daylighting solution. *Building and Environment, 38*(7), 965–972.
- Jenkins, D., & Muneer, T. (2004). Light-pipe prediction methods. *Applied Energy, 79*, 77–86.
- Ji, S., Cao, G., Zhang, J., Yu, F., Li, D., & Yu, J. (2016). Lighting design of underground parking with tubular daylighting devices and LEDs. *Optik - International Journal for Light and Electron Optics, 127*(3), 1213–1216.
- Joseph, A. (2006). The Impact of Light on Outcomes in Healthcare Settings. In *the Center for Health Design* (Vol. 2).
- Karimi, N. (2017). *The performance of east facing photovoltaic panel as shading device in high-rise office buildings in the tropics*. Universiti Teknologi Malaysia.
- Kementerian Sumber Asli dan Alam Sekitar Malaysia. (2015). *Malaysia : Biennial Update Report To The UNFCCC*.
- Kim, J. T., & Kim, G. (2010). Overview and New Developments in Optical Daylighting Systems for Building a healthy Indoor Environment. *Building and Environment, 45*(2), 256–269.

- Kocifaj, M. (2009). Analytical solution for daylight transmission via hollow light pipes with a transparent glazing. *Solar Energy*, 83(2), 186–192.
- Kocifaj, M., Darula, S., & Kittler, R. (2008). HOLIGILM: Hollow light guide interior illumination method – An analytic calculation approach for cylindrical light-tubes. *Solar Energy*, 82(3), 247–259.
- Kómar, L., & Kocifaj, M. (2019). An accurate prediction of daylight pipe harvesting of interior space. *Applied Sciences (Switzerland)*, 9(17), 1–20.
- Krarti, M. (2014). Estimation of Lighting Energy Savings From Atrium Daylighting. *ASME 2014 8th International Conference on Energy Sustainability*, 1–7.
- Krarti, M., Erickson, P. M., & Hillman, T. C. (2005). A simplified method to estimate energy savings of artificial lighting use from daylighting. *Building and Environment*, 40(6), 747–754.
- Leather, P., Pyrgas, M., Beala, D., & Lawrence, C. (1998). Windows in the workplace: Sunlight, view and occupational stress. *Journal of Behavioral Sciences*, 30(6), 739–762.
- Lembaga Penyelidik Undang-Undang. (2015). *Undang-Undang Kecil Bangunan Seragam 1984*. Petaling Jaya: International Law Book Services.
- Li, D. H. W. (2010). A review of daylight illuminance determinations and energy implications. *Applied Energy*, 87(7), 2109–2118.
- Li, D. H. W., Cheung, K. L., Wong, S. L., & Lam, T. N. T. (2010). An analysis of energy-efficient light fittings and lighting controls. *Applied Energy*, 87(2), 558–567.
- Li, D. H. W., & Lam, J. C. (2003). An analysis of lighting energy savings and switching frequency for a daylit corridor under various indoor design illuminance levels. *Applied Energy*, 76(4), 363–378.
- Li, D. H. W., Tsang, E. K. W., Cheung, K. L., & Tam, C. O. (2010). An analysis of light-pipe system via full-scale measurements. *Applied Energy*, 87(3), 799–805.
- Lightway. <https://www.lightwaydaylight.co.uk/gallery/>
- Lim, G. H., Hirning, M. B., Keumala, N., & Ghafar, N. A. (2017). Daylight performance and users' visual appraisal for green building offices in Malaysia. *Energy and Buildings*, 141, 175–185.



- Lim, G. H., Keumala, N., & Ghafar, N. A. (2017). Energy saving potential and visual comfort of task light usage for offices in Malaysia. *Energy and Buildings*, 147, 166–175.
- Lim, Y. W., & Ahmad, M. H. (2014). The Effects of Direct Sunlight on Light Shelf Performance Under Tropical Sky. *Indoor and Built Environment*.
- Lim, Y. W., Kandar, M. Z., Ahmad, M. H., Remaz, D., Kandar, M. Z., Ahmad, M. H., Abdullah, A. M. (2012). Building façade design for daylighting quality in typical government office building. *Building and Environment*, 57, 194–204.
- Mahdavi, A., Rao, S. P., & Inangda, N. (2013). Parametric Studies on Window-To-Wall Ratio for Day lighting Optimisation in High-Rise Office Buildings in Kuala Lumpur, Malaysia. *Journal of Design and Built Environment*, 12(June), 1–8.
- Mahlia, T. M. I., Razak, H. A., & Nursahida, M. A. (2011). Life cycle cost analysis and payback period of lighting retrofit at the University of Malaya. *Renewable and Sustainable Energy Reviews*, 15(2), 1125–1132.
- Mahlia, T. M. I., Taufiq, B. N., Ong, K. P., & Saidur, R. (2011). Exergy analysis for day lighting, electric lighting and space cooling systems for a room space in a tropical climate. *Energy and Buildings*, 43(7), 1676–1684.
- Malet-Damour, B., Boyer, H., Fakra, A. H., & Bojic, M. (2014). Light pipes performance prediction: Inter model and experimental confrontation on vertical circular light-guides. *Energy Procedia*, 57(0), 1977–1986.
- Malet-Damour, B., Guichard, S., Bigot, D., & Boyer, H. (2016). Study of tubular daylight guide systems in buildings: Experimentation, modelling and validation. *Energy and Buildings*, 129, 308–321.
- Marwae, M. A., & Carter, D. J. (2006). A Field Study of Tubular Daylight Guidance Installations. *Lighting Research and Technology*, 38(3), 241–258.
- Mayhoub, M. S. (2014). Innovative daylighting systems' challenges: A critical study. *Energy and Buildings*, 80, 394–405.
- Mayhoub, M.S. (2013). What is Preventing Innovative Daylighting Systems From Widespread use? *LuxEuropa 2013, the 12th European Lighting Conference*, 263–268.
- Mayhoub, M.S., & Carter, D. J. (2011). The Costs and Benefits of Using Daylight Guidance to Light Office Buildings. *Building and Environment*, 46(3), 698–710.
- Mayhoub, Mohammed S. (2011). *Hybrid lighting systems: Performance, Application and Evaluation*. University of Liverpool.

- Ministry of Energy Green Technology and Water. (2017). *Green Technology Master Plan Malaysia 2017 - 2030*.
- Ministry of Environment and Water. (2020). *Malaysia: Third Biennial Report To The UNFCCC*. Putrajaya.
- Mohd Chachuli, F. S., Mat, S., Ludin, N. A., & Sopian, K. (2021). Performance evaluation of renewable energy R&D activities in Malaysia. *Renewable Energy*, 163, 544–560.
- Mohelnikova, J. (2008). Daylighting and energy savings with tubular light guides. *WSEAS Transactions on Environment and Development*, 4(3), 200–209.
- Mohelnikova, J. (2009). Tubular Light Guide Evaluation. *Building and Environment*, 44(10), 2193–2200.
- Mohelnikova, J., & Vajkay, F. (2009). Study of tubular light guides illuminance simulations. *LEUKOS - Journal of Illuminating Engineering Society of North America*, 5(4), 267–277.
- Monodraught.  
<https://www.monodraught.com/resources?product=sunpipe&resource=Image>
- Munaaim, M. A., Al-Obaidi, K. M., Ismail, M. R., & Rahman, A. M. A. (2014). A review study on the application of the fibre optic daylighting system in Malaysian buildings. *International Journal of Sustainable Building Technology and Urban Development*, 5(3), 146–158.
- Muneer, T., Abodahab, N., Weir, G., & Kubie, J. (2000). *Windows in Buildings: Thermal, Acoustic, Visual and Solar Performance*. Oxford: Architectural Press.
- Mushtaha, E., Kana'an, B. A., Al-Jawazneh, R. A., & Hammad, R. S. (2016). Effect of using different light pipe parameters on the daylight quality in buildings: The case of Jordan. *International Journal of Green Energy*, 13(15), 1590–1598.
- Nilsson, A. M., Jonsson, J. C., & Roos, A. (2014). Spectrophotometric measurements and ray tracing simulations of mirror light pipes to evaluate the color of the transmitted light. *Solar Energy Materials and Solar Cells*, 124, 172–179.
- NOAA. NOAA Solar Calculator. 2018. Available online: <https://www.esrl.noaa.gov/gmd/grad/solcalc/> (accessed on 17 July 2019)
- Oakley, G., Riffat, S. B., & Shao, L. (2000). Daylight performance of lightpipes. *Solar Energy*, 69(2), 89–98.

- Obradovic, B., & Matusiak, B. S. (2019). Daylight Transport Systems for Buildings at High Latitudes. *Journal of Daylighting*, 6(2), 60–79.
- Omishore, A., Mohelník, P., & Míček, D. (2018). Light pipe prototype testing. *Przegląd Elektrotechniczny*, 94(4), 107–112.
- Omishore, A., Mohelník, P., & Míček, D. (2020). Light Pipe Comparative Study. *Selected Scientific Papers - Journal of Civil Engineering*, 14(1), 17–26.
- Osibona, O., Solomon, B. D., & Fecht, D. (2021). Lighting in the home and health: A systematic review. *International Journal of Environmental Research and Public Health*, 18(2), 1–20. <https://doi.org/10.3390/ijerph18020609>
- Ossen, D. R. (2005). *Optimum Overhang Geometry for High Rise Office*. Universiti Teknologi Malaysia.
- Paroncini, M., Calcagni, B., & Corvaro, F. (2007). Monitoring of a light-pipe system. *Solar Energy*, 81, 1180–1186.
- Patil, K. N., Kaushik, C., & Garg, S. N. (2018). Performance Prediction and Assessment of Energy Conservation Potential for a Light Pipe System in Indian Composite Climate of New Delhi. *Journal of Solar Energy Engineering*, 140(5), 1–9.
- Pattanasethanon, S. (2007). All sky modeling daylight availability and illuminance / irradiance on horizontal plane for Mahasarakham , Thailand. *Energy Conversion and Management*, 48, 1601–1614.
- Petr, J., Kocifaj, M., & Kómar, L. (2018). Accurate tool for express optical efficiency analysis of cylindrical light-tubes with arbitrary aspect ratios. *Solar Energy*, 169(May), 264–269.
- Plympton, P., Conway, S., & Epstein, K. (2000). Daylighting in Schools: Improving Student Performance and Health at a Price Schools Can Afford. *American Solar Energy Society Conference*, (August), 10.
- Rahim, R., & Mulyadi, R. (2004). Classification of daylight and radiation data into three sky conditions by cloud ratio and sunshine duration. *Energy & Buildings*, 36, 660–666.
- Ramos, G., & Ghisi, E. (2000). Analysis of daylight calculated using the EnergyPlus programme. *Solar Energy*, 69(2), 89–98.
- Reffat, R. M., & Ahmad, R. M. (2020). Determination of optimal energy-efficient integrated daylighting systems into building windows. *Solar Energy*, 209(July), 258–277.

- Romm, J., & Browning, W. D. (1998). Greening the Building and the Bottom Line Increasing Productivity Through Energy-Efficient Design. In *Rocky Mountain Institute*.
- Shahriar, A. N. M., & Mohit, M. A. (2007). Estimating depth of daylight zone and PSALI for side lit office spaces using the CIE Standard General Sky. *Building and Environment*, 42(8), 2850–2859.
- Shao, L., Elmualim, a. a., & Yohannes, I. (1998). Mirror lightpipes : Daylighting performance in real buildings. *Lighting Research and Technology*, 30(1), 37–44.
- Sharma, L., Fatima, S., & Rakshit, D. (2018). Performance evaluation of a top lighting light-pipe in buildings and estimating energy saving potential. *Energy & Buildings*, 179, 57–72.
- Sharp, F., Lindsey, D., Dols, J., & Coker, J. (2014). The use and environmental impact of daylighting. *Journal of Cleaner Production*, 85, 462–471.
- Shin, J. Y., Yun, G. Y., & Kim, J. T. (2011). Evaluation of Daylighting Effectiveness and Energy Saving Potentials of Light-Pipe Systems in Buildings. *Indoor and Built Environment*, 21(1), 129–136.
- Sibley, M., & Garcia, A. P. (2020). Flat Glass or Crystal Dome Aperture ? A Year-Long Comparative Analysis of the Performance of Light Pipes in Real Residential Settings and Climatic Conditions. *Sustainability*, 12(3858), 2–11.
- Spacek, A. D., & Dagostin, L. (2018). Proposal of the Tubular Daylight System Using Acrylonitrile Butadiene Styrene ( ABS ) Metalized with Aluminum for Reflective Tube Structure. *Energies*, 11(199), 1–12.
- Spacek, A. D., Dagostin, L., Hideo, O., Junior, A., Pedro, G., Neto, D. F., Malfatti, C. D. F. (2017). Proposal for an Experimental Methodology for Evaluation of Natural Lighting Systems Applied in Buildings. *Energies*, 10(1014), 1–12.
- Srisamranrungruang, T., & Hiyama, K. (2020). Balancing of natural ventilation, daylight, thermal effect for a building with double-skin perforated facade (DSPF). *Energy and Buildings*, 210.
- Su, Y., Khan, N., Riffat, S. B., & Gareth, O. (2012). Comparative monitoring and data regression of various sized commercial lightpipes. *Energy & Buildings*, 50, 308–314.
- Suruhanjaya Tenaga. (2016). *Guidelines on No-Cost and Low-Cost Measures for Efficient Use of Electricity in Buildings*. Retrieved from [www.st.gov.my](http://www.st.gov.my)
- Suruhanjaya Tenaga. (2019). *Malaysia Energy Statistics Handbook 2019*.

- Swift, P. D., & Smith, G. B. (1995). Cylindrical Mirror Light Pipes. *Solar Energy Materials and Solar Cells*, 36(1995), 159–168.
- Taengchum, T., & Chirarattananon, S. (2015). Ray Tracing Method of Light through Rectangular Light Pipe with Bends. In *Energy Procedia* (Vol. 79).
- Tang, C. K., & Chin, N. (2017). *Building energy efficiency technical guideline for passive design*.
- Taylor, P., Nur, A., Shahriar, M., & Mohit, M. A. (2006). Frequency Distribution of CIE Standard General Skies Frequency Distribution of CIE Standard General Skies for Subang , Malaysia. *Architectural Science Review*, 49.4, 363–366.
- The United Nation (2021). *UNESCO and Sustainable Development Goals*. Retrieved on May 15, 2021, From <https://sdgs.un.org/goals>
- TNB (2021). Tariff for comercial consumer. Retrieved on Sept 20, 2021, From <https://www.tnb.com.my/commercial-industrial/pricing-tariffs1/>
- Tregenza, P., & Wilson, M. (2011). *Daylighting Architecture and Lighting Design*. Madison Avenue, New York: Routledge.
- Tsang, E. K. W., Kocifaj, M., & Li, D. H. W. (2018). Straight light pipes' daylighting : A case study for different climatic zones. *Solar Energy*, 170, 56–63.
- Turan, I., Chegut, A., Fink, D., & Reinhart, C. (2020). The value of daylight in office spaces. *Building and Environment*, 168, 1–13.
- Unit Perancang Ekonomi. (2021). *Rancangan Malaysia Kedua Belas*. Kuala Lumpur.
- Vajkay, F., Bečkovský, D., & Tichomirov, V. (2016). Assessment of tubular light guides with respect to building physics. *Materials and Technology*, 50(3), 409–412.
- Vasilakopoulou, K., Kolokotsa, D., Santamouris, M., Kousis, I., & Asproulis, H. (2017). Analysis of the experimental performance of light pipes. *Energy & Buildings*, 151, 242–249.
- Vathanam, G. S. O., Kalyanasundaram, K., Elavarasan, R. M., Hussain, S., Subramaniam, U., Pugazhendhi, R., Gopalakrishnan, R. M. (2021). A review on effective use of daylight harvesting using intelligent lighting control systems for sustainable office buildings in India. *Sustainability*, 13, 2–32.
- Venturi, L., Wilson, M., Jacobs, A., & Solomon, J. (2006). Light piping performance enhancement using a deflecting sheet. *Lighting Research and Technology*, 38(2), 167–179.

- Vyas, G. S., Jha, K. N., & Rajhans, N. R. (2019). Identifying and evaluating green building attributes by environment, social, and economic pillars of sustainability. *Civil Engineering and Environmental Systems*, 36(2–4), 133–148.
- Wagiman, K. R. (2020). *Daylight Adaptive Optimal Lighting System Control Strategies For Energy Savings And Visual Comfort In Commercial Buildings*. Universiti Tun Hussein Onn Malaysia.
- Wagiman, K. R., Abdullah, M. N., Hassan, M. Y., & Mohammad Radzi, N. H. (2021). A new metric for optimal visual comfort and energy efficiency of building lighting system considering daylight using multi-objective particle swarm optimization. *Journal of Building Engineering*, 43(April), 102525.
- Walch, J. M., Rabin, B. S., Day, R., Williams, J. N., Choi, K., & Kang, J. D. (2005). The effect of sunlight on postoperative analgesic medication use: A prospective study of patients undergoing spinal surgery. *Psychosomatic Medicine*, 67(1), 156–163.
- Whitehead, L. A., Brown, D. N., & Nodwell, R. A. (1984). A new device for distributing concentrated sunlight in building interiors. *Energy and Buildings*, 6(2), 119–125.
- Worlddata. (2021). Worlddata. Retrieved from <https://www.worlddata.info/asia/malaysia/energy-consumption.php>
- Wu, Y. (2008). Research and Development of Solar Light Pipes in China. *2008 International Conference on Information Management, Innovation Management and Industrial Engineering*, 146–149.
- Wu, Y., Jin, R., Li, D., Zhang, W., & Ma, C. (2008). Experimental investigation of top lighting and side lighting solar light pipes under sunny conditions in winter in Beijing. *2008 International Conference on Optical Instruments and Technology: Advanced Sensor Technologies and Applications*, 7157, 715710.
- Wu, Y., & Li, H. (2012). Experimental study on performance of top lighting solar light pipes in the meeting room in winter in Beijing. *Applied Mechanics and Materials*, 178–181, 29–32.
- Yun, G. Y., Kim, H., & Kim, J. T. (2012). Effects of occupancy and lighting use patterns on lighting energy consumption. *Energy and Buildings*, 46, 152–158.
- Yun, G. Y., & Kim, J. T. (2010). Monitoring and Evaluation of a Light-pipe System used in Korea. *Indoor and Built Environment*, 19(1), 129–136.

- Yun, G. Y., Kong, H. J., Kim, H., & Kim, J. T. (2012). A field survey of visual comfort and lighting energy consumption in open plan offices. *Energy and Buildings*, 46, 146–151.
- Zain-Ahmed, A., Sopian, K., Othman, M. Y., Sayigh, A. A., & Surendran, P. . (2002). Daylighting As a Passive Solar Design Strategy in Tropical Buildings: A Case Study of Malaysia. *Energy Conversion and Management*, 43, 1725–1736.
- Zain-Ahmed, A., Sopian, K., Zainol Abidin, Z., & Othman, M. Y. . (2002). The availability of daylight from tropical skies—a case study of Malaysia. *Renewable Energy*, 25, 21–30.
- Zakaria, R., Amirazar, A., Mustaffar, M., Mohammad Zin, R., & Abd Majid, M. Z. (2013). Daylight Factor for Energy Saving in Retrofitting Institutional Building. *Advanced Materials Research*, 724–725, 1630–1635.
- Zastrow, A., & Wittwer, V. (1986). Daylighting with Mirror Light Pipes and with Fluorescent Planar Concentrators. *SPIE Materials and Optic For Solar Energy Convension and Advanced Lighting Technology*, 692, 227–234.
- Zhang, X. (2002). *Daylighting Performance of Tubular Solar Loght Pipes: Measurement, Modelling and Validation*. Napier University.
- Zhang, X., & Muneer, T. (2000). Mathematical Model for The Performance of Light Pipes. *Lighting Research and Technology*, 32(3), 141–146.
- Zhang, X., Muneer, T., & Kubie, J. (2002). A Design Guide for Performance Assessment of Solar Light-Pipes. *Lighting Research and Technology*, 34(2), 149–169.
- Zomorodian, Z. S., & Tahsildoost, M. (2019). Assessing the effectiveness of dynamic metrics in predicting daylight availability and visual comfort in classrooms. *Renewable Energy*, 134, 669–680.